

Product Guide



GAS ENGINE TECHNOLOGY

reliable • efficient • worldwide

■ Table of Contents

6 ■ Ignition Controllers & Harnesses

- 6 Characteristics MIC Series
- 7 Technical Data
- 8 MOST –
MOTORTECH Output Stage Technology
- 9 MICT –
MOTORTECH Integrated Configuration Tool
- 10 System Overview MIC3+/MIC4/MIC5
- 12 MIC3+ Series
- 14 MIC3+CATDI – Retrofit for
CATERPILLAR® G3300 & G3400 Gas Engines
- 14 MIC3+CEC – Retrofit for
WAUKESHA® VGF & VHP Gas Engines
- 15 MIC4 Series
- 18 MIC4-ZS Kits
- 19 MIC5 Series
- 21 MIC6 Series
- 26 PowerView3 – Ignition Control Visualization
- 28 MOT601 Single Cylinder Ignition System
- 30 Harnesses for Competition
Ignition Control Systems

32 ■ Ignition Coils

- 32 New MOTORTECH Style
- 33 MOTORTECH Style
- 33 ALTRONIC® Style
- 34 Ignition Coils for CATERPILLAR® Gas Engines
- 36 Ignition Coil for WÄRTSILÄ® Gas Engines
- 37 Ignition Coil Conversion Kits
for CUMMINS® & WÄRTSILÄ® Gas Engines
- 38 Ignition Coil Extensions
- 40 Accessories for Unshielded Ignition Coils
- 42 Flange Ignition Coils
- 46 Hardware Kit for WAUKESHA® VHP-GL Engines
- 48 Externally Mounted Ignition Coils
- 50 Integral Ignition Coils

54 ■ Pickups & Trigger Drives

- 54 Pickups
- 56 Special Application Pickups
- 57 Pickup Leads
- 58 Trigger Discs
- 60 Reluctor Pins & Trigger Magnets
- 60 Trigger Drives
- 62 Trigger Devices
- 64 Tools & Accessories

66 ■ Primary Leads

- 66 Primary Leads – New Flex Style
- 69 Special Application Primary Leads
- 70 Primary Leads for AlphaRail Wiring Rails

72 ■ Spark Plug Leads & Extensions

- 72 Spark Plug Leads – Patented PolyMot™ Style
- 78 Spark Plug Leads for CATERPILLAR® Gas Engines
- 80 Spark Plug Leads for common Applications
(Non PolyMot™ Style)
- 81 Unshielded Safety Leads
for Shielded Spark Plugs
- 84 Accessories for Unshielded Spark Plug Leads
- 88 MOT-Blues Shielded Spark Plug Leads
- 90 Conventional Shielded Spark Plug Leads
- 91 Terminal Repair Kits
- 92 Spark Plug Extensions –
Patented PolyMot™ Style
- 94 Ignition Coil Extensions
- 95 Ignition Coil Extension Overhaul Kits
- 97 Extensions for Integral Ignition Coils
- 97 Extensions for Shielded Spark Plugs

98 ■ Ignition Wiring Rails & Hardware

- 98 Wiring Rail System for Ignition Control
- 104 Ignition Wiring Rail Upgrade Kits
- 106 Ignition Wiring Rail Kits for
CATERPILLAR® Gas Engines
- 109 Ignition Kits for Unshielded Applications

114 ■ Ignition Tools & Test Equipment

- 114 SparkView High Voltage Indicator
- 115 SparkScan1 High Voltage Clamp
- 115 Digital Scope Meter
- 116 Ignition Coil Tester
- 117 IPS Ignition Pickup Simulator
- 118 Test Adaptor for MOTORTECH Ignition Controllers
- 119 ScopeLite Timing Light
- 120 Tools & Workshop Equipment

124 ■ Spark Plugs & Accessories

- 124 DENSO® Spark Plugs
- 129 MOTORTECH High Performance Spark Plugs
- 130 MOTORTECH Bridge Spark Plugs
- 131 MOTORTECH Pre-Chamber Spark Plugs
- 133 ICP Spark Plugs with Dual Thread
- 134 XT-Plugs – Extended Barrel Spark Plugs
- 136 XTL-Plugs – Extended Barrel Spark Plugs
- 140 Spark Plug Tools
- 146 Spark Plug Accessories

148 ■ Gas Engine Control Systems

- 148 DetCon20 Detonation Control System
- 153 PowerView3 Detonation Control Visualization
- 154 AlphaRail Wiring Rail System for Detonation Control
- 158 TempScan20 Temperature Module
- 159 PowerView3 Temperature Scanner Visualization
- 160 AlphaRail Wiring Rail System for Temperature Control
- 167 Throttle Bodies
- 170 Throttle Bodies with Integrated Stepper Motor
- 174 Throttle Bodies for MAN® Gas Engines
- 176 Throttle Bodies for WAUKESHA® Gas Engines
- 178 ALL-IN-ONE Generator & CHP Control Systems
- 182 Actuator Replacement Kit for WAUKESHA® VHP Series Engines

184 ■ Sensor Systems

- 184 Thermocouple Rails for WAUKESHA® 12 Cylinder VHP Engines
- 186 Thermocouples
- 188 Oxygen Sensors
- 190 MAT – Manifold Air Temperature Sensors
- 190 MAP – Manifold Absolute Pressure Sensor

194 ■ Air/Fuel Ratio Control Systems

- 194 VariFuel Air/Gas Mixer Series
- 206 VariFuel2-TEM Air/Gas Mixer for MWM® Gas Engines
- 208 VariStep3 Stepper Motor Driver
- 209 EmCon5 Lean-Burn Emission Controller

212 ■ Exhaust Gas Aftertreatment

- 212 VariSCR NO_x Emission Controller
- 214 Catalysts

218 ■ Gas Engine Accessories

- 218 Valve Cover Conversion Kit for MAN® E32 Series Gas Engines
- 220 OLC Oil Level Controller
- 224 Coolant Filtration
- 226 Lube Oil Filtration
- 228 Ultrasonic Cleaning Equipment

230 ■ Technical Support & Service

234 ■ A-Z

236 ■ Index

■ Ignition Controllers & Harnesses

Characteristics MIC Series



General

- For 2- and 4-stroke engines
- Ignition technology pulse width modulated
- Technical restriction to 6000 rpm
- Max. trigger impulses 16+1 or 500 teeth on the flywheel

Technical Data & Features

- Ignition timing to 0.1° crankshaft
- Triggered by magnetic, Hall effect or inductive pickup
- Multiple ignition timing control via
 - Potentiometer (except MIC3+ and MIC6 series)
 - Speed curve
 - 0 to 20 mA analog input
 - 0 to 10 V analog input
- Multiple energy control via MOST (MOTORTECH Output Stage Technology)
- Programmable firing order
- Overspeed shutdown function
- Access controlled
- Programmable spark duration
- Energy output control
- 2 programmable speed curves with max. 8 speed points (speed/ignition timing)
- Diagnostic memory
- System status display
- Error memory

Ignition Diagnostics

- Runtime data
- Alarm and error messages
- Data logging
- Primary and secondary misfire detection
- Cylinder individual high-voltage calculation (kV)

Interfaces

- CAN Bus 2.0b interface (CANopen/SAE J1939 protocol)
- RS485 interface (Modbus RTU)
- USB 1.1 interface

Inputs

- Digital ignition release (start/stop)
- Configurable digital input (GPI)
- Digital input for schedule A/B

Outputs

- Max. 2 Auxiliary Synchronization Outputs (ASO) which can support a detonation control system (e.g. DetCon) or fuel injection pump controllers (device dependend)
- Max. 3 multipurpose outputs (GPO) (device dependend)
- Go/NoGo output

Configuration


- Using the graphic user interface MICT (MOTORTECH Integrated Configuration Tool, see page 9)

Certifications

- CSA (Class I, Division 2, Group C, D; T4)
- ATEX (II 3G Ex uA II B T4 X) – on request
- CE

Scope of Supply

- Configuration software MICT (MOTORTECH Integrated Configuration Tool)
- USB interlink cable
- Vibration dampers
- Ground strap
- Fastening material
- Operating manual



Technical Data

Feature		MIC3+ Series	MIC4 Series	MIC5 Series	MIC6 Series
General	Max. number of ignition outputs	12	16	20	24
	Max. number of pickups	2	3	3	6 (2 sets with max. 3 pickups)
	Power supply	10 to 32 V DC	10 to 32 V DC	16.8 to 32 V DC	16.8 to 32 V DC
	Permitted housing surface temperature	-40 °C to + 60 °C -40 °F to +140 °F	-40 °C to + 60 °C (LD) -40 °F to +140 °F (LD)	-40 °C to + 60 °C -40 °F to +140 °F	-40 °C to + 60 °C -40 °F to +140 °F
Output	Max. primary voltage	250 V DC	250 V DC	250 V DC	250 V DC
	Max. ignition energy	300 mJ (500 mJ boost for start phase)	300 mJ (500 mJ boost for start phase)	500 mJ (600 mJ boost for start phase)	1000 mJ (1200 mJ boost for start phase)
	Max. programmable spark duration	100 to 800 µsec	100 to 1000 µsec	100 to 1500 µsec	100 to 1500 µsec
Housing	Available housing versions ¹⁾	Light Duty (LD)	Panel Mount (PM), Light Duty (LD), Heavy Duty (HD)	Heavy Duty (HD)	Heavy Duty (HD)
	Dimensions (length x width x height)	250 x 240 x 89.5 mm (LD) 9.84 x 9.45 x 3.52 in (LD)	304 x 240 x 95.5 mm (LD) 11.97 x 9.45 x 3.76 in (LD)	371 x 240 x 114.5 mm (HD) 14.61 x 9.45 x 4.51 in (HD)	385 x 240 x 114.5 mm (HD) 15.16 x 9.45 x 4.51 in (HD)
	Protection class	IP54 (LD)	IP20 (PM), IP54 (LD), IP65 (HD)	IP65 (HD)	IP65 (HD)
	Engine installation	not permitted	not permitted	not permitted	not permitted
	Number of potentiometers for manual timing adjustment	0	2 (continuous)	2 (continuous)	0
	Input connection	MIL, 35 pole, pin (standard)	terminal strip (standard)	terminal strip (standard)	MIL, 35 pole, pin (standard)
	Output connection	MIL, 17 pole, socket	MIL, 17 pole, socket	MIL, 35 pole, socket	MIL, 35 pole, socket
	Number of status LEDs	5	6	6	11

¹⁾ Consult factory for information on the availability of housing styles.

Ignition Controllers & Harnesses




Patented Technology for MIC3+/MIC4/MIC5/MIC6*

Efficiency-enhanced engines, highly compressed mixtures, as well as the use of a great variety of gas types are putting greater demands on the entire ignition system, including:

- reliable ignition even with weak or fluctuating calorific values of the gas
- compliance with the strictest emission regulations
- avoidance of knocking and misfiring
- reduction of maintenance costs through longer spark plug runtimes

*Patent No.: US 8,893,692 B2

The graphic compares the behavior of a conventional Capacitor Discharge Ignition System (CDI) and Ignition System with MOST




Capacitor Discharge Ignition System (CDI)

The red curve shows that a high peak current is reached during ignition. Afterwards, the current decreases sharply. To achieve longer spark duration, the energy supply must be increased. The result of this is a higher peak current.

Ignition System with MOST

The blue curve shows that a lower peak current is reached during ignition with MOST. The current remains at a constant level until the energy supply ends. Thereafter, the current drops. In this case as well, more energy is supplied for a longer spark duration, however the peak current is not increased in the process.



Settings for MOST in MICT

The settings for MOST are made using the MICT configuration software. On the configuration side *Timing – Schedule A/B – Energy*, you can define different values for the spark duration, spark intensity, breakdown voltage and energy limit for the start phase and normal operation. That way starting difficulties of the engine can be caught. Different energy settings for the two schedules A and B support, for example, optimally matched two gas operation. The settings are dependent on the ignition coils that are used, among other things. They must be suitable for MOST and set correctly on the configuration side *Engine – Ignition Coils*. To optimize the energy settings for an engine, the ignition behavior must be observed and analyzed (misfiring, knock behavior, emission values, etc.). The secondary side diagnostics with MICT, among other things, can help here.

MICT

MOTORTECH INTEGRATED CONFIGURATION TOOL

The MICT is the graphical user interface for all controllers of the MIC3+, MIC4, MIC5 and MIC6 series. With a laptop all configurations can be done and runtime data of the engine can be checked and adjusted.

- Language selectable (German/English/Chinese)
- Microsoft® Windows XP/Vista/7 compatible
- Included data base offers engine information such as firing order, firing sequence, number of ignition coils per cylinder and typical number of teeth on flywheel for easy engine configuration


- Print function of a given moment in the operation can be used for external problem analysis, etc.
- Context sensitive online help
- Different access levels to avoid accidental misconfigurations

Sample Screens – Runtime Data



Overview


In the overview schedule the most important current runtime data such as speed, ignition timing or system status can be registered at a glance.



Breakdown Voltage


The MICT offers a lot of real time and detailed information about the status of each individual ignition output. Important data will be visually prepared, so that any irregularities will stand out easily. For example, secondary voltage will be displayed as bar graph, and the type of misfiring carries a warning light as symbol.

Sample Screens – Parameter Set



Energy Settings

For start phase and normal operation of the engine, durations at different high voltage levels and ignition spark intensity can be adjusted with the advanced energy settings.




Configuration Visualization

The graphic display of the parameter set A and B offers a fast, visual control of the configured values.

■ Ignition Controllers & Harnesses

System Overview MIC3+/MIC4/MIC5 Series



¹⁾ In combination with the MIC3+ series only one crankshaft pickup possible

Legend

Necessary Components

- 1 MIC ignition controller
- 2 Pickup lead*
- 3 Pickup*
- 4 Reluctor pins/trigger magnets

alternative

- 5 Trigger disc

alternative

- Trigger drive
- 6 Output harness*
- 7 Ignition coil*
- 8 1 primary lead/spark plug lead per ignition coil*

* Shielded and unshielded versions available.

Accessories

- A Junction box
- B AlphaRail/LiteRail – ignition wiring rail

System Enhancement

- C DetCon20 – Detonation controller
- D PowerView3 – HMI module

Description

- V Camshaft
- W Crankshaft
- X Engine
- Y Cylinder
- Z Harness to connect the ignition wiring rails and the junction box

Established Pickup Arrangements

3-Pickup Arrangement for 4-Stroke Engines

- 1) Crankshaft (Reset)
Magnetic pickup
(holes, pins, teeth, screws)
- 2) Crankshaft (Speed)
Magnetic pickup
(holes, pins, teeth, screws)
- 3) Camshaft (Reset)
Hall effect pickup
(magnets)

alternative

- 3) Camshaft (Reset)
Inductive pickup
(pins, screws, slots)

1-Pickup Arrangement for 4-Stroke Engines

- 1) Camshaft (N+1/N-1)
Hall effect pickup
(disc with magnets)
- alternative
- 1) Camshaft (N+1/N-1)
Inductive pickup
(disc with pins, screws, slots)

2-Pickup Arrangement for 2-Stroke Engines

- 1) Crankshaft (Reset)
Magnetic pickup
(holes, pins, teeth, screws)
- 2) Crankshaft (Speed)
Magnetic pickup
(holes, pins, teeth, screws)

Ignition Controllers & Harnesses



Ignition Controllers – Light Duty – Standard

P/N	max. Outputs	Connector Style	Connectors		Pickup		Equivalent to
			Input	Output	Inputs	Voltage	
66.00.350-6	6	MIL	35 pole, pin	17 pole, socket	2	programmable via MICT	
66.00.350-12	12	MIL	35 pole, pin	17 pole, socket	2	programmable via MICT	

Input Harnesses for Ignition Controllers – Light Duty – Standard

P/N	Description	Interfaces	Connector	Length	Pickup
06.02.034-160	Input harness for P/N 66.00.350-6/-12	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive
06.02.035-160	Input harness for P/N 66.00.350-6/-12	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	2 inductive
06.02.036-160	Input harness for P/N 66.00.350-6/-12	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 Hall effect
06.02.040-160	Input harness for P/N 66.00.350-6/-12	RS485 (2 wire)	MIL, 35 pole, socket, 180°	160 in	1 Hall effect
06.02.041-160	Input harness for P/N 66.00.350-6/-12	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive, 1 magnetic

Input Harnesses for Ignition Controllers – Light Duty – Standard ¹⁾



P/N	Description	Interfaces	Connector	Length	Pickup
95.30.300-L	Input harness for P/N 66.00.350-6/-12	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 inductive
95.30.301-L	Input harness for P/N 66.00.350-6/-12	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 Hall effect
95.30.302-L	Input harness for P/N 66.00.350-6/-12	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 magnetic

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Output Harnesses for Ignition Controllers – Light Duty – Standard

P/N	Description	Connector	Length	Equivalent to
06.02.618-L	Output harness for P/N 66.00.350-6/-12	MIL, 17 pole, pin, 180°	L= 160/320 in	

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Output Harnesses for Ignition Controllers – Light Duty – Standard ¹⁾



P/N	Description	Connector	Length	Equivalent to
95.40.217-L	Output harness for P/N 66.00.350-6/-12	MIL, 17 pole, pin, 180°	L= 5/15/25/50 ft	

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Output Adaptor Harnesses for Ignition Controllers – Light Duty – Standard – Interface to ALTRONIC® Ignition Controllers

P/N	Description	Connector	Length	Equivalent to
06.02.027	Output adaptor harness for P/N 66.00.350-6/-12, use to replace ALTRONIC® CD200 ignition controller P/N 791070-6, 791070-8	MIL, 17 pole, pin, 180°	12 in	
06.02.028	Output adaptor harness for P/N 66.00.350-6/-12, use to replace ALTRONIC® CD200 ignition controller P/N 791070-12	MIL, 17 pole, pin, 180°	12 in	
77.49.029-L	Output adaptor harness for P/N 66.00.350-6/-12, use to replace ALTRONIC® CPU95 ignition controller P/N 791950-16	MIL, 17 pole, pin, 180°	L= 1/5/7/10 ft	



Junction Box & Accessories

P/N	Figure	Description	Equivalent to
06.05.075	1	Junction box	593600-1
15.07.134	2	Flex conduit, 3/4 in, black ¹⁾	
15.07.231	3	Fitting, 3/4 in, junction box to flex conduit	

¹⁾ Flex conduit needs to be ordered in m/ft in required length.

Ignition Controllers – Light Duty – Special

NEW



P/N	max. Outputs	Connector Style	Connectors		Pickup		Equivalent to
			Input	Output	Inputs	Voltage	
66.00.361-8	8	MIL	10 pole, pin	10 pole, socket	1	programmable via MICT	06.00.520
66.00.362-12	12	MIL	10 pole, pin	14 pole, socket	1	programmable via MICT	06.00.525



1



2



3

Ignition Controllers & Harnesses



NEW

MIC3+CATDI
MOTORTECH IGNITION CONTROLLER

MIC3+CEC
MOTORTECH IGNITION CONTROLLER

Based on the MIC3+ series, MOTORTECH produces special controllers as replacements for the OEM ignition systems used on **CATERPILLAR**® G3300 and G3400 and **WAUKESHA**® VGF and VHP series gas engines. Designed as an exchange device, the MIC3+CATDI and MIC3+CEC enable a quick conversion without great effort.



Scan QR Code®



Scan QR Code®

Ignition Controllers – Light Duty – Special – Retrofit for **CATERPILLAR**® G3300 and G3400 Series Gas Engines

P/N	max. Outputs	Connector Style	Connectors			Pickup		Equivalent to
			Input	Output	Analog Input	Inputs	Voltage	
66.00.356-8 ¹⁾	8	MIL	6 pole, pin	10 pole, pin	10 pole, socket	1	programmable via MICT	CAT DI Model – P/N 163-6164, MOTORTECH MIC500 – P/N 06.00.513
66.00.357-12 ²⁾	12	MIL	6 pole, pin	19 pole, pin	10 pole, socket	1	programmable via MICT	CAT DI Model – P/N 163-6108 MOTORTECH MIC500 – P/N 06.00.514

¹⁾ For use with G3304, G3306, G3406, G3408 ²⁾ For use with G3412

Ignition Controllers – Light Duty – Special – Retrofit for **WAUKESHA**® VGF and VHP Series Gas Engines

P/N	max. Outputs	Connector Style	Connectors			Pickup		Equivalent to
			Input	Output	Analog Input	Inputs	Voltage	
66.00.358-8 ¹⁾	8	MIL	7 pole, pin	10 pole, pin	10 pole, socket	1	programmable via MICT	CEC Models 811/811A – P/N 740608A, 740608 – P/N 69786A, 69786 – P/N 69787B, 69787 MOTORTECH MIC500 – P/N 06.00.515-6/-8
66.00.359-12 ²⁾	12	MIL	7 pole, pin	19 pole, pin	10 pole, socket	1	programmable via MICT	CEC Models 1211/1211A – P/N 740609A, 740609 – P/N 68788A, 69788 MOTORTECH MIC500 – P/N 06.00.516

¹⁾ For use with VGF F18, H24 and VHP F2895, F3521 ²⁾ For use with VGF L36 and VHP L5108, L5790, L7042

Analog Input Harness for Ignition Controllers – Light Duty – Special

P/N	Description	Connector	Length	Equivalent to
06.02.046-160	Analog input harness for P/N 66.00.356-8, 66.00.357-12, 66.00.358-8, 66.00.359-12	MIL, 10 pole, pin, 180°	160 in	

Ignition Controllers & Harnesses



Ignition Controllers – Light Duty – Standard

P/N	max. Outputs	Connector Style	Connectors		Inputs	Pickup Voltage	Equivalent to
			Input	Output			
66.00.410-8	8	MIL/terminal strip	terminal strip	17 pole, socket	3	programmable via MICT	
66.00.410-16	16	MIL/terminal strip	terminal strip	17 pole, socket	3	programmable via MICT	
66.00.424-8	8	MIL	35 pole, pin	17 pole, socket	2	programmable via MICT	
66.00.424-16	16	MIL	35 pole, pin	17 pole, socket	2	programmable via MICT	

Ignition Controllers – Light Duty – Standard (ATEX – II 3G Ex nA IIB T4)



P/N	max. Outputs	Connector Style	Connectors		Inputs	Pickup Voltage	Equivalent to
			Input	Output			
93.00.410-8	8	MIL/terminal strip	terminal strip	17 pole, socket	3	programmable via MICT	
93.00.410-16	16	MIL/terminal strip	terminal strip	17 pole, socket	3	programmable via MICT	

Ignition Controllers – Panel Mount – Standard



P/N	max. Outputs	Connector Style	Connectors		Inputs	Pickup Voltage	Equivalent to
			Input	Output			
66.00.400-8	8	terminal strip	terminal strip	terminal strip	3	programmable via MICT	
66.00.400-16	16	terminal strip	terminal strip	terminal strip	3	programmable via MICT	

Ignition Controllers – Panel Mount – Standard (ATEX – II 3G Ex nA IIB T4 X) ¹⁾



P/N	max. Outputs	Connector Style	Connectors		Inputs	Pickup Voltage	Equivalent to
			Input	Output			
93.00.400-8	8	terminal strip	terminal strip	terminal strip	3	programmable via MICT	
93.00.400-16	16	terminal strip	terminal strip	terminal strip	3	programmable via MICT	

¹⁾ Ignition controllers built into stainless steel enclosure.

MIC3+CATDI | MIC3+CEC | MIC4 Ignition Controller

Light Duty (LD)



Panel Mount (PM)



Heavy Duty (HD)



back

Ignition Controllers & Harnesses

Ignition Controllers – Heavy Duty – Standard



P/N	max. Outputs	Connector Style	Connectors		Inputs	Pickup	Equivalent to
			Input	Output		Voltage	
66.00.440-8	8	MIL/terminal strip	terminal strip	17 pole, socket	3	programmable via MICT	
66.00.440-16	16	MIL/terminal strip	terminal strip	17 pole, socket	3	programmable via MICT	

Input Harnesses for Ignition Controllers – Light Duty – Standard

P/N	Description	Interfaces	Connector	Length	Pickup
06.02.034-160	Input harness for P/N 66.00.424-8/-16	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive
06.02.035-160	Input harness for P/N 66.00.424-8/-16	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	2 inductive
06.02.036-160	Input harness for P/N 66.00.424-8/-16	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 Hall effect
06.02.040-160	Input harness for P/N 66.00.424-8/-16	RS485 (2 wire)	MIL, 35 pole, socket, 180°	160 in	1 Hall effect
06.02.041-160	Input harness for P/N 66.00.424-8/-16	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive, 1 magnetic

Input Harnesses for Ignition Controllers – Light Duty – Standard ¹⁾



P/N	Description	Interfaces	Connector	Length	Pickup
95.30.300-L	Input harness for P/N 66.00.424-8/-16	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 inductive
95.30.301-L	Input harness for P/N 66.00.424-8/-16	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 Hall effect
95.30.302-L	Input harness for P/N 66.00.424-8/-16	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 magnetic

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Output Harnesses for Ignition Controllers – Light Duty/Heavy Duty – Standard

P/N	Description	Connector	Length	Equivalent to
06.02.617-L	Output harness for P/N 66.00.410-8/-16, P/N 66.00.424-8/-16 and P/N 66.00.440-8/-16	MIL, 17 pole, pin, 180°	L= 160/320 in	

Output Harnesses for Ignition Controllers – Light Duty/Heavy Duty – Standard ¹⁾



P/N	Description	Connector	Length	Equivalent to
95.40.217-L	Output harness for P/N 66.00.410-8/-16, P/N 66.00.424-8/-16 and P/N 66.00.440-8/-16	MIL, 17 pole, pin, 180°	L= 5/15/25/50 ft	

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Output Adaptor Harnesses for Ignition Controllers – Light Duty – Standard – Interface to ALTRONIC® Ignition Controllers

P/N	Description	Connector	Length	Equivalent to
06.02.027	Output adaptor harness for P/N 66.00.410-8/-16, P/N 66.00.424-8/-16 and P/N 66.00.440-8/-16, use to replace ALTRONIC® CD200 ignition controller P/N 791070-6 , 791070-8	MIL, 17 pole, pin, 180°	12 in	
06.02.028	Output adaptor harness for P/N 66.00.410-8/-16, P/N 66.00.424-8/-16 and P/N 66.00.440-8/-16, use to replace ALTRONIC® CD200 ignition controller P/N 791070-12	MIL, 17 pole, pin, 180°	12 in	
77.49.029-L	Output adaptor harness for P/N 66.00.410-8/-16, P/N 66.00.424-8/-16 and P/N 66.00.440-8/-16, use to replace ALTRONIC® CPU95 ignition controller P/N 791950-16	MIL, 17 pole, pin, 180°	L= 1/5/7/10 ft	

Junction Box & Accessories



P/N	Figure	Description	Equivalent to
06.05.075	1	Junction box	593600-1
93.05.075	1	Junction box (ATEX – II 3G Ex e nA IIA T4)	593600-1
15.07.134	2	Flex conduit, 3/4 in, black ¹⁾	
15.07.231	3	Fitting, 3/4 in, junction box to flex conduit	

¹⁾ Flex conduit needs to be ordered in m/ft in required length.

Ignition Controllers – Light Duty – Special **NEW**



P/N	max. Outputs	Connector Style	Connectors		Inputs	Pickup	Equivalent to
			Input	Output		Voltage	
66.00.413-16	16	MIL	10 pole, pin	19 pole, socket	1	programmable via MICT	06.00.530
66.00.427-16 ¹⁾	16	MIL	3/4/5 pole, pin	19 pole, socket	2	programmable via MICT	MWM®/DEUTZ® TEM-ZS1 - P/N 1229 8101 KM MWM®/DEUTZ® TEM-ZS3 - P/N 1232 0993 KM

¹⁾ **NOTE:** Can be used for conversions of MWM® TEM-ZS ignition controllers only when TEM engine management system is also replaced by ALL-IN-ONE.

Bracket Sets for Conversions

P/N	Description	Equivalent to
75.10.404	Bracket set for conversion of ALTRONIC® CPU95 ignition controller to MIC4 Light Duty/Heavy Duty	
75.30.146	Universal adaptor plate – MIC4 Light Duty/Heavy Duty	



1



2



3

■ Ignition Controllers & Harnesses

MIC4-ZS MOTORTECH IGNITION CONTROLLER

Based on the MIC4 series, MOTORTECH produces a special controller version as a replacement for the TEM-ZS1 and TEM-ZS3 ignition system used on **MWM®/DEUTZ®** gas engines. Designed as an exchange device, the MIC4-ZS enables a quick conversion without great effort.

In addition to the MIC4-ZS ignition controller, the prepared conversion kits include the required high-performance ignition coils. Pre-chamber spark plugs or spark plug leads can be re-used, as these ignition coils have the same secondary connections as the original ones. The ignition coils – designed for MOTORTECH ignition controllers with MOST technology – guarantee the ideal performance support, especially when it comes to alternative combustibles with alternating or relatively low fuel value, e.g. biogas, mine gas, woodgas, sewage gas, landfill gas etc.



Scan QR Code®

MIC4-ZS Kits

P/N	Description	Quantity	Equivalent to
75.30.150-08	MIC4-ZS kit for MWM®/DEUTZ® 8 cylinder gas engines <i>Contains:</i> ■ MIC4-ZS ignition controller P/N 66.00.425-16 ■ High-performance ignition coil P/N 06.50.065	1 pc 8 pcs	MWM®/DEUTZ® TEM-ZS1 – P/N 1229 8101 KM MWM®/DEUTZ® TEM-ZS3 – P/N 1232 0993 KM
75.30.150-12	MIC4-ZS kit for MWM®/DEUTZ® 12 cylinder gas engines <i>Contains:</i> ■ MIC4-ZS ignition controller P/N 66.00.425-16 ■ High-performance ignition coil P/N 06.50.065	1 pc 12 pcs	MWM®/DEUTZ® TEM-ZS1 – P/N 1229 8101 KM MWM®/DEUTZ® TEM-ZS3 – P/N 1232 0993 KM
75.30.150-16	MIC4-ZS kit for MWM®/DEUTZ® 16 cylinder gas engines <i>Contains:</i> ■ MIC4-ZS ignition controller P/N 66.00.425-16 ■ High-performance ignition coil P/N 06.50.065	1 pc 16 pcs	MWM®/DEUTZ® TEM-ZS1 – P/N 1229 8101 KM MWM®/DEUTZ® TEM-ZS3 – P/N 1232 0993 KM

Accessories (optional)

P/N	Description	Quantity	Equivalent to
06.85.179-20	PolyMot™ spark plug lead for MWM®/DEUTZ® gas engines ■ TBG620 series ■ TCG2020 series	8, 12 or 16 pcs per kit	1230 0136
06.85.310H-11	PolyMot™ spark plug lead for MWM®/DEUTZ® gas engines ■ TBG616 series ■ TCG2016 series	8, 12 or 16 pcs per kit	1227 8370
GL3-3	DENSO® spark plug ■ Thread size M18x1.5, thread reach 0.750 in (19.0 mm) ■ J-type electrode design (Ir/Pt) ■ HEX 13/16 in (20.8 mm) ■ Recommended for natural gas applications	8, 12 or 16 pcs per kit	– 1242 0290, RB75WPCC-1 – 1242 0480, 18GZ5-77-2
GL3-5	DENSO® spark plug ■ Thread size M18x1.5, thread reach 0.750 in (19.0 mm) ■ J-type electrode design (Ir/Ir) ■ HEX 13/16 in (20.8 mm) ■ Recommended for special gas/natural gas applications	8, 12 or 16 pcs per kit	– 1242 0290, RB75WPCC-1 – 1242 0480, 18GZ5-77-2
alternative B8324	MOTORTECH MHP spark plug ■ Thread size M18x1.5, thread reach 0.750 in (19.0 mm) ■ J-type electrode design (Ir/Ir) ■ HEX 13/16 in (20.8 mm) ■ Recommended for special gas/natural gas applications	8, 12 or 16 pcs per kit	1242 0290, 1242 0480

Ignition Controllers & Harnesses



Ignition Controllers – Heavy Duty – Standard

P/N	max. Outputs	Connector Style	Connectors		Pickup		Equivalent to
			Input	Output	Inputs	Voltage	
66.00.540-20	20	MIL/terminal strip	terminal strip	35 pole, socket	3	programmable via MICT	MIC850P/N 66.00.855-24/-24-D
66.00.541-20	20	MIL	35 pole, pin	35 pole, socket	2	programmable via MICT	
66.00.544-20	20	MIL	35 pole, pin	14/17 pole, socket	3	programmable via MICT	

Input Harnesses for Ignition Controllers – Heavy Duty – Standard

P/N	Description	Interfaces	Connector	Length	Pickup
06.02.034-160	Input harness for P/N 66.00.541-20	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive
06.02.035-160	Input harness for P/N 66.00.541-20	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	2 inductive
06.02.036-160	Input harness for P/N 66.00.541-20	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 Hall effect
06.02.040-160	Input harness for P/N 66.00.541-20	RS485 (2 wire)	MIL, 35 pole, socket, 180°	160 in	1 Hall effect
06.02.041-160	Input harness for P/N 66.00.541-20	CAN Bus/RS485 (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive, 1 magnetic
06.02.048-160	Input harness for P/N 66.00.544-20	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive, 2 magnetic

Input Harnesses for Ignition Controllers – Light Duty – Standard ¹⁾



P/N	Description	Interfaces	Connector	Length	Pickup
95.30.300-L	Input harness for P/N 66.00.541-20	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 inductive
95.30.301-L	Input harness for P/N 66.00.541-20	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 Hall effect
95.30.302-L	Input harness for P/N 66.00.541-20	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	L= 5/15/25/50 ft	1 magnetic

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Output Harnesses for Ignition Controllers – Heavy Duty – Standard ¹⁾



P/N	Description	Connector	Length	Equivalent to
95.40.235-L	Output harness for P/N 66.00.540-20 and P/N 66.00.541-20	MIL, 35 pole, pin, 180°	L= 5/15/25/50 ft	

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Ignition Controllers – Heavy Duty – Special



P/N	max. Outputs	Connector Style	Connectors		Pickup		Equivalent to
			Input	Output	Inputs	Voltage	
66.00.542-20	20	MIL/terminal strip	terminal strip	14/17 pole, socket	3	programmable via MICT	WOODWARD® IC9xx, MIC850P/N 66.00.851-24/-24-D

Ignition Controllers & Harnesses

Ignition Controllers – Heavy Duty – Special (ATEX – II 3G Ex nA IIB T4 X)



P/N	max. Outputs	Connector Style	Connectors		Pickup		Equivalent to
			Input	Output	Inputs	Voltage	
93.00.542-20	20	MIL/terminal strip	terminal strip	14/17 pole, socket	3	programmable via MICT	WOODWARD® IC9xx, MIC850 P/N 66.00.851-24/-24-D

Output Harnesses for Ignition Controllers – Heavy Duty – Standard/Special ¹⁾



P/N	Description	Connector	Length	Equivalent to
95.40.214-L	Output harness for P/N 66.00.542-20 and P/N 66.00.544-20	MIL, 14 pole, pin, 180°	L= 5/15/25/50 ft	
95.40.217-L	Output harness for P/N 66.00.542-20 and P/N 66.00.544-20	MIL, 17 pole, pin, 180°	L= 5/15/25/50 ft	

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.

Output Adaptor Harnesses for Ignition Controllers – Heavy Duty – Standard/Special

P/N	Description	Connector	Length	Equivalent to
77.49.006	Output adaptor harness for P/N 66.00.540-20 and P/N 66.00.541-20, use to replace WOODWARD® IC9xx ignition controller and MIC850 P/N 66.00.851-24/-24-D	MIL, 35 pole, pin, 90°	16 in	
77.49.007-L	Output adaptor harness for P/N 66.00.540-20 and P/N 66.00.541-20, use to replace ALTRONIC® CPU95 ignition controller P/N 791950-16	MIL, 35 pole, pin, 90°	L= 1/5/7/10 ft	
77.49.008	Output adaptor harness for P/N 66.00.540-20 and P/N 66.00.541-20, use to replace MIC750 ignition controller P/N 66.00.750/-D	MIL, 35 pole, pin, 90°	16 in	

Junction Box & Accessories



P/N	Figure	Description	Equivalent to
06.05.075	1	Junction box	593600-1
93.05.075	1	Junction box (ATEX – II 3G Ex e nA IIA T4)	593600-1
15.07.134	2	Flex conduit, 3/4 in, black ¹⁾	
15.07.231	3	Fitting, 3/4 in, junction box to flex conduit	

¹⁾ Flex conduit needs to be ordered in m/ft in required length.



1



2



3

Ignition Controllers & Harnesses



NEW

MIC6

MOTORTECH IGNITION CONTROLLER

MIC6 Ignition Controller For Stationary and Marine Applications

MOTORTECH expands its MIC product line with the new MIC6 series. The latest development is ideally suited for medium and high speed applications and convinces with a future oriented electronical concept for more power and a significantly higher degree of efficiency.

The specially developed MIC6-Marine version meets the strict technical requirements of marine applications and certification societies and comes with extra features like a redundant pickup setup.



General

- For medium (900 rpm nominal) and high speed applications (1800 rpm nominal)
- 1000 mJ primary energy max.
- Adjustable spark duration and intensity
- Constant spark intensity via adjusted duration
- 6 pickup inputs for redundant pickup setup

Technical Data & Features

- 18 to 32 V DC supply voltage
- 24 ignition outputs
- 250 V DC primary voltage
- 1000 mJ primary energy (when firing 24 outputs at 900 rpm)
600 mJ primary energy (when firing 24 outputs at 1800 rpm)
- 0.1° crankshaft accuracy
- 6 pickup inputs for integration of 2 redundant pickup sets
- Triggered by 1, 2 or 3 pickups per set (magnetic, Hall effect or inductive/configurable)
- Multiple ignition timing control via
 - Speed curve
 - 0 to 20 mA analog input
 - 0 to 10 V analog input
- Multiple energy control via MOST (MOTORTECH Output Stage Technology)
- Programmable firing order
- 3 multipurpose outputs (GPO)
- 2 Auxiliary Synchronization Outputs (ASO) which can support a detonation control system (e.g. DetCon) or fuel injection pump controllers
- Ignition release input
- Go/NoGo output
- Overspeed shutdown function
- Access controlled

- Ignition diagnostics (primary and secondary)
- More internal memory for faster signal processing and trend data for advanced diagnostics
- Integrated CANopen and RS485 (Modbus RTU) interface
- Easy access per USB port

Ignition Diagnostics

- Runtime data
- Alarm and error messages
- Data logging
- Primary and secondary misfire detection
- Cylinder individual high voltage calculation (kV)
- 11 LEDs provide a quick system state overview

Interfaces

- CAN Bus 2.0b interface (CANopen/SAE J1939 protocol)
- RS485 interface (Modbus RTU)
- USB 1.1 interface

Configuration

- Using the graphic user interface MICT (MOTORTECH Integrated Configuration Tool)

Housing/Connections

- Protection class IP65
- MIL style connectors


Certifications

- CSA (Class I, Division 2, Group C, D; T4) ¹⁾
- Marine type approval certification in accordance with DNV GL, Bureau Veritas, Lloyd's Register ¹⁾
- ATEX (II 3G EX nA IIB T4 X) – on request
- CE

¹⁾ Certification for MIC6 series in preparation.

■ Ignition Controllers & Harnesses

System Overview MIC6 Series



Legend

Necessary Components

- 1 MIC6 ignition controller
- 2 Pickup – Set 1
 - 2a Pickup lead*
 - 2b Pickup*
- 3 Pickup – Set 2
(for redundant purposes)
 - 3a Pickup lead*
 - 3b Pickup*
- 4 Reluctor pins/trigger magnets
alternative
- 5 Trigger disc
alternative
Trigger drive
- 6 Output harness*
- 7 Ignition coil*
- 8 1 primary lead/spark plug lead
per ignition coil*

* Shielded and unshielded versions available.

Accessories

- A Junction box
- B AlphaRail/LiteRail – ignition wiring rail

System Enhancement

- C DetCon20 – Detonation controller

Description

- V Camshaft
- W Crankshaft
- X Engine
- Y Cylinder
- Z Harness to connect the ignition wiring rails and the junction box

Established Pickup Arrangements

3-Pickup Arrangement for 4-Stroke Engines

- 1) Crankshaft (Reset)
Magnetic pickup
(holes, pins, teeth, screws)
 - 2) Crankshaft (Speed)
Magnetic pickup
(holes, pins, teeth, screws)
 - 3) Camshaft (Reset)
Hall effect pickup
(magnets)
- alternative*
- 3) Camshaft (Reset)
Inductive pickup
(pins, screws, slots)

1-Pickup Arrangement for 4-Stroke Engines

- 1) Camshaft (N+1/N-1)
Hall effect pickup
(disc with magnets)
- alternative*
- 1) Camshaft (N+1/N-1)
Inductive pickup
(disc with pins, screws, slots)

2-Pickup Arrangement for 2-Stroke Engines

- 1) Crankshaft (Reset)
Magnetic pickup
(holes, pins, teeth, screws)
- 2) Crankshaft (Speed)
Magnetic pickup
(holes, pins, teeth, screws)

Ignition Controllers & Harnesses



For Stationary Applications



Ignition Controllers – **Heavy Duty** – Standard – For High Speed Applications ¹⁾

P/N	max. Outputs	Connector Style	Connectors		Pickup		Equivalent to
			Input	Output	Inputs	Voltage	
66.00.645-24	24	MIL	35 pole, pin	35 pole, socket	3	programmable via MICT	
66.00.646-24	24	MIL	35/26 pole, pin	35 pole, socket	6	programmable via MICT	
66.00.647-24	24	MIL/terminal strip	terminal strip	35 pole, socket	6	programmable via MICT	

¹⁾ Consult factory for ignition controllers for medium speed applications.

Input Harnesses for Ignition Controllers – **Heavy Duty** – Standard

P/N	Description	Interfaces	Connector	Length	Pickup
06.02.048-160	Input harness for P/N 66.00.645-24 and P/N 66.00.646-24	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive, 2 magnetic
06.02.049-160	Input harness for P/N 66.00.646-24	CAN Bus/RS485 (4 wire)	MIL, 26 pole, socket, 180°	160 in	1 inductive, 2 magnetic



Output Harnesses for Ignition Controllers – **Heavy Duty** – Standard ¹⁾

P/N	Description	Connector	Length	Equivalent to
95.40.235-L	Output harness for P/N 66.00.645-24, P/N 66.00.646-24 and P/N 66.00.647-24	MIL, 35 pole, pin, 180°	L= 5/15/25/50 ft	

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.



Junction Box & Accessories

P/N	Figure	Description	Equivalent to
06.05.075	1	Junction box	593600-1
15.07.134	2	Flex conduit, 3/4 in, black ¹⁾	
15.07.231	3	Fitting, 3/4 in, junction box to flex conduit	

¹⁾ Flex conduit needs to be ordered in m/ft in required length.



1



2



3

Certification for MIC6 series in preparation.

■ Ignition Controllers & Harnesses



MIC6-Marine

MOTORTECH IGNITION CONTROLLER



For Marine Applications

Ignition Controllers – **Heavy Duty** – Standard – For High Speed Applications ¹⁾

MOST

P/N	max. Outputs	Connector Style	Connectors		Pickup		Equivalent to
			Input	Output	Inputs	Voltage	
92.00.646-24	24	MIL	35/26 pole, pin	35 pole, socket	6	programmable via MICT	

¹⁾ Consult factory for ignition controllers for medium speed applications.

Input Harnesses for Ignition Controllers – **Heavy Duty** – Standard

P/N	Description	Interfaces	Connector	Length	Pickup
92.02.001-160	Input harness for P/N 92.00.646-24	CAN Bus (4 wire)	MIL, 35 pole, socket, 180°	160 in	1 inductive, 2 magnetic
92.02.002-160	Input harness for P/N 92.00.646-24	CAN Bus/RS485 (4 wire)	MIL, 26 pole, socket, 180°	160 in	1 inductive, 2 magnetic

NOTE: Please consult factory for individual layout of Marine certified output harnesses.

■ Ignition Controllers & Harnesses



Ignition Control Visualization

The operating data of MIC3/3+, MIC4 and MIC5 series ignition controllers will be completely visualized via HMI module (Human Machine Interface). The overview screen shows the relevant information as engine speed, ignition timing and status of pickups, ignition outputs or active parameter set.

The PowerView3 also allows justification of various ignition parameters such as ignition timing and energy. Functions as the self-test for error diagnostics can also be executed via HMI module. The control keys guarantee simple navigation through different display pages and menus. All in all the PowerView3 HMI module is also able to provide error diagnostics on-site without requiring a laptop!



1

The PowerView3 is also available for data visualization of:

- DetCon Detonation Control
- TempScan20 Temperature Module

General Features

- Visualization of ignition, detonation and temperature control via CAN bus
- Access control
- Display of CAN connection status
- Several display configurations (languages, date, display calibration, etc.)
- For assembly in control panels
- Day and night mode
- CSA® certified (Class I, Division 2, Group C, D; T4)

Ignition Control (MIC3/3+/MIC4/MIC5 series)

- Overview with status indication for
 - Pickup signals
 - Active schedule
 - Analog display of engine speed
 - Ignition timing
 - Spark plugs (operating hours)
- Display of global ignition timing dependent on
 - Base ignition timing
 - Potentiometer adjustment
 - Analog current and voltage input
 - Speed curve
- Displays the ignition of each cylinder
 - Ignition voltage
 - Misfires
- Display of misfires
 - Primary and secondary sided wiring errors
 - Type of error (no connection/short circuit)
- Display and adjustment of energy
 - Spark duration
 - Spark intensity
- Display and adjustment of firing angles and ignition energy
- Self-test activation
- Warning, alarm and error messages


Sample Screens – MIC3/3+/MIC4/MIC5

MIC Overview




- Status displays (pickup, ignition outputs, ignition enabled, system status, schedule)
- Displays the current engine speed
- Shows the current global ignition timing in ° crankshaft
- Displays the previous operating hours of the spark plugs

Ignition



- Displays the estimated ignition voltage for each individual cylinder
- Display of current and past misfires of each individual cylinder

Secondary Voltage



- Display of estimated secondary voltage of all selected cylinders
- Cylinders can be displayed and hidden individually
- Zoom function for detailed view of secondary voltage
- Navigation within the timeline

PowerView3 HMI Modules & Activation Codes



P/N	Figure	Description
06.05.085	1	PowerView3 HMI module
06.05.185	2	PowerView3 HMI module, built into stainless steel enclosure
06.05.186	3	PowerView3 HMI modules (2 pcs), built into stainless steel enclosure, incl. activation codes for visualization of MIC3/3+/MIC4/MIC5 data, for use with dual ignition controller applications
06.05.187	4	PowerView3 HMI module, built into steel enclosure with sight window
06.05.086-F		PowerView3 activation code for visualization of MIC3/3+/MIC4/MIC5 data – Activation code has to be ordered separately with each PowerView3 HMI module
06.05.086-U		PowerView3 activation code for visualization of MIC3/3+/MIC4/MIC5 data – Only available for upgrade of existing PowerView3 HMI module in the field



■ Ignition Controllers & Harnesses

MOT601 MOTORTECH SINGLE CYLINDER IGNITION SYSTEM

The self-powered MOT601 is a capacitor discharge ignition system for use on spark-ignited, single cylinder gas engines with large flywheels. Closely mounted to the engine's flywheel, the electronic components are supplied with power by magnetic charging circuitry.

Features

- Applicable for single cylinder engines with different flywheel sizes
- Self-powered electromagnetic system, no need for external power
- High primary energy
- Using crankshaft reference timing
- High accuracy ignition timing
- Two separate ignition timings (startup and nominal)
- Safety shutdown input
- Supplies panel power

Benefits


- Price effective system and accessories
- Mainly maintenance-free system due to non-moving parts that wear out
- All components are available as spare parts and can be used with competitive systems
- 1 year warranty



Mode of Operation

The charging bar **5** with three strong magnets attached to the flywheel passes the charging generator **3** that is attached to the engine in a fixed position at every revolution of the flywheel. At every revolution the generator module charges a capacitor in the ignition module **2** as a result of the magnetic field.

The trigger bar **6** with two magnets, which is likewise attached to the flywheel, passes a pickup coil **4** that is attached to the engine in a fixed position at every revolution of the engine. When the trigger bar passes the pickup coil, the energy stored in the capacitor is discharged into the attached ignition coil **7**.



Ignition Controllers & Harnesses



Ignition System for Single Cylinder Engines

P/N	Figure	Description	Equivalent to
MOT601	1	MOT601 ignition system for single cylinder engines	AEI® FM601, ARROW® SFI-KIT, MURPHY® 72-70-0125

Subcomponents

P/N	Figure	Description	Equivalent to
M-400A-8814	2	Electronic ignition module	AEI® 400A-8814, ARROW® A400A-8814, MURPHY® 72-00-0024,
M-260D-8810	3	Charging generator	AEI® 260D-8810, ARROW® A260D-8810, MURPHY® 72-00-0025
M-270A-8817	4	Magnetic pickup harness	AEI® 270A-8817, ARROW® A400A-8817, MURPHY® 72-00-0026
M-400A-8813	5	Magnetic charging bar	AEI® 400A-8813, ARROW® A400A-8813, MURPHY® 72-00-0027
M-400A-8811	6	Magnetic trigger bar	AEI® 400A-8811, ARROW® A400A-8811, MURPHY® 72-00-0028
06.50.055	7	Ignition coil	AEI® 1187, ARROW® 330-2-AI-46, MURPHY® 72-70-0235



Ignition Controllers & Harnesses

UNSHIELDED

Harnesses for Competition Ignition Control Systems

For use with competitor ignition systems, MOTORTECH offers a special range of harnesses. Based on the reliable design and quality of MOTORTECH's standard harnesses, this series represents a suitable replacement for existing harnesses in the field.



Output Harnesses for ALTRONIC® Ignition Systems – For Unshielded Applications

P/N	Figure	Description	Connector	Length	Equivalent to
06.31.030-1	1	Output harness for ALT III ignition magneto, for unshielded applications up to 8 cylinders	MIL, 14 pole, socket, 180°	180 in	393018-1, 2W-3742, 69703, 178622
06.31.030-2	1	Output harness for ALT III ignition magneto, for unshielded applications up to 12 cylinders	MIL, 14 pole, socket, 180°	180 in	393018-2, 2W-3744, 269717B
06.31.032-1	1	Output harness for ALT III/III-CPU/V ignition magneto, CPU95-EVS (ignition unit to J-Box or DC-DC power supply), for unshielded applications up to 6 cylinders	MIL, 7 pole, socket, 180°	72 in	393023-1
06.31.032-2	1	Output harness for ALT III/III-CPU/V ignition magneto, CPU95-EVS (ignition unit to J-Box or DC-DC power supply), for unshielded applications up to 6 cylinders	MIL, 7 pole, socket, 180°	180 in	393023-2, 2W-3748, 69692B
06.70.191-180	1	Output harness for DISN800C, DISN801M, CD200D, CPU90, CPU95, CPU95EVS, for unshielded applications up to 12 cylinders	MIL, 19 pole, socket, 180°	180 in	793012-6, 793012-8, 793012-12
06.77.006-72	1	Output harness for ALT V ignition magneto, for unshielded applications up to 6 cylinders	MIL, 5 pole, socket, 180°	72 in	593041-1, 209728
06.77.006-96	1	Output harness for ALT V ignition magneto, for unshielded applications up to 6 cylinders	MIL, 5 pole, socket, 180°	96 in	593041-2



1



2



3



4



5



6

Output Harnesses for **ALTRONIC®** Ignition Systems – For Shielded Applications

P/N	Figure	Description	Connector	Length		Equivalent to
				Conduit	Conductor	
95.30.007-1	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	48 in	72 in	393013-1, 393013-3, 393013-7, 178788, 033-099-004, 208502E, BM-11533-B
95.30.007-2	2	Output harness for ALT III/III-CPU ignition magneto, CPU95-EVS (DC-DC power supply), for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	48 in	180 in	393013-2
95.30.007-4	2	Output harness for ALT III/III-CPU ignition magneto, CPU95-EVS (DC-DC power supply), for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	20 in	60 in	393013-4, 178788A
95.30.007-5	2	Output harness for ALT III/III-CPU ignition magneto, CPU95-EVS (DC-DC power supply), for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	120 in	300 in	393013-5
95.30.007-8	2	Output harness for ALT III/III-CPU ignition magneto, CPU95-EVS (DC-DC power supply), for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	60 in	72 in	393013-8
95.30.007-9	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	48 in	240 in	393013-9
95.30.007-10	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	38 in	72 in	393013-6, 393013-10
95.30.007-12	2	Output harness for ALT III/III-CPU ignition magneto, CPU95-EVS (DC-DC power supply), for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	26 in	48 in	393013-12
95.30.007-13	2	Output harness for ALT III/III-CPU ignition magneto, CPU95-EVS (DC-DC power supply), for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	30 in	48 in	393013-13
95.30.007-14	2	Output harness for ALT III/III-CPU ignition magneto, CPU95-EVS (DC-DC power supply), for shielded applications up to 6 cylinders	MIL, 7 pole, socket, 90°	30 in	80 in	393013-14
95.30.008-1	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 8 cylinders	MIL, 14 pole, socket, 90°	48 in	180 in	393014-1
95.30.008-2	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 12 cylinders	MIL, 14 pole, socket, 90°	48 in	180 in	393014-2
95.30.008-3	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 8 cylinders	MIL, 14 pole, socket, 90°	20 in	42 in	393014-3, 178803
95.30.008-4	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 12 cylinders	MIL, 14 pole, socket, 90°	48 in	72 in	393014-4, 4W-5466, 208502C
95.30.008-5	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 8 cylinders	MIL, 14 pole, socket, 90°	120 in	300 in	393014-5
95.30.008-6	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 12 cylinders	MIL, 14 pole, socket, 90°	120 in	300 in	393014-6
95.30.008-7	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 8 cylinders	MIL, 14 pole, socket, 90°	48 in	72 in	393014-7, 4W-5468
95.30.008-8	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 12 cylinders	MIL, 14 pole, socket, 90°	36 in	60 in	393014-8, 178804
95.30.008-9	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 12 cylinders	MIL, 14 pole, socket, 90°	66 in	96 in	393014-9
95.30.008-10	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 8 cylinders	MIL, 14 pole, socket, 90°	48 in	60 in	393014-10
95.30.008-11	2	Output harness for ALT III/III-CPU ignition magneto, for shielded applications up to 8 cylinders	MIL, 14 pole, socket, 90°	36 in	60 in	393014-11

Harnesses for **WAUKESHA®** VHP Series Gas Engines with ESM

P/N	Figure	Description	Length	Equivalent to
A740749-MOT	3	Harness, crankshaft pickup	45 in	A740749
A740750-MOT	4	Harness, camshaft pickup	43 in	A740750
740744-MOT	5	Harness, electric start	46 in	740744
740753-MOT	6	Harness, ground, left bank to right bank	94 in	740753

Ignition Coils

UNSHIELDED

New MOTORTECH Style

Ignition coils are becoming more and more important in modern, state of the art ignition systems. MOTORTECH offers a series of high performance ignition coils produced in its European facilities which are specially designed for use with newest technologies of MOTORTECH ignitions controllers:

- MOST – MOTORTECH Output Stage Technology of MOTORTECH MIC3/3+, MIC4, MIC5 and MIC6 ignition controllers
- Ideally suited for ignition of alternative fuels such as biogas



P/N	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.100	red	#10-32 UNF studs	M6	(-) ground	X (MIC3/3+/4/5)	
06.50.102	red	#10-32 UNF studs	female	(-) ground	X (MIC3/3+/4/5)	
06.50.104 ¹⁾	blue	#10-32 UNF studs	M6	(-) ground	X (MIC3/3+/4/5/6)	
06.50.105 ¹⁾	blue	#10-32 UNF studs	female	(-) ground	X (MIC3/3+/4/5/6)	
06.50.112	blue	#10-32 UNF studs	M6	(-) ground	X (MIC3/3+/4/5/6)	
06.50.113	blue	#10-32 UNF studs	female	(-) ground	X (MIC3/3+/4/5/6)	
06.50.300 ²⁾	blue	#10-32 UNF studs	M6	(-) ground	X (MIC3/3+)	
06.50.301 ²⁾	blue	#10-32 UNF studs	female	(-) ground	X (MIC3/3+)	

¹⁾ Ignition coils only available as spare parts. ²⁾ Only for use with MIC3/3+ ignition controllers.


MOST

MOTORTECH OUTPUT STAGE TECHNOLOGY

MOST* works with the following principles:

- adjustable ignition spark duration with different available ignition voltages
- constant spark intensity via adjusted ignition spark duration
- 300 to 1000 mJ of primary energy (device dependent) are available

* Patented Technology US 8,893,692 B2



Ignition Coils



MOTORTECH Style

Several EPOXY ignition coils with different ignition characteristics are available for unshielded applications. These coils, commonly used with MIC500 and MIC850 or ALTRONIC® CPU95 series ignition controllers, feature a screw type high voltage termination and are designed to function with the appropriate high voltage indication systems.



P/N	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.003 ¹⁾	06.50.007	black	#10-32 UNF studs	M6	(-) ground	X (MIC3/3+/4/5)	118257
06.50.060 ²⁾		black	#10-32 UNF studs	M6	(-) ground	not applicable	76.64.302

¹⁾ Also for use with MIC500 and MIC850 ignition controllers.

²⁾ For use with ALTRONIC® CPU95 ignition controllers.

ALTRONIC® Style

For existing installations with ALTRONIC® ignition coils, MOTORTECH offers a series of replacement products. The ignition coils are designed to have the same characteristics in regards of standard and extended duration as well as the electrical characteristics to function with the ALTRONIC® patented “Spark Reference” high voltage indication system. See chart below for cross reference numbers.



P/N	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.053	black	#10-32 UNF studs	female	(+) ground	not applicable	291001, 1215 3964
06.50.054	red	#10-32 UNF studs	female	(-) ground	not applicable	591010, Z00-17-001-00, 837/13, 69694B, 4W-5439
06.50.055	blue	#10-32 UNF studs	female	(-) ground	not applicable	501061, Z00-17-000-00, 837/12, 69694, 2W-3747, 76.64.005, 1215 3965
06.50.065	black	#10-32 UNF studs	female	(-) ground	X (MIC3/3+/4/5)	

Thousands of smaller gas engines (including CUMMINS®) are equipped with low cost ignition controllers like ALTRONIC® CD1 or CD200 series that use this compact coil. MOTORTECH offers an alternative.



P/N	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.103	black	#10-32 UNF studs	male	(-) ground	not applicable	591040, 3394578

Ignition Coils

UNSHIELDED

Ignition Coils for CATERPILLAR® Gas Engines

The rising demand for specialized ignition coils has led MOTORTECH to the decision to design a new series of ignition coils, specially made for use with CATERPILLAR® gas engines.

- Compatible with original ignition coils
- Support CATERPILLAR® ignition systems
- Made in Europe



For CATERPILLAR® G3400/C & G3500/B/C/E/H Series Gas Engines (Non CSA Applications)

P/N	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.141	white	DEUTSCH® connector	female	(-) ground	not applicable	437-4049, 232-6348, 165-1591, 131-3277, 129-8802, 108-0615
06.50.145 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	437-4049, 232-6348, 165-1591, 131-3277, 129-8802, 108-0615
06.50.143	white	DEUTSCH® connector	female	(-) ground	not applicable	232-6352, 213-7443
06.50.147 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	232-6352, 213-7443
06.50.151	white	DEUTSCH® connector	female	(-) ground	not applicable	418-4861, 232-6346, 165-1589, 124-0749
06.50.155 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	418-4861, 232-6346, 165-1589, 124-0749
06.50.153	white	DEUTSCH® connector	female	(-) ground	not applicable	437-4106, 232-6350, 199-9011
06.50.157 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	437-4106, 232-6350, 199-9011
NEW 06.50.159	white	DEUTSCH® connector	female	(-) ground	not applicable	356-3701
06.50.160 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X	356-3701



¹⁾ Only for use with MIC3/3+, MIC4 and MIC5 ignition controllers.

For CATERPILLAR® G3400/C & G3500/B Series Gas Engines (CSA Applications)

P/N	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.142	white	DEUTSCH® connector	female	(-) ground	not applicable	232-6349, 165-1592, 122-8070
06.50.146 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	232-6349, 165-1592, 122-8070
06.50.144	white	DEUTSCH® connector	female	(-) ground	not applicable	232-6353, 213-7444
06.50.148 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	232-6353, 213-7444
06.50.152	white	DEUTSCH® connector	female	(-) ground	not applicable	437-4047, 232-6347, 165-1590
06.50.156 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	437-4047, 232-6347, 165-1590
06.50.154	white	DEUTSCH® connector	female	(-) ground	not applicable	418-4862, 259-2078
06.50.158 ¹⁾	white	DEUTSCH® connector	female	(-) ground	X (MIC3/3+/4/5)	418-4862, 259-2078



¹⁾ Only for use with MIC3/3+, MIC4 and MIC5 ignition controllers.

Please see page 38 and page 94 for suitable ignition coil extensions and extension overhaul kits.

For CATERPILLAR® G3500C/E & G3600 Series Gas Engines with Ignition Coil Extension

P/N	Figure	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.164	1	06.50.161	white	MIL, 3 pole, pin	female	(-) ground	not applicable	438-5682, 310-3180, 283-5269, 232-6351, 191-9346
06.50.165 ¹⁾	1	06.50.162	white	MIL, 3 pole, pin	female	(-) ground	X	438-5682, 310-3180, 283-5269, 232-6351, 191-9346

¹⁾ Only for use with MIC3/3+, MIC4 and MIC5 ignition controllers.

For CATERPILLAR® GCM34 Series Gas Engines with Ignition Coil Extension

P/N	Figure	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.174	2	06.50.170	white	MIL, 3 pole, pin	female	(-) ground	not applicable	193-468157, 258-4893
06.50.175 ¹⁾	2		white	MIL, 3 pole, pin	female	(-) ground	X	193-468157, 258-4893

¹⁾ Only for use with MIC3/3+, MIC4 and MIC5 ignition controllers.

For PERKINS® 4016-E61TRS Gas Engines

P/N	Figure	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.111	3		white	DEUTSCH® connector	female	(-) ground	not applicable	837/9, 10000-06176



■ Ignition Coils

UNSHIELDED

Ignition Coil for **WÄRTSILÄ**® Gas Engines



For **WÄRTSILÄ**® 25SG, 28SG and 220G/SG Gas Engines

P/N	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.059	black	2 pole, pin	female	(-) ground	not applicable	1469-008

NEW

Ignition Coil Conversion Kits for **CUMMINS**® QSK60G and QSV91G Gas Engines

Many operators of CUMMINS® motors are regularly confronted with a problem. The ignition coils installed by the engine manufacturer wear out quickly and must be replaced at an early stage. Especially the ignition coil extension made of plastic and its insert can break during operation and lead to engine failure. The various conversion kits can be used to solve this problem in the long run.

The conversion kits P/N 75.30.156 and P/N 75.30.157 are equipped with a standard ignition coil mounted on a metal plate on the engine's valve cover. A PolyMot™ spark plug lead connects ignition coil and spark plug. With the included primary lead, the ignition coil is simply connected to the existing engine wiring. Due to the modular design of the conversion kits, all components can be replaced individually if necessary, thus reducing the operating costs of the engine.



Features

- Easy and fast conversion (plug & play) of existing OEM ignition coil
- Use of long-lasting components
- Components available individually if required
- Cost effective solution

P/N	Description	Quantity	Equivalent to
75.30.156	Ignition coil conversion kit for CUMMINS® QSK60G Contains: ■ Ignition coil ■ Primary lead with connector (3 pole, socket) for connection to engine wiring ■ Ignition coil mounting plate with fastening material ■ PolyMot™ spark plug extension	1 pc 1 pc 1 pc 1 pc	2881124, 4011615, 11.371
75.30.157	Ignition coil conversion kit for CUMMINS® QSV91G Contains: ■ Ignition coil ■ Primary lead with connector (3 pole, socket) for connection to engine wiring ■ Ignition coil mounting plate with fastening material ■ PolyMot™ spark plug extension	1 pc 1 pc 1 pc 1 pc	2881124, 4011615, 11.020

Ignition Coil Conversion Kits for CUMMINS® & WÄRTSILÄ® Gas Engines

As an alternative to the simple variants, ignition coil conversion kits are available, which additionally enable professional monitoring of the high voltage during engine operation at each ignition coil. These conversion kits are equipped with MOTORTECH flange ignition coils with diagnostic interface and integrated primary lead as well as PolyMot™ spark plug extensions and also enable easy and fast retrofitting.

Features

- For CUMMINS® QSK60G and QSV81G/ QSV91G and WÄRTSILÄ® 28SG and 34SG series gas engines
- Easy and fast conversion (plug & play) of existing OEM ignition coil
- Use of long-lasting components
- Components available individually if required
- For unshielded applications (non CSA)
- Professional solution

1 Ignition Coil

- MOTORTECH ignition coil with specific flange
- Diagnostic interface (BNC connector) for easy monitoring of high voltage traces via MOTORTECH SparkView or digital oscilloscope
- Pressure proof metal housing

2 Adaptor Flange

3 Engine specific PolyMot™ Spark Plug Extension

- High quality Teflon® for long life
- Built in 5 kOhm resistor for EMI suppression
- Integrated silicone seal ring for best flashover protection
- Special top thread for easy removal with MOTORTECH removal tool (P/N 44.99.912)

4 Fastening Material



P/N	Description	Quantity	Equivalent to
75.30.143	Ignition coil conversion kit for CUMMINS® QSK60G <i>Contains:</i> ■ Flange ignition coil with diagnostic interface and integrated primary lead ■ Adaptor flange with fastening material ■ PolyMot™ spark plug extension	1 pc 1 pc 1 pc	2881124, 4011615
75.30.144	Ignition coil conversion kit for CUMMINS® QSV81G/QSV91G <i>Contains:</i> ■ Flange ignition coil with diagnostic interface and integrated primary lead ■ Adaptor flange with fastening material ■ PolyMot™ spark plug extension	1 pc 1 pc 1 pc	2881124, 4011615
75.30.154	Ignition coil conversion kit for WÄRTSILÄ® 28SG series <i>Contains:</i> ■ Flange ignition coil with diagnostic interface and integrated primary lead ■ Adaptor flange with fastening material ■ PolyMot™ spark plug extension	1 pc 1 pc 1 pc	2313-011
75.30.155	Ignition coil conversion kit for WÄRTSILÄ® 34SG series <i>Contains:</i> ■ Flange ignition coil with diagnostic interface and integrated primary lead ■ Adaptor flange with fastening material ■ PolyMot™ spark plug extension	1 pc 1 pc 1 pc	120095 (18V34SG) 120096 (20V34SG)

NEW

NEW

■ Ignition Coils

Ignition Coil Extensions

For **MOTORTECH/CATERPILLAR®** Ignition Coils – For **CATERPILLAR®** G3500C/E and G3600 Series Gas Engines

P/N	Figure	Description	Application	Resistance	Teflon® Insulator		Fits Ignition Coil P/N	Equivalent to
					Length	Diameter		
06.80.459H ¹⁾	1	Ignition coil extension	G3500C/E, G3600	0 kΩ	248 mm	26 mm	06.50.161, 06.50.162, 283-5270	308-1380, 283-5271, 264-5323, 150-2050
06.80.600	2	Ignition coil extension	G3500C/E, G3600	0 kΩ	252 mm	26 mm	06.50.164, 06.50.165	

¹⁾ Supersedes ignition coil extensions P/N 06.80.375H and 06.80.446H.

For **MOTORTECH/CATERPILLAR®** Ignition Coils – For **CATERPILLAR®** GCM34 Series Gas Engines

P/N	Figure	Description	Application	Resistance	Teflon® Insulator		Fits Ignition Coil P/N	Equivalent to
					Length	Diameter		
06.80.1013-T	3	Ignition coil extension	GCM34	5 kΩ	530 mm	26 mm	193-468157, 258-4893, 06.50.170	263210167, 3400.7-21.07.02-03
06.80.602	4	Ignition coil extension	GCM34	5 kΩ	534 mm	26 mm	06.50.174, 06.50.175	

For **WÄRTSILÄ®** 34SG and 220G/SG Gas Engines

P/N	Description	Application	Resistance	Teflon® Insulator		Fits Ignition Coil P/N	Equivalent to
				Length	Diameter		
06.80.460	Ignition coil extension	34SG series	5 kΩ	460 mm	26 mm		0012E002200
06.80.461	Ignition coil extension	34SG series	5 kΩ	446 mm	26 mm		0012E006500
06.80.145-1	Ignition coil extension	220G/SG series	5 kΩ	334 mm	24 mm		3340063
06.80.145-2	Ignition coil extension	220G/SG series	5 kΩ	329 mm	24 mm		3341380



Ignition Coil Extension Overhaul Kits

Kits for **MOTORTECH** Ignition Coils – For **CATERPILLAR®** G3400/C and G3500/B/C/E/H Series Gas Engines

P/N	Figure	Supersedes	Description	Application	Teflon® Insulator		Fits Ignition Coil P/N
					Length	Diameter	
06.80.741	5		Extension overhaul kit	G3400 – Non CSA	95 mm	30 mm	06.50.141, 06.50.145
06.80.742	5		Extension overhaul kit	G3400 – CSA	97 mm	30 mm	06.50.142, 06.50.146
06.80.743	5		Extension overhaul kit	G3400 – Non CSA	107 mm	30 mm	06.50.143, 06.50.147
06.80.744	5		Extension overhaul kit	G3400 – CSA	109 mm	30 mm	06.50.144, 06.50.148
06.80.751	5		Extension overhaul kit	G3500 – Non CSA	118 mm	30 mm	06.50.151, 06.50.155
06.80.752	5		Extension overhaul kit	G3500 – CSA	105 mm	30 mm	06.50.152, 06.50.156
06.80.753	5		Extension overhaul kit	G3500 – Non CSA	112 mm	30 mm	06.50.153, 06.50.157
06.80.754	5		Extension overhaul kit	G3500 – CSA	105 mm	30 mm	06.50.154, 06.50.158
06.80.764	5		Extension overhaul kit	G3500 – Non CSA	104 mm	25 mm	06.50.159, 06.50.160

Kits for **CATERPILLAR®** Ignition Coils – For **CATERPILLAR®** G3400/C and G3500/B Series Gas Engines

P/N	Figure	Supersedes	Description	Application	Teflon® Insulator		Fits Ignition Coil P/N
					Length	Diameter	
06.80.419H	5		Extension overhaul kit	G3400 – Non CSA	95 mm	30 mm	232-6348, 165-1591, 131-3277, 129-8802, 108-0615
06.80.742	5	06.80.418H	Extension overhaul kit	G3400 – CSA	97 mm	30 mm	232-6349, 165-1592, 122-8070
06.80.420H	5		Extension overhaul kit	G3400 – Non CSA	107 mm	30 mm	232-6352, 213-7443
06.80.744	5	06.80.417H	Extension overhaul kit	G3400 – CSA	109 mm	30 mm	232-6353, 213-7444
06.80.515H	5	06.80.315H	Extension overhaul kit	G3500 – Non CSA	118 mm	30 mm	232-6346, 165-1589, 124-0749
06.80.752	5	06.80.415H	Extension overhaul kit	G3500 – CSA	105 mm	30 mm	232-6347, 165-1590
06.80.480	5		Extension overhaul kit	G3500 – Non CSA	112 mm	30 mm	232-6350
06.80.754	5	06.80.415H	Extension overhaul kit	G3500 – CSA	105 mm	30 mm	259-2078



5

■ Ignition Coils

Accessories for Unshielded Ignition Coils

Different ignition coil styles require different boots to seal the primary or secondary terminals. MOTORTECH boots are all made from highest grade of silicone (482 °F / 250 °C).

The boots will remain soft and flexible over a long time and protect the operator from touching any low or high voltage terminations. The boots also ensure that the critical areas stay clean and dry even in the worst environment.

Boots for MOTORTECH Ignition Coils

P/N	Figure	Ignition Coil Side		Outlet		Ignition Coil 06.50. ...														
		Primary	Secondary	90 °	180 °	003	053	054	055	060	065	100	102	103	104	105	112	113	300	301
06.80.037	1	x		x		x	x	x	x	x	x									
06.84.082	2	x		x								x	x		x	x	x	x	x	x
06.84.021	3	x		x										x ¹⁾						
06.80.005	4	x			x	x	x	x	x	x	x									
06.84.083	5		x	x								x			x		x		x	
06.80.006	6		x		x	x				x										
06.84.006	7		x		x		x	x	x		x		x			x		x		x

¹⁾ Two boots needed for each ignition coil.



1



2



3



4



5



6



7

Boots for ALTRONIC® Ignition Coils

P/N	Figure	Ignition Coil Side		Outlet		Ignition Coil
		Primary	Secondary	90 °	180 °	
06.80.037	1	x		x		291001, 591010, 501061
06.80.036	2	x			x	291001, 591010, 501061
06.84.006	3		x		x	291001, 591010, 501061



1



2



3

Secondary Connections

P/N	Figure	Description	Ignition Coil 06.50. ...														
			003	053	054	055	060	065	100	102	103	104	105	112	113	300	301
06.80.261		Coil terminal, 180°, requires P/N 06.80.126		x	x	x		x		x			x		x		x
06.80.091		Coil terminal, 180°, requires P/N 06.80.126						x ¹⁾			x	x ¹⁾		x ¹⁾		x ¹⁾	
06.80.108		Crimp terminal base	x				x		x			x		x		x	
06.80.116		Crimp terminal, 90°, requires P/N 06.80.108	x				x										
06.80.116-180		Crimp terminal, 180°, requires P/N 06.80.108							x			x		x		x	
06.80.126		Crimp terminal base		x	x	x		x	x ¹⁾	x	x	x ¹⁾	x	x ¹⁾	x	x ¹⁾	x
06.84.024		Coil terminal, 90°, including terminal P/N 02.85.920										x					
06.84.025		Coil terminal, 180°, including terminal P/N 02.85.920										x					
22.80.009		Coil terminal, 90°, 1 kΩ resistor, requires P/N 06.80.126									x			x		x	

¹⁾ When using SAE contact pin P/N 06.51.223.



Accessories

P/N	Figure	Description	Ignition Coil 06.50. ...														
			003	053	054	055	060	065	100	102	103	104	105	112	113	300	301
06.51.223	1	SAE contact pin							x			x		x		x	
06.90.264 ¹⁾	2	Accessory kit incl. fastening screws and nuts							x	x		x	x	x	x	x	x
02.85.1012	3	SAE spreading adaptor		x	x	x		x		x			x		x		x

¹⁾ Comes with each New MOTORTECH Style ignition coil.



Ignition Coils

SHIELDED

Flange Ignition Coils

MOTORTECH makes available the BLUE and RED flanged ignition coil as a replacement for the existing products sold by ALTRONIC® and the engine manufacturers.

A specially designed version for use with newest technologies of MOTORTECH ignitions controllers is also available:

- MOST – MOTORTECH Output Stage Technology of MOTORTECH MIC3/3+, MIC4, MIC5 and MIC6 ignition controllers



3 Pole Primary Connector Arrangement



P/N	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
06.50.034	95.09.134	red	MIL, 3 pole, pin	female	(-) ground	not applicable	591012, 69694F, 7W-4377
06.50.035	95.09.135	blue	MIL, 3 pole, pin	female	(-) ground	not applicable	591018, 69694G, A69694G
06.50.036	95.09.100	red	MIL, 3 pole, pin	female	(-) ground	x	

Ignition Coils




SHIELDED

Flange Ignition Coils with integrated Primary Lead

Based on its known flange ignition coils, MOTORTECH offers a series with integrated primary leads. Different configurations with 2-pole and 3-pole connectors in 90° and 180° are available to connect the ignition coil directly to a wiring rail or to replace OEM products in the field.



2 Pole Primary Connector Arrangement – For use with AlphaRail Wiring Rails



P/N ¹⁾	Figure	Color	Wiring Rail Connector	HV Termination	Polarity	MOST	Equivalent to
06.50.034-L-C	1	red	MIL, 2 pole, pin, 180°	female	(-) ground	not applicable	
06.50.034-L-D	2	red	MIL, 2 pole, pin, 90°	female	(-) ground	not applicable	
06.50.035-L-C	1	blue	MIL, 2 pole, pin, 180°	female	(-) ground	not applicable	
06.50.035-L-D	2	blue	MIL, 2 pole, pin, 90°	female	(-) ground	not applicable	
06.50.036-L-C	1	red	MIL, 2 pole, pin, 180°	female	(-) ground	X	
06.50.036-L-D	2	red	MIL, 2 pole, pin, 90°	female	(-) ground	X	

¹⁾ Standard primary lead lengths (-L) = 12 in, 18 in, 24 in, 30 in, 36 in, 42 in. Other lengths available on request.

For use with WAUKESHA® ESM Gas Engines



P/N	Figure	Color	Primary Lead Length	Wiring Rail Connector	HV Termination	Polarity	MOST	Equivalent to
06.50.035-30-A	3	blue	30 in	3 pole, socket, 180°	female	(-) ground	not applicable	
06.50.035-36-E	4	blue	36 in	MIL, 3 pole, pin, 180°	female	(-) ground	not applicable	69957, 69957A



Ignition Coils

SHIELDED

Flange Ignition Coils with Diagnostic Interface

These MOTORTECH ignition coils are designed for operators who want to monitor their high voltage traces in a simple way. Measuring high voltage peak (kV) and spark duration (μsec) of all cylinders of an engine with flange ignition coils regularly, will allow easy maintenance of the equipment.

With a MOTORTECH SparkView or digital Scope Meter the operator can receive real time data.



3 Pole Primary Connector Arrangement



P/N	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
95.09.150 ¹⁾	steel	MIL, 3 pole, pin	female	(-) ground	X (MIC3/3+/4/5)	06.50.036, 95.09.100
95.09.153 ²⁾	steel	MIL, 3 pole, pin	female	(+) ground	not applicable	95.09.133
95.09.154 ³⁾	steel	MIL, 3 pole, pin	female	(-) ground	not applicable	06.50.034, 95.09.134
95.09.155 ⁴⁾	steel	MIL, 3 pole, pin	female	(-) ground	not applicable	06.50.035, 95.09.135

¹⁾ Same coil winding as P/N 06.50.036 and 95.09.100, but with diagnostic interface.

²⁾ Same coil winding as P/N 95.09.133, but with diagnostic interface.

³⁾ Same coil winding as P/N 06.50.034 and 95.09.134, but with diagnostic interface. Thus also equivalent to P/N 591012, 69694F and 7W-4377.

⁴⁾ Same coil winding as P/N 06.50.035 and 95.09.135, but with diagnostic interface. Thus also equivalent to P/N 591018, 69694G and A69694G.

Additional BNC connector for high voltage measurement



SparkView

MOTORTECH HIGH VOLTAGE INDICATOR

The SparkView is a handheld device developed by MOTORTECH that can monitor the high voltage required by the spark plug while the engine is running. With a measuring clamp or cable and the display for up to 40 kV, it is easy to determine the condition of the spark plugs and the time at which they need to be replaced.



See page 114.


Ignition Coils



SHIELDED

Flange Ignition Coils with Diagnostic Interface and integrated Primary Lead

MOTORTECH flange ignition coils with diagnostic interface are also available with integrated primary leads. These include different connector arrangements for a direct wiring rail connection and to offer an upgrade and replacement to used OEM products.



2 Pole Primary Connector Arrangement – For use with AlphaRail Wiring Rails

P/N ¹⁾	Figure	Color	Wiring Rail Connector	HV Termination	Polarity	MOST	Equivalent to
95.09.150-L-C	1	steel	MIL, 2 pole, pin, 180°	female	(-) ground	X (MIC3/3+/4/5)	
95.09.150-L-D	2	steel	MIL, 2 pole, pin, 90°	female	(-) ground	X (MIC3/3+/4/5)	
95.09.154-L-C	1	steel	MIL, 2 pole, pin, 180°	female	(-) ground	not applicable	
95.09.154-L-D	2	steel	MIL, 2 pole, pin, 90°	female	(-) ground	not applicable	
95.09.155-L-C	1	steel	MIL, 2 pole, pin, 180°	female	(-) ground	not applicable	
95.09.155-L-D	2	steel	MIL, 2 pole, pin, 90°	female	(-) ground	not applicable	

¹⁾ Standard primary lead lengths (-L) = 12 in, 18 in, 24 in, 30 in, 36 in, 42 in. Other lengths available on request.

For use with WAUKESHA® ESM Gas Engines



P/N	Figure	Color	Primary Lead Length	Wiring Rail Connector	HV Termination	Polarity	MOST	Equivalent to
95.09.155-30-A ¹⁾	3	steel	30 in	3 pole, socket, 180°	female	(-) ground	not applicable	06.50.035-30-A
95.09.155-36-E ²⁾	4	steel	36 in	MIL, 3 pole, pin, 180°	female	(-) ground	not applicable	06.50.035-36-E

¹⁾ Same coil winding as P/N 06.50.035-30-A, but with diagnostic interface.

²⁾ Same coil winding as P/N 06.50.035-36-E, but with diagnostic interface. Thus also equivalent to P/N 69957 and 69957A.

For use with CUMMINS® and WÄRTSILÄ® Gas Engines

P/N	Figure	Color	Primary Lead Length	Wiring Rail Connector	HV Termination	Polarity	MOST	Equivalent to
95.09.156-20-B ¹⁾		steel	20 in	3 pole, socket, 180°	female	(-) ground	X (MIC3/3+/4/5)	
95.09.157-28-G ²⁾	5	steel	28 in	MIL, 5 pole, pin, 180°	female	(-) ground	X (MIC3/3+/4/5)	

¹⁾ Use of ignition coil only possible, if conversion kits P/N 75.30.143 (CUMMINS® QSK60G) or 75.30.144 (CUMMINS® QSV81/91G) previously were used.

²⁾ Use of ignition coil only possible, if conversion kits P/N 75.30.154 (WÄRTSILÄ® 28SG) or 75.30.155 (WÄRTSILÄ® 34SG) previously were used.



■ Ignition Coils

Spark Plug Carrier and Flange Adaptor Hardware Kit for **WAUKESHA®** VHP-GL Engines – CSA® Conversion

- For modification of standard ignition coil to flange ignition coil arrangement
- Available as single parts
- Stock item



A Primary Lead

P/N	Description	Equivalent to	Required Qty per Cylinder
95.01.020-30	Primary lead, Conventional Style, 3 pole ignition coil connector, 1/2-14 NPT junction box adaptor	208503K, 593027-30	1
alternative 95.01.120-30	Primary lead, New Flex Style, 3 pole ignition coil connector, 1/2-14 NPT junction box adaptor	95.01.020-30	1

B Flange Ignition Coil

P/N	Description	Equivalent to	Required Qty per Cylinder
06.50.035	Flange ignition coil	A69694G, 69694G, 591018	1
alternative 95.09.155 ¹⁾	Flange ignition coil with diagnostic interface	06.50.035	1

¹⁾ Same coil winding as P/N 06.50.035, but with diagnostic interface. Thus also equivalent to P/N 591018 and 69694G, A69694G.

C PolyMot™ Spark Plug Extension

P/N	Description	Equivalent to	Required Qty per Cylinder
06.80.321-T	PolyMot™ spark plug extension	A211797H, A211797P, 211357P, 211357U, A211797R	1

D Spark Plug

P/N	Description	Equivalent to	Required Qty per Cylinder
FB77WPCC	CHAMPION® spark plug, M18x1.5, reach 0.750 in, J-type Ir/Pt, HEX 7/8 in (22.2 mm)	69919, 60999T	1
alternative B8324	MOTORTECH MHP spark plug, M18x1.5, reach 0.750 in, J-type Ir/Ir, HEX 13/16 in (20.8 mm)		1
alternative GI3-3	DENSO® spark plug, M18x1.5, reach 0.750 in, J-type Ir/Pt, HEX 7/8 in (22.2 mm)		1

SparkView
MOTORTECH HIGH VOLTAGE INDICATOR

The SparkView is a handheld device developed by MOTORTECH that can monitor the high voltage required by the spark plug while the engine is running. With a measuring clamp or cable and the display for up to 40 kV, it is easy to determine the condition of the spark plugs and the time at which they need to be replaced.

Ignition Coils



A



B



C



D



E



F



E Adaptor for Flange Ignition Coil/Spark Plug Carrier

P/N	Description	Equivalent to	Required Qty per Cylinder
211749-MOT	Adaptor for flange ignition coil/spark plug carrier	211749	1

NOTE: Screws and washers for fastening of flange ignition coil not included.
Hex head screws (3 pcs 5/16-18x3/4 in – WED P/N 21309) and washers (3 pcs 5/16 in – WED P/N 21051) have to be supplied by customer.

F Spark Plug Carrier

P/N	Description	Equivalent to	Required Qty per Cylinder
209567R-MOT	Spark plug carrier	209567R	1

NOTE: Screws and washers for fastening of flange adaptor not included.
Hex head screws (4 pcs 1/4-28x1/2 in – WED P/N 21296) and lock washers (4 pcs 1/4 in – WED P/N 21050) have to be supplied by customer.

Optional Tools

Installation Tool for Spark Plug Carrier

P/N	Description
44.01.015	Installation tool for spark plug carrier



Spare Part for Installation Tool

P/N	Description
44.01.017	Feather key for installation tool

Extended Barrel Magnetic Spark Plug Sockets

P/N	Description
07.99.022-3-16	Magnetic spark plug socket, HEX 7/8 in (22.2 mm), 1/2 in drive, length 16 in (406.4 mm), for use with spark plugs P/N 69919, 60999T, FB77WPCC, GI3-3
07.99.022-4-16	Magnetic spark plug socket, HEX 13/16 in (20.8 mm), 1/2 in drive, length 16 in (406.4 mm), for use with spark plug P/N B8324



SparkView – High Voltage Indicator

P/N	Description
06.90.099-105	SparkView high voltage indicator – incl. BNC cable P/N 06.90.105, for use with flange ignition coils with diagnostic interface

Ignition Coils

SHIELDED

Externally Mounted Ignition Coils

Shielded – externally mounted – ignition coils are encapsulated in a steel housing with welded lids. A bracket is used to install the ignition coils on a wiring rail or directly on the engine. This type of ignition coil is connected to the spark plug by a shielded spark plug lead with a 3/4 in or 1 in termination. Primary voltage connection is made by a 2 or 3 pole military style screw connector. All parts meet the CSA Class I, Division 2, Group C/D.



3 Pole Primary Connector Arrangement



P/N	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
95.09.005		steel	MIL, 3 pole, pin	3/4-20 UNEF	(-) ground	X (MIC3/3+/4/5)	
95.09.053	95.09.001	steel	MIL, 3 pole, pin	3/4-20 UNEF	(+) ground	not applicable	291001-S, R65431A
95.09.054	95.09.003	steel	MIL, 3 pole, pin	3/4-20 UNEF	(-) ground	not applicable	591010-S
95.09.055	95.09.002	steel	MIL, 3 pole, pin	3/4-20 UNEF	(-) ground	not applicable	501061-S, 2881178, 701501, 028-989-001

2 Pole Primary Connector Arrangement



P/N	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
95.08.003	95.08.001, 95.08.002	steel	MIL, 2 pole, pin	1-20 UNEF	(-) ground	X	PPT2477AD, PPT2477ADL
95.08.005		steel	MIL, 2 pole, pin	3/4-20 UNEF	(+) ground	not applicable	10-382040-1

Ignition Coils



Externally Mounted Ignition Coils with Diagnostic Interface

These MOTORTECH ignition coils are designed for operators who want to monitor their high voltage traces in a simple way. Measuring high voltage peak (kV) and spark duration (µsec) of all cylinders of an engine with externally mounted ignition coils regularly, will allow easy maintenance of the equipment.

With a MOTORTECH SparkView or digital Scope Meter the operator can receive real time data.



3 Pole Primary Connector Arrangement

P/N	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
95.09.070 ¹⁾		steel	MIL, 3 pole, pin	3/4-20 UNEF	(-) ground	X	95.09.005
95.09.073 ²⁾		steel	MIL, 3 pole, pin	3/4-20 UNEF	(+) ground	not applicable	95.09.053
95.09.074 ³⁾		steel	MIL, 3 pole, pin	3/4-20 UNEF	(-) ground	not applicable	95.09.054
95.09.075 ⁴⁾		steel	MIL, 3 pole, pin	3/4-20 UNEF	(-) ground	not applicable	95.09.055

¹⁾ Same coil winding as P/N 95.09.005, but with diagnostic interface.

²⁾ Same coil winding as P/N 95.09.053, but with diagnostic interface. Thus also equivalent to P/N 291001-S and R65431A.

³⁾ Same coil winding as P/N 95.09.054, but with diagnostic interface. Thus also equivalent to P/N 591010-S.

⁴⁾ Same coil winding as P/N 95.09.055, but with diagnostic interface. Thus also equivalent to P/N 501061-S, 2881178, 701501 and 028-989-001.

2 Pole Primary Connector Arrangement

P/N	Supersedes	Color	Primary Termination	HV Termination	Polarity	MOST	Equivalent to
95.08.070 ¹⁾		steel	MIL, 2 pole, pin	1-20 UNEF	(-) ground	X	95.08.003

¹⁾ Same coil winding as P/N 95.08.003, but with diagnostic interface. Thus also equivalent to P/N PPT2477AD and PPT2477ADL.

Additional BNC connector for high voltage measurement



SparkView MOTORTECH HIGH VOLTAGE INDICATOR

The SparkView is a handheld device developed by MOTORTECH that can monitor the high voltage required by the spark plug while the engine is running. With a measuring clamp or cable and the display for up to 40 kV, it is easy to determine the condition of the spark plugs and the time at which they need to be replaced.



See page 114.

Ignition Coils

SHIELDED

Integral Ignition Coils – Slim Design

Integral ignition coils are mostly used in shielded applications and are designed to be mounted directly on a dual threaded spark plug. This design does not require a spark plug lead. The ignition coil life is affected by the temperature that is transferred into the coil by the spark plug. On occasions where the spark plug leaks, high combustion pressure enters the ignition coil and forces the base coil to blow out of its housing. MOTORTECH's design with a new top cover and a modern production process will not allow this to happen.



Top cover with integrated HEX for easy installation/deinstallation



3 Pole Primary Connector Arrangement – ALTRONIC®, MIC3/3+, MIC4 Compatible – MOST



P/N ¹⁾	Supersedes	Color	Length	Primary Termination	HV Termination		Polarity	MOST	Equivalent to
					Outer Thread	Inner Thread			
95.09.222-6 ²⁾	95.09.012-6, 95.09.040-6, 95.09.022-6	steel	6.00 in	MIL, 3 pole, pin		13/16-20 UNEF	(-) ground	X (MIC3/3+/4)	591011A, 107-2400
95.09.222-12 ²⁾	95.09.012-12, 95.09.040-12, 95.09.022-12	steel	12.00 in	MIL, 3 pole, pin		13/16-20 UNEF	(-) ground	X (MIC3/3+/4)	591011B, 591011C, 215-2434, 69694D
95.09.223-6 ²⁾	95.09.010, 95.09.030, 95.09.023-6	steel	6.00 in	MIL, 3 pole, pin	1-20 UNEF	13/16-20 UNEF	(-) ground	not applicable	591007, 4W-4959, 60615F
95.09.233-6 ³⁾	95.09.011, 95.09.031, 95.09.033-6	steel	6.00 in	MIL, 3 pole, pin	1-20 UNEF	13/16-20 UNEF	(+) ground	not applicable	591008

¹⁾ Ignition coils in 10 in. only available on special request.

²⁾ For use with MIC500, MIC3/3+, MIC4, ALT I, ALT III, ALT V, CD200, CD200D, DISN, CPU90, CPU95, CEC, CATERPILLAR® (163-6164, 163-6108).

³⁾ For use with ALT II, DIS, CPU2000.

2 Pole Primary Connector Arrangement – FAIRBANKS MORSE® Style



P/N ¹⁾	Supersedes	Color	Length	Primary Termination	HV Termination		Polarity	MOST	Equivalent to
					Outer Thread	Inner Thread			
95.08.222-6 ²⁾	95.08.010-6, 95.08.030-6, 95.08.022-6	steel	6.00 in	MIL, 2 pole, pin		13/16-20 UNEF	(-) ground	X (MIC3/3+/4)	PPT2477AA6
95.08.222-12 ²⁾	95.08.010-12, 95.08.030-12, 95.08.022-12	steel	12.00 in	MIL, 2 pole, pin		13/16-20 UNEF	(-) ground	X (MIC3/3+/4)	PPT2477AA12

¹⁾ Ignition coils in 8 in (PPT2477AA8) and 10 in (PPT2477AA10) only available on special request.

²⁾ For use with MIC3/3+, MIC4, MIC500, MIC850.

Integral Ignition Coils – Fat Design

For slow and mid speed gas engines it is favorable to have more spark energy available. MOTORTECH offers a full line of special and more powerful integral ignition coils with a proven design including different lengths and versions for use with MOTORTECH MIC3/3+, MIC4, MIC5, MIC500 and MIC850 series ignition controllers (support MOST and ASC technology) to meet the application and spark plug requirement.



Top cover with integrated HEX for easy installation/deinstallation



3 Pole Primary Connector Arrangement – MIC3/3+, MIC4, MIC5 Compatible – MOST



P/N ¹⁾	Supersedes	Color	Length	Primary Termination	HV Termination		Polarity	MOST	Equivalent to
					Outer Thread	Inner Thread			
95.09.142-11 ²⁾	95.09.060-11	steel	11.00 in	MIL, 3 pole, pin		13/16-20 UNEF	(-) ground	X	
95.09.143-6 ²⁾	95.09.013-6, 95.09.050-6	steel	6.00 in	MIL, 3 pole, pin	1-20 UNEF	13/16-20 UNEF	(-) ground	X	

¹⁾ Ignition coils in 12 in and 14.5 in only available on special request.

²⁾ For use with MIC3/3+, MIC4, MIC5, MIC500, MIC850. P/N 95.09.142-11 for use on WAUKESHA® VHP-GSI with rain shield.

For existing installations with **ALTRONIC®** ignition controllers, MOTORTECH offers a special series of high energy integral ignition coils with 3 pole primary connector.

The ignition coils are designed to have the electrical characteristics to function with the **ALTRONIC®** patented “**Spark Reference**” high voltage indication system.

3 Pole Primary Connector Arrangement – ALTRONIC® Compatible



P/N ¹⁾	Supersedes	Color	Length	Primary Termination	HV Termination		Polarity	MOST	Equivalent to
					Outer Thread	Inner Thread			
95.09.122-11 ²⁾	95.09.061-11	steel	11.00 in	MIL, 3 pole, pin		13/16-20 UNEF	(-) ground	not applicable	
95.09.123-6 ²⁾	95.09.051-6	steel	6.00 in	MIL, 3 pole, pin	1-20 UNEF	13/16-20 UNEF	(-) ground	not applicable	

¹⁾ Ignition coils in 12 in and 14.5 in only available on special request.

²⁾ For use with MIC500, ALT I, ALT III, ALT V, CD200, CD200D, DISN, CPU90, CPU95, CEC. P/N 95.09.122-11 for use on WAUKESHA® VHP-GSI with rain shield.

MOTORTECH high energy integral ignition coils are also available with 2 pole primary connector for use with MOTORTECH MIC3/3+, MIC4, MIC5, MIC500 and MIC850

(includes support of ASC and MOST feature) series ignition controllers.

2 Pole Primary Connector Arrangement – FAIRBANKS MORSE® Style – MOST



P/N ¹⁾	Supersedes	Color	Length	Primary Termination	HV Termination		Polarity	MOST	Equivalent to
					Outer Thread	Inner Thread			
95.08.142-11 ²⁾	95.08.050-11	steel	11.00 in	MIL, 2 pole, pin		13/16-20 UNEF	(-) ground	X	
95.08.143-6 ²⁾	95.08.020-6, 95.08.040-6	steel	6.00 in	MIL, 2 pole, pin	1-20 UNEF	13/16-20 UNEF	(-) ground	X	PPT2477AB6

¹⁾ Ignition coils in 12 in (PPT2477AB12) and 14.5 in only available on special request.

²⁾ For use with MIC3/3+, MIC4, MIC5, MIC500, MIC850. P/N 95.08.142-11 for use on WAUKESHA® VHP-GSI with rain shield.

■ Ignition Coils

As an additional accessory, MOTORTECH offers suitable grommets for certain applications. Made of Teflon® or silicone, these grommets perfectly fit the slim and fat design integral ignition coils and protect the spark plug well against dirt and fluids.



Grommets for Integral Ignition Coils

P/N	Figure	Description	Material	Integral Ignition Coil Type	Engine Make and Model	Equivalent to
06.84.026	1	Grommet	Silicone	Slim Design	CATERPILLAR® G342, G379, G398, G399	9Y-3987, ICG-625
06.84.116	2	Grommet	Teflon®	Slim Design	CATERPILLAR® G3300 series	106-9185
06.84.117	2	Grommet	Teflon®	Slim Design	CATERPILLAR® G3400 series	9Y-7361
06.84.069	2	Grommet	Teflon®	Fat Design	WAUKESHA® VHP and VGF series	



1



2

Pickups & Trigger Drives

UNSHIELDED

Pickups

A wide range of standard ignition pickups are available from MOTORTECH to allow service companies and operators to select what they need to do a professional installation. High quality, designed to meet the application and temperature requirements, MOTORTECH pickups will last and ensure you are not experiencing any unexpected shut downs.



Magnetic Pickups – Thread Size 5/8-18 UNF ¹⁾



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
66.60.001-125	1	06.60.101	5/8-18 UNF	1.25 in	holes, pins, teeth, screws	
66.60.001-175	1	06.60.105	5/8-18 UNF	1.75 in	holes, pins, teeth, screws	691118-1
66.60.001-250	1	06.60.102	5/8-18 UNF	2.50 in	holes, pins, teeth, screws	691118-2
66.60.001-400	1	06.60.103	5/8-18 UNF	4.00 in	holes, pins, teeth, screws	691118-4
66.60.001-600	1	06.60.107	5/8-18 UNF	6.00 in	holes, pins, teeth, screws	691118-6

¹⁾ Not for use with WAUKESHA® ESM system.

Hall Effect Pickups – Thread Size 5/8-18 UNF – Active Low



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
66.60.002-125	2		5/8-18 UNF	1.25 in	magnets	
66.60.002-175	2	06.60.020	5/8-18 UNF	1.75 in	magnets	791050-1
66.60.002-250	2	06.60.021	5/8-18 UNF	2.50 in	magnets	791050-2
66.60.002-450	2	06.60.022	5/8-18 UNF	4.50 in	magnets	791050-4
66.60.002-600	2		5/8-18 UNF	6.00 in	magnets	791050-6

Hall Effect Pickups – Thread Size 5/8-18 UNF – Active High ¹⁾



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
66.60.012-175	2		5/8-18 UNF	1.75 in	magnets	591014-1
66.60.012-250	2		5/8-18 UNF	2.50 in	magnets	591014-2
66.60.012-450	2		5/8-18 UNF	4.50 in	magnets	591014-4
66.60.012-600	2		5/8-18 UNF	6.00 in	magnets	591014-6

¹⁾ For use with ALTRONIC® CPU90, CPU95, CPU2000 ignition controllers.

Inductive Pickups – Thread Size M12x1



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
66.60.003-60	3	06.60.027, 06.60.042	M12x1	60 mm	pins, screws, slots	
66.60.003-100	3	06.60.023, 06.60.040	M12x1	100 mm	pins, screws, slots	

Pickups & Trigger Drives



SHIELDED

Magnetic Pickups – Thread Size 5/8-18 UNF ¹⁾



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
95.70.001-125	4		5/8-18 UNF	1.25 in	holes, pins, teeth, screws	
95.70.001-175	4		5/8-18 UNF	1.75 in	holes, pins, teeth, screws	691118-1
95.70.001-250	4		5/8-18 UNF	2.50 in	holes, pins, teeth, screws	691118-2
95.70.001-400	4		5/8-18 UNF	4.00 in	holes, pins, teeth, screws	691118-4
95.70.001-600	4		5/8-18 UNF	6.00 in	holes, pins, teeth, screws	691118-6

¹⁾ Not for use with WAUKESHA® ESM system.

Hall Effect Pickups – Thread Size 5/8-18 UNF – Active Low



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
95.70.002-125	5		5/8-18 UNF	1.25 in	magnets	
95.70.002-175	5		5/8-18 UNF	1.75 in	magnets	791050-1
95.70.002-250	5		5/8-18 UNF	2.50 in	magnets	791050-2
95.70.002-450	5		5/8-18 UNF	4.50 in	magnets	791050-4
95.70.002-600	5		5/8-18 UNF	6.00 in	magnets	791050-6

Hall Effect Pickups – Thread Size 5/8-18 UNF – Active High ¹⁾



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
95.70.012-175	5		5/8-18 UNF	1.75 in	magnets	591014-1
95.70.012-250	5		5/8-18 UNF	2.50 in	magnets	591014-2
95.70.012-450	5		5/8-18 UNF	4.50 in	magnets	591014-4
95.70.012-600	5		5/8-18 UNF	6.00 in	magnets	591014-6

¹⁾ For use with ALTRONIC® CPU90, CPU95, CPU2000 ignition controllers.

Inductive Pickups – Thread Size M12x1



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
95.70.003-60	6		M12x1	60 mm	pins, screws, slots	
95.70.003-100	6		M12x1	100 mm	pins, screws, slots	

Legend



slots



magnets



pins



teeth



screws



holes



See page 64 for available pickup thread adaptors.

Conversion: 1 inch = 25,4 mm / 1 foot = 0,3 m

Pickups & Trigger Drives

UNSHIELDED

Special Application Pickups

For use with competitor ignition systems, MOTORTECH offers a special series of pickups. Based on the reliable design of MOTORTECH's standard versions, this series represents a

suitable replacement for existing competitor pickups in the field.

Magnetic Pickups – Thread Size 3/4-16 UNF ¹⁾



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
66.60.011-180	1		3/4-16 UNF	1.80 in	holes, pins, teeth, screws	791015-1
66.60.011-340	1		3/4-16 UNF	3.40 in	holes, pins, teeth, screws	791016-2

¹⁾ For use with ALTRONIC® CD1, CD200, CD200D and CD200EVS ignition controllers.

Magnetic Pickup – Thread Size M12x1 ¹⁾



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
66.60.021-300	2		M12x1	3.00 in	holes, pins, teeth, screws	791041-3, 10.362-1, 600-00-111-00

¹⁾ For use with ALTRONIC® CD200, CD200D and CD200EVS ignition controllers.

Active Pickup – Thread Size M18x1 ¹⁾



P/N	Figure	Supersedes	Thread Size	Thread Length	Trigger	Equivalent to
66.60.023-450	3		M18x1	4.50 in	magnets	791037-4, 1229 9989

¹⁾ For use with MWM®/DEUTZ® gas engines.

Pickup Coil for ALTRONIC® I Magneto Ignition System **NEW**

P/N	Figure	Supersedes	Connector	Lead Length	Trigger	Equivalent to
101181-MOT	4		MIL, 3 pole, socket, 180°	180.00 in (blue 200 in)	magnets	101181

Legend



Conversion: 1 inch = 25.4 mm/1 foot = 0.3 m

Pickups & Trigger Drives



UNSHIELDED

Pickup Leads

The reliability of an electronic ignition system comes with its accessories. Every pickup needs a lead to connect to the ignition controller and ensure that the signal is transmitted without any malfunctions. MOTORTECH offers high grade

pickup leads that are all shielded against EMI interference. Preferably a 90° connector is used as it routes the wire downwards and puts less side load stress on the pickup.



Magnetic Pickup Leads

P/N	Figure	Supersedes	Connector	Lead Length	Equivalent to
06.71.001-L	1		MIL, 2 pole, socket, 90°	L= 5/15/25/50 ft	

Hall Effect Pickup Leads



P/N	Figure	Supersedes	Connector	Lead Length	Equivalent to
06.71.002-L	2		MIL, 3 pole, socket, 90°	L= 5/15/25/50 ft	

Inductive Pickup Lead



P/N	Figure	Supersedes	Connector	Lead Length	Equivalent to
06.71.007	3		4 pole, socket, 90°	400 in	

SHIELDED

Magnetic Pickup Leads



P/N ¹⁾	Figure	Supersedes	Connector	Adaptor to Junction Box	Equivalent to
95.60.010-L	4		MIL, 2 pole, socket, 180°	1/2-14 NPT	593048-L
95.60.020-L	4		MIL, 2 pole, socket, 90°	1/2-14 NPT	593054-L

¹⁾ Standard braid lengths (-L) = 6 in, 12 in, 18 in, 24 in, 36 in, 48 in, 72 in, 96 in, 120 in, 150 in, 180 in; other lengths available on request.

Hall Effect Pickup Leads



P/N ¹⁾	Figure	Supersedes	Connector	Adaptor to Junction Box	Equivalent to
95.60.030-L	5		MIL, 3 pole, socket, 180°	1/2-14 NPT	593052-L
95.60.040-L	5		MIL, 3 pole, socket, 90°	1/2-14 NPT	593057-L

¹⁾ Standard braid lengths (-L) = 6 in, 12 in, 18 in, 24 in, 36 in, 48 in, 72 in, 96 in, 120 in, 150 in, 180 in; other lengths available on request

Inductive Pickup Lead



P/N	Figure	Supersedes	Connector	Lead Length	Adaptor to Junction Box	Equivalent to
95.60.050-400	6		4 pole, socket, 90°	400 in	M12x1.5	

Pickup Harnesses for WAUKESHA® VHP Series Gas Engines with ESM

P/N	Figure	Description	Length	Equivalent to
A740749-MOT		Harness, crankshaft pickup	45 in	A740749
A740750-MOT		Harness, camshaft pickup	43 in	A740750



Conversion: 1 inch = 25,4 mm/1 foot = 0,3 m

Pickups & Trigger Drives

Trigger Discs

A large variety of different trigger discs is available to support upgrades performed by installing new electronic ignition systems on engines that used to be equipped with mechanical driven magnetos. Select between universal trigger discs with magnets, metal inlets or discs that are specially designed for particular engine models.



Trigger Discs with Magnets

P/N	Supersedes	Description	Diameter	Events	Equivalent to
06.20.300		Trigger disc with magnet	5.00 in	1	
06.20.301		Trigger disc with magnet	7.45 in	1	
06.20.302		Trigger disc with magnets	5.00 in	2+1	
06.20.303		Trigger disc with magnets	7.45 in	2+1	
06.20.304		Trigger disc with magnets	5.00 in	3+1	
06.20.305		Trigger disc with magnets	7.45 in	3+1	
06.20.306		Trigger disc with magnets	5.00 in	4+1	790114-1
06.20.307		Trigger disc with magnets	7.45 in	4+1	790104-1
06.20.308		Trigger disc with magnets	5.00 in	5+1	790115-1
06.20.309		Trigger disc with magnets	7.45 in	5+1	790105-1
06.20.310		Trigger disc with magnets	3.40 in	6+1	790165
06.20.311		Trigger disc with magnets	4.00 in	6+1	790144
06.20.312		Trigger disc with magnets	5.00 in	6+1	790169
06.20.313		Trigger disc with magnets	5.00 in	6+1	790116-1
06.20.314		Trigger disc with magnets	7.45 in	6+1	790106-1
06.20.316		Trigger disc with magnets	5.00 in	8+1	790118-1
06.20.317		Trigger disc with magnets	7.45 in	8+1	790150
06.20.318		Trigger disc with magnets	7.45 in	8+1	790108-1
06.20.319		Trigger disc with magnets	7.45 in	8+1	790022
06.20.321		Trigger disc with magnets	7.45 in	12+1	790122-1
06.20.322		Trigger disc with magnets	7.45 in	12+1	790151
06.20.323		Trigger disc with magnets	7.45 in	12+1	790021

Conversion: 1 inch = 25,4 mm/1 foot = 0,3 m

Pickups & Trigger Drives



Trigger Discs with Magnets – Compatible with WAUKESHA® CEC Ignition System

P/N	Figure	Supersedes	Description	Application	Diameter	Events	Equivalent to
06.20.069-1	1		Trigger disc with magnet	WAUKESHA® VHP series	7.45 in	1	
06.20.069-6	1		Trigger disc with magnets	WAUKESHA® VHP series – 6 cylinders	7.45 in	6+1	305805R
06.20.069-12	1		Trigger disc with magnets	WAUKESHA® VHP series – 12 cylinders	7.45 in	12+1	305805P
06.20.254	2		Trigger disc with magnet	WAUKESHA® VHP series	5.35 in	1	
06.20.252	2		Trigger disc with magnets	WAUKESHA® VHP series – 16 cylinders	5.35 in	8+1	305805N
06.20.026-1 ¹⁾	3		Trigger disc with magnet	WAUKESHA® VHP series	7.45 in	1	
06.20.025 ¹⁾	3		Trigger disc with magnets	WAUKESHA® VHP series – 6 cylinders	7.45 in	6+1	305805F
06.20.026 ¹⁾	3	06.20.025-1	Trigger disc with magnets	WAUKESHA® VHP series – 12 cylinders	7.45 in	12+1	305805G
06.20.045-1	4		Trigger disc with magnet	WAUKESHA® VGF series	5.00 in	1	
06.20.045-6	4		Trigger disc with magnets	WAUKESHA® VGF series – 6 cylinders	5.00 in	6+1	305805
06.20.045-8	4		Trigger disc with magnets	WAUKESHA® VGF series – 8 cylinders	5.00 in	8+1	305805A

¹⁾ Comes with lock nut.

Accessories for Trigger Discs for WAUKESHA® VHP Series Gas Engines

P/N	Figure	Supersedes	Description	Equivalent to
06.20.070	1B		Hub for trigger discs P/N 06.20.069-1/-6/-12	A168368E

Trigger Discs with Metal Inlets

P/N	Figure	Supersedes	Description	Diameter	Events	Equivalent to
06.20.400	5		Trigger disc with metal inlets	7.45 in	2+1	790302-1
06.20.401	5		Trigger disc with metal inlets	7.45 in	3+1	790303-1
06.20.402	5		Trigger disc with metal inlets	5.00 in	4+1	790314-1
06.20.403	5		Trigger disc with metal inlets	5.00 in	6+1	790316-1
06.20.404	5		Trigger disc with metal inlets	5.00 in	8+1	790318-1

Trigger Disc for IVECO® 5.9

P/N	Figure	Supersedes	Description	Diameter	Events	Equivalent to
06.20.251	6		Trigger disc with metal inlets	11.50 in	3+1	



Conversion: 1 inch = 25,4 mm / 1 foot = 0,3 m

Pickups & Trigger Drives

Reluctor Pins & Trigger Magnets

Reluctor Pin

P/N	Figure	Supersedes	Description	Diameter	Length	Equivalent to
06.80.104	1		Reluctor pin	0.25 in	0.75 in	

See page 64 for reluctor pin installation tool.

Trigger Magnets

P/N	Figure	Supersedes	Description	Thread	Length	Equivalent to
06.60.900	2		Trigger magnet	1/4-20 UNC	0.65 in	
06.60.922	2		Trigger magnet	M8x1.25	0.70 in	720002
06.60.925	3		Trigger magnet for CATERPILLAR® G3500 series	M8x1.25	1.34 in	260605, 260604

Trigger Drives

Trigger Conversion Kits for CATERPILLAR® G3300 & G3400 Series Gas Engines

P/N	Figure	Supersedes	Description	Events	Equivalent to
75.30.131-1	4	75.30.119-1, 75.30.101-1	Trigger conversion kit for CATERPILLAR® G3304/G3306	1	
75.30.132 ¹⁾	4	75.30.119	Trigger conversion kit for CATERPILLAR® G3304	4+1	
75.30.131 ¹⁾	4	75.30.101	Trigger conversion kit for CATERPILLAR® G3306	6+1	
75.30.133-1	4	75.30.100-1	Trigger conversion kit for CATERPILLAR® G3406	1	
75.30.133 ¹⁾	4	75.30.100	Trigger conversion kit for CATERPILLAR® G3406	6+1	

¹⁾ Trigger conversion kits also included in ignition kits (unshielded/shielded) for CATERPILLAR® G3300 & G3400 series gas engines.

Accessories for Trigger Conversion Kits for CATERPILLAR® G3300 & G3400 Series Gas Engines


P/N	Figure	Supersedes	Description	Engine	Equivalent to
24.95.002 ¹⁾	4a		Flange cover plate for magneto	G3300, G3400	
44.04.005 ²⁾	4b		Fork spanner, swan-necked	G3406	

¹⁾ Flange cover plate also included in ignition kits (unshielded/shielded) for CATERPILLAR® G3300 & G3400 series gas engines.

²⁾ Needs to be ordered separately.




1



2



3



4

Pickups & Trigger Drives



Trigger Conversion Kit for **DOOSAN**® GV222TI Gas Engine

P/N	Figure	Supersedes	Description	Events	Equivalent to
75.30.137 ¹⁾	5		Trigger conversion kit for DOOSAN® GV222TI	6+1	

¹⁾ Required pickup P/N 66.60.003-60 and pickup lead P/N 06.71.007 have to be ordered separately. Only for use, when GILL® ignition system was installed before. Illustration shows mounted kit on camshaft gear.

Trigger Drives for **WHITE SUPERIOR**® G825 & GT825 Gas Engines

P/N	Figure	Supersedes	Description	Events	Equivalent to
06.22.400-1 ¹⁾	6		Trigger drive for WHITE SUPERIOR® G825, GT825	1	
06.22.400-6 ¹⁾	6		Trigger drive for WHITE SUPERIOR® G825, GT825	6+1	
06.22.400-8 ¹⁾	6		Trigger drive for WHITE SUPERIOR® G825, GT825	8+1	

¹⁾ Required pickup P/N 66.60.003-60 and pickup lead P/N 06.71.007 have to be ordered separately.

Trigger Drive for **MAN**® E2842 E302 & **DOOSAN**® GV222TI Gas Engines

P/N	Figure	Supersedes	Description	Events	Equivalent to
06.23.001 ¹⁾	7		Trigger drive for MAN® E2842 E302, DOOSAN® GV222TI	6+1	

¹⁾ Required pickup P/N 66.60.003-60 and pickup lead P/N 06.71.007 have to be ordered separately.

Trigger Drive for **MAN**® E2866 E302 Gas Engine

P/N	Figure	Supersedes	Description	Events	Equivalent to
06.23.004 ¹⁾	8		Trigger drive for MAN® E2866 E302	6+1	

¹⁾ Required pickup P/N 66.60.003-60 and pickup lead P/N 06.71.007 have to be ordered separately.




4a



4b



5



6



7



8

■ Pickups & Trigger Drives



Trigger Devices

For applications where a trigger disc cannot be mounted due to difficult camshaft access, a trigger device is available. This unit is mounted at the location where the ignition magneto was installed. A built in trigger disc will sense the events necessary to trigger the ignition control unit. One (1) to a maximum of eight (8) trigger events are possible.

This covers most of the engines up to 16 cylinders operated in the field today. A proper mounting flange can be selected from a variety of flange designs typically used in the industry. Heavy duty bearings and a smart product design offer a long operating life cycle.

Specification Table

Before trying to specify the correct trigger device, please make available the ignition magneto part number. For details you might even want to look up the **ALTRONIC®** application chart. That Information will lead you to the MOTORTECH TriDev part number.

If any help is required, please call your nearest MOTORTECH sales partner.


ALTRONIC B MEDIUM ENGINES, 2-16 CYLINDERS		IDENTIFICATION FORM AIR AL-10-58
ALTRONIC B UNIT PART NO. DESIGNATION		
P A T T E R N S		
MOUNTING	A = Vertical Flange, 1 stud B2 = Base Mount, 2 studs D = Horizontal Flange, 3/8" pitch, 2 studs E = Base Mount, Stud G = Horizontal Flange, 2 studs G1 = Horizontal Flange, fine coupling G2 = Horizontal Flange, gear coupling H = Vertical Flange, 2 studs H1 = Vertical Flange, 2 studs, gear coupling J = Vertical Flange, 3 studs	
OPTIONS	K = High Output Option L = Exhaust Throttle Option	
EXHAUST MOUNTING	0 = 1/2" Bore 1 = 3/4" Bore 2 = 1" Bore 3 = 1 1/4" Bore 4 = 1 3/4" Bore 5 = 2" Bore	
GEAR RATIO	1 = 1:1 2 = 2:1 3 = 3:1 4 = 4:1 5 = 5:1 6 = 6:1	
PISTON PATTERN	A = Even Firing Pattern Other Letters = Odd Firing Pattern	
NO. CYLINDERS	2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 16	

Refer to **ALTRONIC III**
Application List – Chap-
ter Identification – and
choose **Gear Ratio** from
Part Number Designation
of former used magneto.

ALTRONIC III MEDIAN ENGINE, 2-1/2 CYLINDERS		APPLICATION LIST FORM AL-13-10-96			
ENGINE MODEL NO.	GEAR	NOTES	ALTRONIC III PART NO.	QUANTITY	QTY. x NOTES
CATERPILLAR					
5.15R1	1.1	CON	850P100.1	10	8.50
5.15R1	1.1	CON	850P100.2	6	5.10
5.15R1	1.1	CON	850P100.3	6	5.10
5.15R1	1.1	CON	850P100.4	6	5.10
5.15R1	1.1	CON	850P100.5	6	5.10
5.15R1	1.1	CON	850P100.6	6	5.10
5.15R1	1.1	CON	850P100.7	6	5.10
5.15R1	1.1	CON	850P100.8	6	5.10
5.15R1	1.1	CON	850P100.9	6	5.10
5.15R1	1.1	CON	850P100.10	6	5.10
5.15R1	1.1	CON	850P100.11	6	5.10
5.15R1	1.1	CON	850P100.12	6	5.10
5.15R1	1.1	CON	850P100.13	6	5.10
5.15R1	1.1	CON	850P100.14	6	5.10
5.15R1	1.1	CON	850P100.15	6	5.10
5.15R1	1.1	CON	850P100.16	6	5.10
5.15R1	1.1	CON	850P100.17	6	5.10
5.15R1	1.1	CON	850P100.18	6	5.10
5.15R1	1.1	CON	850P100.19	6	5.10
5.15R1	1.1	CON	850P100.20	6	5.10
5.15R1	1.1	CON	850P100.21	6	5.10
5.15R1	1.1	CON	850P100.22	6	5.10
5.15R1	1.1	CON	850P100.23	6	5.10
5.15R1	1.1	CON	850P100.24	6	5.10
5.15R1	1.1	CON	850P100.25	6	5.10
5.15R1	1.1	CON	850P100.26	6	5.10
5.15R1	1.1	CON	850P100.27	6	5.10
5.15R1	1.1	CON	850P100.28	6	5.10
5.15R1	1.1	CON	850P100.29	6	5.10
5.15R1	1.1	CON	850P100.30	6	5.10
5.15R1	1.1	CON	850P100.31	6	5.10
5.15R1	1.1	CON	850P100.32	6	5.10
5.15R1	1.1	CON	850P100.33	6	5.10
5.15R1	1.1	CON	850P100.34	6	5.10
5.15R1	1.1	CON	850P100.35	6	5.10
5.15R1	1.1	CON	850P100.36	6	5.10
5.15R1	1.1	CON	850P100.37	6	5.10
5.15R1	1.1	CON	850P100.38	6	5.10
5.15R1	1.1	CON	850P100.39	6	5.10
5.15R1	1.1	CON	850P100.40	6	5.10
5.15R1	1.1	CON	850P100.41	6	5.10
5.15R1	1.1	CON	850P100.42	6	5.10
5.15R1	1.1	CON	850P100.43	6	5.10
5.15R1	1.1	CON	850P100.44	6	5.10
5.15R1	1.1	CON	850P100.45	6	5.10
5.15R1	1.1	CON	850P100.46	6	5.10
5.15R1	1.1	CON	850P100.47	6	5.10
5.15R1	1.1	CON	850P100.48	6	5.10
5.15R1	1.1	CON	850P100.49	6	5.10
5.15R1	1.1	CON	850P100.50	6	5.10
5.15R1	1.1	CON	850P100.51	6	5.10
5.15R1	1.1	CON	850P100.52	6	5.10
5.15R1	1.1	CON	850P100.53	6	5.10
5.15R1	1.1	CON	850P100.54	6	5.10
5.15R1	1.1	CON	850P100.55	6	5.10
5.15R1	1.1	CON	850P100.56	6	5.10
5.15R1	1.1	CON	850P100.57	6	5.10
5.15R1	1.1	CON	850P100.58	6	5.

Refer to **ALTRONIC III Application List** and choose **Rotation** of your engine make and model from the list.


Selection **1 to 8** for use with inductive pickups only. Requires - **E** - **Pickup Port Arrangement A**.
Selection **9** for use with Hall effect pickups only. Requires - **E** - **Pickup Port Arrangement F**.



Refer to **ALTRONIC III Application List - Chapter Identification** - and choose Flange option from Part Number Designation of former used magneto.

Selection **A** to be used for
- **C** - **Trigger Arrangement**
1 to 8 only. Selection **F** to
be used for - **C** - **Trigger**
Arrangement 9 only.

Pickups & Trigger Drives



P/N 06.22. A B C - D - E

A	Gear Ratio		
1	1:1		
2	2:1		
3	3:1		
6	1.5:1		
B	Rotation		
1	CW (clockwise)		
2	CCW (counterclockwise)		
C	Trigger Arrangement		
1	1	Pin	Multiple pickup arrangement
2	2+1	Pins	Single pickup arrangement
3	3+1	Pins	Single pickup arrangement
4	4+1	Pins	Single pickup arrangement
6	6+1	Pins	Single pickup arrangement
8	8+1	Pins	Single pickup arrangement
9	1	Magnet	Multiple pickup arrangement
D	Flange		
A	Flange mount, vertical, 1 slot		
B	Base mount		
D	Flange mount, horizontal, 3 in. pilot, 2 slots		
G	Flange mount, horizontal, 2 slots		
GL	Flange mount, horizontal, flex coupling		
GN	Flange mount, horizontal, gear coupling		
GO	Flange mount, horizontal, 2 slots		
GV	Flange mount, vertical, 2 slots		
GVN	Flange mount, vertical, gear coupling		
J	Flange mount, vertical, 3 slots		
E	Pickup Port Arrangement		
A	M12 x 1	Pickup port for inductive pickup	
F	5/8-18 UNF	Pickup port for Hall effect pickup	

NOTE: Pickup and pickup lead have to be ordered separately.

Pickups & Trigger Drives

Tools & Accessories

Installation Tool for Reluctor Pin

P/N	Figure	Supersedes	Description	Equivalent to
44.99.011	1		Installation tool for reluctor pin	

Thread Adaptors


P/N	Figure	Supersedes	Description	Outer Thread	Inner Thread	Length	Equivalent to
06.60.908	2		Thread adaptor	5/8-18 UNF	M12x1	40 mm	
06.60.926	2		Thread adaptor	M18x1	M12x1	40 mm	
06.95.058	2		Thread adaptor	3/4-16 UNF	M12x1	24 mm	

Junction Boxes

P/N	Figure	Supersedes	Description	Connection	Hubs	Equivalent to
15.02.226	3		Junction box	1/2 in	2	
15.02.326	4		Junction box	1/2 in	3	
15.02.426	5		Junction box	1/2 in	4	

Drive Coupling for Magnetos and TriDev Trigger Devices

P/N	Figure	Supersedes	Description	Equivalent to
06.75.103	6	06.75.102	Drive coupling with roll pin, black	510454-P, 510454-U



Primary Leads

SHIELDED

Primary Leads – New Flex Style

In addition to its conventional primary leads, MOTORTECH offers a new type of primary lead that is produced with a special wire. The new primary leads are compliant with CSA Class I, Division 2, Group D, and they offer a significantly higher flexibility than conventional leads, shielded with braided steel, while being highly resistant to all kinds of environmental conditions.

The multi-layer design of the wire is free of entrapped air and prevents the accumulation of condensed water which can result in primary voltage flash-overs. Several different configurations with durable 90-degrees and 180-degrees 2-pole and 3-pole connectors are available.



New Flex Style



Conventional Style




The oil and UV resistant multi-conductor wire is specially designed for shielded CSA certified primary leads. It consists of a multi layer design:

- Fine bare copper wire
- PVC/Nylon insulation
- Aluminum-plated foil and tinned copper braid
- PVC jacket
- Temperature range -40° C to +90° C (-40° F to +194° F)

This design ensures that no humidity can be trapped in the lead.

Primary Leads



Primary Leads – 3 Pole Ignition Coil Connection – NPT Adaptors to Junction Box

Shielded		Unshielded	Ignition Coil Connector	Junction Box Adaptor	Conductor	Equivalent to ²⁾
New Flex Style	Conventional Style					
P/N ¹⁾						
95.01.110-L	95.01.010-L		MIL, 3 pole, socket, 180°	1/2-14 NPT, 180°	2 wire	593022-L
95.01.110-L-3	95.01.010-L-3		MIL, 3 pole, socket, 180°	3/8-18 NPT, 180°	2 wire	LT73002-L
95.01.120-L	95.01.020-L		MIL, 3 pole, socket, 90°	1/2-14 NPT, 180°	2 wire	593027-L
95.01.120-L-3	95.01.020-L-3		MIL, 3 pole, socket, 90°	3/8-18 NPT, 180°	2 wire	LT73012-L
95.01.121-L	95.01.021-L		MIL, 3 pole, socket, 90°	1/2-14 NPT, 180°	2 wire	593029-L
95.01.122-L	95.01.022-L		MIL, 3 pole, socket, 90°	1/2-14 NPT, 180°	2 wire ³⁾	593036-L
95.01.123-L	95.01.023-L		MIL, 3 pole, socket, 180°	1/2-14 NPT, 180°	2 wire ³⁾	593035-L

¹⁾ Standard braid lengths (-L) = 6 in, 9 in, 12 in, 15 in, 18 in, 24 in, 30 in, 36 in, 42 in, 48 in, 54 in, 60 in, 72 in, 84 in, 96 in, 108 in, 120 in, 135 in, 138 in, 150 in; other lengths available on request.

²⁾ Shown cross references refer to MOTORTECH Conventional Style primary leads. New Flex Style primary leads can be used instead as an upgrade.

³⁾ Wire length is double of braid length.




Repair Kits for Conventional Style Shielded Primary Leads – 3 Pole Ignition Coil Connection

P/N	Description	Lead Length	Ignition Coil Connector	Conductor	For use with Primary Lead, Length 10 to 180 in	Equivalent to
95.01.010-42-RC	Repair kit	42 in	MIL, 3 pole, socket, 180°	2 wire	95.01.010-L, 593022-L	583017-42
95.01.010-60-RC	Repair kit	60 in	MIL, 3 pole, socket, 180°	2 wire	95.01.010-L, 593022-L	583017-60
95.01.010-96-RC	Repair kit	96 in	MIL, 3 pole, socket, 180°	2 wire	95.01.010-L, 593022-L	583017-96
95.01.010-180-RC	Repair kit	180 in	MIL, 3 pole, socket, 180°	2 wire	95.01.010-L, 593022-L	583017-180
95.01.020-42-RC	Repair kit	42 in	MIL, 3 pole, socket, 90°	2 wire	95.01.020-L, 593027-L	583018-42
95.01.020-60-RC	Repair kit	60 in	MIL, 3 pole, socket, 90°	2 wire	95.01.020-L, 593027-L	583018-60
95.01.020-96-RC	Repair kit	96 in	MIL, 3 pole, socket, 90°	2 wire	95.01.020-L, 593027-L	583018-96
95.01.020-180-RC	Repair kit	180 in	MIL, 3 pole, socket, 90°	2 wire	95.01.020-L, 593027-L	583018-180



Primary Leads

Primary Leads – 2 Pole Ignition Coil Connection – NPT Adaptors to Junction Box



Shielded		Unshielded	Ignition Coil Connector	Junction Box Adaptor	Conductor	Equivalent to ²⁾
New Flex Style	Conventional Style					
P/N ¹⁾						
95.06.110-L	95.06.010-L		MIL, 2 pole, socket, 180°	1/2-14 NPT, 180°	2 wire	A754-L, LT2001-L
95.06.120-L	95.06.020-L		MIL, 2 pole, socket, 90°	1/2-14 NPT, 180°	2 wire	B754-L, LT2011-L
	95.06.030-L		MIL, 2 pole, socket, 180°	5/8-24 NPT, 90°	2 wire	C754-L, LT2100-L

¹⁾ Standard braid lengths (-L) = 6 in, 9 in, 12 in, 15 in, 18 in, 24 in, 30 in, 36 in, 42 in, 48 in, 54 in, 60 in, 72 in, 84 in, 96 in, 108 in, 120 in, 135 in, 138 in, 150 in; other lengths available on request.

²⁾ Shown cross references refer to MOTORTECH Conventional Style primary leads. New Flex Style primary leads can be used instead as an upgrade.

Primary Leads – 3 Pole Ignition Coil Connection – Special



Shielded		Unshielded	Ignition Coil Connector	Electronic Box Connector	Conductor	Equivalent to ²⁾
New Flex Style	Conventional Style					
P/N ¹⁾						
95.01.130-L	95.01.030-L		MIL, 3 pole, socket, 90°	MIL, 3 pole, socket, 180°	2 wire	593069-L
95.01.131-L	95.01.031-L		MIL, 3 pole, socket, 90°	MIL, 3 pole, pin, 90°	2 wire	
95.01.133-L	95.01.033-L		MIL, 3 pole, socket, 90°	MIL, 3 pole, socket, 180°	3 wire	

¹⁾ Standard braid lengths (-L) = 6 in, 9 in, 12 in, 15 in, 18 in, 24 in, 30 in, 36 in, 42 in, 48 in, 54 in, 60 in, 72 in, 84 in, 96 in, 108 in, 120 in, 135 in, 138 in, 150 in; other lengths available on request.

²⁾ Shown cross references refer to MOTORTECH Conventional Style primary leads. New Flex Style primary leads can be used instead as an upgrade.

Primary Leads – 2 Pole Ignition Coil Connection – Special



Shielded		Unshielded	Ignition Coil Connector	Electronic Box Connector	Conductor	Equivalent to
New Flex Style	Conventional Style					
P/N ¹⁾						
95.01.132-L	95.01.032-L		MIL, 2 pole, pin, 90°	MIL, 2 pole, pin, 90°	2 wire	

¹⁾ Standard braid lengths (-L) = 6 in, 9 in, 12 in, 15 in, 18 in, 24 in, 30 in, 36 in, 42 in, 48 in, 54 in, 60 in, 72 in, 84 in, 96 in, 108 in, 120 in, 135 in, 138 in, 150 in; other lengths available on request.



Primary Leads



Cable Assemblies – NPT Adaptors to Junction Box

Shielded		Unshielded	Ignition Coil Connector	Outlet Junction Adaptor	Conductor	Equivalent to ²⁾
New Flex Style	Conventional Style					
P/N ¹⁾						
95.01.111-L	95.01.011-L		MIL, 3 pole, socket, 180°	1/2-14 NPT, 180°	3 wire	
95.01.124-L	95.01.024-L		MIL, 3 pole, socket, 90°	1/2-14 NPT, 180°	3 wire	593024-L
	95.01.025-L		MIL, 4 pole, socket, 90°	1/2-14 NPT, 180°	5 wire	593025-L
	95.01.026-L		MIL, 5 pole, socket, 90°	1/2-14 NPT, 180°	6 wire	593026-L

¹⁾ Standard braid lengths (-L) = 6 in, 9 in, 12 in, 15 in, 18 in, 24 in, 30 in, 36 in, 42 in, 48 in, 54 in, 60 in, 72 in, 84 in, 96 in, 108 in, 120 in, 135 in, 138 in, 150 in; other lengths available on request.

²⁾ Shown cross references refer to MOTORTECH Conventional Style primary leads. New Flex Style primary leads can be used instead as an upgrade.

Special Application Primary Leads

Primary Leads for ROLLS-ROYCE® Gas Engines



Shielded		Unshielded	Ignition Coil Connector	Wiring Rail Connector	Conductor	Equivalent to
New Flex Style	Conventional Style					
P/N ¹⁾						
	95.01.012-14		MIL, 3 pole, socket, 90°	3 pole, socket, 90°	2 wire	702930, 593068-1
	95.01.013-30		MIL, 3 pole, socket, 90°	3 pole, socket, 180°	2 wire	705165, 593068-2

¹⁾ Standard braid lengths 14 in and 30 in; other lengths available on request.

Primary Leads for WAUKESHA® ESM Gas Engines



Shielded		Unshielded	Ignition Coil Connector	Wiring Rail Connector	Conductor	Equivalent to 2)
New Flex Style	Conventional Style					
P/N						
95.01.107-24 1)		A740746-MOT	MIL, 3 pole, socket, 90°	3 pole, socket, 180°	2 wire	A740746, 740746D
		740746B-MOT	2 wire, 180°	3 pole, socket, 180°	2 wire	740746B

¹⁾ Standard lead length 24 in; other lengths available on request.

²⁾ Shown cross references refer to unshielded primary leads. New Flex Style primary leads can be used instead as an upgrade.

Primary Lead for ALTRONIC® EZRAIL Ignition Rail System – Unshielded



P/N ¹⁾	Description	Ignition Coil Connector	Lead Length	Conductor	Equivalent to
06.30.111-60	Primary lead	MIL, 3 pole, socket, 180°	60 in	2 wire	583017-60KT

¹⁾ Other lengths available on request.

Primary Leads for WAUKESHA® ESM Gas Engines



P/N A740746-MOT



P/N 740746B-MOT

Primary Leads



Primary Leads for MOTORTECH AlphaRail Wiring Rails


For linking flange, integral or externally mounted ignition coils to its AlphaRail ignition wiring rails, MOTORTECH offers a special series of primary leads. Several different configurations are available to offer an individual solution for any application.

- 1 2 or 3 pole MIL style connectors as 90° or 180° type for ignition coil connection
- 2 Primary leads available for shielded applications (Conventional or New Flex Style) or unshielded applications
- 3 2 pole MIL style connector as 90° or 180° type for wiring rail connection



Shielded		Unshielded	Ignition Coil Connector	Wiring Rail Connector	Conductor	Equivalent to
New Flex Style	Conventional Style					
P/N ¹⁾						
95.01.140-L	95.01.040-L	06.01.040-L	MIL, 3 pole, socket, 180°	MIL, 2 pole, pin, 180°	2 wire	
95.01.141-L	95.01.041-L	06.01.041-L	MIL, 3 pole, socket, 90°	MIL, 2 pole, pin, 180°	2 wire	
95.01.142-L	95.01.042-L	06.01.042-L	MIL, 2 pole, socket, 180°	MIL, 2 pole, pin, 180°	2 wire	
95.01.143-L	95.01.043-L	06.01.043-L	MIL, 2 pole, socket, 90°	MIL, 2 pole, pin, 180°	2 wire	
95.01.144-L	95.01.044-L	06.01.044-L	MIL, 3 pole, socket, 180°	MIL, 2 pole, pin, 90°	2 wire	
95.01.145-L	95.01.045-L	06.01.045-L	MIL, 3 pole, socket, 90°	MIL, 2 pole, pin, 90°	2 wire	
95.01.146-L	95.01.046-L	06.01.046-L	MIL, 2 pole, socket, 180°	MIL, 2 pole, pin, 90°	2 wire	
95.01.147-L	95.01.047-L	06.01.047-L	MIL, 2 pole, socket, 90°	MIL, 2 pole, pin, 90°	2 wire	

¹⁾ Standard lead lengths (-L) = 6 in, 9 in, 12 in, 15 in, 18 in, 24 in, 30 in, 36 in, 42 in, 48 in, 54 in, 60 in, 72 in, 84 in; other lengths available on request.
Add suffix "-X" to part number for cross wired primary leads for positive grounded ignition systems (e.g. 95.01.140-18-X).



■ Spark Plug Leads & Extensions

UNSHIELDED



PolyMot™ Spark Plug Leads

MOTORTECH's PolyMot™ spark plug lead was globally patented in 1996. Since then more than one million leads were manufactured to this design. These spark plug leads are unique and offer several advantages when being compared to the OEM or aftermarket competition. With the knowledge gathered in ignition control and ignition coil research and manufacturing, a lot of the details were implemented into these products. The unique structure has achieved tremendous reliability records in the field.

General Features

- Rigid design
- Insulators made of high quality Teflon® and up to 36 inch length
- Ceramic insert with 5 kΩ resistor for EMI suppression (0 kΩ available on request)
- Reliable ignition coil and spark plug terminals
- Critical high voltage areas are protected with seals
- Designed to match the engine model, the spark plug type and application
- Insulators are labeled with P/N and production code for easy traceability
- Long life product

Key Design Features

- 1 Reliable terminals to fit a large variety of different ignition coil types
- 2 The blue ignition cable is specially designed for high dielectric strength
- 3 Special silicone boots for wire output with excellent temperature and aging characteristics
- 4 Highest dielectric strength due to Teflon® insulator
- 5 Ceramic insert with 5 kΩ resistor for EMI suppression
- 6 Integrated silicone seal rings for best flashover protection will not stick on the spark plug insulator when pulling off the Teflon® insulator




Spark Plug Leads & Extensions



Specification Table

Please consult factory or your nearest MOTORTECH distributor to get the correct PolyMot™ spark plug lead specified for your engine application.



Questionnaire for PolyMot™ Specification.

Engine make	
Series	
Engine model	
Spark plug make and model A	
Spark plug well depth B	
Spark plug well inner diameter C	
Spark plug well outer diameter D	
Spark plug well to valve cover distance E	
Length of ignition cable F	
Ignition coil make and model G	
Built in 5 kΩ ceramic resistor (recommended) H	☐ Yes ☐ No
Seal ring on Teflon® insulator J	☐ Yes ☐ No
Grommet to cover the spark plug well K	☐ Yes ☐ No
Lead output from Teflon® insulator L	☐ 90° ☐ 180°
Terminal to ignition coil (preferred) M	☐ 90° ☐ 180°

Spark Plug Leads & Extensions

UNSHIELDED

PolyMot™ Spark Plug Leads for common Applications

P/N	Engine Make	Model	Spark Plug	P/N Silicone Seal Ring	Teflon® Insulator Length	Resistance ¹⁾	Lead Output from Teflon® Insulator	Ignition Cable Length ²⁾	Ignition Coil Connection
06.85.908-22	AJAX®	2802	3076	06.84.059	6 in	6 kΩ	180°	17 in	6
06.85.1047-24	AJAX®	DPC2802	W80N	06.84.040	5 in	5 kΩ	180°	19 in	5A
06.85.1054-18	CATERPILLAR®	G3400 series	B4321	06.84.044	13 in	5 kΩ	90°	18 in	1
06.85.751-18	CATERPILLAR®	G3400 series	GE3-5, RN79G	06.84.059	13 in	5 kΩ	90°	18 in	1
06.85.1019-16	CATERPILLAR®	G3400 series	GE3-5, RN79G	06.84.059	13 in	6 kΩ	90°	18 in	6
06.85.594-22	CATERPILLAR®	G3500 series	GI3-3, FB77WPCC	06.84.040	15 in	5 kΩ	90°	16 in	1
06.85.954-16	CATERPILLAR®	G3500 series	GI3-3, FB77WPCC	06.84.040	15 in	6 kΩ	90°	16 in	6
06.85.966-35	CLARK®	TCV-16	GK3-5, RC78PYP	06.84.044	11 in	5 kΩ	180°	24 in	5A
06.85.1020-24	CLARK®	TCVD12	RW80N	06.84.040	7 in	5 kΩ	90°	24 in	5A
06.85.1069-20	CLARK®	TCVD12	RW80N	06.84.040	12 in	5 kΩ	90°	20 in	5A
06.85.505-18	CLARK®	TLA-6	RW80N	06.84.040	11 in	5 kΩ	90°	18 in	5A
06.85.1071-18	COOPER®	12W330	B7224	06.84.040	8 in	5 kΩ	90°	18 in	5A
06.85.670-16	COOPER®	GMV-8	RW77PP	06.84.040	11 in	5 kΩ	90°	12 in	5A
06.85.1047-24	COOPER®	GMV-8	W80N	06.84.040	5 in	5 kΩ	180°	19 in	5A
06.85.958-16	COOPER®	LSV-16 (Center)	RW80PP	06.84.040	22 in	5 kΩ	90°	16 in	5A
06.85.910-18	COOPER®	LSV-16 (Center)	RW80PP	06.84.040	22 in	5 kΩ	90°	18 in	1
06.85.957-22	COOPER®	LSV-16 (Side)	RW80PP	06.84.040	14 in	5 kΩ	90°	22 in	5A
06.85.909-24	COOPER®	LSV-16 (Side)	RW80PP	06.84.040	14 in	5 kΩ	90°	24 in	1
06.85.083-22	CUMMINS®	5.9, GTA 8.3	GK3-5, RC78PYP	06.84.033	6 in	5 kΩ	180°	16 in	4
06.85.683-18	CUMMINS®	G855	GK3-5, RC78PYP	06.84.044	12 in	5 kΩ	90°	18 in	1
06.85.675-16	CUMMINS®	GTA14	GK3-5, RC78PYP	06.84.033	10 in	5 kΩ	90°	16 in	4
06.85.1014-12	CUMMINS®	KTA19GC	GE3-5, RN79G	06.84.059	14 in	5 kΩ	90°	12 in	1
06.85.1066-12	CUMMINS®	KTA19GC	GE3-5, RN79G	06.84.059	14 in	5 kΩ	90°	12 in	8
06.85.1068-18	DOOSAN®	GV222TIC	GK3-5, RC78PYP	06.84.033	6 in	5 kΩ	180°	12 in	1
06.85.835-18	DOOSAN®	GV222TIC	GK3-5, RC78PYP	06.84.033	6 in	6 kΩ	180°	12 in	6
06.85.528-14	GUASCOR®	SFGLD series	GI3-1, FB77WPCC	06.84.040	11 in	5 kΩ	180°	14 in	1
06.85.586-14	GUASCOR®	SFGLD series	GI3-1, FB77WPCC	06.84.040	11 in	5 kΩ	180°	14 in	2
06.85.864-26	GUASCOR®	SFGLD series	GI3-1, FB77WPCC	06.84.040	11 in	5 kΩ	180°	14 in	7
06.85.926-20	IVECO®	GE8291SRG75	GK3-5, RC78PYP	06.84.044	10 in	5 kΩ	90°	20 in	1
06.85.487-18	LIEBHERR®	G924, G926	GK3-5, RC78PYP	06.84.033	6 in	5 kΩ	180°	12 in	2
06.85.873-18	LIEBHERR®	G926TI	GK3-5, RC78PYP	06.84.033	6 in	5 kΩ	180°	12 in	7
06.85.1037-16	MAN®	E0834E/LE, E0836E	B4321	06.84.044	6 in	5 kΩ	180°	10 in	7
06.85.709H-18	MAN®	E0834E/LE, E0836E	GK3-5, RC78PYP	06.84.044	6 in	5 kΩ	180°	10 in	1
06.85.988-18	MAN®	E0834E/LE, E0836E	GK3-5, RC78PYP	06.84.044	6 in	5 kΩ	180°	10 in	1A
06.85.577H-16	MAN®	E0834E/LE, E0836E	GK3-5, RC78PYP	06.84.044	6 in	5 kΩ	180°	10 in	2
06.85.717H-24	MAN®	E0834E/LE, E0836E	GK3-5, RC78PYP	06.84.044	6 in	6 kΩ	180°	18 in	6
06.85.839H-16	MAN®	E0834E/LE, E0836E	GK3-5, RC78PYP	06.84.044	6 in	5 kΩ	180°	10 in	7
06.85.1030-16	MAN®	E0836LE, E28 series	B4321	06.84.044	6 in	5 kΩ	180°	10 in	1
06.85.1049-16	MAN®	E0836LE, E28 series	B4321	06.84.044	5 in	5 kΩ	180°	11 in	2
06.85.1031-16	MAN®	E0836LE, E28 series	B4321	06.84.044	6 in	5 kΩ	180°	10 in	7
06.85.580H-18	MAN®	E0836LE, E28 series	GE3-5, RN79G	06.84.059	6 in	5 kΩ	180°	12 in	1
06.85.989-18	MAN®	E0836LE, E28 series	GE3-5, RN79G	06.84.059	6 in	5 kΩ	180°	10 in	1A
06.85.415H-16	MAN®	E0836LE, E28 series	GE3-5, RN79G	06.84.059	6 in	5 kΩ	180°	10 in	2

¹⁾ For 0 kΩ resistance, please add "-0" to part number (e.g. 06.85.908-22-0).

²⁾ Other lengths in 2 in increments available on request. For loose connector and 36 in length add "-K" to part number (e.g. 06.85.908-K)

Spark Plug Leads & Extensions



PolyMot™ Spark Plug Leads for common Applications

P/N	Engine Make	Model	Spark Plug	P/N Silicone Seal Ring	Teflon® Insulator Length	Resistance ¹⁾	Lead Output from Teflon® Insulator	Ignition Cable Length ²⁾	Ignition Coil Connection
06.85.836H-16	MAN®	E0836LE, E28 series	GE3-5, RN79G	06.84.059	6 in	5 kΩ	180°	10 in	7
06.85.1038-20	MAN®	E26 series	B4321	06.84.044	11 in	5 kΩ	180°	10 in	7
06.85.929-20	MAN®	E26 series	GK3-5, RC78PYP	06.84.044	11 in	5 kΩ	180°	10 in	7
06.85.1005-24	MAN®	E28 series	GL3-5, B8324	06.84.040	7 in	5 kΩ	180°	17 in	1A
06.85.1050-18	MAN®	E32 series	B4321	06.84.044	8 in	5 kΩ	180°	10 in	1
06.85.1023-18	MAN®	E32 series	B4321	06.84.044	10 in	5 kΩ	180°	13 in	7
06.85.1058-18	MAN®	E32 series	GE3-5, RN79G	06.84.059	8 in	5 kΩ	180°	10 in	2
06.85.959-18	MAN®	E32 series	GE3-5, RN79G	06.84.059	10 in	5 kΩ	180°	13 in	7
06.85.1042-18	MAN®	E32 series	GL3-5, B8324	06.84.040	10 in	5 kΩ	180°	10 in	7
06.85.1073-18	MAN®	E32 series with new valve covers ³⁾	14GZ-LL	06.84.059	8 in	5 kΩ	180°	10 in	7
06.85.1079-18	MAN®	E32 series with new valve covers ³⁾	B4321	06.84.044	8 in	5 kΩ	180°	10 in	7
06.85.1080-18	MAN®	E32 series with new valve covers ³⁾	B8324	06.84.040	8 in	5 kΩ	180°	10 in	7
06.85.1078-18	MAN®	E32 series with new valve covers ³⁾	GE3-5, 14R-4DIU2	06.84.059	8 in	5 kΩ	180°	10 in	7
06.85.1074-18	MAN®	E32 series with new valve covers ³⁾	GL3-5, 7308	06.84.040	8 in	5 kΩ	180°	10 in	7
06.85.1081-14	mitsubishi®	S12R-PTA	B7224	06.84.040	13 in	5 kΩ	90°	14 in	1
06.85.320H-18	MWM®/DEUTZ®	232, 234 series	GE3-5, RN79G	06.84.059	6 in	5 kΩ	90°	18 in	1
06.85.179-20	MWM®/DEUTZ®	604, 620, 2020 series	GL3-3, RB75WPCC	06.84.040	10 in	5 kΩ	90°	20 in	1
06.85.178-20	MWM®/DEUTZ®	604, 620, 2020 series	GL3-3, RB75WPCC	06.84.040	10 in	5 kΩ	90°	20 in	2
06.85.998-20	MWM®/DEUTZ®	604, 620, 2020 series	GL3-3, RB75WPCC	06.84.040	10 in	5 kΩ	90°	20 in	7
06.85.310H-11	MWM®/DEUTZ®	616, 2016 series	GL3-3, RB75WPCC	06.84.040	9 in	5 kΩ	90°	11 in	1
06.85.1070-18	PERKINS®	3000 series	GK3-5, RC78PYP	06.84.044	9 in	5 kΩ	90°	18 in	7
06.85.479	PERKINS®	4000 series	GI3-3, FB77WPCC	06.84.040	12 in	5 kΩ	180°	13 in	1
06.85.1072-28	ROLLSROYCE®	K-Series	GE3-5, RN79G	06.84.059	17 in	5 kΩ	90°	28 in	1

¹⁾ For 0 kΩ resistance, please add "-0" to part number (e.g. 06.85.908-22-0).

²⁾ Other lengths in 2 in increments available on request. For loose connector and 36 in length add "-K" to part number (e.g. 06.85.908-K).

³⁾ Please also see page 219 for MOTORTECH valve cover conversion kit for recommended retrofitting of already operating engines without safety devices.



5A = ALTRONIC® style; 5B = BENDIX® style; 5C = MOTORTECH

Spark Plug Leads & Extensions

UNSHIELDED

PolyMot™ Spark Plug Leads for common Applications

P/N	Engine Make	Model	Spark Plug	P/N Silicone Seal Ring	Teflon® Insulator Length	Resistance ¹⁾	Lead Output from Teflon® Insulator	Ignition Cable Length ²⁾	Ignition Coil Connection
06.85.271	WÄRTSILÄ®	25SG series	GE3-5, RN79G	06.84.059	17 in	5 kΩ	90°	14 in	4
06.85.272	WÄRTSILÄ®	25SG series	GI3-3, FB77WPCC	06.84.040	17 in	5 kΩ	90°	14 in	4
06.85.312	WÄRTSILÄ®	25SG series	GI3-3, FB77WPCC	06.84.040	16 in	5 kΩ	90°	14 in	4
06.85.281	WÄRTSILÄ®	28SG series	GI3-3, FB77WPCC	06.84.040	21 in	5 kΩ	180°	14 in	4
06.85.306-18	WAUKESHA®	VGF series	GI3-3, FB77WPCC	06.84.040	12 in	5 kΩ	90°	18 in	1
06.85.326-16	WAUKESHA®	VGF series	GI3-3, FB77WPCC	06.84.040	10 in	5 kΩ	180°	6 in	1
06.85.429-14	WAUKESHA®	VGF series	GI3-3, FB77WPCC	06.84.040	11 in	5 kΩ	90°	14 in	1
06.85.357-26	WAUKESHA®	VGF series	GI3-3, FB77WPCC	06.84.040	12 in	5 kΩ	180°	14 in	2
06.85.423-16	WAUKESHA®	VHP GL series	GT3-1, RM77N	06.84.040	11 in	5 kΩ	90°	16 in	1
06.85.649-16	WAUKESHA®	VHP GL series	GT3-1, RM77N	06.84.040	11 in	5 kΩ	90°	24 in	5A
06.85.739-16	WAUKESHA®	VHP GL series	GT3-1, RM77N	06.84.040	9 in	5 kΩ	90°	16 in	1
06.85.945-16	WAUKESHA®	VHP GL series	GT3-1, RM77N	06.84.040	9 in	6 kΩ	90°	16 in	6
06.85.993-24	WAUKESHA®	VHP GU series	D14, D14N	06.84.077	13 in	5 kΩ	90°	24 in	1
06.85.688-16	WAUKESHA®	VHP GU series	GI3-1, FB77WPCC	06.84.040	11 in	5 kΩ	90°	16 in	1
06.85.422-16	WAUKESHA®	VHP GU series	GT3-1, RM77N	06.84.040	13 in	5 kΩ	90°	16 in	1
06.85.672H-22	WAUKESHA®	VHP GU/GSI series	GI3-3, FB77WPCC	06.84.040	14 in	5 kΩ	90°	22 in	5A
06.85.705-16	WAUKESHA®	VHP GU/GSI series	GT3-1, RM77N	06.84.040	12 in	5 kΩ	90°	16 in	1
06.85.720-18	WAUKESHA®	VHP GU/GSI series	GT3-1, RM77N	06.84.040	12 in	5 kΩ	90°	18 in	1
06.85.894-18	WAUKESHA®	VHP GU/GSI series	GT3-1, RM77N	06.84.040	14 in	6 kΩ	90°	18 in	6
06.85.699-16	WAUKESHA®	VHP GU/GSI series	M82N	06.84.040	12 in	5 kΩ	90°	16 in	1
06.85.848-16	WAUKESHA®	VHP Series Four	GI3-3, FB77WPCC	06.84.040	16 in	5 kΩ	90°	16 in	1
06.85.714-24	WAUKESHA®	VHP, AT series	GI3-3, FB77WPCC	06.84.040	18 in	5 kΩ	90°	24 in	1
06.85.678-24	WAUKESHA®	VSG series	GE3-5, RN79G	06.84.059	5 in	5 kΩ	180°	18 in	1
06.85.667-26	WHITESUPERIOR®	G825 series	GT3-1, RM77N	06.84.040	8 in	5 kΩ	90°	24 in	1
06.85.723-24	WHITESUPERIOR®	GTLB825	D16	06.81.005	6 in	5 kΩ	90°	24 in	1
06.85.999-14	WORTHINGTON®	MLV (Center)	RW80N	06.84.040	15 in	5 kΩ	90°	14 in	5A
06.85.1000-14	WORTHINGTON®	MLV (Side)	RW80N	06.84.040	22 in	5 kΩ	90°	14 in	5A
06.85.913-30	WORTHINGTON®	MLV10 (Center)	RW82P	06.84.040	20 in	5 kΩ	90°	30 in	5A
06.85.912-24	WORTHINGTON®	MLV10 (Side)	GK3-5, RC78PYP	06.84.044	17 in	5 kΩ	90°	24 in	5A
06.85.1063-14	WORTHINGTON®	MLV14	RW80N	06.84.040	18 in	5 kΩ	90°	14 in	5A

¹⁾ For 0 kΩ resistance, please add “-0” to part number (e.g. 06.85.908-22-0).

²⁾ Other lengths in 2 in increments available on request. For loose connector and 36 in length add “-K” to part number (e.g. 06.85.908-K).

Ignition Coil Connections



5A = ALTRONIC® style; 5B = BENDIX® style; 5C = MOTORTECH

■ Spark Plug Leads & Extensions



Silicone Seal Rings for PolyMot™ Spark Plug Leads ¹⁾

P/N	Description	Fits Spark Plug ²⁾	Dimensions			Quantity	Equivalent to
			OD	ID	Height		
06.84.033-100	Silicone seal ring	GK3-5, RC78PYP, B4321	19.0 mm	10.0 mm	12.0 mm	100 pcs	
06.84.034-100	Silicone seal ring	GI3-1, FB77WPCC, B8324	20.0 mm	12.0 mm	15.0 mm	100 pcs	
06.84.038-100	Silicone seal ring	RW80N	20.0 mm	14.4 mm	15.0 mm	100 pcs	
06.84.040-100	Silicone seal ring	GI3-1, FB77WPCC, B8324	20.0 mm	14.0 mm	15.0 mm	100 pcs	
06.84.044-100	Silicone seal ring	GK3-5, RC78PYP, B4321	20.0 mm	10.0 mm	15.0 mm	100 pcs	
06.84.059-100	Silicone seal ring	GE3-5, RN79G	20.0 mm	11.2 mm	15.0 mm	100 pcs	
06.84.077-100	Silicone seal ring	D14, D14N	20.0 mm	13.5 mm	15.0 mm	100 pcs	
06.84.121-100	Silicone seal ring	GK3-5, RC78PYP, B4321	16.0 mm	10.0 mm	11.0 mm	100 pcs	




¹⁾ Silicone seal rings require replacement every 3000 running hours. See MOTORTECH homepage for appropriate instruction for replacing silicone seal rings.

²⁾ Information provided only for comparison purposes.

Installation Tool for **WAUKESHA**® Grommet

P/N	Supersedes	Description	Equivalent to
07.99.016		Installation tool for WAUKESHA® VHP grommet	



Flange Kit for Spark Plug Leads for **WAUKESHA**® VHP/AT and **CATERPILLAR**® G3500 Series Gas Engines

P/N	Supersedes	Description	Equivalent to
06.51.248		Flange kit for use with P/N 06.85.714-L, 06.85.594-L and 06.85.954-L	



■ Spark Plug Leads & Extensions

Spark Plug Leads for CATERPILLAR® G3300 & G3400 Series Gas Engines

The spark plug leads installed by engine manufacturers are not always the best choice when it comes to longevity and trouble-free operation of the engine. Especially for use on CATERPILLAR® G3300 and G3400 series gas engines, MOTORTECH offers suitable spark plug leads for easy replacement of original parts and as an upgrade for every engine. These spark plug leads offer several advantages when being compared to the OEM or aftermarket competition and solve the problems faced by plant operators on regular basis.

General Features

- Rigid design
- Insulators made of high quality Teflon®
- Reliable ignition coil and spark plug terminals
- Critical high voltage areas are protected with seals
- Designed to match the engine model, the spark plug type and application
- Long life product



Spark Plug Leads for CATERPILLAR® G3300 & G3400 Series Gas Engines

P/N	Engine Make	Model	Spark Plug	P/N Silicone Seal Ring	Teflon® Insulator Length	Resistance ¹⁾	Lead Output from Teflon® Insulator	Ignition Cable Length ²⁾	Ignition Coil Connection
06.88.009-16 ³⁾	CATERPILLAR®	G3300 series	GE3-5, RN79G	06.84.059	3.75 in	1 kΩ	180°	12 in	1
06.88.010-16	CATERPILLAR®	G3300 series	GE3-5, RN79G	06.84.059	4.25 in	0 kΩ	180°	12 in	2
06.85.1054-18	CATERPILLAR®	G3400 series	B4321	06.84.044	13.00 in	5 kΩ	90°	18 in	1
06.85.751-18 ⁴⁾	CATERPILLAR®	G3400 series	GE3-5, RN79G	06.84.059	13.00 in	5 kΩ	90°	18 in	1
06.85.939-18	CATERPILLAR®	G3400 series	GE3-5, RN79G	06.84.059	13.00 in	5 kΩ	90°	18 in	5A
06.85.1019-16	CATERPILLAR®	G3400 series	GE3-5, RN79G	06.84.059	13.00 in	6 kΩ	90°	18 in	6

¹⁾ For 0 kΩ resistance, please add “-0” to part number (e.g. 06.85.939-18-0).

²⁾ Other lengths in 2 in increments available on request. For loose connector and 36 in length add “-K” to part number (e.g. 06.85.751-K).

³⁾ P/N 06.88.009-16 equivalent to P/N 7W-2479.

⁴⁾ P/N 06.85.751-18 equivalent to P/N 7W-8542, 262-4855, 250-2149, 9Y-3362, 217-5922. Supersedes 06.88.003-L/-K, 06.85.687-L.

Ignition Coil Connections



5A = ALTRONIC® style; 5B = BENDIX® style; 5C = MOTORTECH

■ Spark Plug Leads & Extensions



CATERPILLAR®
P/N 7W-2479



MOTORTECH
P/N 06.88.009-16



Spark Plug Lead for CATERPILLAR® G3300 Series – Comparison


- | | |
|---|---|
| <p>1 The ignition coil connector features four instead of two contact springs which lead to a more reliable connection. The resistant silicone boot improves the protection against flashovers as well as the stability of the connection with the ignition coil.</p> <p>2 Silicone boot with excellent temperature and aging characteristics for wire output and spark plug well sealing</p> | <p>3 Reliable terminal for best spark plug connection</p> <p>4 Much thicker insulator is made of Teflon® instead of plastic for highest dielectric strength</p> <p>5 Integrated silicone seal ring for best flashover protection</p> |
|---|---|



CATERPILLAR®
P/N 250-2149



MOTORTECH
P/N 06.85.751-18



Spark Plug Lead for CATERPILLAR® G3400 Series – Comparison

- | | |
|--|---|
| <p>1 The ignition coil connector features four contact springs which lead to a more reliable connection. The resistant silicone boot improves the protection against flashovers as well as the stability of the connection with the ignition coil.</p> <p>2 Silicone boot with excellent temperature and aging characteristics for wire output and spark plug well sealing. Height-adjustable to compensate length differences of spark plug insulators.</p> | <p>3 Much thicker insulator is made of Teflon® instead of plastic for highest dielectric strength</p> <p>4 Ceramic insert with 5 kΩ resistor for EMI suppression and reliable terminal for best spark plug connection</p> <p>5 Integrated silicone seal ring for best flashover protection will not stick on the spark plug insulator when pulling off the Teflon® insulator</p> |
|--|---|

Spark Plug Leads & Extensions

UNSHIELDED

Spark Plug Leads for common Applications (Non PolyMot™ Style)

P/N	Engine Make	Model	Spark Plug	P/N Silicone Seal Ring	Insulator Length	Resistance ¹⁾	Lead Output from Insulator	Ignition Cable Length ²⁾	Ignition Coil Connection
06.85.697-20	AJAX®	230	GT3-1, RM77N	06.84.040	5 in	0 kΩ	90°	20 in	1
06.85.698-30	AJAX®	230	GT3-1, RM77N	06.84.040	5 in	0 kΩ	90°	30 in	5A
06.85.773-15	AJAX®	230	GT3-1, RM77N	06.84.034	5 in	0 kΩ	90°	15 in	5A
06.85.719-16	AJAX®	230	W18	06.81.017	5 in	0 kΩ	90°	16 in	1
06.85.860-16	ARROW®	VRG176, VRG220, VRG330	J6C, J8C	06.84.059	5 in	1 kΩ	90°	14 in	6
06.85.514-16	CLARK®	TLA-6	RW80N	06.84.038	8 in	0 kΩ	90°	16 in	5A
06.85.1046-16 ⁴⁾	CUMMINS®	G/GTA 5.9	GK3-5, RC78PYP		4 in	0 kΩ	180°	12 in	8
06.85.903-22 ³⁾	CUMMINS®	GTA 8.3	GK3-5, RC78PYP		5 in	5 kΩ	180°	17 in	8
06.85.1062-16	CUMMINS®	ISL G280	GK3-5, RC78PYP	06.84.121	6 in	5 kΩ	180°	10 in	7
06.85.949-10	DEUTZ®	2015 series	B4321, 14GZ6-77-2	06.84.033	9 in	6 kΩ	90°	10 in	6
06.88.015-48	INGERSOLL RAND®	KVSR12	RW80N	06.84.040	4 in	0 kΩ	180°	14 in	5A
06.85.1044-27	INGERSOLL RAND®	TVR10	RW83F	06.84.040	4 in	0 kΩ	180°	23 in	5A
06.85.964-20	LIEBHERR®	G9408	GK3-5, RC78PYP	06.81.071	6 in	5 kΩ	180°	14 in	2
06.85.1052-24	SCANIA®	DC12	GK3-5, RC78PYP	06.84.121	11 in	5 kΩ	90°	24 in	7
06.85.697-20	WAUKESHA®	F1197G	GT3-1, RM77N	06.84.040	11 in	0 kΩ	90°	20 in	1
06.85.695-24	WHITE SUPERIOR®	G825 series	D14N	06.84.040	8 in	0 kΩ	90°	24 in	5A
06.85.690-24	WHITE SUPERIOR®	G825 series	GK3-5, RC78PYP	06.84.044	5 in	0 kΩ	90°	24 in	1
06.85.1095-24	WHITE SUPERIOR®	G825 series	RD16, RD18Y	06.84.040	8 in	0 kΩ	90°	24 in	1
06.85.689-24	WHITE SUPERIOR®	G825 series (lean burn)	GK3-5, RC78PYP	06.84.044	8 in	0 kΩ	90°	24 in	1

¹⁾ For 0 kΩ resistance, please add "-0" to part number (e.g. 06.85.949-10-0).

²⁾ Other lengths in 2 in increments available on request. For loose connector and 36 in length add "-K" to part number (e.g. 06.85.697-K).

³⁾ P/N 06.85.903-22 equivalent to P/N 4989132.

⁴⁾ P/N 06.85.1046-16 equivalent to P/N 4090567 and P/N 26354.

Spark Plug Lead Kits

P/N	Engine Make	Model	Spark Plug	Number of included Leads	Insulator Length	Resistance	Lead Output from Insulator	Ignition Coil Connection
06.85.1006	ARROW®	VR330CF	GE3-5, RN79G	6	5 in	6 kΩ	180°	6
06.85.952 ¹⁾	GM®	V8	GK3-5, RC78PYP	8	4 in	0 kΩ	180°	4
06.85.379 ²⁾	MAN®	E2866 E302	GE3-5, RN79G	6	5 in	6 kΩ	180°	6
06.85.380 ²⁾	MAN®	E2842 E302	GE3-5, RN79G	12	5 in	6 kΩ	180°	6

¹⁾ Spark plug lead kit includes connecting leads from ignition coil to distributor.

²⁾ Spark plug lead kits include distributor caps and connecting leads from ignition coil to distributor

Ignition Coil Connections



5A = ALTRONIC® style; 5B = BENDIX® style; 5C = MOTORTECH


Spark Plug Leads & Extensions



Unshielded Safety Leads for Shielded Spark Plugs

P/N ¹⁾	SP Termination Well Depth	Spark Plug End	Ignition Coil End	Inductive Pickup Spacer	5 kΩ Resistor	Ignition Coil	Equivalent to
09.02.1000-L	2.125 in	180°	180°			291001-S, 501061-S, 591010-S	USL2A-"L"A, AWH81-"L"
09.02.1001-L	2.125 in	90°	180°			291001-S, 501061-S, 591010-S	USL2LA-"L"A
09.02.1010-L	2.125 in	180°	90°			291001-S, 501061-S, 591010-S	USL2AL-"L"A
09.02.1011-L	2.125 in	90°	90°			291001-S, 501061-S, 591010-S	USL2LAL-"L"A
09.02.1100-L	2.125 in	180°	180°	x		291001-S, 501061-S, 591010-S	USL2A-"L"AIPS
09.02.1101-L	2.125 in	90°	180°	x		291001-S, 501061-S, 591010-S	USL2LA-"L"AIPS
09.02.1110-L	2.125 in	180°	90°	x		291001-S, 501061-S, 591010-S	USL2AL-"L"AIPS
09.02.1111-L	2.125 in	90°	90°	x		291001-S, 501061-S, 591010-S	USL2LAL-"L"AIPS
09.02.1200-L	2.125 in	180°	180°		x	291001-S, 501061-S, 591010-S	RSL2A-"L"A
09.02.1201-L	2.125 in	90°	180°		x	291001-S, 501061-S, 591010-S	RSL2LA-"L"A
09.02.1210-L	2.125 in	180°	90°		x	291001-S, 501061-S, 591010-S	RSL2AL-"L"A
09.02.1211-L	2.125 in	90°	90°		x	291001-S, 501061-S, 591010-S	RSL2LAL-"L"A
09.02.1300-L	2.125 in	180°	180°	x	x	291001-S, 501061-S, 591010-S	RSL2A-"L"AIPS
09.02.1301-L	2.125 in	90°	180°	x	x	291001-S, 501061-S, 591010-S	RSL2LA-"L"AIPS
09.02.1310-L	2.125 in	180°	90°	x	x	291001-S, 501061-S, 591010-S	RSL2AL-"L"AIPS
09.02.1311-L	2.125 in	90°	90°	x	x	291001-S, 501061-S, 591010-S	RSL2LAL-"L"AIPS
09.02.2000-L	2.125 in	180°	180°			10-320790-1, 10-382040-1	USL2B-"L"A, AWH22-"L"
09.02.2001-L	2.125 in	90°	180°			10-320790-1, 10-382040-1	USL2LB-"L"A
09.02.2010-L	2.125 in	180°	90°			10-320790-1, 10-382040-1	USL2BL-"L"A
09.02.2011-L	2.125 in	90°	90°			10-320790-1, 10-382040-1	USL2LBL-"L"A
09.02.2100-L	2.125 in	180°	180°	x		10-320790-1, 10-382040-1	USL2B-"L"AIPS
09.02.2101-L	2.125 in	90°	180°	x		10-320790-1, 10-382040-1	USL2LB-"L"AIPS
09.02.2110-L	2.125 in	180°	90°	x		10-320790-1, 10-382040-1	USL2BL-"L" AIPS
09.02.2111-L	2.125 in	90°	90°	x		10-320790-1, 10-382040-1	USL2LBL-"L"AIPS
09.02.2200-L	2.125 in	180°	180°		x	10-320790-1, 10-382040-1	RSL2B-"L"A
09.02.2201-L	2.125 in	90°	180°		x	10-320790-1, 10-382040-1	RSL2LB-"L"A
09.02.2210-L	2.125 in	180°	90°		x	10-320790-1, 10-382040-1	RSL2BL-"L"A
09.02.2211-L	2.125 in	90°	90°		x	10-320790-1, 10-382040-1	RSL2LBL-"L"A
09.02.2300-L	2.125 in	180°	180°	x	x	10-320790-1, 10-382040-1	RSL2B-"L"AIPS
09.02.2301-L	2.125 in	90°	180°	x	x	10-320790-1, 10-382040-1	RSL2LB-"L"AIPS
09.02.2310-L	2.125 in	90°	90°	x	x	10-320790-1, 10-382040-1	RSL2LBL-"L"AIPS
09.02.2311-L	2.125 in	180°	90°	x	x	10-320790-1, 10-382040-1	RSL2BL-"L"AIPS
09.02.3000-L	2.125 in	180°	180°			PPT2477AD, PPT2477AD-L	USL2C-"L"A, AWH42-"L"

¹⁾ Standard lead lengths (-L) = 12 in, 18 in, 24 in, 30 in, 36 in; other lengths available on request. Consult factory for other configurations.



■ Spark Plug Leads & Extensions

Unshielded Safety Leads for Shielded Spark Plugs

P/N ¹⁾	SP Termination Well Depth	Spark Plug End	Ignition Coil End	Inductive Pickup Spacer	5 kΩ Resistor	Ignition Coil	Equivalent to
09.02.3001-L	2.125 in	90°	180°			PPT2477AD, PPT2477AD-L	USL2LC-“L”A
09.02.3010-L	2.125 in	180°	90°			PPT2477AD, PPT2477AD-L	USL2CL-“L”A
09.02.3011-L	2.125 in	90°	90°			PPT2477AD, PPT2477AD-L	USL2LCL-“L”A
09.02.3100-L	2.125 in	180°	180°	x		PPT2477AD, PPT2477AD-L	USL2C-“L”AIPS
09.02.3101-L	2.125 in	90°	180°	x		PPT2477AD, PPT2477AD-L	USL2LC-“L”AIPS
09.02.3110-L	2.125 in	180°	90°	x		PPT2477AD, PPT2477AD-L	USL2CL-“L”AIPS
09.02.3111-L	2.125 in	90°	90°	x		PPT2477AD, PPT2477AD-L	USL2LCL-“L”AIPS
09.02.3200-L	2.125 in	180°	180°		x	PPT2477AD, PPT2477AD-L	RSL2C-“L”A
09.02.3201-L	2.125 in	90°	180°		x	PPT2477AD, PPT2477AD-L	RSL2LC-“L”A
09.02.3210-L	2.125 in	180°	90°		x	PPT2477AD, PPT2477AD-L	RSL2CL-“L”A
09.02.3211-L	2.125 in	90°	90°		x	PPT2477AD, PPT2477AD-L	RSL2LCL-“L”A
09.02.3300-L	2.125 in	180°	180°	x	x	PPT2477AD, PPT2477AD-L	RSL2C-“L”AIPS
09.02.3301-L	2.125 in	90°	180°	x	x	PPT2477AD, PPT2477AD-L	RSL2LC-“L”AIPS
09.02.3310-L	2.125 in	180°	90°	x	x	PPT2477AD, PPT2477AD-L	RSL2CL-“L”AIPS
09.02.3311-L	2.125 in	90°	90°	x	x	PPT2477AD, PPT2477AD-L	RSL2LCL-“L”AIPS
09.02.4000-L	2.125 in	180°	180°			291001, 501061, 591010	USL2E-“L”A, AWH72-“L”
09.02.4001-L	2.125 in	90°	180°			291001, 501061, 591010	USL2LE-“L”A
09.02.4100-L	2.125 in	180°	180°	x		291001, 501061, 591010	USL2E-“L”AIPS
09.02.4101-L	2.125 in	90°	180°	x		291001, 501061, 591010	USL2LE-“L”AIPS
09.02.4110-L	2.125 in	180°	180°	x		291001, 501061, 591010	USL2E-“L”A w. 06.80.261
09.02.4200-L	2.125 in	180°	180°		x	291001, 501061, 591010	RSL2E-“L”A
09.02.4201-L	2.125 in	90°	180°		x	291001, 501061, 591010	RSL2LE-“L”A
09.02.4300-L	2.125 in	180°	180°	x	x	291001, 501061, 591010	RSL2E-“L”AIPS
09.02.4301-L	2.125 in	90°	180°	x	x	291001, 501061, 591010	RSL2LE-“L”AIPS
09.02.5000-L	2.125 in	180°	180°			PPT2477P, PPT2477L	USL2F-“L”A, AWH82-“L”
09.02.5001-L	2.125 in	90°	180°			PPT2477P, PPT2477L	USL2LF-“L”A
09.02.5100-L	2.125 in	180°	180°	x		PPT2477P, PPT2477L	USL2F-“L”AIPS
09.02.5101-L	2.125 in	90°	180°	x		PPT2477P, PPT2477L	USL2LF-“L”AIPS
09.02.5200-L	2.125 in	180°	180°		x	PPT2477P, PPT2477L	RSL2F-“L”A
09.02.5201-L	2.125 in	90°	180°		x	PPT2477P, PPT2477L	RSL2LF-“L”A
09.02.5300-L	2.125 in	180°	180°	x	x	PPT2477P, PPT2477L	RSL2F-“L”AIPS
09.02.5301-L	2.125 in	90°	180°	x	x	PPT2477P, PPT2477L	RSL2LF-“L”AIPS
09.02.7000-L	2.125 in	180°	180°			Unshielded in Coil Box inst.	USL2G-“L”A, AWH62-“L”
09.02.7001-L	2.125 in	90°	180°			Unshielded in Coil Box inst.	USL2LG-“L”A
09.02.7100-L	2.125 in	180°	180°	x		Unshielded in Coil Box inst.	USL2G-“L”AIPS
09.02.7101-L	2.125 in	90°	180°	x		Unshielded in Coil Box inst.	USL2LG-“L”AIPS
09.02.7200-L	2.125 in	180°	180°		x	Unshielded in Coil Box inst.	RSL2G-“L”A
09.02.7201-L	2.125 in	90°	180°		x	Unshielded in Coil Box inst.	RSL2LG-“L”A
09.02.7300-L	2.125 in	180°	180°	x	x	Unshielded in Coil Box inst.	RSL2G-“L”AIPS
09.02.7301-L	2.125 in	90°	180°	x	x	Unshielded in Coil Box inst.	RSL2LG-“L”AIPS

¹⁾ Standard lead lengths (-L) = 12 in, 18 in, 24 in, 30 in, 36 in; other lengths available on request.
Consult factory for other configurations.


Spark Plug Leads & Extensions



Unshielded Safety Leads for Conventional Spark Plugs

P/N ¹⁾	Fits max. Ceramic Diameter	Spark Plug End	Ignition Coil End	Inductive Pickup Spacer	5 kΩ Resistor	Ignition Coil	Equivalent to
09.03.1000-L	0.485 in	180°	180°			291001-S, 501061-S, 591010-S	USLA14SPB-“L”A
09.03.4000-L	0.485 in	180°	180°			291001, 501061, 591010	USLE14SPB-“L”A
09.04.1000-L	0.560 in	180°	180°			291001-S, 501061-S, 591010-S	USLA18SPB-“L”A
09.04.4000-L	0.560 in	180°	180°			291001, 501061, 591010	USLE18SPB-“L”A
09.05.1000-L	0.485 in	180°	180°			291001-S, 501061-S, 591010-S	USLA35SPB-“L”A
09.05.4000-L	0.485 in	180°	180°			291001, 501061, 591010	USLE35SPB-“L”A
09.06.1000-L	0.545 in	180°	180°			291001-S, 501061-S, 591010-S	USLA36SPB-“L”A
09.06.4000-L	0.545 in	180°	180°			291001, 501061, 591010	USLE36SPB-“L”A
09.07.1000-L	0.385 in	180°	180°			291001-S, 501061-S, 591010-S	USLA45SPB-“L”A
09.07.4000-L	0.385 in	180°	180°			291001, 501061, 591010	USLE45SPB-“L”A
09.08.1000-L	0.470 in	180°	180°			291001-S, 501061-S, 591010-S	USLA51SPB-“L”A
09.08.4000-L	0.470 in	180°	180°			291001, 501061, 591010	USLE51SPB-“L”A
09.09.1000-L	0.580 in	180°	180°			291001-S, 501061-S, 591010-S	USLA78SPB-“L”A
09.09.2000-L	0.580 in	180°	180°			10-320790-1, 10-382040-1	USLB78SPB-“L”A
09.09.4000-L	0.580 in	180°	180°			291001, 501061, 591010	USLE78SPB-“L”A
09.10.1000-L	Silicone Boot	180°	180°			291001-S, 501061-S, 591010-S	USLASB180-“L”A
09.10.2000-L	Silicone Boot	180°	180°			10-320790-1, 10-382040-1	USLBSB180-“L”A
09.10.3000-L	Silicone Boot	180°	180°			PPT2477AD, PPT2477ADL	USLCSB180-“L”A
09.10.4000-L	Silicone Boot	180°	180°			291001, 501061, 591010	USLESB180-“L”A
09.11.1000-L	Silicone Boot	90°	180°			291001-S, 501061-S, 591010-S	USLASL90-“L”A
09.11.2000-L	Silicone Boot	90°	180°			10-320790-1, 10-382040-1	USLBSL90-“L”A
09.11.3000-L	Silicone Boot	90°	180°			PPT2477AD, PPT2477ADL	USLCSL90-“L”A
09.11.4000-L	Silicone Boot	90°	180°			291001, 501061, 591010	USLESL90-“L”A
09.12.1000-L	Terminal	90°	180°			291001-S, 501061-S, 591010-S	USLA18T22-“L”A
09.12.2000-L	Terminal	90°	180°			10-320790-1, 10-382040-1	USLB18T22-“L”A
09.12.3000-L	Terminal	90°	180°			PPT2477AD, PPT2477ADL	USLC18T22-“L”A
09.12.4000-L	Terminal	90°	180°			291001, 501061, 591010	USLE18T22-“L”A
09.13.1000-L	Terminal	180°	180°			291001-S, 501061-S, 591010-S	USLA18T33-“L”A
09.13.2000-L	Terminal	180°	180°			10-320790-1, 10-382040-1	USLB18T33-“L”A
09.13.3000-L	Terminal	180°	180°			PPT2477AD, PPT2477ADL	USLC18T33-“L”A
09.13.4000-L	Terminal	180°	180°			291001, 501061, 591010	USLE18T33-“L”A

¹⁾ Standard lead lengths (-L) = 12 in, 18 in, 24 in, 30 in, 36 in; other lengths available on request.
Consult factory for other configurations.



Conversion: 1 inch = 25.4 mm / 1 foot = 0.3 m

■ Spark Plug Leads & Extensions

Accessories for Unshielded Spark Plug Leads

Ignition Cables – Nickel Plated Copper Wire

P/N	Figure	Description	Color	Equivalent to
02.85.757	1	Ignition cable, 7 mm silicone, 17-19 strands, 100 ft spool	blue	5419-100
02.85.758 ¹⁾	2	Ignition cable, 7 mm silicone, 17-19 strands, 100 ft spool	orange	757, 5419-151

¹⁾ Ignition cable with stainless steel wire available on special request.

Silicone Hoses

P/N	Figure	Description	Outer Diameter	Color	Equivalent to
02.85.965-82	3	Silicone hose, 8x2 mm, 82 ft spool	12 mm	blue	21606
02.85.865-82	3	Silicone hose, 8x2 mm, 82 ft spool	12 mm	orange	
02.85.914-82	3	Silicone hose, 12x1.5 mm, 82 ft spool	15 mm	blue	SO-5
02.85.814-82	3	Silicone hose, 12x1.5 mm, 82 ft spool	15 mm	orange	

Inductive Pickup Spacer

P/N	Figure	Description	Position	Quantity	Equivalent to
06.84.010-100	4	Inductive pickup spacer	end of lead	100 pcs	
06.84.043-100	5	Inductive pickup spacer	middle of lead	100 pcs	

Spark Plug Connectors (for 14 mm Spark Plugs only)

P/N	Figure	Description	Quantity	Equivalent to
06.84.024-100	6	Spark plug connector, 90°, silicone, for use with 7 mm ignition cable, including terminal P/N 02.85.920	100 pcs	ST-22XL
06.84.025-100	7	Spark plug connector, 180°, silicone, for use with 7 mm ignition cable, including terminal P/N 02.85.920	100 pcs	ST-33XL



Conversion: 1 inch = 25.4 mm / 1 foot = 0.3 m

Spark Plug Leads & Extensions



Spark Plug Boots

P/N	Figure	Description	Quantity	Equivalent to
06.84.008-100	8	Spark plug boot, 90°, silicone, for use with 7 mm ignition cable and terminal P/N 22.85.803	100 pcs	
06.84.009-100	9	Spark plug boot, 180°, silicone, for use with 7 mm ignition cable and terminal P/N 22.85.802	100 pcs	W54883

Terminals for Spark Plug Connectors and Boots

P/N	Figure	Description	Quantity	Equivalent to
02.85.920-100	10	Terminal, for use with spark plug connectors P/N 06.84.024 and P/N 06.84.025	100 pcs	D-199
22.85.802-100	11	Terminal, for use with spark plug boot P/N 06.84.009	100 pcs	
22.85.803-100	12	Terminal, for use with spark plug boot P/N 06.84.008	100 pcs	5419-150

Silicone Boot

P/N	Figure	Description	Quantity	Equivalent to
02.99.004-100	13	Silicone boot, 90°	100 pcs	

Spark Plug Connectors

P/N	Figure	Description	Quantity	Equivalent to
02.85.924-100	14	Spark plug connector, 90°, for use with 7 mm ignition cable	100 pcs	T-22, 21459
02.85.925-100	15	Spark plug connector, 180°, for use with 7 mm ignition cable	100 pcs	T-33, 21418

Ignition Coil Connectors

P/N	Figure	Description	Quantity	Equivalent to
06.80.261-100	16	Ignition coil connector, 180°, 0 kΩ resistance, requires crimp terminal P/N 06.80.126	100 pcs	
22.80.009-100	17	Ignition coil connector, 90°, 1 kΩ resistance, requires crimp terminal P/N 06.80.126	100 pcs	
06.80.091-100 ¹⁾	18	Ignition coil connector, 180°, 0 kΩ resistance, requires crimp terminal P/N 06.80.126	100 pcs	

¹⁾ For ignition coils with positive secondary termination.



■ Spark Plug Leads & Extensions

Crimp Terminals

P/N	Figure	Description	Quantity	Equivalent to
06.80.012-100	1	Crimp terminal, 180°, for use with spreading adaptor P/N 02.85.1012	100 pcs	
06.80.116-100	2	Crimp terminal, 90°, for use with MOTORTECH Style ignition coils	100 pcs	
06.80.116-180-100	3	Crimp terminal, 180°, for use with New MOTORTECH Style ignition coils	100 pcs	
06.80.108-100	4	Crimp terminal base, for use with crimp terminals P/N 06.80.116-100 and P/N 06.80.116-180-100	100 pcs	
06.80.126-100	5	Crimp terminal base, for use ignition coil terminals P/N 06.80.261 and P/N 22.80.009	100 pcs	

Spreading Adaptor

P/N	Figure	Supersedes	Description	Quantity	Equivalent to
02.85.1012-100	6	02.85.1004-100	Spreading adaptor for ALTRONIC® Style ignition coils	100 pcs	

Distance Collars

P/N	Figure	Description	Quantity	Equivalent to
06.86.001-100	7	Distance collar, for use with 7 mm ignition cable	100 pcs	
06.86.002-100	8	Distance collar, for use with 7 mm ignition cable	100 pcs	
06.86.003-100	9	Distance collar, for use with 7 mm ignition cable	100 pcs	
06.86.005-100	10	Distance collar, for use with 7 mm ignition cable	100 pcs	



■ Spark Plug Leads & Extensions



Silicone Seal Rings for Spark Plug Leads ¹⁾

P/N	Figure	Description	Fits Spark Plug ²⁾	Dimensions			Quantity	Equivalent to
				OD	ID	Height		
06.84.033-100	11	Silicone seal ring	GK3-5, RC78PYP, B4321	19.0 mm	10.0 mm	12.0 mm	100 pcs	
06.84.034-100	11	Silicone seal ring	GI3-1, FB77WPCC, B8324	20.0 mm	12.0 mm	15.0 mm	100 pcs	
06.84.038-100	11	Silicone seal ring	RW80N	20.0 mm	14.4 mm	15.0 mm	100 pcs	
06.84.040-100	11	Silicone seal ring	GI3-1, FB77WPCC, B8324	20.0 mm	14.0 mm	15.0 mm	100 pcs	
06.84.044-100	11	Silicone seal ring	GK3-5, RC78PYP, B4321	20.0 mm	10.0 mm	15.0 mm	100 pcs	
06.84.059-100	11	Silicone seal ring	GE3-5, RN79G	20.0 mm	11.2 mm	15.0 mm	100 pcs	
06.84.077-100	11	Silicone seal ring	D14, D14N	20.0 mm	13.5 mm	15.0 mm	100 pcs	
06.84.121-100	11	Silicone seal ring	GK3-5, RC78PYP, B4321	16.0 mm	10.0 mm	11.0 mm	100 pcs	

¹⁾ Silicone seal rings require replacement every 3000 running hours. See MOTORTECH homepage for appropriate instruction for replacing silicone seal rings.

²⁾ Information provided only for comparison purposes.

Grommets for CUMMINS® Ignition Coils

P/N	Figure	Description	Color	Quantity	Equivalent to
06.84.048-100	12	Grommet, for use with CUMMINS® ignition coil P/N 3930027	orange	100 pcs	3938860
06.84.053-100	13	Grommet, for use with CUMMINS® 8.3 ignition coil	black	100 pcs	3973945

Silicone Seals for ALTRONIC®, BG®, CUMMINS® and WAUKESHA® Spark Plug Extensions

P/N	Figure	Description	Color	Quantity	Equivalent to
06.84.047-100	14	Silicone seal, for 14 mm spark plug extension	orange	100 pcs	
06.84.049-100	15	Silicone seal, for 18 mm spark plug extension	blue	100 pcs	740011

Silicone Boot for WÄRTSILÄ® 25SG Series Spark Plug Leads **NEW**

P/N	Figure	Description	Color	Equivalent to
06.84.011	16	Silicone boot for WÄRTSILÄ® 25SG series spark plug leads	black	9150902801

Silicone Seal Ring for CATERPILLAR® G3400 Series Gas Engines **NEW**

P/N	Figure	Description	Color	Equivalent to
06.84.090	17	Silicone seal ring for spark plug well, CATERPILLAR® G3400 series gas engines	black	7E-0079



[11](#)



[12](#)



[13](#)



[14](#)



[15](#)



[16](#)



[17](#)

■ Spark Plug Leads & Extensions

SHIELDED

MOT-Blues 
SHIELDED SPARK PLUG LEADS

MOT-Blues Shielded Spark Plug Leads for Externally Mounted Ignition Coils

There is an alternative to the commonly failing conventional shielded spark plug leads. MOTORTECH has designed a CSA approved shielded spark plug lead for Class I, Division 2, Group D that will perform better than the industry standard. There is no need to convert to unshielded when you cannot keep the engine running with the conventional leads.



New Flex Style



Conventional Style



The MOT-Blues ignition cable is specially designed for shielded CSA certified spark plug leads. It consists of a multi layer design:

- Nickel plated copper core
- 2 layers of silicone
- Stainless steel braid
- Silicone jacket

This design ensures that no humidity can be trapped in the lead.

■ Spark Plug Leads & Extensions



MOTORTECH Style – 1-20 UNEF Ignition Coil Termination



P/N ¹⁾	Description	Spark Plug Termination Well Depth ²⁾	Spark Plug Termination	Ignition Coil Termination	Equivalent to
95.91.020-L	MOT-Blues shielded spark plug lead	1 in	3/4-20 UNEF, 180°	1-20 UNEF, 180°	A755-L, HT1400-L
95.91.030-L	MOT-Blues shielded spark plug lead	2 in	3/4-20 UNEF, 180°	1-20 UNEF, 180°	A755-L-2, HT2400-L

¹⁾ Standard lead lengths (-L) = 10 in, 13 in, 16 in, 18 in, 20 in, 21 in, 22 in, 24 in, 30 in, 35 in; other lengths available on request.

²⁾ Spark plug leads with 1 in spark plug termination well depth only available on special request.

All terminals made of ceramic. HEX-nut on spark plug side.

ALTRONIC® Style – 3/4-20 UNEF Ignition Coil Termination



P/N ¹⁾	Description	Spark Plug Termination Well Depth ²⁾	Spark Plug Termination	Ignition Coil Termination	Equivalent to
95.90.020-L	MOT-Blues shielded spark plug lead	1 in	3/4-20 UNEF, 180°	3/4-20 UNEF, 180°	593020-L, HT1300-L
95.90.030-L	MOT-Blues shielded spark plug lead	2 in	3/4-20 UNEF, 180°	3/4-20 UNEF, 180°	593030-L, HT2300-L

¹⁾ Standard lead lengths (-L) = 10 in, 13 in, 16 in, 18 in, 20 in, 21 in, 22 in, 24 in, 30 in, 35 in; other lengths available on request.

²⁾ Spark plug leads with 1 in spark plug termination well depth only available on special request.

All terminals made of ceramic. HEX-nut on spark plug side.



■ Spark Plug Leads & Extensions

SHIELDED

Conventional Shielded Spark Plug Leads for Externally Mounted Ignition Coils

MOTORTECH Style – 1-20 UNEF Ignition Coil Termination



P/N ¹⁾	Description	Spark Plug Termination Well Depth ²⁾	Spark Plug Termination	Ignition Coil Termination	Equivalent to
95.85.020-L	Shielded spark plug lead	1 in	3/4-20 UNEF, 180°	1-20 UNEF, 180°	A755-L, HT1400-L
95.85.030-L	Shielded spark plug lead	2 in	3/4-20 UNEF, 180°	1-20 UNEF, 180°	A755-L-2, HT2400-L

¹⁾ Standard lead lengths (-L) = 10 in, 13 in, 16 in, 18 in, 20 in, 21 in, 22 in, 24 in, 30 in, 35 in; other lengths available on request.

²⁾ Spark plug leads with 1 in spark plug termination well depth only available on special request.

All terminals made of ceramic. HEX-nut on both sides.

ALTRONIC® Style – 3/4-20 UNEF Ignition Coil Termination




P/N ¹⁾	Description	Spark Plug Termination Well Depth ²⁾	Spark Plug Termination	Ignition Coil Termination	Equivalent to
95.80.020-L	Shielded spark plug lead	1 in	3/4-20 UNEF, 180°	3/4-20 UNEF, 180°	593020-L, HT1300-L
95.80.030-L	Shielded spark plug lead	2 in	3/4-20 UNEF, 180°	3/4-20 UNEF, 180°	593030-L, HT2300-L

¹⁾ Standard lead lengths (-L) = 10 in, 13 in, 16 in, 18 in, 20 in, 21 in, 22 in, 24 in, 30 in, 35 in; other lengths available on request.

²⁾ Spark plug leads with 1 in spark plug termination well depth only available on special request.

All terminals made of ceramic. HEX-nut on both sides.



■ Spark Plug Leads & Extensions



Terminal Repair Kits for Shielded and Unshielded Spark Plug Leads

Kits for MOT-Blues **Shielded** Spark Plug Leads

P/N	Description	Stud Thread Size	Adaptor	Equivalent to
02.85.1006	Terminal kit, spark plug sided	M3	3/4-20 UNEF, 2 in termination well depth ¹⁾	
02.85.1007	Terminal kit, ignition coil sided	M3	3/4-20 UNEF, ALTRONIC® Style	
02.85.1008	Terminal kit, ignition coil sided	M3	1-20 UNEF, MOTORTECH Style	

¹⁾ Consult factory for terminal kits to fit spark plugs with 3/4-20 UNEF thread and 1 in terminal well depth.

Kits for Conventional **Shielded** Spark Plug Leads

P/N	Description	Stud Thread Size	Adaptor	Equivalent to
02.85.991	Terminal kit, spark plug sided	M3	3/4-20 UNEF, 1 in termination well depth	
02.85.991-2	Terminal kit, spark plug sided	3/48 UNC	3/4-20 UNEF, 1 in termination well depth	SC1K, 504205
02.85.992	Terminal kit, spark plug sided	M3	3/4-20 UNEF, 2 in termination well depth	
02.85.992-2	Terminal kit, spark plug sided	3/48 UNC	3/4-20 UNEF, 2 in termination well depth	SC2K, 504137
02.85.979	Terminal kit, spark plug sided	3/48 UNC	3/4-20 UNEF, 1 in termination well depth	
02.85.992-1	Terminal kit, ignition coil sided	M3	3/4-20 UNEF, BENDIX® Style	
02.85.992-3	Terminal kit, ignition coil sided	3/48 UNC	3/4-20 UNEF, BENDIX® Style	
02.85.996	Terminal kit, ignition coil sided	M3	3/4-20 UNEF, ALTRONIC® Style	
02.85.996-2	Terminal kit, ignition coil sided	3/48 UNC	3/4-20 UNEF, ALTRONIC® Style	ALTSS-2
02.85.997	Terminal kit, ignition coil sided	M3	1-20 UNEF, MOTORTECH Style	
02.85.997-2	Terminal kit, ignition coil sided	3/48 UNC	1-20 UNEF, MOTORTECH Style	

Kits for **Unshielded** Spark Plug Leads

P/N	Description	Stud Thread Size	Adaptor	Equivalent to
02.85.993	Terminal kit, ignition coil sided	M3	3/4-20 UNEF, ALTRONIC® Style	
02.85.993-2	Terminal kit, ignition coil sided	3/48 UNC	3/4-20 UNEF, ALTRONIC® Style	ALTOS-1, 510480
02.85.994	Terminal kit, ignition coil sided	M3	3/4-20 UNEF, BENDIX® Style	
02.85.994-2	Terminal kit, ignition coil sided	3/48 UNC	3/4-20 UNEF, BENDIX® Style	BENDOS-1
02.85.995	Terminal kit, ignition coil sided	M3	1-20 UNEF, MOTORTECH Style	
02.85.995-2	Terminal kit, ignition coil sided	3/48 UNC	1-20 UNEF, MOTORTECH Style	FMOS-1



■ Spark Plug Leads & Extensions

UNSHIELDED



PolyMot™ Spark Plug Extensions

Besides all the successful spark plug leads, MOTORTECH has also designed a large number of spark plug extensions under the PolyMot™ design. These extensions are unique and offer several advantages when being compared to the OEM or aftermarket competition. With the knowledge gathered in ignition control and ignition coil research and manufacturing, a lot of the details were implemented into these products. The unique structure has achieved tremendous reliability records in the field.

General Features

- Rigid design
- Extensions made of high quality Teflon® and up to 36 inch length
- Ceramic insert with 5 kΩ resistor for EMI suppression (0 kΩ available on request)
- Reliable ignition coil and spark plug terminal
- Critical high voltage areas are protected with seals
- Designed to match the engine model, the spark plug type and application
- Extensions are labeled with P/N and production code for easy traceability
- Top thread for easy removal with special tool
- Long life product

Key Design Features

- 1 Spring-loaded secondary terminal rod to ignition coil
- 2 Special O-ring made of Viton® with excellent temperature and aging characteristics for best protection of ignition coil secondary terminal
- 3 Large thread on top end for easy removal with special tool P/N 44.99.912
- 4 Highest dielectric strength due to Teflon® insulator
- 5 Ceramic insert with 5 kΩ resistor for EMI suppression
- 6 Integrated silicone seal rings for best flashover protection will not stick on the spark plug insulator when pulling off the extension



P/N 44.99.912 Removal Tool

Spark Plug Leads & Extensions



PolyMot™ Spark Plug Extensions for common Applications

P/N ¹⁾	Supersedes	Engine Make	Model	Teflon® Insulator Length	Resistance	Spark Plug	P/N Silicone Seal Ring	Thread on Top End	Equivalent to
06.80.320-T	06.80.320, 06.80.320H, 06.80.320H-T, 06.80.381H, 06.80.381H-T	CATERPILLAR®	G3500 series	11 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	123-4710, 25080-04, 5419-806
06.80.319-T	06.80.319, 06.80.319H, 06.80.319H-T	CATERPILLAR®	G3600 series	11 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	207-4509, 207-4508, 123-8641, 25080-03, 5419-805
06.80.202-T	06.80.202	COOPER®	2400G series	9 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040		656-701-003, 25080-02, 5419-801
06.80.755-T ²⁾		CUMMINS®	QSK60G	13 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	
06.80.756-T ²⁾		CUMMINS®	QSV81/91G	15 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	
06.80.1134 ³⁾		WÄRTSILÄ®	28SG series	19 in	5 kΩ	GI3-4, FB77WPCC, B8324/-LTN	06.84.040	x	
06.80.1132 ³⁾		WÄRTSILÄ®	34SG series	23 in	5 kΩ	GI3-4, FB77WPCC, B8324/-LTN	06.84.040	x	
06.80.471-T		WAUKESHA®	275GL+ series	15 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	A296064J, A296064K, 26400-10, 26510-10
06.80.469-T		WAUKESHA®	APG series	10 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	A211797M, A211797T, 25080-10, 26400-08, 26510-08
06.80.206-T	06.80.206	WAUKESHA®	AT25GL series	15 in	5 kΩ	GT3-1, RM77N, B8124	06.84.040	x	A211357L, A211357N, A211357T, A211357Y, A296805A, 26400-02, 26510-02, 25080-09, 5419-802
06.80.330-T	06.80.330	WAUKESHA®	AT25GL-LR series	15 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	A211357R, A211357V, A211357Z, A296805, 25080-08, 26400-04, 26510-04, 5419-808
06.80.213-T	06.80.213	WAUKESHA®	AT27GL series	15 in	5 kΩ	GT3-1, RM77N, B8124	06.84.040	x	296064B, 296064C, A296064C, A296064E, A296064G, 25080-11, 26400-03, 26510-03
06.80.310-T	06.80.310	WAUKESHA®	AT27GL-LR series	14 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	296064D, 296064F, 296064H, A296064D, A296064F, A296064H, A296064L, 25080-07, 26400-05, 26510-05, 5419-804
06.80.309-T	06.80.309	WAUKESHA®	VGF series	9 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	A211357X, A211797J, A211797K, A211797S, 25080-01, 26400-07, 26510-07, 5419-803
06.80.340-T	06.80.340	WAUKESHA®	VHP-4 series	13 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	211797A, A211797G, 25080-06, 26510-06, 5419-735
06.80.321-T	06.80.321, 06.80.321H, 06.80.321H-T	WAUKESHA®	VHP-GL series	13 in	5 kΩ	GI3-3, FB77WPCC, B8324/-LTN	06.84.040	x	211357P, 211357U, A211797H, A211797P, A211797R, 25080-05, 25080-12, 26400-01, 26510-01, 5419-807

¹⁾ For 0 kΩ resistance, please add “-0” to part number (e.g. 06.80.320-T-0).

²⁾ Fits application only, if conversion kits P/N 75.30.143 (CUMMINS® QSK60G) or 75.30.144 (CUMMINS® QSV81/91G) previously were used.

³⁾ Fits application only, if conversion kits P/N 75.30.154 (WÄRTSILÄ® 28SG) or 75.30.155 (WÄRTSILÄ® 34SG) previously were used.

Removal Tool for Spark Plug Extensions with Thread on Top End

P/N	Supersedes	Description	Equivalent to
44.99.912		Spark plug extension removal tool	

■ Spark Plug Leads & Extensions

Ignition Coil Extensions

For **MOTORTECH/CATERPILLAR®** Ignition Coils – For **CATERPILLAR®** G3520C/E and G3600 Series Gas Engines

P/N	Figure	Description	Application	Resistance	Teflon® Insulator		Fits Ignition Coil P/N	Equivalent to
					Length	Diameter		
06.80.459H ¹⁾	1	Ignition coil extension	G3520C/E, G3600	0 kΩ	248 mm	26 mm	06.50.161, 06.50.162, 283-5270	308-1380, 283-5271, 264-5323, 150-2050
06.80.600	2	Ignition coil extension	G3520C/E, G3600	0 kΩ	252 mm	26 mm	06.50.164, 06.50.165	

¹⁾ Supersedes ignition coil extensions P/N 06.80.375H and 06.80.446H.

For **MOTORTECH/CATERPILLAR®** Ignition Coils – For **CATERPILLAR®** GCM34 Series Gas Engines

P/N	Figure	Description	Application	Resistance	Teflon® Insulator		Fits Ignition Coil P/N	Equivalent to
					Length	Diameter		
06.80.1013-T	3	Ignition coil extension	GCM34	5 kΩ	530 mm	26 mm	193-468157, 258-4893, 06.50.170	263210167, 3400.7-21.07.02-03
06.80.602	4	Ignition coil extension	GCM34	5 kΩ	534 mm	26 mm	06.50.174, 06.50.175	

For **CATERPILLAR®** Ignition Coils

P/N	Figure	Description	Teflon® Insulator		Equivalent to
			Length	Diameter	
06.80.356H	5	Ignition coil extension	118 mm	25 mm	133-5078
06.80.360H	5	Ignition coil extension	118 mm	30 mm	169-4295

For **WÄRTSILÄ®** 34SG and 220G/SG Series Gas Engines

P/N	Description	Application	Resistance	Teflon® Insulator		Fits Ignition Coil P/N	Equivalent to
				Length	Diameter		
06.80.460	Ignition coil extension	34SG series	5 kΩ	460 mm	26 mm		0012E002200
06.80.461	Ignition coil extension	34SG series	5 kΩ	446 mm	26 mm		0012E006500
06.80.145-1	Ignition coil extension	220G/SG series	5 kΩ	334 mm	24 mm		3340063
06.80.145-2	Ignition coil extension	220G/SG series	5 kΩ	329 mm	24 mm		3341380



■ Spark Plug Leads & Extensions



Ignition Coil Extension Overhaul Kits

Kits for **MOTORTECH** Ignition Coils – For **CATERPILLAR®** G3400/C and G3500/B/C/E/H Series Gas Engines

P/N	Figure	Supersedes	Description	Application	Teflon® Insulator		Fits Ignition Coil P/N
					Length	Diameter	
06.80.741	6		Extension overhaul kit	G3400 – Non CSA	95 mm	30 mm	06.50.141, 06.50.145
06.80.742	6		Extension overhaul kit	G3400 – CSA	97 mm	30 mm	06.50.142, 06.50.146
06.80.743	6		Extension overhaul kit	G3400 – Non CSA	107 mm	30 mm	06.50.143, 06.50.147
06.80.744	6		Extension overhaul kit	G3400 – CSA	109 mm	30 mm	06.50.144, 06.50.148
06.80.751	6		Extension overhaul kit	G3500 – Non CSA	118 mm	30 mm	06.50.151, 06.50.155
06.80.752	6		Extension overhaul kit	G3500 – CSA	105 mm	30 mm	06.50.152, 06.50.156
06.80.753	6		Extension overhaul kit	G3500 – Non CSA	112 mm	30 mm	06.50.153, 06.50.157
06.80.754	6		Extension overhaul kit	G3500 – CSA	105 mm	30 mm	06.50.154, 06.50.158
06.80.764	6		Extension overhaul kit	G3500 – Non CSA	104 mm	25 mm	06.50.159, 06.50.160

Above Overhaul Kits contain following Subcomponents

P/N	P/N Teflon® Insulator including Seal Ring	P/N included Silicone Seal Ring	P/N included Insulator Seal	P/N Lip Seal Ring ¹⁾	P/N Secondary Terminal
06.80.741	06.80.741-2	06.84.059		06.81.051 7	02.85.881 8
06.80.742	06.80.742-2	06.84.059	06.81.084	06.81.051 7	06.51.134 8
06.80.743	06.80.743-2	06.84.059		06.81.051 7	06.51.136 8
06.80.744	06.80.744-2	06.84.059	06.81.084	06.81.051 7	06.51.133 8
06.80.751	06.80.751-2	06.84.040		06.81.051 7	02.85.881 8
06.80.752	06.80.752-2	06.84.040	06.81.084	06.81.051 7	02.85.870 8
06.80.753	06.80.753-2	06.84.040		06.81.051 7	02.85.881 8
06.80.754	06.80.754-2	06.84.040	06.81.084	06.81.051 7	02.85.870 8
06.80.764	06.80.764-2	06.84.040		06.81.051 7	02.85.870 8

¹⁾ Lip seal ring P/N 06.81.051 equivalent to P/N 135-2651.



■ Spark Plug Leads & Extensions

Kits for **CATERPILLAR®** Ignition Coils – For **CATERPILLAR®** G3400/C and G3500/B Series Gas Engines

P/N	Figure	Supersedes	Description	Application	Teflon® Insulator		Fits Ignition Coil P/N
					Length	Diameter	
06.80.419H	1		Extension overhaul kit	G3400 – Non CSA	95 mm	30 mm	232-6348, 165-1591, 131-3277, 129-8802, 108-0615
06.80.742	1	06.80.418H	Extension overhaul kit	G3400 – CSA	97 mm	30 mm	232-6349, 165-1592, 122-8070
06.80.420H	1		Extension overhaul kit	G3400 – Non CSA	107 mm	30 mm	232-6352, 213-7443
06.80.744	1	06.80.417H	Extension overhaul kit	G3400 – CSA	109 mm	30 mm	232-6353, 213-7444
06.80.515H	1	06.80.315H	Extension overhaul kit	G3500 – Non CSA	118 mm	30 mm	232-6346, 165-1589, 124-0749
06.80.752	1	06.80.415H	Extension overhaul kit	G3500 – CSA	105 mm	30 mm	232-6347, 165-1590
06.80.480	1		Extension overhaul kit	G3500 – Non CSA	112 mm	30 mm	232-6350
06.80.754	1	06.80.415H	Extension overhaul kit	G3500 – CSA	105 mm	30 mm	259-2078

Above Overhaul Kits contain following Subcomponents

P/N	P/N Teflon® Insulator including Seal Ring	P/N included Silicone Seal Ring	P/N included Insulator Seal	P/N Lip Seal Ring ¹⁾	P/N Secondary Terminal
06.80.419H	06.80.279H	06.84.059		06.81.051 2	02.85.881 3
06.80.742	06.80.742-2	06.84.059	06.81.084	06.81.051 2	06.51.134 3
06.80.420H	06.80.280H	06.84.059		06.81.051 2	06.51.136 3
06.80.744	06.80.744-2	06.84.059	06.81.084	06.81.051 2	06.51.133 3
06.80.515H	06.80.335H-1	06.84.040		06.81.051 2	02.85.881 3
06.80.752	06.80.752-2	06.84.040	06.81.084	06.81.051 2	02.85.870 3
06.80.480	06.80.481	06.84.040		06.81.051 2	02.85.881 3
06.80.754	06.80.754-2	06.84.040	06.81.084	06.81.051 2	02.85.870 3

¹⁾ Lip seal ring P/N 06.81.051 equivalent to P/N 135-2651.

Teflon® Covered Extension Rods – Low Cost Style ¹⁾

P/N ²⁾	Description	Primary Connection	Secondary Connection	Equivalent to
06.80.349-L	Teflon® covered extension rod	SAE	snap-on attachment	TCRC-L
06.80.376-L	Teflon® covered extension rod	SAE	#8-32 screw-on attachment	TCR-L
06.80.376-10	Teflon® covered extension rod	SAE	#8-32 screw-on attachment	TCR-10WM, 207927A

¹⁾ We recommend using PolyMot™ spark plug leads.

²⁾ Standard lengths (-L) = 3 in, 4 in, 5 in, 6 in, 8 in, 10 in, 12 in, 14 in, 16 in, 18 in, 20 in, 24 in; other lengths available on request.



■ Spark Plug Leads & Extensions



SHIELDED

Extensions for Shielded Spark Plugs to Shielded Spark Plug Leads



P/N ¹⁾	Figure	Description	Spark Plug Connection	Termination Well Depth	Ignition Coil Connection	Termination Well Depth	Equivalent to
95.07.020-L	1	Shielded spark plug extension	5/8-24 UNEF	1 in	5/8-24 UNEF	1 in	
95.07.021-L	1	Shielded spark plug extension	3/4-20 UNEF	1 in	3/4-20 UNEF	1 in	M"L"-2S
95.07.022-L	1	Shielded spark plug extension	3/4-20 UNEF	2 in	3/4-20 UNEF	2 in	M"L"-2E
95.07.023-L	1	Shielded spark plug extension	5/8-24 UNEF	1 in	3/4-20 UNEF	2 in	
95.07.024-L	1	Shielded spark plug extension	3/4-20 UNEF	1 in	3/4-20 UNEF	2 in	

¹⁾ Standard lengths (-L) = 4 in, 5 in, 6 in, 8 in, 10 in, 12 in, 18 in; other lengths available on request.

Extensions for Integral Ignition Coils to Shielded Spark Plugs



P/N ¹⁾	Figure	Description	Spark Plug Connection	Termination Well Depth	Ignition Coil Connection	Termination Well Depth	Equivalent to
95.07.010-L	2	Integral ignition coil extension	5/8-24 UNEF	1 in	1-20 UNEF	2 in	BG E Series
95.07.011-L	2	Integral ignition coil extension	3/4-20 UNEF	1 in	1-20 UNEF	2 in	593120-L, M"L"-2C
95.07.012-L	2	Integral ignition coil extension	3/4-20 UNEF	2 in	1-20 UNEF	2 in	593130-L, M"L"-1C
95.07.013-L	2	Integral ignition coil extension	13/16-20 UNEF	2 in	1-20 UNEF	2 in	593140-L

¹⁾ Standard lengths (-L) = 1.5 in, 3 in, 6 in, 9 in, 11 in, 19 in; other lengths available on request.



1



2

■ Ignition Wiring Rails & Hardware



SHIELDED

AlphaRail 
MOTORTECH WIRING RAIL SYSTEM

Wiring Rail System for Ignition Control

MOTORTECH stainless steel, vibration resistant rail assembly will withstand any harsh environment commonly found in the oil & gas industry. The proven design is made for engine manufacturers and the global aftermarket. Do not go Low-Tech and take the risk of engine down time because of equipment being under repair. Eliminate the need for constant rewiring, connector exchanges or straightening out weak and bent aluminum wiring rails.

- Made of stainless steel
- Rigid military style connectors
- Rails are filled with special foam to ensure that all wires are separated from ground and will not vibrate
- Water-proof design – built to last in uncovered environment
- Repairable by MOTORTECH's assigned distributors in the event of mechanically damage
- Wiring rails can be used for shielded and unshielded applications
- Due to base rail structure easy for stocking
- Quick service access with quick-disconnect connections



1 AlphaRail for Ignition Control – Specification Table

P/N 95.8

A

B

C

D

E

F

G

H

J

A

Ignition Coils per Cylinder

6

Engine with one ignition coil per cylinder

7

Engine with two ignition coils per cylinder ¹⁾

1)

See “HJ” for distance between two ignition coils.

B

Number of Cylinders per Bank

1

Special version

5

5 cylinders

2

2 cylinders

6

6 cylinders

3

3 cylinders

8

8 cylinders

4

4 cylinders

0

10 cylinders

CD

Distance between the Cylinders

04

4 in

12

12 in

06

6 in

13

13 in

07

7 in

14

14 in

08

8 in

16

16 in

10

10 in

27

27 in

11

11 in

33

33 in

E

Ignition Coil Mounting

N

STANDARD – NO ignition coil mounted

F

Double Rail ¹⁾ – Length of Flex Conduit

A

NO Double Rail

E

24 in

B

12 in

F

32 in

C

16 in

G

40 in

D

20 in

H

52 in

1)

Two ignition wiring rails connected by flex conduit.

G

Specification of Ignition Coil

N

STANDARD – NO ignition coil mounted ¹⁾

1)

Ignition coils have to be ordered separately
(see page 32 – Ignition Coils)

HJ

Distance between two Ignition Coils – Only for two Ignition Coils per Cylinder

04

4 in

16

16 in

06

6 in

18

18 in

08

8 in

20

20 in

10

10 in

22

22 in

12

12 in

24

24 in

14

14 in

■ Ignition Wiring Rails & Hardware

1 AlphaRail for Ignition Control – Wiring Rails for common Applications ¹⁾

P/N	Description	Engine Make	Model	Required Quantity per Engine
95.86.406-NAN	AlphaRail wiring rail	CATERPILLAR®	G3304	1
95.86.606-NAN	AlphaRail wiring rail	CATERPILLAR®	G3306	1
95.86.607-NAN	AlphaRail wiring rail	CATERPILLAR®	G3406	1
95.86.407-NAN	AlphaRail wiring rail	CATERPILLAR®	G3408	2
95.86.607-NAN	AlphaRail wiring rail	CATERPILLAR®	G3412	2
95.86.411-NAN	AlphaRail wiring rail	CATERPILLAR®	G3508	2
95.86.611-NAN	AlphaRail wiring rail	CATERPILLAR®	G3512	2
95.86.811-NAN	AlphaRail wiring rail	CATERPILLAR®	G3516	2
95.87.631-NGN-08	AlphaRail wiring rail	CLARK®	HBA-6T	1
95.87.531-NAN-08	AlphaRail wiring rail	CLARK®	HBA-10T	2
95.87.637-NAN	AlphaRail wiring rail	CLARK®	TCVD-12	2
95.87.631-NGN-10	AlphaRail wiring rail	CLARK®	TLA-6T	1
95.87.544-NGN-06	AlphaRail wiring rail	COOPER®	GMVH-10	2
95.87.541-NGN-10	AlphaRail wiring rail	COOPER®	GMW-10	2
95.87.340-NAN	AlphaRail wiring rail	COOPER®	GMWC-6	2
95.87.822-NGN-06	AlphaRail wiring rail	COOPER®	LSV-16	2
95.87.633-NFN-22	AlphaRail wiring rail	INGERSOLL RAND®	KVR-412	2
95.87.344-NAN-04	AlphaRail wiring rail	INGERSOLL RAND®	KVS-6	2
95.86.427-NDN	AlphaRail wiring rail	INGERSOLL RAND®	PKVG-8	2
95.86.627-NDN	AlphaRail wiring rail	INGERSOLL RAND®	PKVG-12	2
95.86.627-NFN	AlphaRail wiring rail	INGERSOLL RAND®	PKVGR-12	2
95.86.437-NAN	AlphaRail wiring rail	INGERSOLL RAND®	XVG-8	2
95.86.606-NAN	AlphaRail wiring rail	WAUKESHA®	F817	1
95.86.614-NAN	AlphaRail wiring rail	WAUKESHA®	F1197GL/GU	1
95.86.608-NAN	AlphaRail wiring rail	WAUKESHA®	VG F18	1
95.86.808-NAN	AlphaRail wiring rail	WAUKESHA®	VG F H24	1
95.86.609-NAN	AlphaRail wiring rail	WAUKESHA®	VG F L36	2
95.86.809-NAN	AlphaRail wiring rail	WAUKESHA®	VG F P48	2
95.86.614-NAN	AlphaRail wiring rail	WAUKESHA®	VHP F2895GL/GSI	1
95.86.614-NAN	AlphaRail wiring rail	WAUKESHA®	VHP F3521GSI	1
95.86.614-NAN	AlphaRail wiring rail	WAUKESHA®	VHP L5790GSI	2
95.86.614-NAN	AlphaRail wiring rail	WAUKESHA®	VHP L7042G/GL/GU/GSI	2
95.86.614-NAN	AlphaRail wiring rail	WAUKESHA®	VHP L7044GL/GSI	2
95.86.814-NFN	AlphaRail wiring rail	WAUKESHA®	VHP P9390GL/GSI	2
95.86.815-NAN	AlphaRail wiring rail	WAUKESHA®	8L-AT27GL	1
95.86.618-NAN	AlphaRail wiring rail	WAUKESHA®	12V-AT27GL	2
95.86.818-NAN	AlphaRail wiring rail	WAUKESHA®	16V-AT27GL	2
95.86.814-NAN	AlphaRail wiring rail	WHITE SUPERIOR®	2408G	1
95.86.613-NAN	AlphaRail wiring rail	WHITE SUPERIOR®	6G/GT/GTL825	1
95.86.813-NAN	AlphaRail wiring rail	WHITE SUPERIOR®	8G/GTL825	1
95.86.616-NAN	AlphaRail wiring rail	WHITE SUPERIOR®	12GTLA825	2
95.86.616-NAN	AlphaRail wiring rail	WHITE SUPERIOR®	12SGT	2
95.86.816-NAN	AlphaRail wiring rail	WHITE SUPERIOR®	16GT/GTLB825	2
95.86.816-NAN	AlphaRail wiring rail	WHITE SUPERIOR®	16SGT	2
95.87.531-NAN-08	AlphaRail wiring rail	WORTHINGTON®	UTC-10	2

¹⁾ **NOTE:** Applications may vary due to different variants or attachments, which could affect the installation of mentioned wiring rails. Consult factory for details and final confirmation.

Ignition Wiring Rails & Hardware



2 Bracket Configuration

P/N ¹⁾	Figure	Description
75.10.303	2A	Bracket, 40x40 mm (Standard)
75.10.097	2B	Flat bar, 180° (Standard)
75.10.120	2C	Flat bar, 150°
75.10.280	2D	Flat bar, 90°

¹⁾ For packs of ten please add suffix "-10" to part number (e.g. 75.10.303-10).

3 Primary Lead Kits for Ignition Coils – Unshielded ¹⁾

P/N	Figure	Description	For use with Ignition Coil P/N
06.99.200-1	3A	Primary lead kit incl. fastening material for ignition coil	06.50.003, 06.50.053, 06.50.054, 06.50.055, 06.50.060, 06.50.065
06.99.200-2	3B	Primary lead kit incl. fastening material for ignition coil	06.50.100, 06.50.102, 06.50.104, 06.50.105, 06.50.112, 06.50.113, 06.50.300, 06.50.301
06.99.200-3	3C	Primary lead kit incl. fastening material for ignition coil	06.50.103

¹⁾ Primary lead kits have to be ordered separately in required quantity.

3 Primary Lead Kits for Ignition Coils – Shielded ¹⁾

P/N	Figure	Description	For use with Ignition Coil P/N
95.99.200-1	3D	Primary lead kit incl. fastening material for ignition coil	95.08.003, 95.08.070
95.99.200-2	3E	Primary lead kit incl. fastening material for ignition coil	95.09.005, 95.09.054, 95.09.055, 95.09.070, 95.09.074, 95.09.075
95.99.200-2-X	3E	Primary lead kit incl. fastening material for ignition coil	95.09.053, 95.09.073

¹⁾ Primary lead kits have to be ordered separately in required quantity. See page 70 for primary leads for use with flange or integral ignition coils.

4 Harnesses to connect Wiring Rail and Junction Box ¹⁾

P/N	Figure	Description	Connector	Length
95.40.114-L	4A	Harness, with fitting for 1/2 in flex conduit	MIL, 14 pole, socket, 180°	L= 5/15/25/50 ft
95.40.314-L	4B	Harness, with fitting for 1/2 in flex conduit	MIL, 14 pole, socket, 90°	L= 5/15/25/50 ft

¹⁾ For CSA applications flex conduit has to be ordered separately or supplied by customer.



Ignition Wiring Rails & Hardware

5 Harnesses to connect Ignition Controller and Junction Box – Specification Table




P/N 95.4 **A**.**B** **C** **D** **E**

A	Harness
0	Standard harness, with fitting for 1/2 in or 3/4 in flex conduit

B	Connector Arrangement
1	socket 180°
2	pin 180°
3	socket 90°
4	pin 90°

CD	Number of Sockets/Pins in Connector
05	5 pole, with fitting for 1/2 in flex conduit
07	7 pole, with fitting for 1/2 in flex conduit
10	10 pole, with fitting for 1/2 in flex conduit
14	14 pole, with fitting for 1/2 in flex conduit
17	17 pole, with fitting for 3/4 in flex conduit
19	19 pole, with fitting for 3/4 in flex conduit
35	35 pole, with fitting for 3/4 in flex conduit

E	Length of Harness
5	5 ft
15	15 ft
25	25 ft
50	50 ft



6 Accessories

P/N	Figure	Description	Equivalent to
06.05.075	6A	Junction box	593600-1
15.07.112	6B	Flex conduit, 1/2 in, black ¹⁾	
15.07.221	6C	Fitting, 1/2 in, junction box to flex conduit	
15.07.134	6B	Flex conduit, 3/4 in, black ¹⁾	
15.07.231	6C	Fitting, 3/4 in, junction box to flex conduit	

¹⁾ Flex conduit needs to be ordered in m/ft in required length.



6A



6B



6C

Ignition Wiring Rails & Hardware

SHIELDED



Ignition Wiring Rail Upgrade Kits


Wiring Rail Kits for **CATERPILLAR®** G3300 and G3400 Series Gas Engines – **Shielded Applications with Magneto**



P/N	Description	Equivalent to
95.75.025-1-B	Ignition wiring rail kit without ignition control unit for CATERPILLAR® G3304 ■ Incl. harness to ALTRONIC® magneto ■ Mounting bracket welded to the rail ■ “G” lead connector ■ New Flex Style shielded primary leads to fit 3 pole integral ignition coils ¹⁾ ■ Timing light adaptor	251-2052
95.75.025-1	Ignition wiring rail kit without ignition control unit for CATERPILLAR® G3304 ■ Incl. harness to ALTRONIC® magneto ■ Mounting bracket welded to the rail ■ “G” lead connector ■ Conventional Style shielded primary leads to fit 3 pole integral ignition coils ¹⁾ ■ Timing light adaptor	251-2052
95.75.024-1-B	Ignition wiring rail kit without ignition control unit for CATERPILLAR® G3306 ■ Incl. harness to ALTRONIC® magneto ■ Mounting bracket welded to the rail ■ “G” lead connector ■ New Flex Style shielded primary leads to fit 3 pole integral ignition coils ¹⁾ ■ Timing light adaptor	251-2053
95.75.024-1	Ignition wiring rail kit without ignition control unit for CATERPILLAR® G3306 ■ Incl. harness to ALTRONIC® magneto ■ Mounting bracket welded to the rail ■ “G” lead connector ■ Conventional Style shielded primary leads to fit 3 pole integral ignition coils ¹⁾ ■ Timing light adaptor	251-2053
95.75.067-1-B	Ignition wiring rail kit without ignition control unit for CATERPILLAR® G3406 ■ Incl. harness to CATERPILLAR® ignition control unit ■ Mounting bracket welded to the rail ■ “G” lead connector ■ New Flex Style shielded primary leads to fit 3 pole integral ignition coils ¹⁾ ■ Timing light adaptor	291-5862 (wiring rail) 290-7079 (harness)
95.75.067-1	Ignition wiring rail kit without ignition control unit for CATERPILLAR® G3406 ■ Incl. harness to CATERPILLAR® ignition control unit ■ Mounting bracket welded to the rail ■ “G” lead connector ■ Conventional Style shielded primary leads to fit 3 pole integral ignition coils ¹⁾ ■ Timing light adaptor	291-5862 (wiring rail) 290-7079 (harness)

¹⁾ Integral ignition coils need to be ordered separately. See page 50 – Ignition Coils.

Options available on included Primary Leads



Ignition Wiring Rail



New Flex Style Primary Leads



Conventional Style Primary Leads

■ Ignition Wiring Rails & Hardware




UNSHIELDED


Ignition Upgrade Kits for **CATERPILLAR®** G3300 and G3400 Series Gas Engines to replace Magneto Ignition Systems
Unshielded Applications

P/N	Supersedes	Description	Equivalent to
75.00.536	75.00.338	Ignition upgrade kit for CATERPILLAR® G3304 ■ Incl. MIC3+ ignition controller ■ Input and output harnesses ■ AlphaRail wiring rail with high energy ignition coils and brackets ■ Spark plug leads ■ Mechanical trigger conversion kit with disc (4+1), adaptor ring, gaskets and inductive pickup ■ Magneto drive cover kit	
75.00.537	75.00.337	Ignition upgrade kit for CATERPILLAR® G3306 ■ Incl. MIC3+ ignition controller ■ Input and output harnesses ■ AlphaRail wiring rail with high energy ignition coils and brackets ■ Spark plug leads ■ Mechanical trigger conversion kit with disc (6+1), adaptor ring, gaskets and inductive pickup ■ Magneto drive cover kit	
75.00.538	75.00.336	Ignition upgrade kit for CATERPILLAR® G3406 ■ Incl. MIC3+ ignition controller ■ Input and output harnesses ■ AlphaRail wiring rail with high energy ignition coils and brackets ■ PolyMot™ spark plug leads ■ Mechanical trigger kit with disc (6+1), adaptor ring, gaskets and inductive pickup ■ Magneto drive cover kit	
75.00.539		Ignition upgrade kit for CATERPILLAR® G3408 ■ Incl. MIC3+ ignition controller ■ Input and output harnesses ■ High energy ignition coils ■ PolyMot™ spark plug leads ■ TriDev trigger device and inductive pickup	
75.00.540		Ignition upgrade kit for CATERPILLAR® G3412 ■ Incl. MIC3+ ignition controller ■ Input and output harnesses ■ High energy ignition coils ■ PolyMot™ spark plug leads ■ TriDev trigger device and inductive pickup	

Kit for In-line Engines
CATERPILLAR® G3304/G3306/G3406



Kit for V-Engines
CATERPILLAR® G3408/G3412



Ignition Wiring Rails & Hardware

SHIELDED



Wiring Rail Kits for CATERPILLAR® G3600 Series Gas Engines



P/N	Description	Equivalent to
95.75.108-B	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3606 ■ AlphaRail wiring rail assembly ■ Connecting harness, main junction box to wiring rail ■ New Flex Style shielded primary leads for AlphaRail	213-6308
95.75.108	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3606 ■ AlphaRail wiring rail assembly ■ Connecting harness, main junction box to wiring rail ■ Conventional Style shielded primary leads for AlphaRail	213-6308
95.75.103-B	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3608 ■ AlphaRail wiring rail assembly ■ Connecting harness, main junction box to wiring rail ■ New Flex Style shielded primary leads for AlphaRail	219-9946
95.75.103	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3608 ■ AlphaRail wiring rail assembly ■ Connecting harness, main junction box to wiring rail ■ Conventional Style shielded primary leads for AlphaRail	219-9946
95.75.106-B	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3612 ■ AlphaRail wiring rail assembly, right and left bank ■ Connecting harnesses, main junction box to wiring rails ■ New Flex Style shielded primary leads for AlphaRail	191-5007 (right) 191-5008 (left)
95.75.106	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3612 ■ AlphaRail wiring rail assembly, right and left bank ■ Connecting harnesses, main junction box to wiring rails ■ Conventional Style shielded primary leads for AlphaRail	191-5007 (right) 191-5008 (left)
95.75.107-B	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3616 ■ AlphaRail wiring rail assembly, right and left bank ■ Connecting harnesses, main junction box to wiring rails ■ New Flex Style shielded primary leads for AlphaRail	198-2938 (right) 198-2941 (left)
95.75.107	Wiring rail kit, ignition/detonation control for CATERPILLAR® G3616 ■ AlphaRail wiring rail assembly, right and left bank ■ Connecting harnesses, main junction box to wiring rails ■ Conventional Style shielded primary leads for AlphaRail	198-2938 (right) 198-2941 (left)

Options available on included Primary Leads



AlphaRail Wiring Rail Assembly



Connecting Harness



New Flex Style Primary Leads



Conventional Style Primary Leads

■ Ignition Wiring Rails & Hardware



Wiring Rail Kits for **WAUKESHA®** VGF Series Gas Engines – Shielded Applications with CEC Ignition Controller



P/N	Description	Equivalent to
95.75.339	Ignition wiring rail upgrade kit for WAUKESHA® VGF F18 For use with existing WAUKESHA® CEC ignition controller ■ AlphaRail wiring rail and mounting brackets ■ Connecting harness, ignition controller to wiring rail ■ New Flex Style shielded primary leads for AlphaRail	
95.75.340	Ignition wiring rail upgrade kit for WAUKESHA® VGF H24 For use with existing WAUKESHA® CEC ignition controller ■ AlphaRail wiring rail and mounting brackets ■ Connecting harness, ignition controller to wiring rail ■ New Flex Style shielded primary leads for AlphaRail	



Wiring Rail Kits for 12 Cylinder **WAUKESHA®** VHP ESM Series Gas Engines



P/N	Description	Equivalent to
95.75.048-B	Ignition wiring rail kit for 12 Cylinder WAUKESHA® VHP ESM Series Gas Engines ■ AlphaRail wiring rails and mounting brackets ■ Connecting harness assembly, ESM to wiring rails ■ New Flex Style shielded primary leads for AlphaRail	740283
95.75.048	Ignition wiring rail kit for 12 Cylinder WAUKESHA® VHP ESM Series Gas Engines ■ AlphaRail wiring rails and mounting brackets ■ Connecting harness assembly, ESM to wiring rails ■ Conventional Style shielded primary leads for AlphaRail	740283

Options available on included Primary Leads



AlphaRail Wiring Rail



Connecting Harness



New Flex Style Primary Leads



Conventional Style Primary Leads

■ Ignition Wiring Rails & Hardware



Upgrade Kits for **WAUKESHA®** VHP G/GU/GSI 12 Cylinder Gas Engines – Ignition and Detonation Control

P/N	Description
95.75.120-12 	Shielded ignition control upgrade kit for WAUKESHA® VHP G/GU/GSI 12 cylinder engines ■ MIC4 series ignition controller ■ 1 pickup arrangement (Hall effect) incl. shielded pickup leads, trigger disc and hub ■ Output wiring and junction box with fittings to connect ignition controller and wiring rails ■ AlphaRail wiring rails with hardware kit ■ High energy integral ignition coils ■ New Flex Style primary leads for connection of wiring rails and integral ignition coils
77.75.120-12	Unshielded ignition control upgrade kit for WAUKESHA® VHP G/GU/GSI 12 cylinder engines ■ MIC4 series ignition controller ■ 1 pickup arrangement (Hall effect) incl. shielded pickup leads, trigger disc and hub ■ Output wiring and junction box with fittings to connect ignition controller and wiring rails ■ AlphaRail wiring rails with hardware kit ■ High energy ignition coils ■ Primary lead and mounting kits for connection of wiring rails and ignition coils ■ PolyMot™ spark plug leads
95.75.121-12 	Shielded ignition control upgrade kit for WAUKESHA® VHP G/GU/GSI 12 cylinder engines For use with existing WAUKESHA® CEC ignition controller ■ Output wiring and junction box with fittings to connect CEC ignition controller and wiring rails ■ AlphaRail wiring rails with hardware kit ■ Integral ignition coils to work with CEC Spark Reference System ■ New Flex Style primary leads for connection of wiring rails and integral ignition coils
77.75.121-12	Unshielded ignition control upgrade kit for WAUKESHA® VHP G/GU/GSI 12 cylinder engines For use with existing WAUKESHA® CEC ignition controller ■ Output wiring and junction box with fittings to connect CEC ignition controller and wiring rails ■ AlphaRail wiring rails with hardware kit ■ Ignition coils to work with CEC Spark Reference System ■ Primary lead and mounting kits for connection of wiring rails and ignition coils ■ PolyMot™ spark plug leads
43.00.421-12 ¹⁾	Detonation control upgrade kit for WAUKESHA® VHP G/GU/GSI/GL 12 cylinder engines ■ DetCon20 detonation controller with 20 inputs ■ Harnesses to connect detonation controller and wiring rails ■ AlphaRail wiring rails with hardware kit ■ Leads for connection of wiring rails and detonation sensors ■ Detonation sensors to monitor each cylinder individually ²⁾

¹⁾ For use in hazardous and non-hazardous environments.

²⁾ Prepared cylinder head cap screws for each detonation sensor available on request.

Ignition Kits for Unshielded Applications

Ignition Kits for **MAN**® E0834 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.651	E0834 E302/312/LE302	MIC3+ series	LiteRail	06.50.300	06.85.839H-16	GK3-5	66.60.003-60 (1)	75.41.006
75.00.581 ³⁾	E0834 E302/312/LE302	MIC3+ series	LiteRail	06.50.300	06.85.1037-16	B4321	66.60.003-60 (1)	75.41.006
75.00.501	E0834 E302/312/LE302	MIC4 series	LiteRail	06.50.104	06.85.839H-16	GK3-5	66.60.003-60 (1)	75.41.006
75.00.601 ³⁾	E0834 E302/312/LE302	MIC4 series	LiteRail	06.50.104	06.85.1037-16	B4321	66.60.003-60 (1)	75.41.006

Ignition Kits for **MAN**® E0836 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.652	E0836 E302/312	MIC3+ series	LiteRail	06.50.300	06.85.839H-16	GK3-5	66.60.003-60 (1)	75.41.011
75.00.582 ³⁾	E0836 E302/312	MIC3+ series	LiteRail	06.50.300	06.85.1037-16	B4321	66.60.003-60 (1)	75.41.011
75.00.502	E0836 E302/312	MIC4 series	LiteRail	06.50.104	06.85.839H-16	GK3-5	66.60.003-60 (1)	75.41.011
75.00.602 ³⁾	E0836 E302/312	MIC4 series	LiteRail	06.50.104	06.85.1037-16	B4321	66.60.003-60 (1)	75.41.011
75.00.653	E0836 LE202	MIC3+ series	LiteRail	06.50.300	06.85.836H-16	GE3-5	66.60.003-60 (1)	75.41.011
75.00.583 ³⁾	E0836 LE202	MIC3+ series	LiteRail	06.50.300	06.85.1031-16	B4321	66.60.003-60 (1)	75.41.011
75.00.503	E0836 LE202	MIC4 series	LiteRail	06.50.104	06.85.836H-16	GE3-5	66.60.003-60 (1)	75.41.011
75.00.603 ³⁾	E0836 LE202	MIC4 series	LiteRail	06.50.104	06.85.1031-16	B4321	66.60.003-60 (1)	75.41.011

Ignition Kits for **MAN**® E2676 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.655	E2676 E302/LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.929-20	GK3-5	66.60.003-60 (1)	75.41.003
75.00.585 ³⁾	E2676 E302/LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1038-20	B4321	66.60.003-60 (1)	75.41.003
75.00.505	E2676 E302/LE202/212	MIC4 series	LiteRail	06.50.104	06.85.929-20	GK3-5	66.60.003-60 (1)	75.41.003
75.00.605 ³⁾	E2676 E302/LE202/212	MIC4 series	LiteRail	06.50.104	06.85.1038-20	B4321	66.60.003-60 (1)	75.41.003

Ignition Kits for **MAN**® E2876 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.654	E2876 E302/312/TE302	MIC3+ series	LiteRail	06.50.300	06.85.836H-16	GE3-5	66.60.003-60 (1)	75.41.005
75.00.584 ³⁾	E2876 E302/312/TE302	MIC3+ series	LiteRail	06.50.300	06.85.1031-16	B4321	66.60.003-60 (1)	75.41.005
75.00.504	E2876 E302/312/TE302	MIC4 series	LiteRail	06.50.104	06.85.836H-16	GE3-5	66.60.003-60 (1)	75.41.005
75.00.604 ³⁾	E2876 E302/312/TE302	MIC4 series	LiteRail	06.50.104	06.85.1031-16	B4321	66.60.003-60 (1)	75.41.005
75.00.656	E2876 LE202/212/302	MIC3+ series	LiteRail	06.50.300	06.85.836H-16	GE3-5	66.60.003-60 (1)	75.41.025
75.00.586 ³⁾	E2876 LE202/212/302	MIC3+ series	LiteRail	06.50.300	06.85.1031-16	B4321	66.60.003-60 (1)	75.41.025
75.00.506	E2876 LE202/212/302	MIC4 series	LiteRail	06.50.104	06.85.836H-16	GE3-5	66.60.003-60 (1)	75.41.025
75.00.606 ³⁾	E2876 LE202/212/302	MIC4 series	LiteRail	06.50.104	06.85.1031-16	B4321	66.60.003-60 (1)	75.41.025

¹⁾ Mentioned spark plugs for comparison purposes only and not included in scope of supply.

²⁾ Mounting kits for wiring rails are not included in scope of supply and need to be ordered separately.

³⁾ Ignition kit includes magnetic spark plug socket to fit MHP spark plug B4321 with long insulator.

■ Ignition Wiring Rails & Hardware



Ignition Kits for **MAN**® E2848 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.657	E2848 LE322	MIC3+ series	LiteRail	06.50.300	06.85.836H-16	GE3-5	66.60.003-100 (1)	75.41.002, alternative 75.41.026
75.00.587 ³⁾	E2848 LE322	MIC3+ series	LiteRail	06.50.300	06.85.1031-16	B4321	66.60.003-100 (1)	75.41.002, alternative 75.41.026
75.00.507	E2848 LE322	MIC4 series	LiteRail	06.50.104	06.85.836H-16	GE3-5	66.60.003-100 (1)	75.41.002, alternative 75.41.026
75.00.607 ³⁾	E2848 LE322	MIC4 series	LiteRail	06.50.104	06.85.1031-16	B4321	66.60.003-100 (1)	75.41.002, alternative 75.41.026

Ignition Kits for **MAN**® E2842 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.658	E2842 E/LE312	MIC3+ series	LiteRail	06.50.300	06.85.836H-16	GE3-5	66.60.003-100 (1), 66.60.001-250 (1)	75.41.013
75.00.588 ³⁾	E2842 E/LE312	MIC3+ series	LiteRail	06.50.300	06.85.1031-16	B4321	66.60.003-100 (1), 66.60.001-250 (1)	75.41.013
75.00.508	E2842 E/LE312	MIC4 series	LiteRail	06.50.104	06.85.836H-16	GE3-5	66.60.003-100 (1), 66.60.001-250 (1)	75.41.013
75.00.608 ³⁾	E2842 E/LE312	MIC4 series	LiteRail	06.50.104	06.85.1031-16	B4321	66.60.003-100 (1), 66.60.001-250 (1)	75.41.013
75.00.659	E2842 LE202/322/332	MIC3+ series	LiteRail	06.50.300	06.85.836H-16	GE3-5	66.60.003-100 (1)	75.41.001, alternative 75.41.027
75.00.589 ³⁾	E2842 LE202/322/332	MIC3+ series	LiteRail	06.50.300	06.85.1031-16	B4321	66.60.003-100 (1)	75.41.001, alternative 75.41.027
75.00.509	E2842 LE202/322/332	MIC4 series	LiteRail	06.50.104	06.85.836H-16	GE3-5	66.60.003-100 (1)	75.41.001, alternative 75.41.027
75.00.609 ³⁾	E2842 LE202/322/332	MIC4 series	LiteRail	06.50.104	06.85.1031-16	B4321	66.60.003-100 (1)	75.41.001, alternative 75.41.027

¹⁾ Mentioned spark plugs for comparison purposes only and not included in scope of supply.

²⁾ Mounting kits for wiring rails are not included in scope of supply and need to be ordered separately.

³⁾ Ignition kit includes magnetic spark plug socket to fit MHP spark plug B4321 with long insulator.

■ Ignition Wiring Rails & Hardware



Ignition Kits for **MAN®** E3268 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.661	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.959-18	GE3-5	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.668-141 ⁴⁾	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.1078-18	GE3-5, 14R-4DIU2, 7315	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.591 ³⁾	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.1023-18	B4321	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.668-142 ⁴⁾	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.1079-18	B4321	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.668-143 ⁴⁾	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.1073-18	14GZ-LL	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.595	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.1042-18	GL3-5, B8324	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.668-181 ⁴⁾	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.1074-18	GL3-5, 7308	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.668-182 ⁴⁾	E3268 LE212/222	MIC3+ series	LiteRail	06.50.300	06.85.1080-18	B8324	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.511	E3268 LE212/222	MIC4 series	LiteRail	06.50.104	06.85.959-18	GE3-5	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.611 ³⁾	E3268 LE212/222	MIC4 series	LiteRail	06.50.104	06.85.1023-18	B4321	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.596	E3268 LE212/222	MIC4 series	LiteRail	06.50.112	06.85.1042-18	GL3-5, B8324	66.60.003-100 (1)	75.41.023, alternative 75.41.033

¹⁾ Mentioned spark plugs for comparison purposes only and not included in scope of supply.

²⁾ Mounting kits for wiring rails are not included in scope of supply and need to be ordered separately.

³⁾ Ignition kit includes magnetic spark plug socket to fit MHP spark plug B4321 with long insulator.

⁴⁾ Included PolyMot™ spark plug leads fit new valve covers with flange safety device of MAN® E32 series.

NEW

Valve Cover Conversion Kit with Flange Safety Device for Spark Plug Leads For **MAN® E32 Series** Gas Engines

Please also see page 218 for MOTORTECH valve cover conversion kit for recommended retrofitting of already operating engines without safety devices.



■ Ignition Wiring Rails & Hardware

Ignition Kits for MAN® E3262 Series Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	PolyMot™ Spark Plug Lead		Pickup P/N (Qty)	Mounting Kit for Wiring Rail P/N ²⁾
					P/N	Fits Spark Plug ¹⁾		
75.00.627	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.959-18	GE3-5	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.669-141 ⁴⁾	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.1078-18	GE3-5, 14R-4DIU2, 7315	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.631	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.1023-18	B4321	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.669-142 ⁴⁾	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.1079-18	B4321	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.669-143 ⁴⁾	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.1073-18	14GZ-LL	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.647	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.1042-18	GL3-5, B8324	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.669-181 ⁴⁾	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.1074-18	GL3-5, 7308	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.669-182 ⁴⁾	E3262 E302	MIC3+ series	LiteRail	06.50.300	06.85.1080-18	B8324	66.60.003-100 (1), 66.60.001-250 (1)	75.41.023
75.00.660	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.959-18	GE3-5	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.670-141 ⁴⁾	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1078-18	GE3-5, 14R-4DIU2, 7315	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.590 ³⁾	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1023-18	B4321	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.670-142 ⁴⁾	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1079-18	B4321	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.670-143 ⁴⁾	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1073-18	14GZ-LL	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.597	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1042-18	GL3-5, B8324	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.670-181 ⁴⁾	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1074-18	GL3-5, 7308	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.670-182 ⁴⁾	E3262 LE202/212	MIC3+ series	LiteRail	06.50.300	06.85.1080-18	B8324	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.510	E3262 LE202/212	MIC4 series	LiteRail	06.50.104	06.85.959-18	GE3-5	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.610 ³⁾	E3262 LE202/212	MIC4 series	LiteRail	06.50.104	06.85.1023-18	B4321	66.60.003-100 (1)	75.41.023, alternative 75.41.033
75.00.598	E3262 LE202/212	MIC4 series	LiteRail	06.50.112	06.85.1042-18	GL3-5, B8324	66.60.003-100 (1)	75.41.023, alternative 75.41.033

¹⁾ Mentioned spark plugs for comparison purposes only and not included in scope of supply.

²⁾ Mounting kits for wiring rails are not included in scope of supply and need to be ordered separately.

³⁾ Ignition kit includes magnetic spark plug socket to fit MHP spark plug B4321 with long insulator.

⁴⁾ Included PolyMot™ spark plug leads fit new valve covers with flange safety device of MAN® E32 series.

Please also see page 218 for MOTORTECH valve cover conversion kit for recommended retrofitting of already operating engines without safety devices.



■ Ignition Wiring Rails & Hardware



Mounting Kits for Ignition Kits for **MAN**® Gas Engines

P/N	Description	Engine Model	Rail Mounting on
75.41.006	Mounting kit for ignition rail	E0834 E302/312/LE302	Engine
75.41.011	Mounting kit for ignition rail	E0836 E302/312/LE202	Engine
75.41.003	Mounting kit for ignition rail	E2676 E302/LE202/212	Engine
75.41.005	Mounting kit for ignition rail	E2876 E302/312/TE302	Engine
75.41.025	Mounting kit for ignition rail	E2876 LE202/212/302	Engine
75.41.002	Mounting kit for ignition rails	E2848 LE322	Engine
75.41.026	Mounting kit for ignition rails	E2848 LE322	Intercooler
75.41.013	Mounting kit for ignition rails	E2842 E/LE312	Engine
75.41.001	Mounting kit for ignition rails	E2842 LE202/322/332	Engine
75.41.027	Mounting kit for ignition rails	E2842 LE202/322/332	Intercooler
75.41.023	Mounting kit for ignition rails	E3268 LE212/222, E3262 E302/LE202/212	Engine
75.41.033	Mounting kit for ignition rails	E3268 LE212/222, E3262 LE202/212	Intercooler



Rail mounting on intercooler



Rail mounting on engine

Ignition Kits for **LIEBHERR**® Gas Engines

P/N	Engine Model	Ignition Controller	Wiring Rail Type	Ignition Coil P/N	Spark Plug ¹⁾	Pickup ²⁾	Mounting Kit for Wiring Rail
75.00.433	G944	MIC4 series	AlphaRail	06.50.104	not included	not included	75.41.010
75.00.434	G946	MIC4 series	AlphaRail	06.50.104	not included	not included	75.41.008
75.00.435	G9508	MIC4 series	AlphaRail	06.50.104	not included	not included	75.41.022
75.00.436	G9512	MIC4 series	AlphaRail	06.50.104	not included	not included	75.41.021

¹⁾ MOTORTECH XTL Plug P/N B432BEX9-A107 has to be ordered separately in required quantity.

²⁾ Scope of supply only includes wiring for LIEBHERR® pickup.



Ignition kit for LIEBHERR® gas engines

■ Ignition Tools & Test Equipment

SparkView MOTORTECH HIGH VOLTAGE INDICATOR

The SparkView is a handheld device developed by MOTORTECH that can monitor the high voltage required by the spark plug while the engine is running. With a measuring clamp or cable and the display for up to 40 kV, it is easy to determine the condition of the spark plugs and the time at which they need to be replaced. This guarantees a constant performance of the engine and a maximum utilization of the spark plugs.

Quick and comfortable monitoring on a running engine makes it possible to detect

- Wear of spark plugs
- Failure of the ignition system (damaged ignition coil, spark plug lead or ignition controller)
- Faulty compression of a cylinder



SparkView High Voltage Indicator

P/N	Figure	Description
06.90.099-100	1	SparkView high voltage indicator, incl. SparkScan1 high voltage clamp P/N 06.90.100, for use with spark plug leads
06.90.099-105	2	SparkView high voltage indicator, incl. BNC cable P/N 06.90.105, for use with flange ignition coils or externally mounted ignition coils with diagnostic interface



SparkScan1

MOTORTECH HIGH VOLTAGE CLAMP

SparkScan1 is designed for operators who want to monitor their high voltage traces in a simple way. The inductive high voltage clamp is connected to a Scope Meter. When attached to a conventional ignition cable (7 mm), the clamp measures the high voltage pulse and via scope screen the operator can analyse the ignition trace.

Measuring high voltage peak (kV) and spark duration (μsec) of all cylinders of an engine in a routine manner, will allow preventive maintenance of the equipment.



SparkScan1 High Voltage Clamp

P/N	Description	Length
06.90.100	SparkScan1 high voltage clamp	2.0 m/7.0 ft

Digital Scope Meter

The digital scope meter is a compact 20 MHz or 40 MHz two channel scope. Ideal for troubleshooting of industrial machinery, instrumentation, control and power systems. The scope meter has unique features like connect-and-view and trendplot that simplify taking measurements and reduce troubleshooting time when working in the field or in industrial environments.



Digital Scope Meter

P/N	Description
06.98.005-110	Digital scope meter, 110 V
06.98.005-220	Digital scope meter, 220 V

BNC Cable for use with SparkView or Digital Scope Meter

P/N	Description	Length
06.90.105	BNC cable	2.0 m/7.0 ft



■ Ignition Tools & Test Equipment



This test equipment is designed to offer service companies a professional tool to test all different kinds of ignition coils that were sold by engine manufacturers or aftermarket companies. A built in CD ignition, high voltage clamp and a spark gap allow realistic testing.



Ignition Coil Tester

P/N	Description
06.98.054	Ignition coil tester, incl. standard adaptor kits for popular ignition coils

Adaptor Kits – Standard – including Teflon® Ignition Coil Adaptors and Connecting Leads ¹⁾

P/N	Description	Connections of included Lead	
		Ignition Coil	Ignition Coil Tester
06.98.054-1	Adaptor kit for CATERPILLAR® ignition coils, G3400 & G3500	DEUTSCH® connector	XLR connector
06.98.054-2	Adaptor kit for ALTRONIC® Style ignition coils	2 pole	XLR connector
06.98.054-3	Adaptor kit for MOTORTECH Style ignition coils	2 pole	XLR connector
06.98.054-4	Adaptor kit for flange ignition coils	MIL, 3 pole, socket, 180°	XLR connector
06.98.054-5	Adaptor kit for integral ignition coils, outer thread	MIL, 2/3 pole, socket, 180°	XLR connector
06.98.054-6	Adaptor kit for integral ignition coils, inner thread	MIL, 2/3 pole, socket, 180°	XLR connector
06.98.054-7	Adaptor kit for externally mounted ignition coils	MIL, 2/3 pole, socket, 180°	XLR connector

¹⁾ All adaptor kits included in ignition coil tester.

Adaptor Kits – Special – including Connecting Leads

P/N	Description	Connections of included Lead	
		Ignition Coil	Ignition Coil Tester
06.70.192-5	Adaptor kit for CUMMINS® ignition coil P/N 3964547	4 pole, 180°	XLR connector
06.70.192-6	Adaptor kit for GE JENBACHER® ignition coil P/N 369083	4 pole, 180°	XLR connector

IPS

MOTORTECH IGNITION PICKUP SIMULATOR

Anyone trying to troubleshoot electronic ignition systems has come to the conclusion that there are so many different things that can create problems.

The ignition pickup simulator allows the operator to simulate all pickup signals that are supposed to be generated by the different pickups installed on flywheel and camshaft. This way the ignition can actually be triggered with the appropriate amount of trigger events while the engine is not cranking. The IPS can be programmed for single and multiple pickup signal frequency.

A variety of adaptor harnesses is available to allow use of the IPS with different ignition controller brands and models.



IPS Ignition Pickup Simulator

P/N	Description
07.98.047	IPS Ignition Pickup Simulator

Adaptor Harnesses for IPS Ignition Pickup Simulator ¹⁾

P/N	IPS Adaptor Harness for use with
07.70.001	WOODWARD® IC9xx series
07.70.002-1	MIC500 series (P/N 06.00.508), WOODWARD® IC100 series with inductive pickup
07.70.002-2	MIC500 series (P/N 06.00.508), WOODWARD® IC100 series with Hall effect pickup
07.70.002-3	MIC500 series (P/N 06.00.508), WOODWARD® IC100 series with magnetic pickup
07.70.003	MIC500 series (P/N 06.00.510)
07.70.004	MIC3+CATDI (P/N 66.00.356-8, 66.00.357-12), MIC3+CEC (P/N 66.00.358-8, 66.00.359-12), MIC500 series (P/N 06.00.513, 06.00.514), ALTRONIC® DIS & DISN, CATERPILLAR® (P/N 163-6164, 163-6108)
07.70.005	FAIRBANKS MORSE® IQ250 series
07.70.006	ALTRONIC® CPU95 series
07.70.009	MOTORTECH MIC500 series (P/N 06.00.511)
07.70.010	MIC500 series (P/N 06.00.515-6, 06.00.515-8, 06.00.516, 06.00.517), WAUKESHA® CEC (VHP/VGF series)
07.70.011	MIC3/3+ series (P/N 66.00.310-6/-12, 66.00.350-6/-12), MIC4 series (P/N 66.00.424-8/-16), MIC5 series (P/N 66.00.541-20)
07.70.012	FAIRBANKS MORSE® IQ750 series
07.70.013	MIC500 series (P/N 06.00.520, 06.00.525, 06.00.530)
07.70.014	MIC850 series (P/N 66.00.850-24/-D, 66.00.851-24/-D, 66.00.855-12/-D/-24/-D)
07.70.015	MIC4 series (66.00.400-8/-16/410-8/-16/440-8/-16), MIC5 series (P/N 66.00.540-20/66.00.542-20)

¹⁾ Need to be ordered separately.

■ Ignition Tools & Test Equipment

Test Adaptor for MOTORTECH Ignition Controllers

To enable operators and service personnel to check input signals to the ignition controller in a simple way, MOTORTECH offers a Test Adaptor that links between the 35 pole input connector and the appropriate harness.

Terminals located around the test box allow easy access to each input signal entering the ignition controller. By use of a commonly used Digital Scope Meter, the following signals can be checked:

- Input voltage
- Analog input signal (4-20mA)
- Pickup signals
- Start/Stop signal
- Go/NoGo signal
- Timing schedule selection switch (A/B)



Test Adaptor for MIC3/3+, MIC4, MIC5 and MIC6 Series Ignition Controllers

P/N	Supersedes	Description	For use with MOTORTECH Ignition Controllers
06.98.130		Test adaptor	MIC3/3+ series (P/N 66.00.310-6/-12, 66.00.350-6/-12) MIC4 series (P/N 66.00.424-8/-16) MIC5 series (P/N 66.00.541-20) MIC6 series (P/N 66.00.645-24)



ScopeLite

MOTORTECH TIMING LIGHT

The self-powered ScopeLite is designed to work with fully shielded ignition systems. A special clamp picks up the small trigger signal through the braid of conventional or MOT-Blues shielded spark plug leads. The signal is processed by the timing light and via LED technology a sequence of flashes is generated. On applications where MOTORTECH ignition coils with diagnostic interface are used, the ScopeLite can be attached directly to the BNC connector of the ignition coil.

Even on applications with integral or standard flange ignition coils, the clamp can be attached to the shielded primary lead. When timing is checked on engines with non-shielded spark plug leads, a selector switch needs to be pushed which then steps down sensitivity. The automatic time based shut-off function saves the 2 built in 9 V batteries in case the operator forgets to turn off power.

Makes it easy and safe for the operator!



ScopeLite Timing Light

P/N	Description
06.98.100-200	ScopeLite timing light with LEDs, incl. clamp, 200 in standard connecting lead and carrying case


Connecting Leads (Standard and Non Standard Lengths) ¹⁾

P/N	Description	Length
06.90.104-100	ScopeLite connecting lead	2.5 m/100 in
06.90.104-200	ScopeLite connecting lead	5.0 m/200 in
06.90.104-300	ScopeLite connecting lead	7.5 m/300 in
06.90.104-400	ScopeLite connecting lead	10.0 m/400 in
06.90.104-600	ScopeLite connecting lead	15.0 m/600 in

¹⁾ If non standard length is required, please order separately from above chart.



Use with MOT-Blues shielded spark plug leads.



Use with conventional shielded spark plug leads.



Use with MOTORTECH ignition coils with diagnostic interface or with shielded primary lead.

■ Ignition Tools & Test Equipment

Timing Light – Conventional Style

P/N	Description	Lead Length
06.98.043-10	Timing light	3.0 m/10.0 ft
06.98.043-30	Timing light	9.0 m/30.0 ft



Digital Protractor


The Digital Protractor is a compact rotational angle measuring tool. The unit is equipped with magnets for easy and flexible installation on flywheel, camshaft, pulley or any other rotating gear.

P/N	Description
06.98.096	Digital protractor



Spark Plug Lead Removal Tool for MAN® Gas Engines

P/N	Description
44.99.918	Spark plug lead removal tool for MAN® gas engines



Installation Tool for Reluctor Pin

P/N	Description
44.99.011	Installation tool for reluctor pin P/N 06.80.104



Workshop Equipment

P/N	Figure	Description
06.05.903-1	1	Spark plug test stand for M14, M18 and 7/8-18 UNS spark plugs
06.05.904-1	2	Engine simulator with 24 spark gap rack



1



2

NEW

Brush Kit to clean Termination Wells

Expensive ignition components, such as ignition coils, spark plug leads and extensions and extended barrel spark plugs can have an extended life if proper maintenance is available. The new brush kit is available to easily clean away the dirt, grime, and corrosion that can affect product life.

Brush kit for use with

- Ignition coils
- Spark plug leads and extensions
- Extended barrel spark plugs

Features

- Easy to use tool
- Cleans away dirt and corrosion safely
- Helps to increase component service life
- Bristles are of nylon impregnated with silicone to clean without scratching or removing any Teflon®
- Kit components separately available



Cleaning of spark plug extension



Cleaning of extended barrel spark plug



Cleaning of externally mounted ignition coil

Brush Kit to clean Termination Wells

P/N	Supersedes	Description	Quantity	Equivalent to
07.98.075		Brush kit to clean termination wells <i>Contains:</i> ■ Nylon brushes, thread shanked ■ Removable T-handle with screw ■ Silicone grease, 5 oz (140 g) tube ■ Grease applicator brush	3 pcs 1 pc 1 pc 1 pc	

■ Ignition Tools & Test Equipment

Harness Connector Assembly Tools

P/N	Figure	Description
06.98.011	4	Crimping tool for studs
06.98.017	1	Extraction tool for ITT® contacts „16S“
06.98.046	7	Installation tool for MIL style connector pins
06.98.051	6	Removal tool for MIL style connector pins

Spark Plug Lead Assembly Tools

P/N	Figure	Description
06.98.011	4	Crimping tool for studs
06.98.013	5	Crimping tool for P/N 06.80.116
06.98.019	2	Assembly tool for P/N 06.98.109
06.98.047	3	Crimping tool for P/N 06.80.126 (already includes crimping tool insert P/N 06.98.048)
06.98.048	8	Crimping tool insert for P/N 06.98.047 to crimp terminal P/N 06.80.126
06.98.050	9	Crimping tool insert for P/N 06.98.047 to crimp terminal P/N 22.85.802 and P/N 22.85.803




■ Spark Plugs & Accessories




The DDI's key to long plug life

DENSO has launched the latest generation of hard-wearing spark plugs – the DENSO DOUBLE IRIDIUM (DDI) spark plug. DDI spark plug technology improves and extends the spark plug's lifespan and requires significantly less maintenance than competitor spark plugs. The DDI spark plug is particularly effective when used in biogas engines. Try DENSO DDI spark plugs today.




IRIDIUM SAVER DDI




IRIDIUM SAVER

The SAVER's key to long plug life

DENSO's OEM expertise and commitment to innovation enables them to remain at the forefront of cutting-edge gas engine spark plug development. The unique and specialist technology used in the Iridium Saver and Iridium Saver Performer spark plugs range extends their lifespan, making them ideal for high-compression lean-burn engines. Iridium Saver and Iridium Performer spark plugs also help to maximise engine performance and deliver extra durability. Because they require minimal maintenance compared to standard plugs, Iridium Saver and Iridium Saver Performer spark plugs increase service interval times.



**IRIDIUM SAVER
PERFORMER**



IRIDIUM SAVER

Specifications and Cross References

for Gas Engines

G I 3 - 1 (A)

Installation Dimension and Tightening Torque					
No	Thread Size	HEX	Thread Reach	Tightening Torque	
E	M14x1.25	13/16 in (20.8 mm)	0.750 in (19.0 mm)	with lubricant	20 Nm (15 lb-ft)
N			0.500 in (12.7 mm)	without lubricant	30 Nm (22 lb-ft)
K		5/8 in (16 mm)	0.750 in (19.0 mm)		
L	M18x1.5	13/16 in (20.8 mm)	0.811 in (20.6 mm)	with lubricant	30 Nm (22 lb-ft)
I		7/8 in (22.2 mm)	0.543 in (13.8 mm)	without lubricant	45 Nm (33 lb-ft)
T					

Initial Gap	
No	Nominal Value
3	0.3 mm
5	0.5 mm

Terminal Design		
	No	SPEC.
	none	solid
	A	with nut

Electrode Design	
1. IRIDIUM SAVER Iridium pad without cross groove on center electrode and Platinum pad on ground electrode.	
3. IRIDIUM SAVER For vehicle.	
5. IRIDIUM SAVER DDI Iridium pad without cross groove on center electrode and Iridium pad on ground electrode.	
1. IRIDIUM SAVER PERFORMER Iridium pad with cross groove on center electrode and Platinum pad on ground electrode.	
3. IRIDIUM SAVER Iridium pad without cross groove on center electrode and Platinum pad on ground electrode.	
5. IRIDIUM SAVER DDI Iridium pad without cross groove on center electrode and Iridium pad on ground electrode.	

Cross References

	CHAMPION®	STITT®	ALTRONIC®	BERU®	BOSCH®	IRIDIUM SAVER	IRIDIUM SAVER DDI	IRIDIUM SAVER PERFORMER
M14	RN79G (0.015)	407XL, R407XL	J1463DP	14R-3CPU, 14-3CPU, 14R-5DPU, 14R-4CDP	7311	GE3-1	GE3-5	
				14R-4CIU (Z187), 14R-4CIU2 (Z215), 14R-4DIU2 (Z258), 14R-4DIU3, 14GZ-LL	7315		GE3-5	
	RN79G (0.020)			14R-4CIU (Z205)	7313	GE5-1		
	RC78PYP, RC78PYP15			14FR-4DPUO	7321	GK3-1	GK3-5	
M18	RC78WYP15			14FR-4DIU, 14GZ-LL-FR	7322			
	RL85G, RL15B	407L, R407L	J1443DP	14R-5BPU, 14R-4ADP, 14R-5BIU		GN3-1		
	FB77WPCC, RB77WPCC, KB77WPCC, RB77CC, PB78WPC		L1863IP	18GZ4-77, 18GZ6-77-2	7305, 7306	GI3-3	GI3-5	GI3-1
	RB75N, RB75PP	R807LL	L1863B, L1863DP	18GZ20	7302	GI3-3	GI3-5	GI3-1
	RB75WPCC-1			18GZ5-77-2	7307, 7308	GL3-3	GL3-5	GL3-1
	RB76N, RB76PP	R807LL		18GZ7		GI3-3	GI3-5	GI3-1
	RM77N	807, 827, 847, U827, U847	L1843B	18GZ22	7303			GT3-1
	RM77PP		L1843IP					

■ Spark Plugs & Accessories



NEW

DENSO® Spark Plug GI3-4 For **ROLLS ROYCE®**, **WÄRTSILÄ®** and **CATERPILLAR®** Gas Engines

The DENSO® spark plug GI3-4, for years an exclusively made product for engine manufacturers like ROLLS ROYCE® and WÄRTSILÄ®, is now available for the gas engine aftermarket.

Provided with all positive characteristics of the IRIIDIUM SAVER PERFORMER family, the Cross Groove design, the 360° laser welding and iridium/platinum alloy on center and ground electrode, this spark plug type is one more DENSO® product standing for high quality and long life.



The SAVER's key to long plug life

Unique "Iridium Alloy"

A unique, high welding point "iridium alloy" developed and patented by DENSO®, dramatically improves wear resistance compared to other iridium spark plugs.

360° Laser Welding

Secure welding of the iridium tip by "360° laser welding" can withstand all extreme engine conditions.

Cross Groove Design

4 small electrodes created by Cross Groove improve sparking performance and suppress dispersion in voltage value, for an outstanding voltage decrease.

Installation Dimension and Tightening Torque				
Thread Size	HEX	Thread Reach	Tightening Torque	
M18x1.5	7/8 in (22.2 mm)	0.874 in (20.6 mm)	without lubricant	45 Nm, 33 lb-ft

GI3-4



Electrode Design

Iridium pad with cross groove on center electrode and platinum pad on copper cored ground electrode.



Cross References

IRIDIUM SAVER PERFORMER	ROLLS ROYCE®	WÄRTSILÄ®	CATERPILLAR®
GI3-4	706522	PAAE059695	193468054, 339-9790



NEW

Iridium Saver Spark Plug & Boot Kit For **CUMMINS®** ISL-G Engine Applications

MOTORTECH is pleased to offer the DENSO® GK3-7 Iridium Saver Spark Plug and rubber boot kit for CUMMINS® ISL-G gas engines. This protective rubber boot insulates the spark plug from the harsh environment. Combined with the reliable, long lasting Iridium Saver Spark Plug, this kit is the perfect combination for CUMMINS® natural gas engines.

Technical Benefits

- Unique iridium alloy
- 360° laser welding
- Highly reliable monolithic resistor
- Special nickel plating with better corrosive resistance
- High dielectric ceramics



DENSO® Spark Plug G13-4 | Spark Plug & Boot Kit for CUMMINS®

P/N	Description	Quantity	Equivalent to
4955850-MOT	Spark plug and boot kit Contains: ■ Iridium 3-prong spark plug P/N GK3-7 ■ Spark plug boot P/N 06.84.053 ■ Dielectric grease	1 pc 1 pc 1 pc	4955850 4937472 4989131, 3973945

■ Spark Plugs & Accessories

MHP-Plugs MOTORTECH HIGH PERFORMANCE SPARK PLUGS


The expansion of MOTORTECH's state-of-the-art ignition controllers is driven by the latest developments of modern spark ignited gas engines. The operation of these high performance engines with advanced compression rates and very efficient lean-burn combustion systems require much higher voltages to allow a perfect and effective combustion.

MHP spark plugs are designed to meet the requirements, both of modern and common engine developments and reliably deliver highest voltages and thus a strong spark down into the combustion chamber. The J-type electrode design with IRIDIUM alloy discs on center and ground electrode provides reliable combustion and increased spark plug life and helps to reduce service costs due less spark plug changes.



General Features

- Hot lock technology ensures increased spark plug durability even in high compression engines
- J-type electrode design for enhanced combustion
- Supplies even highest voltages of modern ignition systems like MOTORTECH's MIC series
- Long design insulators for best flash-over protection
- Advanced spark erosion resistance
- Suppression of electromagnetic interference (EMI)
- Less spark plug changes reduce operation costs
- Available with different thread sizes and reaches
 - M14x1.25
 - M18x1.5
 - M22x1.5
 - 7/8-18 UNS




Spark Plugs & Accessories



Key Design Features

- 1 Removable threaded brass SAE terminal
- 2 Long aluminum oxide ceramic insulator offers best flashover protection, especially in combination with PolyMot™ spark plug leads and extensions
- 3 Integrated stress resistant monolithic resistor suppresses electromagnetic interference (EMI)
- 4 Unified hex size reduces amount of required service tools for installation
- 5 J-type electrode design and use of higher erosion resistance materials ensure better combustion particularly on lean burn gas engines and longest service life
- 6 Copper cored center electrode with laser welded IRIDIUM alloy disc
- 7 Copper cored ground electrode with laser welded IRIDIUM alloy disc



MOTORTECH High Performance Spark Plugs

P/N ¹⁾	Description	Thread Size	Thread Reach	Electrode Design (Alloy)	HEX	Equivalent to ²⁾
B4321	MHP spark plug	M14x1.25	0.750 in (19.0 mm)	J-type (Ir/Ir)	5/8 in (16.0 mm)	J1463DP, 14FR-4DIU3, 14GZ-LL, 14GZ-LL2, 14GZ-LL-FR, 14GZ6-77-2, RN79G, RC78PYP, GE3-5, GK3-5
B8124	MHP spark plug	M18x1.5	0.500 in (12.7 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	L1843IP, 18GZ22, RB485-1, RM77N, RM77PP, GT3-1, 7303
B8324	MHP spark plug	M18x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	L1863IP, 18GZ5-77-2, 18GZ6-77-2, RB75WPCC, FB77WPCC, GL3-5, GI3-5, 7305, 7306, 7307, 7308
NEW B8324-LTN ³⁾	MHP spark plug	M18x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	306-6663, 243-4291, 194-8518, 76.64.375, 76.64.292, 76.64.291, 69919D, 69919C, 69919A, 69919
B8524	MHP spark plug	M18x1.5	1.000 in (25.4 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	
B2224	MHP spark plug	M22x1.5	0.600 in (15.0 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	
B2324	MHP spark plug	M22x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	
B2424	MHP spark plug	M22x1.5	0.875 in (22.2 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	
B7224	MHP spark plug	7/8-18 UNS	0.600 in (15.0 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	L2252IP, 7/8GZ9, RB212-1, RW80N
B7324	MHP spark plug	7/8-18 UNS	0.750 in (19.0 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	7/8GZ11, RW78N, W18, R717
B7424	MHP spark plug	7/8-18 UNS	0.875 in (22.2 mm)	J-type (Ir/Ir)	13/16 in (20.8 mm)	L2282IP, RB114-1, RW77N, RW77PP, W77N

¹⁾ MOTORTECH MHP-Plugs only available in packs of 4 pcs.

²⁾ Refer to current MHP-Plugs sales flyer for further cross references and notes.

³⁾ Spark plug comes with longer terminal nut to have identical overall length as to be replaced spark plug.
Must be used on applications with ignition coils fixed on the cylinder head (e.g. CATERPILLAR G3500C, G3600, etc.)

■ Spark Plugs & Accessories

MBP-Plugs MOTORTECH BRIDGE SPARK PLUGS

Modern gas engines are permanently operating under absolute extreme conditions with an effective mean pressure of more than 20 bar, with highly corrosive fuels (H₂S) and lean mixtures – simultaneously demanding longer life periods.

The MOTORTECH MBP1800 spark plug uses an innovative, highly solid electrode design, thus granting three times longer lifetimes than any traditional J-gap spark plug can do.

General Features

- Long life
- New bridge electrode design
- Large spark surface area
- Double iridium electrodes
- Advanced welding process
- M18 thread

Double Iridium Electrodes

The MBP1800's special double iridium electrode structure lead to a large spark surface area of 11 mm²/ 0.017 sq inch.

Innovative Electrode Design

The bridge design offers two heat paths, maximizing the heat dissipation of the ground electrode, reducing the electrode wear out, thus extending the spark plug life period.

Patented Welding Process


The electron beam welding is the most robust of all currently known welding processes. The vacuum environment and the precise electron beam provide for the best possible bi-metal connection.

MOTORTECH Bridge Spark Plug

P/N ¹⁾	Supersedes	Description	Thread Size	Thread Reach	Electrode Design (Alloy)	HEX	Equivalent to
MBP1800		MBP spark plug	M18x1.5	0.875 in (20.2 mm)	Bridge-type (Ir/Ir)	7/8 in (22.2 mm)	FEDERAL MOGUL® FB78WW, ROLLS ROYCE® 710785

¹⁾ MOTORTECH MBP1800 spark plug only available in packs of 4 pcs.

²⁾ Call MOTORTECH or your nearest MOTORTECH sales partner for information about the range of application.



MPC-Plugs

MOTORTECH PRE-CHAMBER SPARK PLUGS

MOTORTECH's MPC1900 pre-chamber spark plug is a cost-effective high performance solution for a wide variety of stationary gas engines. It features a rigid design for industrial purposes that guarantees a long service life. The innovative product optimizes combustion in the engine and improves efficiency and emission values.

General Features

- Made in Germany
- Iridium/Platinum alloy on center and ground electrode
- Resistant high quality ceramics made for best mechanical, thermal and electrical properties
- Laser technology makes a perfect alloy at the seam possible
- Hot locking technology guarantees high durability in high compression engines
- Monolithic resistor
- High quality steel shell, nickel-plated for excellent corrosion resistance



MOTORTECH Pre-Chamber Spark Plug

P/N ¹⁾	Supersedes	Description	Thread Size	Thread Reach	Electrode Design (Alloy)	HEX	Equivalent to ²⁾
MPC1900	MPC1800	MPC spark plug	M18x1.5	0.866 in (22.0 mm)	Pre-Chamber (Ir/Pt)	13/16 in (20.8 mm)	

¹⁾ MOTORTECH MPC1900 spark plug only available in packs of 4 pcs.

²⁾ Call MOTORTECH or your nearest MOTORTECH sales partner for information about the range of application.


■ Spark Plugs & Accessories

ICP-Plugs MOTORTECH INTEGRAL IGNITION COIL SPARK PLUGS

For operators who prefer to use a long integral ignition coil, MOTORTECH manufactures the dual threaded spark plugs. For years these plugs have been successfully operated worldwide.

General Features

- Hot lock technology ensures increased spark plug durability even in high compression engines
- J-type electrode design for enhanced combustion
- Supplies even highest voltages of modern ignition systems like MOTORTECH's MIC series
- Special isolation for ceramic insulators for best flashover protection
- Advanced spark erosion resistance
- Suppression of electromagnetic interference (EMI)
- Less spark plug changes reduce operation costs
- Available with different thread sizes and reaches
 - M14x1.25
 - M18x1.5
 - 7/8-18 UNS



13/16-20 UNEF top thread for coil connection with full 6 threads to meet the CSA requirements




Competitor top threads with only 4 threads do not meet the CSA requirements

■ Spark Plugs & Accessories



Key Design Features

- 1 Additional silicone isolation on aluminum oxide ceramic insulator offers best flashover protection
- 2 Integrated stress resistant monolithic resistor suppresses electromagnetic interference (EMI)
- 3 13/16-20 UNEF top thread for coil connection with full 6 threads to meet the CSA requirements
- 4 Rigid welds
- 5 J-type electrode design and use of higher erosion resistance materials ensure better combustion particularly on lean burn gas engines and longest service life
- 6 Copper cored center electrode with laser welded IRIDIUM alloy disc
- 7 Copper cored ground electrode with laser welded IRIDIUM alloy disc



Dual Threaded Spark Plugs for use with Integral Ignition Coils

P/N ¹⁾	Description	Thread Size	Thread Reach	Electrode Design	HEX	Thread Size Ignition Coil	Equivalent to
ICPB412	ICP spark plug	M14x1.25	0.500 in (12.7 mm)	J-type (Ir/Ir)	15/16 in (23.8 mm)	13/16-20 UNEF	RTL85G, 9Y-3985
ICPB432	ICP spark plug	M14x1.25	0.750 in (19.0 mm)	J-type (Ir/Ir)	15/16 in (23.8 mm)	13/16-20 UNEF	RTN79G, 4W-2256
ICPB812	ICP spark plug	M18x1.5	0.500 in (12.7 mm)	J-type (Ir/Ir)	15/16 in (23.8 mm)	13/16-20 UNEF	RTM77N, RTM77PP, 60999G
ICPB832	ICP spark plug	M18x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)	15/16 in (23.8 mm)	13/16-20 UNEF	RTB77WPCC

¹⁾ MOTORTECH ICP-Plugs only available in packs of 4 pcs.

■ Spark Plugs & Accessories

MOTORTECH Extended Barrel Spark Plugs

For certain applications extended barrel spark plugs are required. For example when the operator cannot get a conventional spark plug down the narrow spark plug well, he will need a special product that allows him to torque the plug from the top end. MOTORTECH offers an improved product to the market. Several of the known problems of products made by competitors are eliminated.

Besides an increase in reliability the spark plug run time needed to be extended. To achieve this, MOTORTECH uses base spark plugs with Iridium alloy (J-type) on center and ground electrode. MOTORTECH extended barrel spark plugs can be ordered in different lengths, terminal styles or with an integrated ignition cable.

Features

- No more trapped air in the extension barrel
- No more condensation
- No internal flash over
- Built in ceramics
- High dielectric strength
- Rigid welds



*The **J-type** ground electrode ensures better combustion, particularly on lean burn gas engines.*

XT-Plugs 
MOTORTECH EXTENDED BARREL SPARK PLUGS

MOTORTECH XT-Plugs are available with three different terminal styles to be connected directly to a spark plug lead or a short integral ignition coil.

The “**S2-Type**” has a 3/4 inch male thread and used to be called the AIRCRAFT STYLE spark plug. This spark plug is designed to be connected to a shielded spark plug lead.



The “**DCP-Type**” has a female thread to adapt to a short integral ignition coil. This combination is popular in applications, where customers have had bad experiences with shielded spark plug leads.




The “**C-Type**” is an extended barrel plug that has a conventional ceramic insulator on the top end. This allows the use of a standard spark plug lead. Preferable the connector includes a 5 kΩ resistor to suppress electromagnetic interference (EMI).



Spark Plugs & Accessories



Specification Table



P/N A B C D E - F

A	Spark Plug Style
C	C-Type – for use with spark plug leads
DCP	DCP-Type – for use with integral ignition coils
S2	S2-Type – for use with shielded spark plug leads or unshielded safety leads

B	C	D	Thread Size	Thread Reach	Electrode Design
B4	1	2	M14x1.25	0.500 in (12.7 mm)	J-type (Ir/Ir)
B4	3	2	M14x1.25	0.750 in (19.0 mm)	J-type (Ir/Ir)
B8	1	2	M18x1.5	0.500 in (12.7 mm)	J-type (Ir/Ir)
B8	3	2	M18x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)
B8	5	2	M18x1.5	1.000 in (25.4 mm)	J-type (Ir/Ir)
B2	2	2	M22x1.5	0.600 in (15.0 mm)	J-type (Ir/Ir)
B2	3	2	M22x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)
B2	4	2	M22x1.5	0.875 in (22.2 mm)	J-type (Ir/Ir)
B7	2	2	7/8-18 UNS	0.600 in (15.0 mm)	J-type (Ir/Ir)
B7	3	2	7/8-18 UNS	0.750 in (19.0 mm)	J-type (Ir/Ir)
B7	4	2	7/8-18 UNS	0.875 in (22.2 mm)	J-type (Ir/Ir)

E	Extended Barrel Length – Other lengths available on request
BEX6	6 in
BEX8	8 in
BEX10	10 in
BEX12	12 in
BEX16	16 in

F	Electrode Gap
010	0.010 in (0.25 mm)
012	0.012 in (0.30 mm)
014	0.014 in (0.35 mm)

optional

Recommended Tightening Torque ¹⁾		
Thread Size	Tightening Torque (Cast Iron Head)	
M14x1.25	30 to 40 Nm	22 to 29 lb-ft
M18x1.5	50 to 60 Nm	37 to 44 lb-ft
M22x1.5	70 to 80 Nm	52 to 59 lb-ft
7/8-18 UNS	70 to 80 Nm	52 to 59 lb-ft

¹⁾ Please observe the tightening torques rendered by each engine manufacturer.

Conversion 1 inch = 25,4 mm / 1 foot = 0,3 m

■ Spark Plugs & Accessories


UNSHIELDED

XTL-Plugs

MOTORTECH EXTENDED BARREL SPARK PLUGS

Based on the concept of the extended barrel spark plugs, MOTORTECH offers another style of spark plugs. MOTORTECH XTL-Plugs are manufactured with an integrated 7 mm ignition cable, which allows a direct connection to an externally mounted ignition coil.

MOTORTECH XTL-Plugs can be ordered with different barrel and cable lengths and a wide range of ignition coil connectors. This guarantees a custom-made spark plug which definitely fits your application.



Available Connectors to Ignition Coil



5A = ALTRONIC® style; 5B = BENDIX® style; 5C = MOTORTECH style

Specification Table – for unshielded Applications

A	B	C	Thread Size	Thread Reach	Electrode Design
B4	1	2	M14x1.25	0.500 in (12.7 mm)	J-type (Ir/Ir)
B4	3	2	M14x1.25	0.750 in (19.0 mm)	J-type (Ir/Ir)
B8	1	2	M18x1.5	0.500 in (12.7 mm)	J-type (Ir/Ir)
B8	3	2	M18x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)
B8	5	2	M18x1.5	1.000 in (25.4 mm)	J-type (Ir/Ir)
B2	2	2	M22x1.5	0.600 in (15.0 mm)	J-type (Ir/Ir)
B2	3	2	M22x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)
B2	4	2	M22x1.5	0.875 in (22.2 mm)	J-type (Ir/Ir)
B7	2	2	7/8-18 UNS	0.600 in (15.0 mm)	J-type (Ir/Ir)
B7	3	2	7/8-18 UNS	0.750 in (19.0 mm)	J-type (Ir/Ir)
B7	4	2	7/8-18 UNS	0.875 in (22.2 mm)	J-type (Ir/Ir)

D	Extended Barrel Length – Other lengths available on request
BEX6	6 in
BEX8	8 in
BEX10	10 in
BEX12	12 in
BEX16	16 in

E	Cable Output from Extended Barrel
B	180°

F	Cable Length – Other lengths available on request
8	8 in
10	10 in
12	12 in
14	14 in
16	16 in
18	18 in

G	Ignition Coil Connector
1	Non CSA ALTRONIC® Style – male, 180°
1A	Non CSA ALTRONIC® Style – female, 180°, with spreading adaptor
2	Non CSA MOTORTECH Style – M6, 90°
3	Non CSA ALTRONIC® Style – male, 180°
4	Non CSA ALTRONIC® Style – female, 90°
5A	CSA ALTRONIC® Style – Externally Mounted – 3/4-20 UNEF
5B	CSA BENDIX® Style – Externally Mounted – 3/4-20 UNEF
5C	CSA MOTORTECH Style – Externally Mounted – 1-20 UNEF
6	Non CSA ALTRONIC® Style – male, 90°
7	Non CSA New MOTORTECH Style – M6, 180°
8	Non CSA ALTRONIC® Style – female, 90°
9	Non CSA FAIRBANKS MORSE®-Style – male – no boot

P/N A B C D E F G H

H	Electrode Gap
010	0.010 in (0.25 mm)
012	0.012 in (0.30 mm)
014	0.014 in (0.35 mm)

Recommended Tightening Torque ¹⁾		
Thread Size	Tightening Torque (Cast Iron Head)	
M14x1.25	30 to 40 Nm	22 to 29 lb-ft
M18x1.5	50 to 60 Nm	37 to 44 lb-ft
M22x1.5	70 to 80 Nm	52 to 59 lb-ft
7/8-18 UNS	70 to 80 Nm	52 to 59 lb-ft

¹⁾ Please observe the tightening torques rendered by each engine manufacturer.

optional

Conversion 1 inch = 25,4 mm / 1 foot = 0,3 m


■ Spark Plugs & Accessories

SHIELDED

XTL-Plugs MOTORTECH EXTENDED BARREL SPARK PLUGS

MOTORTECH XTL-Plugs are also available for shielded applications. To meet CSA requirements, this type of spark plug is fitted with an integrated and specially designed ignition cable. This is also known from MOTORTECH's MOT-Blues shielded spark plug leads. The multilayer design ensures that no humidity can be trapped in the ignition cable.

MOTORTECH XTL-Plugs can be ordered with different barrel and cable lengths and suitable ignition coil connectors, to allow direct connection to a shielded ignition coil. This guarantees a custom-made spark plug which definitely fits your application.



The specially designed ignition cable consists of a multilayer design:

- Nickel plated copper core
- 2 layers of silicone
- Stainless steel braid
- Silicone jacket

Spark Plugs & Accessories



Specification Table – for shielded Applications

P/N		A	B	C	D	E	F	G	H	I
A		Spark Plug Style								
I		Shielded Application								
B	C	D	Thread Size	Thread Reach	Electrode Design					
B4	1	2	M14x1.25	0.500 in (12.7 mm)	J-type (Ir/Ir)					
B4	3	2	M14x1.25	0.750 in (19.0 mm)	J-type (Ir/Ir)					
B8	1	2	M18x1.5	0.500 in (12.7 mm)	J-type (Ir/Ir)					
B8	3	2	M18x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)					
B8	5	2	M18x1.5	1.000 in (25.4 mm)	J-type (Ir/Ir)					
B2	2	2	M22x1.5	0.600 in (15.0 mm)	J-type (Ir/Ir)					
B2	3	2	M22x1.5	0.750 in (19.0 mm)	J-type (Ir/Ir)					
B2	4	2	M22x1.5	0.875 in (22.2 mm)	J-type (Ir/Ir)					
B7	2	2	7/8-18 UNS	0.600 in (15.0 mm)	J-type (Ir/Ir)					
B7	3	2	7/8-18 UNS	0.750 in (19.0 mm)	J-type (Ir/Ir)					
B7	4	2	7/8-18 UNS	0.875 in (22.2 mm)	J-type (Ir/Ir)					
E		Extended Barrel Length – Other lengths available on request								
BEX6		6 in								
BEX8		8 in								
BEX10		10 in								
BEX12		12 in								
BEX16		16 in								
F		Cable Output from Extended Barrel								
B		180°								
G		Cable Length – Other lengths available on request								
8		8 in								
10		10 in								
12		12 in								
14		14 in								
16		16 in								
18		18 in								
H		Ignition Coil Connector								
5A		CSA	ALTRONIC® Style – Externally Mounted – 3/4-20 UNEF							
5B		CSA	BENDIX® Style – Externally Mounted – 3/4-20 UNEF							
5C		CSA	MOTORTECH Style – Externally Mounted – 1-20 UNEF							
I		Electrode Gap								
010		0.010 in (0.25 mm)								
012		0.012 in (0.30 mm)								
014		0.014 in (0.35 mm)								

Recommended Tightening Torque ¹⁾		
Thread Size	Tightening Torque (Cast Iron Head)	
M14x1.25	30 to 40 Nm	22 to 29 lb-ft
M18x1.5	50 to 60 Nm	37 to 44 lb-ft
M22x1.5	70 to 80 Nm	52 to 59 lb-ft
7/8-18 UNS	70 to 80 Nm	52 to 59 lb-ft

¹⁾ Please observe the tightening torques rendered by each engine manufacturer.

optional

■ Spark Plugs & Accessories

Spark Plug Tools

Spark Plug Cleaning Kit

Regular maintenance is required to achieve the maximum service life in particular with high price spark plugs with precious metal alloys.

Apart from readjusting the electrode gap, the spark plug should also be freed from deposits and residues that have formed during operation. By using the MOTORTECH spark plug cleaning kit these impurities can be removed easily and gently in the electrode area and on the thread within a regular maintenance interval.

This will increase spark plug service life and cut maintenance costs.

Features

- Professional cleaning of spark plugs without pre-chamber
- Different nozzle sizes matching M14, M18, M22, and 7/8-18 spark plugs
- Oil residues and deposits in the electrode area are removed without residues by high pressure
- Special blasting grit for gentle cleaning of the electrode and thread area
- Blasting grit is captured and can be reused
- No dust development



Scope of Delivery

The spark plug cleaning kit is supplied with the following parts:

- Spark plug cleaning device with compressed air quick release coupling, blasting grit container and dust collector bag
- Cleaning nozzles for M14, M18, M22 and 7/8-18 spark plugs
- Blasting grit, 1 kg, in separate container
- Operating manual
- Hard shell carrying case with foam insert



P/N	Supersedes	Description
44.01.023	44.01.000	Spark plug cleaning kit

Subcomponents

P/N	Supersedes	Description
44.01.009		Blasting grit, 1 kg
44.01.024	44.01.005	Cleaning nozzles, kit for M14, M18 and 7/8-18 UNS spark plugs
44.01.025	44.01.006	Dust collector bag for spark plug cleaning device

■ Spark Plugs & Accessories



MOTORTECH Spark Plug Gap Setting Tool

The gap between the center and ground electrodes is of fundamental importance for clean combustion as well as the optimal functioning of any spark plug. During the operation of a gas engine, however, the gap between the electrodes can increase, e.g. because of spark erosion, which can lead to increased voltage requirements or even misfiring.

The electrode gap should be re-adjusted at regular maintenance intervals in order to maximize the service life of spark plugs, especially for high-priced industrial spark plugs.

MOTORTECH's innovative spark plug gap setting tool provides every gas engine operator or employee of a service company with a smart tool to professionally adjust the electrode gap on-site in a material-conserving manner.

Features

- Simple-to-use tool for setting the electrode gap on different spark plug types
- The quick-release lock of the thread adaptor ensures that spark plugs can be changed quickly
- The tool is hand-operated and does not need to be additionally mounted on a workbench
- The spark plug gap setting tool can be custom-configured with optionally available accessory components
- The tool and all accessories can be stowed in the included carrying case
- Transportable, which makes it ideal for service companies

Functional Description (Example J-Type Spark Plug)



- 1** The tool is first fitted with the base insert that fits the corresponding spark plug.



- 2** Thread adaptors are available in various sizes for the spark plugs that need to be set (M14, M18, 7/8-18 or M22). The adaptors can be mounted or exchanged easily with the included screws and the hex key.



- 3** The integrated quick-release lock guarantees rapid changes and secure holding of the spark plugs while they are being set.



- 4** Light pressure on the lever is enough to set the electrode gap to the desired distance with the help of a feeler gauge.



■ Spark Plugs & Accessories

Basic Kits ¹⁾

P/N	Figure	Supersedes	Description
07.98.120-14	1	07.98.113	Spark plug gap setting tool, basic kit including thread adaptor for spark plugs with M14x1.25 thread
07.98.120-18	1	07.98.113	Spark plug gap setting tool, basic kit including thread adaptor for spark plugs with M18x1.5 thread
07.98.120-78	1	07.98.113	Spark plug gap setting tool, basic kit including thread adaptor for spark plugs with M22x1.5 and 7/8-18 UNS thread

¹⁾ Needs appropriate accessory kit in addition.

Thread Adaptors ¹⁾

P/N	Figure	Supersedes	Description
07.98.121-14	2		Thread adaptor for spark plugs with M14x1.25 thread
07.98.121-18	2		Thread adaptor for spark plugs with M18x1.5 thread
07.98.121-78	2		Thread adaptor for spark plugs with M22x1.5 and 7/8-18 UNS thread

¹⁾ Can be ordered separately in addition to chosen basic kit.

Accessory Kits ¹⁾

P/N	Figure	Supersedes	Description
07.98.122-A	3		Accessory kit for J-type spark plugs
07.98.122-B	3		Accessory kit for CHAMPION® N-type spark plugs
07.98.122-C	3		Accessory kit for BERU® spark plugs 18GZ44 (Z283), Super Blue Ignition (Z351)
07.98.122-D	3		Accessory kit for BERU® spark plug 18GZ46 (Z377)
07.98.122-E	3		Accessory kit for BERU® spark plug 18GZ47
07.98.122-F	3		Accessory kit for bridge spark plugs MBP1800, CHAMPION® FB78WW, ROLLS ROYCE® 710875

¹⁾ Need to be ordered separately in addition to chosen basic kit.

Feeler Gauges

P/N	Figure	Supersedes	Description	Size
07.98.131	4		Feeler gauge, 8 blades	0.002 to 0.020 in (0.05 to 0.50 mm)
07.98.037	5		Feeler gauge clamp tool	
07.98.059	6		Feeler gauge shim roll, 12.7 mm x 5.0 m	0.008 in (0.20 mm)
07.98.034	6		Feeler gauge shim roll, 12.7 mm x 5.0 m	0.010 in (0.25 mm)
07.98.035	6		Feeler gauge shim roll, 12.7 mm x 5.0 m	0.012 in (0.30 mm)
07.98.036	6		Feeler gauge shim roll, 12.7 mm x 5.0 m	0.014 in (0.35 mm)



[1](#)



[2](#)




[3](#)



[4](#)



[5](#)



[6](#)

■ Spark Plugs & Accessories





MOTORTECH Extended Barrel Magnetic Spark Plug Sockets

When it comes to service of a gas engine, the exchange of a spark plug is one of the easier tasks. However there are a few things you need to consider. Especially with modern high-end spark plugs it is essential to carry out a service with a tool for professionals and to avoid damage when the spark plug is screwed in or out.


MOTORTECH offers a complete range of extended barrel magnetic spark plug sockets in various lengths for all types of HEX. Integrated strong magnets hold the spark plug securely in any position, which guarantees an easy assembly and disassembly work especially on large engines with deep spark plug wells.

Features

- Strong magnets for firm connection of the spark plug
- Use of magnets ensures largest possible clearance spark plug ceramic insulator
- Equipped with a cross knurl, the sockets are extremely handy and non-slip
- Different lengths for use with various engine applications
- 1/2 inch drive



1/2 inch drive and cross knurled surface



Standard lengths 6, 12, 16, 18 and 20 inch



Integrated magnets

Spark Plug Gap Setting Tool | Extended Barrel Magnetic Spark Plug Sockets

Extended Barrel Magnetic Spark Plug Sockets – Standard Versions

P/N ¹⁾	Description	HEX	Outer Dimensions max.	Drive	Typical used Spark Plugs
07.99.022-5-L	Magnetic spark plug socket	5/8 in (16.0 mm)	0.83 in (21.0 mm)	1/2 in	14FR-4DIU, B4321, GK3-1, GK3-5, RC78PYP
07.99.022-4-L	Magnetic spark plug socket	13/16 in (20.8 mm)	1.12 in (28.5 mm)	1/2 in	14R-4DIU, 18GZ5-77-2, B8124, B8324, GE3-1, GE3-5, GL3-3, GL3-5, RB75WPCC, RN79G
07.99.022-3-L	Magnetic spark plug socket	7/8 in (22.2 mm)	1.22 in (31.0 mm)	1/2 in	18GZ6-77-2, FB77WPCC, GI3-1, GI3-3, GI3-5, RHL79G, RM77N, RTB77WPCC, RTM77N
07.99.022-2-L	Magnetic spark plug socket	15/16 in (23.8 mm)	1.24 in (31.5 mm)	1/2 in	7/8GZ9, 7/8GZ11, ICPB432, ICPB812, ICPB832, RTL85G, RTN79G, RW80PP, W80N
07.99.022-1-L	Magnetic spark plug socket	1 in (25.4 mm)	1.39 in (34.0 mm)	1/2 in	18GZ34, K97F, W77N

¹⁾ Standard barrel lengths (-L) = 6 in, 12 in, 16 in, 18 in. Other lengths available on request

■ Spark Plugs & Accessories

Extended Barrel Magnetic Spark Plug Sockets – Special Versions

P/N	Supersedes	Description	HEX	Drive
07.99.022-3-36		Magnetic spark plug socket – NORDBERG®	7/8 in (22.2 mm)	1/2 in
07.99.022-6-6		Magnetic spark plug socket – MAN® E0836LE/E28 series	13/16 in (20.8 mm)	1/2 in
07.99.022-6-10		Magnetic spark plug socket – MAN® E32 series	13/16 in (20.8 mm)	1/2 in

Spark Plug Socket for MOTORTECH XTL-Plugs (unshielded Applications)

P/N	Supersedes	Description	HEX	Drive
07.99.022-6-2		Spark plug socket	7/8 in (22.2 mm)	1/2 in

Torque Wrench

P/N	Supersedes	Description	Torque	Drive
07.98.065	07.98.063	Torque wrench	7.4 to 74 lb-ft (10 to 100 Nm)	1/2 in

Seat & Thread Reconditioners

Use seat & thread reconditioner to clean cylinder head threads and seal seats in one operation.

P/N	Supersedes	Description	Thread Size	Thread Reach
07.98.114-12	07.98.022	Seat & thread reconditioner	M14x1.25	1/2 in
07.98.114-34	07.98.023	Seat & thread reconditioner	M14x1.25	3/4 in
07.98.118-12	07.98.024	Seat & thread reconditioner	M18x1.5	1/2 in
07.98.118-34	07.98.025	Seat & thread reconditioner	M18x1.5	3/4 in
07.98.178-58	07.98.026	Seat & thread reconditioner	7/8-18 UNS	5/8 in
07.98.178-78	07.98.026-1	Seat & thread reconditioner	7/8-18 UNS	7/8 in

Extended Barrel Seat & Thread Reconditioners – 1/2 Inch Drive

P/N	Supersedes	Description	Thread Size	Thread Reach
07.98.114-12-BEX6		Seat & thread reconditioner, 6 in length	M14x1.25	1/2 in
07.98.114-12-BEX12		Seat & thread reconditioner, 12 in length	M14x1.25	1/2 in
07.98.114-34-BEX6		Seat & thread reconditioner, 6 in length	M14x1.25	3/4 in
07.98.114-34-BEX12		Seat & thread reconditioner, 12 in length	M14x1.25	3/4 in
07.98.118-12-BEX6		Seat & thread reconditioner, 6 in length	M18x1.5	1/2 in
07.98.118-12-BEX12		Seat & thread reconditioner, 12 in length	M18x1.5	1/2 in
07.98.118-34-BEX6		Seat & thread reconditioner, 6 in length	M18x1.5	3/4 in
07.98.118-34-BEX12		Seat & thread reconditioner, 12 in length	M18x1.5	3/4 in
07.98.178-58-BEX6		Seat & thread reconditioner, 6 in length	7/8-18 UNS	5/8 in
07.98.178-58-BEX12		Seat & thread reconditioner, 12 in length	7/8-18 UNS	5/8 in
07.98.178-78-BEX6		Seat & thread reconditioner, 6 in length	7/8-18 UNS	7/8 in
07.98.178-78-BEX12		Seat & thread reconditioner, 12 in length	7/8-18 UNS	7/8 in

■ Spark Plugs & Accessories



Thread Plug Gauges – Go/No-Go **NEW**

P/N	Supersedes	Description	Thread Size	Equivalent to
07.98.064-14		Thread plug gauge (Go/No-Go)	M14x1.25	GNG-14
07.98.064-18		Thread plug gauge (Go/No-Go)	M18x1.5	GNG-18
07.98.064-78		Thread plug gauge (Go/No-Go)	7/8-18 UNS	GNG-78

Extended Barrel Thread Plug Gauges – Go/No-Go **NEW**

P/N	Supersedes	Description	Thread Size	Equivalent to
07.98.070-14		Thread plug gauge (Go/No-Go), 15 in length	M14x1.25	
07.98.070-18		Thread plug gauge (Go/No-Go), 15 in length	M18x1.5	

Extended Barrel Thread Cutting Taps **NEW**


P/N	Supersedes	Description	Thread Size	Drive	Equivalent to
07.98.066-BEX6		Thread cutting tap, 6 in length	M14x1.25	1/2 in	
07.98.066-BEX12		Thread cutting tap, 12 in length	M14x1.25	1/2 in	
07.98.067-BEX6		Thread cutting tap, 6 in length	M18x1.5	1/2 in	
07.98.067-BEX12		Thread cutting tap, 12 in length	M18x1.5	1/2 in	

Installation & Service Kit for MOTORTECH XTL-Plugs

Spark plugs play a crucial role in an ignition system. Maintenance and, in particular, the correct handling of spark plugs is vital to ensure flawless functioning and long

service life. MOTORTECH provides an installation and service kit that is specifically designed for XTL spark plugs with integrated spark plug lead and M14 thread.

P/N	Supersedes	Description	For Spark plugs with	
			Thread Size	Thread Reach
07.98.214-34		Installation & service kit for MOTORTECH XTL-Plugs	M14x1.25	3/4 in



■ Spark Plugs & Accessories

Spark Plug Accessories

Gaskets for Spark Plugs

P/N	Description	For Thread Size	Quantity
02.85.015-100	Spark plug gasket	M14x1.25	100 pcs
02.85.016-100	Spark plug gasket	M18x1.5	100 pcs
02.85.017-100	Spark plug gasket	M22x1.5, 7/8-18 UNS	100 pcs



Spark plug gaskets just once provide an optimal seal between spark plug and seat. Spark plugs must be installed with a new gasket after every service in order to ensure the best possible seal in future operation.

Gaskets for MOTORTECH ICP-Plugs

P/N	Description	Quantity
75.90.295-100	Spark plug gasket, copper	100 pcs



Thread Lubricant

This lubricant is non-metallic and non-conductive. Guarantees easy spark plug removal and prevents thread damage. Also for use with seat & thread reconditioner.

P/N	Description	Equivalent to
07.98.718	Thread lubricant, 4 oz (115 g)	A718



■ Gas Engine Control Systems

DetCon

MOTORTECH DETONATION CONTROL SYSTEM

The gas engine operators are calling for increased power output from their engines. More load means higher temperatures, pressures and tougher operation. This mostly ends in catastrophic engine damages due to detonation or pre-ignition.

As MOTORTECH has proven for years, detonation can be detected professionally with the DetCon2 or DetCon20. Single cylinder sensors constantly monitor the sound level of the combustion chamber. If detonation is detected the system will take steps to eliminate detonation immediately.

Upgrade your engines and increase availability of the equipment!



Detonation Sensor

Can be installed on cylinder head screw or stud.
Measures the detonation signal and transfers it to the controller.



DetCon Software

DetCon comes with a WINDOWS® based software package that allows the operator to analyze all data in real time on his PC.




Function

Once the controller detects soft detonation on one of the sensors (this is a specific stage before real detonation occurs), several steps will take place:

- Alarm signal turns on
- Ignition retard by 0 to 5 V or 4 to 20 mA analog output.
- If this action does not cure the detonation, the load reduction output will be activated.
- If the load drop does not stop the engine from detonating the engine STOP output will be activated.



... THIS FROM HAPPENING



Gas Engine Control Systems



1 DetCon20 Control Units

P/N	Description
43.00.020 ¹⁾	DetCon20 control unit, 20 inputs, CSA, IP20
43.00.120	DetCon20 control unit, 20 inputs, built into an CSA enclosure, includes ISU ignition sensor unit P/N 43.20.002
43.00.220 ²⁾	DetCon20 control unit, 20 inputs, built into an CSA enclosure

¹⁾ The control unit has to be installed in (CSA approved) control panel or enclosure.

²⁾ For use with MIC3/3+, MIC4, MIC5, MIC6 and MIC850 series ignition controllers. Ignition sensor unit is not required.



DetCon20 Detonation Control Kits

P/N ¹⁾	Description
43.00.020-04	DetCon20 detonation control kit, incl. DetCon20 control unit, detonation sensor lead P/N 43.30.004-60 (4 pcs), detonation sensor P/N 43.20.001 (4 pcs)
43.00.020-06	DetCon20 detonation control kit, incl. DetCon20 control unit, detonation sensor lead P/N 43.30.004-60 (6 pcs), detonation sensor P/N 43.20.001 (6 pcs)
43.00.020-08	DetCon20 detonation control kit, incl. DetCon20 control unit, detonation sensor lead P/N 43.30.004-60 (8 pcs), detonation sensor P/N 43.20.001 (8 pcs)
43.00.020-12	DetCon20 detonation control kit, incl. DetCon20 control unit, detonation sensor lead P/N 43.30.004-60 (12 pcs), detonation sensor P/N 43.20.001 (12 pcs)
43.00.020-16	DetCon20 detonation control kit, incl. DetCon20 control unit, detonation sensor lead P/N 43.30.004-60 (16 pcs), detonation sensor P/N 43.20.001 (16 pcs)
43.00.020-20	DetCon20 detonation control kit, incl. DetCon20 control unit, detonation sensor lead P/N 43.30.004-60 (20 pcs), detonation sensor P/N 43.20.001 (20 pcs)

¹⁾ If required, ISU ignition sensor unit needs to be ordered separately.



2 DetCon2 Control Units

P/N	Description
43.00.002 ¹⁾	DetCon2 control unit, 2 inputs, CSA, IP20
43.00.102	DetCon2 control unit, 2 inputs, built into an CSA enclosure, includes ISU ignition sensor unit P/N 43.20.002
43.00.202 ²⁾	DetCon2 control unit, 2 inputs, built into an CSA enclosure

¹⁾ The control unit has to be installed in (CSA approved) control panel or enclosure.

²⁾ For use with MIC3/3+, MIC4, MIC5, MIC6 and MIC850 series ignition controllers. Ignition sensor unit is not required.



1



2

3 Detonation Sensor Lead (1 per Detonation Sensor required)

P/N	Description
43.30.004-60	Detonation sensor lead, 60 ft (18 m)

4 Detonation Sensor (1 per Cylinder required)

P/N	Description
43.20.001	Detonation sensor w/o lead, 2 pole

5 Engine Specific Cylinder Head Screws prepared for Detonation Sensor (1 per Cylinder required) ¹⁾

P/N	Description	Application
236-0484-DS	Cylinder head screw CATERPILLAR® P/N 236-0484, prepared, incl. mounting screw for detonation sensor	CATERPILLAR® G3406, G3408/C, G3412/C
51.90020-0381-DS	Cylinder head screw MAN® P/N 51.90020-0381, prepared, incl. mounting screw for detonation sensor	MAN® E08 series
51.90490-0022-DS	Cylinder head screw MAN® P/N 51.90490-0022, prepared, incl. mounting screw for detonation sensor	MAN® E28 series
51.90020-0421-DS	Cylinder head screw MAN® P/N 51.90020-0421, prepared, incl. mounting screw for detonation sensor	MAN® E26, E32 series
169994B-DS	Cylinder head screw WAUKESHA® P/N 169994B, prepared, incl. mounting screw for detonation sensor	WAUKESHA® VHP series
305948A-DS	Cylinder head screw WAUKESHA® P/N 305948A, prepared, incl. mounting screw for detonation sensor	WAUKESHA® VGF series

¹⁾ Please observe the installation instructions rendered by each engine manufacturer.



3



4



5

■ Gas Engine Control Systems

Detonation Sensor Adaptor for **MWM®/DEUTZ®** 604/620 Series Gas Engines (1 per Detonation Sensor required)

P/N	Description
43.20.018	Detonation sensor adaptor

6 ISU Ignition Sensor Unit (1 per System required) ¹⁾

P/N	Description
43.20.002	ISU ignition sensor unit

¹⁾ Not required if MIC3/3+, MIC4, MIC5, MIC6, MIC850 or DetCon20 control unit P/N 43.00.102 or 43.00.120 is used.



PowerView3 MOTORTECH ENGINE INFORMATION MONITOR

Detonation Control Visualization

The operating data of the DetCon Detonation Control system will be completely visualized via HMI module (Human Machine Interface). The overview screen shows the relevant information as engine knocking, knock intensity and status for activated load reduction or emergency shutdown of engine. The control keys guarantee simple navigation through the different display pages and menus. All in all the PowerView3 HMI module is also able to provide error diagnostics on-site without requiring a laptop!

The PowerView3 is also available for data visualization of:

- MIC Ignition Control (MIC3/3+, MIC4 and MIC5 series)
- TempScan20 Temperature Module




1

Sample Screens




Overview

Screen shows the most important operating data of the connected DetCon control unit.



Knocking Intensity

Visualization of knocking intensity of each monitored cylinder. Different colors inform about the system status (Normal – Reduction – Critical).



Trending Knocking Intensity

Visualization of knocking intensity trend data for each individual cylinder.

PowerView3 HMI Modules & Activation Codes

P/N	Figure	Description
06.05.085	1	PowerView3 HMI module
06.05.185	2	PowerView3 HMI module, built into stainless steel enclosure
06.05.187	3	PowerView3 HMI module, built into steel enclosure with sight window
06.05.087-F		PowerView3 activation code for visualization of DetCon data – Activation code has to be ordered separately with each PowerView3 HMI module
06.05.087-U		PowerView3 activation code for visualization of DetCon data – Only available for upgrade of existing PowerView3 HMI module in the field





■ Gas Engine Control Systems



Wiring Rail System for Detonation Control

MOTORTECH stainless steel, vibration resistant rail assembly will withstand any harsh environment commonly found in the oil & gas industry. The proven design is made for engine manufacturers and the global aftermarket. Do not go low-tech and take the risk of engine down time because of equipment being under repair. Eliminate the need for constant rewiring, connector exchanges or straightening out weak and bent aluminum wiring rails.

- Made of stainless steel which performs better than aluminum in harsh environments (and where operators use any kind of equipment to hold or stand on)
- Made to perfectly fit the application
- Rigid military style connectors are securely fastened into the stainless steel rail
- Rails are filled with special foam to ensure that all wires are separated from ground and will not vibrate and eventually short out to ground
- Water proof design – built to last in uncovered environment
- Repairable by MOTORTECH's assigned distributors in the event of mechanically damage



1 AlphaRail for Detonation Control – Specification Table

		P/N 77.8					
		A	B	C	D	E	F
A	Sensor System						
1	Detonation control						
B	Number of Detonation Sensors per Bank						
1	Special version						
2	2 detonation sensors						
3	3 detonation sensors						
4	4 detonation sensors						
5	5 detonation sensors						
6	6 detonation sensors						
8	8 detonation sensors						
CD	Distance between the Detonation Sensors						
04	4 in						
06	6 in						
07	7 in						
08	8 in						
10	10 in						
11	11 in						
12	12 in						
13	13 in						
14	14 in						
16	16 in						
27	27 in						
33	33 in						
E	Output Design						
D	MIL, 3 pole, pin						
F	Double Rail ¹⁾ – Length of Flex Conduit						
A	NO Double Rail						
B	12 in						
C	16 in						
D	20 in						
E	24 in						
F	32 in						
G	40 in						
H	52 in						

¹⁾ Two wiring rails connected by flex conduit.

Gas Engine Control Systems

1 AlphaRail for Detonation Control – Wiring Rails for common Applications ¹⁾

P/N	Description	Engine Make	Model	Required Quantity per Engine	Equivalent to
77.81.406-DA	AlphaRail wiring rail	CATERPILLAR®	G3304	1	
77.81.606-DA	AlphaRail wiring rail	CATERPILLAR®	G3306	1	
77.81.607-DA	AlphaRail wiring rail	CATERPILLAR®	G3406	1	
77.81.407-DA	AlphaRail wiring rail	CATERPILLAR®	G3408	2	
77.81.607-DA	AlphaRail wiring rail	CATERPILLAR®	G3412	2	
77.81.411-DA	AlphaRail wiring rail	CATERPILLAR®	G3508	2	
77.81.611-DA	AlphaRail wiring rail	CATERPILLAR®	G3512	2	
77.81.811-DA	AlphaRail wiring rail	CATERPILLAR®	G3516	2	
77.81.631-DG	AlphaRail wiring rail	CLARK®	HBA-6T	1	
77.81.531-DA	AlphaRail wiring rail	CLARK®	HBA-10T	2	
77.81.637-DA	AlphaRail wiring rail	CLARK®	TCVD-12	2	
77.81.631-DG	AlphaRail wiring rail	CLARK®	TLA-6T	1	
77.81.544-DG	AlphaRail wiring rail	COOPER®	GMVH-10	2	
77.81.541-DG	AlphaRail wiring rail	COOPER®	GMW-10	2	
77.81.340-DA	AlphaRail wiring rail	COOPER®	GMWC-6	2	
77.81.822-DG	AlphaRail wiring rail	COOPER®	LSV-16	2	
77.81.633-DF	AlphaRail wiring rail	INGERSOLL RAND®	KVR-412	2	
77.81.344-DA	AlphaRail wiring rail	INGERSOLL RAND®	KVS-6	2	
77.81.427-DD	AlphaRail wiring rail	INGERSOLL RAND®	PKVG-8	2	
77.81.627-DD	AlphaRail wiring rail	INGERSOLL RAND®	PKVG-12	2	
77.81.627-DF	AlphaRail wiring rail	INGERSOLL RAND®	PKVGR-12	2	
77.81.437-DA	AlphaRail wiring rail	INGERSOLL RAND®	XVG-8	2	
77.81.606-DA	AlphaRail wiring rail	WAUKESHA®	F817	1	
77.81.614-DA	AlphaRail wiring rail	WAUKESHA®	F1197GL/GU	1	
77.81.608-DA	AlphaRail wiring rail	WAUKESHA®	VG F18	1	
77.81.808-DA	AlphaRail wiring rail	WAUKESHA®	VG F H24	1	
77.81.609-DA	AlphaRail wiring rail	WAUKESHA®	VG F L36	2	
77.81.809-DA	AlphaRail wiring rail	WAUKESHA®	VG F P48	2	
77.81.614-DA	AlphaRail wiring rail	WAUKESHA®	VHP F2895GL/GSI	1	
77.81.614-DA	AlphaRail wiring rail	WAUKESHA®	VHP F3521GSI	1	
77.81.614-DA	AlphaRail wiring rail	WAUKESHA®	VHP L5790GSI	2	
77.81.614-DA	AlphaRail wiring rail	WAUKESHA®	VHP L7042G/GL/GU/GSI	2	
77.81.614-DA	AlphaRail wiring rail	WAUKESHA®	VHP L7044GL/GSI	2	
77.81.814-DF	AlphaRail wiring rail	WAUKESHA®	VHP P9390GL/GSI	2	
77.81.815-DA	AlphaRail wiring rail	WAUKESHA®	8L-AT27GL	1	
77.81.618-DA	AlphaRail wiring rail	WAUKESHA®	12V-AT27GL	2	
77.81.818-DA	AlphaRail wiring rail	WAUKESHA®	16V-AT27GL	2	
77.81.814-DA	AlphaRail wiring rail	WHITE SUPERIOR®	2408G	1	
77.81.613-DA	AlphaRail wiring rail	WHITE SUPERIOR®	6G/GT/GTL825	1	
77.81.813-DA	AlphaRail wiring rail	WHITE SUPERIOR®	8G/GTL825	1	
77.81.616-DA	AlphaRail wiring rail	WHITE SUPERIOR®	12GTLA825	2	
77.81.616-DA	AlphaRail wiring rail	WHITE SUPERIOR®	12SGT	2	
77.81.816-DA	AlphaRail wiring rail	WHITE SUPERIOR®	16GT/GTLB825	2	
77.81.816-DA	AlphaRail wiring rail	WHITE SUPERIOR®	16SGT	2	
77.81.531-DA	AlphaRail wiring rail	WORTHINGTON®	UTC-10	2	

¹⁾ **NOTE:** Applications may vary due to different variants or attachments, which could affect the installation of mentioned wiring rails. Consult factory for details and final confirmation.

2 Bracket Configuration

P/N ¹⁾	Figure	Description
75.10.303	2A	Bracket, 40x40 mm (Standard)
75.10.097	2B	Flat bar, 180° (Standard)
75.10.120	2C	Flat bar, 150°
75.10.280	2D	Flat bar, 90°

¹⁾ For packs of ten please add suffix "-10" to part number (e.g. 75.10.303-10).

3 Leads to connect Wiring Rail and Detonation Sensor (1 per Sensor required)

P/N	Figure	Description	Sensor Connector	Wiring Rail Connector	Length ¹⁾
43.30.016-L	3	Detonation sensor lead	2 pole, socket, 180°	MIL, 3 pole, socket, 180°	L=10/20/25/30/40/60in

¹⁾ Other lengths available on request.

4 Detonation Sensor (1 per Cylinder required)

P/N	Figure	Description
43.20.001	4	Detonation sensor w/o lead, 2 pole

5 Harnesses to connect Wiring Rail and DetCon Control Unit (1 per Rail required)

P/N	Figure	Description	Wiring Rail Connector	Length
77.41.117-L	5A	Harness	MIL, 17 pole, socket, 180°	L= 5/15/25/50 ft
77.41.317-L	5B	Harness	MIL, 17 pole, socket, 90°	L= 5/15/25/50 ft

6 Accessories

P/N	Figure	Description
15.07.134	6A	Flex conduit, 3/4 in, black ¹⁾
15.07.231	6B	Fitting, 3/4 in, junction box to flex conduit
06.05.075	6C	Junction box

¹⁾ Flex conduit needs to be ordered in m/ft in required length.



2A



2B



2C



2D



3



4



5A



5B



6A



6B



6C

Gas Engine Control Systems


TempScan20

MOTORTECH TEMPERATURE MODULE

Temperature Module with 20 Channels

The TempScan20 temperature module monitors up to 20 thermocouples and provides the temperature information to the PowerView3 HMI module via CANopen.

- Channels are independently configurable as Type J, K, B, E, N, R, S or T thermocouples
- Temperature information can include
 - ▶ Exhaust temperature
 - ▶ Winding temperature
 - ▶ Fluid temperature
- No additional programming or configuration required
- Integral diagnostics determine thermocouple integrity
- All channels are fully isolated from the CAN line and from the power supply
- The temperature module features rugged packaging and watertight connectors for an IP65 rating



TempScan20 Temperature Module

P/N	Figure	Description
63.03.002-20	1	TempScan20 temperature module, including connector package for power supply, CAN Bus and thermocouple wiring, operating manual
63.03.012-20	2	TempScan20 temperature module, built into stainless steel enclosure, including connector package for power supply, CAN Bus and thermocouple wiring, operating manual



PowerView3 MOTORTECH ENGINE INFORMATION MONITOR

Temperature Module Visualization

The operating data of the TempScan20 temperature module will be completely visualized via HMI module (Human Machine Interface). The overview screen shows the relevant information as combustion chamber temperature individually by cylinder or status of programmed temperature thresholds (Low – Normal – High – Switching Digital Output).

The control keys guarantee simple navigation through different display pages and menus. All in all the PowerView3 HMI module is also able to provide error diagnostics on-site without requiring a laptop!





1

The PowerView3 is also available for data visualization of:

- MIC Ignition Control (MIC3/3+, MIC4 and MIC5 series)
- DetCon Detonation Control

Sample Screens



Overview

Screen shows the currently measured temperatures individually for each programmed channel/cylinder. Different colored gauges inform about programmed temperature thresholds (Low – Normal – High – Switching Digital Output).

Channel Settings

Channels can be configured individually and include options like user defined channel names, thermocouple type and temperature thresholds.

Trending Cylinder Temperatures

Visualization of temperature trend data for each individual cylinder.

PowerView3 HMI Modules & Activation Codes



P/N	Figure	Description
06.05.085	1	PowerView3 HMI module
06.05.185	2	PowerView3 HMI module, built into stainless steel enclosure
06.05.187	3	PowerView3 HMI module, built into steel enclosure with sight window
06.05.088-F		PowerView3 activation code for visualization of TempScan data – Activation code has to be ordered separately with each PowerView3 HMI module
06.05.088-U		PowerView3 activation code for visualization of TempScan data – Only available for upgrade of existing PowerView3 HMI module in the field



■ Gas Engine Control Systems



Wiring Rail System for Temperature Control

The stainless steel wiring rails which are water tight due to a well approved foaming process, offer an easy and fast installation of accessory control systems such as

- Temperature control
- Gas valve systems



With individual outlet port connectors, the sensors can be individually connected and easily wired to the rail. A disconnectable main harness routes all sensors to one main control unit or individual wiring boxes.

Details on the Thermocouple Wiring Rail:

- Up to 10 thermocouple inputs per rail
- As standard each rail comes with 2 additional thermocouple inputs for temperature measurement pre and post turbocharger
- All thermocouples need to be Type K (NiCrNi)
- Made of stainless steel which performs better than aluminum in harsh environments (and where operators use any kind of equipment to hold or stand on)
- Made to perfectly fit the application
- Rigid military style connectors are securely fastened into the stainless steel
- Rails are filled with special foam to ensure that all wires are separated from ground and will not vibrate and eventually short out to ground
- Water proof design – built to last in uncovered environment
- Repairable by MOTORTECH's assigned distributors in the event of mechanical damage

General Details:

- Low voltage signals can be grouped in one rail. It is not recommended to have low and high voltage signals in one rail. In this case, detonation sensor and thermocouple leads match perfectly.
- Ignition and gas valve control wire work together well.



1 AlphaRail for Temperature Control – Specification Table

P/N 77.8		A	B	C	D	E	F
A	Sensor System						
2	Temperature control						
B	Number of Thermocouples per Bank ¹⁾						
1	Special version						
2	2 thermocouples						
3	3 thermocouples						
4	4 thermocouples						
5	5 thermocouples						
6	6 thermocouples						
8	8 thermocouples						
0	10 thermocouples						
¹⁾ As standard each rail includes 2 additional thermocouple inputs for temperature measurement pre and post turbocharger.							
CD	Distance between the Thermocouples						
04	4 in						
06	6 in						
07	7 in						
08	8 in						
10	10 in						
11	11 in						
12	12 in						
13	13 in						
14	14 in						
16	16 in						
27	27 in						
33	33 in						
E	Output Design						
H	MIL, 3 pole, socket, bayonet						
F	Double Rail ¹⁾ – Length of Connecting Flex Conduit						
A	NO Double Rail						
B	12 in						
C	16 in						
D	20 in						
E	24 in						
F	32 in						
G	40 in						
H	52 in						

¹⁾ Two wiring rails connected by flex conduit.

Gas Engine Control Systems

1 AlphaRail for Temperature Control – Wiring Rails for common Applications ¹⁾

P/N	Description	Engine Make	Model	Required Quantity per Engine	Equivalent to
77.82.406-HA	AlphaRail wiring rail	CATERPILLAR®	G3304	1	
77.82.606-HA	AlphaRail wiring rail	CATERPILLAR®	G3306	1	
77.82.607-HA	AlphaRail wiring rail	CATERPILLAR®	G3406	1	
77.82.407-HA	AlphaRail wiring rail	CATERPILLAR®	G3408	2	
77.82.607-HA	AlphaRail wiring rail	CATERPILLAR®	G3412	2	
77.82.411-HA	AlphaRail wiring rail	CATERPILLAR®	G3508	2	
77.82.611-HA	AlphaRail wiring rail	CATERPILLAR®	G3512	2	
77.82.811-HA	AlphaRail wiring rail	CATERPILLAR®	G3516	2	
77.82.631-HG	AlphaRail wiring rail	CLARK®	HBA-6T	1	
77.82.531-HA	AlphaRail wiring rail	CLARK®	HBA-10T	2	
77.82.637-HA	AlphaRail wiring rail	CLARK®	TCVD-12	2	
77.82.631-HG	AlphaRail wiring rail	CLARK®	TLA-6T	1	
77.82.544-HG	AlphaRail wiring rail	COOPER®	GMVH-10	2	
77.82.541-HG	AlphaRail wiring rail	COOPER®	GMW-10	2	
77.82.340-HA	AlphaRail wiring rail	COOPER®	GMWC-6	2	
77.82.822-HG	AlphaRail wiring rail	COOPER®	LSV-16	2	
77.82.633-HF	AlphaRail wiring rail	INGERSOLL RAND®	KVR-412	2	
77.82.344-HA	AlphaRail wiring rail	INGERSOLL RAND®	KVS-6	2	
77.82.427-HD	AlphaRail wiring rail	INGERSOLL RAND®	PKVG-8	2	
77.82.627-HD	AlphaRail wiring rail	INGERSOLL RAND®	PKVG-12	2	
77.82.627-HF	AlphaRail wiring rail	INGERSOLL RAND®	PKVGR-12	2	
77.82.437-HA	AlphaRail wiring rail	INGERSOLL RAND®	XVG-8	2	
77.82.606-HA	AlphaRail wiring rail	WAUKESHA®	F817	1	
77.82.614-HA	AlphaRail wiring rail	WAUKESHA®	F1197GL/GU	1	
77.82.608-HA	AlphaRail wiring rail	WAUKESHA®	VG F18	1	
77.82.808-HA	AlphaRail wiring rail	WAUKESHA®	VG F H24	1	
77.82.609-HA	AlphaRail wiring rail	WAUKESHA®	VG F L36	2	
77.82.809-HA	AlphaRail wiring rail	WAUKESHA®	VG F P48	2	
77.82.614-HA	AlphaRail wiring rail	WAUKESHA®	VHP F2895GL/GSI	1	
77.82.614-HA	AlphaRail wiring rail	WAUKESHA®	VHP F3521GSI	1	
77.82.614-HA	AlphaRail wiring rail	WAUKESHA®	VHP L5790GSI	2	
77.82.614-HA	AlphaRail wiring rail	WAUKESHA®	VHP L7042G/GL/GU/GSI	2	
77.82.614-HA	AlphaRail wiring rail	WAUKESHA®	VHP L7044GL/GSI	2	
77.82.814-HF	AlphaRail wiring rail	WAUKESHA®	VHP P9390GL/GSI	2	
77.82.815-HA	AlphaRail wiring rail	WAUKESHA®	8L-AT27GL	1	
77.82.618-HA	AlphaRail wiring rail	WAUKESHA®	12V-AT27GL	2	
77.82.818-HA	AlphaRail wiring rail	WAUKESHA®	16V-AT27GL	2	
77.82.814-HA	AlphaRail wiring rail	WHITE SUPERIOR®	2408G	1	
77.82.613-HA	AlphaRail wiring rail	WHITE SUPERIOR®	6G/GT/GTL825	1	
77.82.813-HA	AlphaRail wiring rail	WHITE SUPERIOR®	8G/GTL825	1	
77.82.616-HA	AlphaRail wiring rail	WHITE SUPERIOR®	12GTLA825	2	
77.82.616-HA	AlphaRail wiring rail	WHITE SUPERIOR®	12SGT	2	
77.82.816-HA	AlphaRail wiring rail	WHITE SUPERIOR®	16GT/GTLB825	2	
77.82.816-HA	AlphaRail wiring rail	WHITE SUPERIOR®	16SGT	2	
77.82.531-HA	AlphaRail wiring rail	WORTHINGTON®	UTC-10	2	

¹⁾ **NOTE:** Applications may vary due to different variants or attachments, which could affect the installation of mentioned wiring rails. Consult factory for details and final confirmation.

Gas Engine Control Systems

2 Bracket Configuration

P/N ¹⁾	Figure	Description
75.10.303	2A	Bracket, 40x40 mm (Standard)
75.10.097	2B	Flat bar, 180° (Standard)
75.10.120	2C	Flat bar, 150°
75.10.280	2D	Flat bar, 90°

¹⁾ For packs of ten please add suffix “-10” to part number (e.g. 75.10.303-10).

3 Thermocouples with Lead and Wiring Rail Connector – 90° (1 per Cylinder required)

P/N	Figure	Description	Wiring Rail Connector	Length
56.01.090-10	3A	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	10 in
56.01.090-20	3A	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	20 in
56.01.090-25	3A	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	25 in
56.01.090-30	3A	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	30 in
56.01.090-40	3A	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	40 in
56.01.090-60	3A	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	60 in
56.01.090-K ¹⁾	3A	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	177 in

¹⁾ Comes with loose connector and 177 in lead length.

3 Thermocouples with Lead and Wiring Rail Connector – 180° (1 per Cylinder required)

P/N	Figure	Description	Wiring Rail Connector	Length
56.01.180-10	3B	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	10 in
56.01.180-20	3B	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	20 in
56.01.180-25	3B	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	25 in
56.01.180-30	3B	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	30 in
56.01.180-40	3B	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	40 in
56.01.180-60	3B	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	60 in
56.01.180-K ¹⁾	3B	Thermocouple, Type K (NiCrNi)	MIL, 3 pole, pin, 180°, bay.	177 in

¹⁾ Comes with loose connector and 177 in lead length.



■ Gas Engine Control Systems



4 Harnesses to connect Wiring Rails with up to 8 Thermocouples and TempScan Temperature Module (1 per Rail required)

P/N	Description	Wiring Rail Connector	Length
77.42.317-L	Harness for wiring rails	MIL, 17 pole, pin, 90°	L= 5/15/25/50 ft

4 Harnesses to connect Wiring Rails with more than 8 Thermocouples and TempScan Temperature Module (1 per Rail required)

P/N	Description	Wiring Rail Connector	Length
77.42.327-L	Harness for wiring rails	MIL, 17/10 pole, pin, 90°	L= 5/15/25/50 ft

5 Accessories

P/N	Figure	Description
06.05.076	5	Junction box
76.70.007		MIL connector, 3 pole, pin, 180°, bay., for connection of already installed thermocouples to AlphaRail wiring rail
28.10.014		Cable, 2x1.5 mm², type K (NiCrNi) ¹⁾

¹⁾ Cable needs to be ordered in m/ft in required length.

6 TempScan20 Temperature Module

P/N	Figure	Description
63.03.002-20	6	TempScan20 temperature module, including connector package for power supply, CAN Bus and thermocouple wiring, operating manual
63.03.012-20		TempScan20 temperature module, built into stainless steel enclosure, including connector package for power supply, CAN Bus and thermocouple wiring, operating manual

7 PowerView3 HMI Modules & Activation Codes

P/N	Figure	Description
06.05.085	7	PowerView3 HMI module
06.05.185		PowerView3 HMI module, built into stainless steel enclosure
06.05.187		PowerView3 HMI module, built into steel enclosure with sight window
06.05.088-F		PowerView3 activation code for visualization of TempScan data – Activation code has to be ordered separately with each PowerView3 HMI module
06.05.088-U		PowerView3 activation code for visualization of TempScan data – Only available for upgrade of existing PowerView3 HMI module in the field



3A



3B



5



6



7

■ Gas Engine Control Systems

Throttle Bodies


Within a speed control system, a throttle body is used to regulate the supply of the gas/air mixture and thus the speed and power of a gas engine

MOTORTECH throttle bodies have been specially developed for use on naturally aspirated and turbocharged gas engines and can be used for operation with a wide range of gas types (natural gas, biogas, sewage gas, mine gas, etc.). The standard throttle bodies, for connection to an external actuator, and ITB throttle bodies with integrated stepper motors meet the highest quality and performance requirements, enabling precise control of the gas engine and maintenance-free operation for a long period of time.



General Features

- For use on naturally aspirated and turbocharged gas engines
- Use with various types of gas (natural gas, biogas, sewage gas, mine gas, etc.)
- The series 50, 100, 140 and 200 cover a wide range of applications
- Butterfly diameter from 1.65 to 4.92 inch (42 to 125 mm)
- Use of high-temperature ball bearings, designed for low-friction operation
- Additional sealing of the throttle body shaft for installation before and after the turbocharger
- O-rings embedded in the housing are used for flange sealing instead of paper seals
- Butterfly and shaft made of stainless steel
- Rigid design for long service life
- Other sizes and custom made designs on request



Throttles
MOTORTECH THROTTLES/BUTTERFLY VALVES

ITB
MOTORTECH INTEGRATED THROTTLE BODY

NEW

Throttles



MOTORTECH THROTTLES/BUTTERFLY VALVES

Throttle Bodies

MOTORTECH throttle bodies are equipped with a lever for connecting an external actuator. An end stop and a screw for idle speed adjustment provide additional adjustment options for optimum operation of stationary gas engines.

Features:

- End stop and screw for idle speed adjustment included
- Lever can be mounted on both sides of the shaft for flexible installation
- Mounting position of the throttle body is freely selectable
- Applicable for temperatures up to 392 °F (200 °C)



■ Gas Engine Control Systems

Standard – Series 50 (Inner Diameter 41 to 42 mm)

P/N	Supersedes	Description	ID	A	B	C	D	E	F	G	H	Equivalent to
30.41.050-42-HT	30.40.050-42, 30.40.051-42, 30.40.051-42-HT	Throttle body	42 mm	87 mm	57 mm	135 mm	100 mm	10 mm	96 mm	9 mm	40 mm	451-00-042-00

Standard – Series 100 (Inner Diameter 48 to 68 mm)

P/N	Supersedes	Description	ID	A	B	C	D	E	F	G	H	Equivalent to
30.41.100-60-HT	30.40.100-60, 30.40.101-60, 30.40.101-60-HT	Throttle body	60 mm	112 mm	75 mm	160 mm	100 mm	10 mm	125 mm	11 mm	61 mm	
30.41.100-68-HT	30.40.100-68, 30.40.101-68, 30.40.101-68-HT	Throttle body	68 mm	112 mm	75 mm	160 mm	100 mm	10 mm	125 mm	11 mm	61 mm	452-00-068-00

Standard – Series 140 (Inner Diameter 73 to 85 mm)


P/N	Supersedes	Description	ID	A	B	C	D	E	F	G	H	Equivalent to
30.41.140-75-HT	30.40.140-75, 30.40.141-75, 30.40.141-75-HT	Throttle body	75 mm	149 mm	95 mm	200 mm	150 mm	10 mm	166 mm	11 mm	76 mm	
30.41.140-80-HT	30.40.140-80, 30.40.141-80, 30.40.141-80-HT	Throttle body	80 mm	149 mm	95 mm	200 mm	150 mm	10 mm	166 mm	11 mm	76 mm	
30.41.140-85-HT	30.40.140-85, 30.40.141-85, 30.40.141-85-HT	Throttle body	85 mm	149 mm	95 mm	200 mm	150 mm	10 mm	166 mm	11 mm	76 mm	453-00-085-01

Standard – Series 150 (Inner Diameter 82 to 104 mm)

P/N	Supersedes	Description	ID	A	B	C	D	E	F	G	H	Equivalent to
30.41.150-90-HT	30.40.150-90, 30.40.151-90, 30.40.151-90-HT	Throttle body	90 mm	149 mm	110 mm	200 mm	150 mm	10 mm	194 mm	9 mm	80 mm	
30.41.150-100-HT	30.40.150-100, 30.40.151-100, 30.40.151-100-HT	Throttle body	100 mm	149 mm	110 mm	200 mm	150 mm	10 mm	194 mm	9 mm	80 mm	

Standard – Series 200 (Inner Diameter 98 to 125 mm)

P/N	Supersedes	Description	ID	A	B	C	D	E	F	G	H	Equivalent to
30.41.200-100-HT	30.40.200-100, 30.40.201-100, 30.40.201-100-HT	Throttle body	100mm	179 mm	126mm	230 mm	150 mm	10 mm	200 mm	11 mm	110mm	
30.41.200-105-HT	30.40.200-105, 30.40.201-105, 30.40.201-105-HT	Throttle body	105mm	179 mm	126mm	230 mm	150 mm	10 mm	200 mm	11 mm	110mm	
30.41.200-110-HT	30.40.200-110, 30.40.201-110, 30.40.201-110-HT	Throttle body	110mm	179 mm	126mm	230 mm	150 mm	10 mm	200 mm	11 mm	110mm	
30.41.200-115-HT	30.40.200-115, 30.40.201-115, 30.40.201-115-HT	Throttle body	115mm	179 mm	126mm	230 mm	150 mm	10 mm	200 mm	11 mm	110mm	454-00-115-00
30.41.200-125-HT	30.40.200-125, 30.40.201-125, 30.40.201-125-HT	Throttle body	125mm	179 mm	126mm	230 mm	150 mm	10 mm	200 mm	11 mm	110mm	



■ Gas Engine Control Systems

NEW

ITB

MOTORTECH INTEGRATED THROTTLE BODY




Throttle Bodies with Integrated Stepper Motor


MOTORTECH ITB throttle bodies are equipped with an integrated stepper motor, which eliminates the use for an external actuator. The stepper motor is extremely precisely actuated by the VariStep3 stepper motor driver in combination with the SC100 speed controller.

Features:

- High-resolution stepper motors
- Precise adjustment due to microstep operation
- Short adjustment times for butterfly position
- Very precise control of the programmed positions without overshooting
- Mounting position of the throttle body is freely selectable
- Applicable for temperatures up to 257 °F (125 °C), High temperature types (-HT) up to 392 °F (200 °C)
- Precisely actuated by the VariStep3 stepper motor driver and SC100 speed controller



System Overview



Required Accessories

- 1 ITB throttle body with integrated stepper motor
- 2 Stepper motor harness
- 3 Speed control kit incl.
 - VariStep3 stepper motor driver
 - SC100 speed controller
- 4 Magnetic pickup

Description

- A Gastrain
- B VariFuel2/VariFuel2+ air/gas mixer
- C Stepper motor harness
- D VariStep3 stepper motor driver
- E Master control
- F Engine
- G Flywheel
- H Air filter

Gas Engine Control Systems

1 Standard – Series 50 (Inner Diameter 41 to 42 mm)

P/N ¹⁾	Supersedes	Description	A	B	C	D	E	F	G	Equivalent to
30.43.050-ID	30.42.050-ID	Integrated throttle body	87 mm	57 mm	233 mm	96 mm	9 mm	40 mm	58 mm	
30.43.050-ID-HT	30.42.050-ID-HT	Integrated throttle body	87 mm	57 mm	248 mm	96 mm	9 mm	40 mm	58 mm	

¹⁾ Standard inner diameters (-ID) = 42 mm; other inner diameters available on request.

1 Standard – Series 100 (Inner Diameter 48 to 68 mm)

P/N ¹⁾	Supersedes	Description	A	B	C	D	E	F	G	Equivalent to
30.43.100-ID	30.42.100-ID	Integrated throttle body	112 mm	75 mm	258 mm	125 mm	11 mm	61 mm	61 mm	
30.43.100-ID-HT	30.42.100-ID-HT	Integrated throttle body	112 mm	75 mm	273 mm	125 mm	11 mm	61 mm	61 mm	

¹⁾ Standard inner diameters (-ID) = 60 mm, 68 mm; other inner diameters available on request.

1 Standard – Series 140 (Inner Diameter 73 to 85 mm)

P/N ¹⁾	Supersedes	Description	A	B	C	D	E	F	G	Equivalent to
30.43.140-ID	30.42.140-ID	Integrated throttle body	149 mm	95 mm	295 mm	166 mm	11 mm	76 mm	76 mm	
30.43.140-ID-HT	30.42.140-ID-HT	Integrated throttle body	149 mm	95 mm	310 mm	166 mm	11 mm	76 mm	76 mm	

¹⁾ Standard inner diameters (-ID) = 75 mm, 80 mm, 85 mm; other inner diameters available on request.

1 Standard – Series 150 (Inner Diameter 82 to 104 mm)

P/N ¹⁾	Supersedes	Description	A	B	C	D	E	F	G	Equivalent to
30.43.150-ID	30.42.150-ID	Integrated throttle body	149 mm	110 mm	323 mm	194 mm	9 mm	80 mm	86 mm	
30.43.150-ID-HT	30.42.150-ID-HT	Integrated throttle body	149 mm	110 mm	348 mm	194 mm	9 mm	80 mm	86 mm	

¹⁾ Standard inner diameters (-ID) = 90 mm, 100 mm; other inner diameters available on request.

1 Standard – Series 200 (Inner Diameter 98 to 125 mm)

P/N ¹⁾	Supersedes	Description	A	B	C	D	E	F	G	Equivalent to
30.43.200-ID	30.42.200-ID	Integrated throttle body	179 mm	126 mm	352 mm	200 mm	11 mm	110 mm	88 mm	
30.43.200-ID-HT	30.42.200-ID-HT	Integrated throttle body	179 mm	126 mm	377 mm	200 mm	11 mm	110 mm	88 mm	

¹⁾ Standard inner diameters (-ID) = 100 mm, 105 mm, 110 mm, 115 mm, 125 mm; other inner diameters available on request.

Conversion: 1 inch = 25.4 mm / 1 foot = 0.3 m

Gas Engine Control Systems

2A Stepper Motor Harnesses – Standard

P/N	Supersedes	Description	Connector	Length	Equivalent to
31.01.942		Stepper motor harness	MIL, 10 pole, socket , 90°	10 m (400 in)	
31.01.947-10		Stepper motor harness, with corrugated tube	MIL, 10 pole, socket , 90°	10 m (400 in)	
31.02.087-10		Stepper motor harness	MIL, 10 pole, socket , 90°	10 m (400 in)	31.01.942

2B Stepper Motor Harness – Special

P/N	Supersedes	Description	Connector	Length	Equivalent to
95.30.942-32 ¹⁾		Stepper motor harness, with fitting for 1/2 in flex conduit	MIL, 10 pole, socket , 90°	10 m (400 in)	

¹⁾ Flex conduit has to be ordered separately or supplied by customer.

Accessories for Stepper Motor Harness – Special

P/N	Supersedes	Description	Equivalent to
15.07.112		Flex conduit, 1/2 in, black ¹⁾	
15.07.221		Fitting, 1/2 in, junction box to flex conduit	
06.05.075		Junction box	

¹⁾ Flex conduit needs to be ordered in m/ft in required length.

3 Speed Control Kit incl. VariStep3 Stepper Motor Driver and SC100 Speed Controller

P/N	Supersedes	Description	Equivalent to
63.04.002		Speed control kit incl. VariStep3 stepper motor driver and SC100 speed controller	

4 Magnetic Pickups for Speed Control

P/N	Supersedes	Description	Thread Size	Thread Length	Trigger	Equivalent to
63.60.001-50		Magnetic pickup with cable, 50 ft (15 m)	M16x1.5	3.125 in	holes, pins, teeth, screws	
63.60.002-50		Magnetic pickup with cable, 50 ft (15 m)	5/8-18 UNF	3.125 in	holes, pins, teeth, screws	



2A



2B



3



4

■ Gas Engine Control Systems

Throttle Bodies for **MAN**® E2876 LE 202/212/302, E2842 E312, E2842 LE312




Based on its proven design, MOTORTECH offers a special throttle body for MAN® engine series E2876 LE and E2842 E/LE. Engineered as a replacement and plug & play solution for the original part, the throttle body perfectly fits into the existing structure between both manifolds behind the intercooler of the engine.

In addition to the commonly used version, MOTORTECH completes the series with the ITB throttle body design. The integrated stepper motor is extremely precisely actuated by the VariStep3 stepper motor driver in combination with the SC100 speed controller and eliminates the use of an external actuator. This version is especially suited for new installations or plant and engine revisions.

Properties & Features


- Applicable for media such as natural gas and special gases
- Reinforced shaft and butterfly valve made of stainless
- High temperature resistant shaft seals
- Use of ball bearings instead of plain bearings
- End stop and screw for idle speed adjustment
- Lever for connection to the external actuator or integrated stepper motor
- Same flange design for a simple replacement
- O-rings for sealing embedded in the housing
- Maintenance-free part



Flange opposite to intercooler



Flange intercooler-sided




End stop and screw for idle speed adjustment



Lever for connection to an external actuator


Gas Engine Control Systems



Integrated stepper motor




MIL connector for connection to VariStep3 stepper motor driver



Stepper motor harness



VariStep3 stepper motor driver



SC100 speed controller



Pickup

Throttle Body

P/N	Supersedes	Description	Equivalent to
30.41.152-100-HT		Throttle body for MAN® E2876 LE 2xx/302, E2842 E312, E2842 LE312	51.13105-6013, 51.13105-6021

ITB Throttle Body & Accessories

P/N	Figure	Supersedes	Description	Equivalent to
30.43.152-100			ITB throttle body for MAN® E2876 LE 2xx/302, E2842 E312, E2842 LE312	30.41.152-100-HT
31.01.942	7A		Stepper motor harness, MIL, 10 pole, socket, 90°, length 400 in (10 m)	
31.02.087-10	7B		Stepper motor harness, MIL, 10 pole, socket, 90°, length 400 in (10 m)	31.01.942
63.04.002	8		Speed control kit incl. VariStep3 stepper motor driver and SC100 speed controller	
63.60.001-50	9		Pickup, magnetic, M16x1,5 x 3.125 in (79 mm), 50 ft (15 m) cable	
alternative 63.60.002-50	9		Pickup, magnetic, 5/8-18 UNF x 3.125 in (79 mm), 50 ft (15 m) cable	

NEW

■ Gas Engine Control Systems


Throttle Bodies for **WAUKESHA**® VHP G/ GSI/ LT 6 and 12 Cylinder Engines

Based on its proven design, MOTORTECH offers a special throttle body series for WAUKESHA® VHP series in-line and V-engines. Designed as a replacement and plug-and-play solution, the throttle bodies perfectly fit the position of the original part below the intake manifold.


In addition and as an upgrade to the commonly used version, MOTORTECH completes the series with the ITB throttle body design. The integrated stepper motor is extremely precisely actuated by the VariStep3 stepper motor driver and eliminates the use of an external actuator. Both, ITB throttle body and VariStep3 stepper motor driver, operate with the standard WOODWARD® 2301D speed governor or with the MOTORTECH SC100 speed controller.

Properties & Features

- Same design and shape for easy replacement of original part
- Reinforced shaft and butterfly valve made of stainless for high durability even when backfiring has occurred
- Use of ball bearings instead of plain bearings
- Including end stop and idle speed adjustment
- Lever for connection to the external actuator or integrated stepper motor
- High temperature resistant shaft seals
- Usable with natural and special gases
- Maintenance free product



Consult factory for availability of throttle bodies for **WAUKESHA**® VHP GL Series Engines.



Same flange sizes as original part



Identical design and shape for easy assembly



End stop with adjustment screw for idle speed



Lever for connection to the external actuator

Gas Engine Control Systems




Integrated stepper motor



MIL style connector for connection to VariStep3 stepper motor driver



VariStep3 stepper motor driver



SC100 speed controller

Throttle Bodies

P/N	Description	Equivalent to
30.41.151-106-VHP-6	Throttle body for WAUKESHA® VHP 6 cylinder in-line engines F2895G/GSI, F3521G/GSI	E204072
30.41.151-106-VHP-12	Throttle body for WAUKESHA® VHP 12 cylinder V-engines L5108G/GSI, L5790G/GSI, L5774LT, L5794GSI, L7042G/GSI, L7044GSI, fits left and right bank	E204072, A204072, E204072A, A204072A, F204072A

ITB Throttle Bodies & Accessories

P/N	Description	Quantity	Equivalent to
75.30.148-6	ITB throttle body conversion kit for WAUKESHA® VHP 6 cylinder in-line engines F2895G/GSI, F3521G/GSI Contains: – ITB throttle body P/N 30.43.151-106-VHP-6 – Stepper motor harness P/N 31.01.942 – VariStep3 stepper motor driver P/N 31.01.960 7	– 1 pc – 1 pc – 1 pc	30.41.151-106-VHP-6
alternative 75.30.149-6	ITB throttle body conversion kit for WAUKESHA® VHP 6 cylinder in-line engines F2895G/GSI, F3521G/GSI Contains: – ITB throttle body P/N 30.43.151-106-VHP-6 – Stepper motor harness P/N 31.01.942 – VariStep3 stepper motor driver P/N 31.01.960 7 Stepper motor driver built into stainless steel enclosure	– 1 pc – 1 pc – 1 pc	30.41.151-106-VHP-6
75.30.148-12	ITB throttle body conversion kit for WAUKESHA® VHP 12 cylinder V-engines L5108G/GSI, L5790G/GSI, L5774LT, L5794GSI, L7042G/GSI, L7044GSI Contains: – ITB throttle body P/N 30.43.151-106-VHP-12, fits left and right bank – Stepper motor harness P/N 31.01.942 – VariStep3 stepper motor driver P/N 31.01.960 7 – Isolation amplifier P/N 63.02.017	– 2 pcs – 2 pcs – 2 pcs – 1 pc	30.41.151-106-VHP-12
alternative 75.30.149-12	ITB throttle body conversion kit for WAUKESHA® VHP 12 cylinder V-engines L5108G/GSI, L5790G/GSI, L5774LT, L5794GSI, L7042G/GSI, L7044GSI Contains: – ITB throttle body P/N 30.43.151-106-VHP-12, fits left and right bank – Stepper motor harness P/N 31.01.942 – VariStep3 stepper motor driver P/N 31.01.960 7 – Isolation amplifier P/N 63.02.017 Stepper motor drivers and isolation amplifier pre wired and built into stainless steel enclosure	– 2 pcs – 2 pcs – 2 pcs – 1 pc	30.41.151-106-VHP-12
optional 63.50.114	SC100 speed controller 8 to replace WOODWARD® 2301D speed governor	– 1 pc per kit	

■ Gas Engine Control Systems

ALL-IN-ONE

MOTORTECH GENERATOR & CHP CONTROL SYSTEM

For monitoring, controlling, regulating and system protection. ALL-IN-ONE is an expandable controller for both single and multiple gen-sets operating in standby or parallel modes, especially in cogeneration (CHP) and other complex applications.

Modular design (consisting of AIO controller and display unit) allows easy installation with the ability to add many different extension modules designed to suit individual customer requirements.

Integrated functions such as fully automatic synchronization or uninterruptible back-synchronisation in mains parallel operation as well as integrated solutions for multi-unit operation, load sharing or automatic operating hours adjustment of the individual units are standard features of the AIO generator & CHP control system. Up to 32 units can be combined in one group.

AIO supports many standard ECU (electronic control unit) types from which it can read relevant control data via Bus. A powerful graphic display with user-friendly controls allows any operator to find the information they need. The display on the basic version is capable of displaying graphical characters (e.g. Chinese).



AIO.GAS Controller

AIO.Vision12 Display

Benefits

- Support of engines with ECU (Electronic control unit)
- Individually configurable to match customer's needs exactly
- Complete integrated gen-set solution incorporating built-in PLC and signal sharing via CAN bus – minimum external components needed
- Many communication options – easy remote supervising and servicing
- Perfect price / performance ratio
- Gen-set performance log for easy problem tracing
- Air/Fuel Ratio function for lean burn gas engines (requires additional hardware dongle)

Features

- CHP support (programmable PID control loops and other built-in PLC functions)
- Support of engines with ECU (J1939, Modbus and other proprietary interfaces); alarm codes displayed in text form
- Automatic synchronizing and power control (via speed governor or ECU)
- Baseload, Import/Export, TempByPower
- Peak shaving

- Voltage and power factor control (AVR)
- Generator measurement: U, I, Hz, kW, kVAr, kVA, PF, kWh, kVAh
- Mains measurement: U, I, Hz, kW, kVAr, PF
- Selectable measurement ranges for AC voltages and currents – 120/277 V, 0-1/0-5 A
- Inputs and outputs configurable for various customer needs
- Controller redundancy
- 2× RS232/RS485 interface with Modbus protocol
- Support; Analog/GSM/ISDN/CDMA modem communication support; SMS messages; ECU Modbus interface; secondary RS485 converter is isolated
- Event-based history (up to 1000 records) with customer-selectable list of stored values; RTC; statistic values
- Integrated PLC programmable functions
- Interface to remote display units (3× AIO.Vision-display)
- USB 2.0 slave interface
- Sealed to IP65

Integrated fixed and configurable protections

- 3 phase integrated generator protections (U + f)
- IDMT overcurrent + shortcurrent protection
- Overload protection
- Reverse power protection
- Earth fault current protection
- 3 phase integrated mains protections (U + f)
- Vector shift protection
- All binary/analog inputs free configurable for various protection types
- Phase rotation and phase sequence protection
- Additional 160 programmable protections configurable for any measured value to create customer-specific protections
- Application security



Gas Engine Control Systems

Controllers

NEW

P/N	Supersedes	Description
63.50.104	63.50.102	ALL-IN-ONE.NTC controller – universal gen-set controller (incl. AFR control ¹⁾ and AirGate® technology)
63.50.104-HSS	63.50.102-HSS	ALL-IN-ONE.NTC controller – universal gen-set controller P/N 63.50.104 incl. Plug-on module I-HSS-BIN6/10
63.50.096		ALL-IN-ONE.GAS controller – universal gen-set controller (incl. AFR control ¹⁾ and AirGate® technology)
63.50.082		Mini-ALL-IN-ONE controller – universal controller for small gen-sets (incl. AFR control ²⁾ – for applications up to 75 kWel only)

¹⁾ Requires hardware dongle P/N 63.50.061 or 63.50.062 for activation.

²⁾ Requires hardware dongle P/N 63.50.085 for activation (for applications up to 75 kWel only).

Display Units for ALL-IN-ONE.NTC/.GAS Controllers

NEW

NEW

P/N	Supersedes	Description
63.50.105		ALL-IN-ONE.Vision5 display – 5.7 in color display unit for ALL-IN-ONE.NTC and ALL-IN-ONE.GAS controllers
63.50.101		ALL-IN-ONE.Vision8 display – 8.0 in color display unit for ALL-IN-ONE.NTC and ALL-IN-ONE.GAS controllers
63.50.097		ALL-IN-ONE.Vision12 display – 12.0 in color touch display unit for ALL-IN-ONE.NTC and ALL-IN-ONE.GAS controllers
63.50.129	63.50.115, 63.50.120	ALL-IN-ONE.Vision18 display – 18.5 in color touch display unit for ALL-IN-ONE.NTC and ALL-IN-ONE.GAS controller

Dongles

P/N	Supersedes	Description
63.50.061		Hardware dongle for ALL-IN-ONE.NTC/.GAS controllers – AFR-PCM Enables single island or single parallel with mains operation ■ Air/fuel ratio function for lean burn gas engines
63.50.062		Hardware dongle for ALL-IN-ONE.NTC/.GAS controllers – AFR-PCLSM+PMS ■ Enables multiple island parallel or multiple parallel with mains operation ■ Power management operation via CAN bus ■ Digital load sharing ■ Digital VAR sharing ■ Optimizing number of running engines: kW, kVA, load percentage or running hours based power management ■ Air/fuel ratio function for lean burn gas engines
63.50.085		Hardware dongle for Mini-ALL-IN-ONE – miniAFR-PCM ■ Enables single island or single parallel with mains operation ■ Air/fuel ratio function for lean burn gas engines ■ For applications up to 75 kWel only



AIO Controllers

AIO.NTC Controller
P/N 63.50.104



AIO.GAS Controller
P/N 63.50.096



Mini-AIO Controller
P/N 63.50.082



Available Display Units for AIO.NTC and AIO.GAS Controllers



AIO.Vision18
P/N 63.50.129



AIO.Vision12
P/N 63.50.097



AIO.Vision8
P/N 63.50.101




AIO.Vision5
P/N 63.50.105

Other Controllers


P/N	Supersedes	Description
63.50.064		Mains supervision controller – IM-NT
63.50.064-BTB		Mains supervision controller Bus Tie Breaker – IM-NT BTB
63.50.064-MCB		Mains supervision controller Mains Circuit Breaker – IM-NT MCB

Accessories

P/N	Supersedes	Description
63.50.092		Analog input extension module – I-AIN8
63.50.002		Analog input extension module – IS-AIN8
63.50.093	63.50.108	Analog input extension module for thermocouples only – I-AIN8TC
63.50.118	63.50.005	Input/output extension module – IO8/8
63.50.007		Analog/binary input/output module – IGS-PTM
63.50.007-HSS		Analog/binary input/output module P/N 63.50.007 incl. plug-on module I-HSS-BIN8
63.50.011		AVR interface module – IG-AVRi
63.50.010-100		Power supply transformer for IG-AVRi module, 100-120 VAC, 50-60 Hz
63.50.010-230		Power supply for IG-AVRi module, 230-480 VAC, 50-60 Hz
63.50.054		Analog output module – I-AOUT8
63.50.075	63.50.006	Modem extension unit – I-LB+
63.50.112	63.50.022	Internet communication module – IB-NT
63.50.088		CAN repeater module – I-CR



Sample Control Panel



■ Gas Engine Control Systems

MOT-Actuator

MOTORTECH ELECTRIC ESM EXT ACTUATOR

MOTORTECH Actuator Replacement Kit for **WAUKESHA®** VHP Series Four® with ESM and Extender® Series Engines

Features

- Drop in replacement
- Eliminates HEINZMANN® actuator
- Works on WAUKESHA® VHP L5774LT, L5794GSI/LT and L7044GSI



Replacement Kit for WAUKESHA® VHP Series Four® with ESM and Extender® Series Engines

P/N	Supersedes	Description	Equivalent to
63.04.176	63.04.175	Actuator replacement kit	214046



- Plug and play connection
- Does **not** require any
 - ESM software adjustment
 - Harness modification



- Mounting bracket included
- Allows easy drop in installation



- Lever included
- Simple connection to existing linkage

INSTALLATION NOTICE: If used on 6 cylinder WAUKESHA® VHP engines the IMPCO® throttle needs to be readjusted by flipping it over 180 degrees.


■ Sensor Systems

Thermocouple Rails for **WAUKESHA®** 12 Cylinder VHP Engines

MOTORTECH offers a series of different Thermocouple Rail Upgrade Kits. The rails are installed in the “Vee” or on the side of the engine. These rail kits replace any prior system if installed.

Features

- Direct replacement for WAUKESHA® Thermocouple Conduit Assembly
- Available in different versions
- Prefabricated system guarantees easy exchange and installation
- Serviceable stainless steel wiring rail, no foam inside
- 14 thermocouples, Type K (NiCrNi), 90°
- Harness with flex conduit and J-Box or a large connector to fit the ESM
- Rail mounting brackets included in each kit
- 3 versions available



Thermocouples, Type K, NiCrNi, 90°



Harness with flex conduit and fitting

Thermocouple Wiring Rail Kit with 8 ft Harness to Junction Box

Contains:

- 14 thermocouples, Type K (NiCrNi), 90°, equivalent to WAUKESHA® P/N 211288S
- 8.5 ft harness with flex conduit and fitting
- Rail mounting bracket (2 sets)
- Junction box P/N 06.05.076 with 44 terminals



P/N	Description	Equivalent to
D211359G-MOT	Thermocouple wiring rail kit	D211359G

Sensor Systems



Thermocouple Wiring Rail Kit with 50 ft Harness for Direct Wiring

Contains:

- 14 thermocouples, Type K (NiCrNi), 90°, equivalent to WAUKESHA® P/N 211288S, but 50 ft cable length
- 50 ft harness with flex conduit and fitting
- Rail mounting bracket (2 sets)



P/N	Description	Equivalent to
77.75.068-50	Thermocouple wiring rail kit	

Thermocouple Wiring Rail Kit with 8 ft Harness and Connector to ESM Wiring System

Contains:

- 14 thermocouples, Type K (NiCrNi), 90°, equivalent to WAUKESHA® P/N 211288S
- 8 ft harness with flex conduit and 33 pole connector, socket
- Rail mounting bracket (2 sets)



P/N	Description	Equivalent to
77.75.066	Thermocouple wiring rail kit	214036D

Optional Parts

P/N	Description	Required Quantity	Equivalent to
64.40.038	Fitting, 1/4 in, outer thread 1/4 in NPT	14 pcs per rail kit	194929



Spare Parts

P/N	Description	Lead Length	For use with	Equivalent to
56.01.094-23	Thermocouple, Type K (NiCrNi), 90°	23 ft	D211359G-MOT, 77.75.066	211288S
56.01.094-59	Thermocouple, Type K (NiCrNi), 90°	59 ft	77.75.068-50	



Sensor Systems

Thermocouples

Thermocouples for **CATERPILLAR®** G3500/B/C/E & G3600 Series Gas Engines

P/N	Figure	Description	Connector	Length	Equivalent to
56.01.092-28	1	Thermocouple, Type K (NiCrNi), 90°	2 pole, pin, 180°	28.00 in	383-2989, 241-9591, 175-5341, 6I-0407 ¹⁾
56.01.098-34	1	Thermocouple, Type K (NiCrNi), 90°	3 pole, pin, 180°	34.00 in	152-0807

¹⁾ If the MOTORTECH thermocouple is used to replace thermocouple 175-5341 or 6I-0407, the engine wiring harness must be modified by replacing the bullet connector with kit P/N 75.30.046. Please order separately with each thermocouple.

Connector Kit for Thermocouples

P/N	Description	Equivalent to
75.30.046	Connector kit incl. housing, contacts and wedge lock	

Thermocouple for **CUMMINS®** QSK60G and QSV81/91G – For use with AlphaRail Wiring Rail System for Temperature Control

P/N ¹⁾	Description	Wiring Rail Connector	Length	Equivalent to
56.01.091-25	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	25.00 in	

¹⁾ Other lengths available on request.

Thermocouple and Connecting Cable for **MAN®** E08, E26, E28 & E32 Series Gas Engines

P/N	Figure	Description	Connector	Length	Equivalent to
51.27421-0158-MOT	2	Thermocouple, Type K (NiCrNi), 90°	4 pole, socket, 180°	14.00 in	51.27421-0158
06.30.112		Connecting cable for thermocouple	4 pole, pin, 180°	210.00 in	51.25411-6028

Thermocouples for **MWM®/DEUTZ®** Gas Engines

P/N	Figure	Description	Engine Series
1229 6754	3	Thermocouple, Type K (NiCrNi)	TBG 616
1229 9487	3	Thermocouple, Type K (NiCrNi)	TBG 616, TCG 2016
1229 3602	3	Thermocouple, Type K (NiCrNi)	TBG 616, TBG 620
1232 3810	3	Thermocouple, Type K (NiCrNi)	TBG 616, TBG 620, TCG 2016, TCG 2020
1232 2279	3	Thermocouple, Type K (NiCrNi)	TCG 2016



Thermocouples for WAUKESHA® AT25 & AT27 Series Gas Engines

P/N	Figure	Description	Wiring Rail Connector	Length	Equivalent to
56.01.005-42	4	Thermocouple, Type K (NiCrNi), 180°	3 pole socket, 180°	42.00 in	295962
56.01.005-53	4	Thermocouple, Type K (NiCrNi), 180°	3 pole socket, 180°	53.00 in	295962A
56.01.005-70	4	Thermocouple, Type K (NiCrNi), 180°	3 pole socket, 180°	70.00 in	295962B
56.01.005-81	4	Thermocouple, Type K (NiCrNi), 180°	3 pole socket, 180°	81.00 in	295962C


AlphaRail

MOTORTECH WIRING RAIL SYSTEM


Thermocouples for use with AlphaRail Wiring Rail System for Temperature Control

P/N	Figure	Description	Wiring Rail Connector	Length	Equivalent to
56.01.090-10	5	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	10.00 in	
56.01.090-20	5	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	20.00 in	
56.01.090-25	5	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	25.00 in	
56.01.090-30	5	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	30.00 in	
56.01.090-40	5	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	40.00 in	
56.01.090-60	5	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	60.00 in	
56.01.090-K ¹⁾	5	Thermocouple, Type K (NiCrNi), 90°	MIL, 3 pole, pin, 180°, bay.	177.00 in	
56.01.180-10	6	Thermocouple, Type K (NiCrNi), 180°	MIL, 3 pole, pin, 180°, bay.	10.00 in	
56.01.180-20	6	Thermocouple, Type K (NiCrNi), 180°	MIL, 3 pole, pin, 180°, bay.	20.00 in	
56.01.180-25	6	Thermocouple, Type K (NiCrNi), 180°	MIL, 3 pole, pin, 180°, bay.	25.00 in	
56.01.180-30	6	Thermocouple, Type K (NiCrNi), 180°	MIL, 3 pole, pin, 180°, bay.	30.00 in	
56.01.180-40	6	Thermocouple, Type K (NiCrNi), 180°	MIL, 3 pole, pin, 180°, bay.	40.00 in	
56.01.180-60	6	Thermocouple, Type K (NiCrNi), 180°	MIL, 3 pole, pin, 180°, bay.	60.00 in	
56.01.180-K ¹⁾	6	Thermocouple, Type K (NiCrNi), 180°	MIL, 3 pole, pin, 180°, bay.	177.00 in	

¹⁾ Comes with loose connector and 177 in lead length.



4



5



6

Sensor Systems

Sensors

For several years MOTORTECH offers oxygen sensors that can be used as replacements for the OEM part. Shielded and unshielded versions can be selected.



Oxygen Sensors for **CATERPILLAR®** G3400 and G3500 Series Gas Engines

P/N	Figure	Description	Connector	Length	Equivalent to
19.60.027	1	Oxygen sensor, unshielded	MIL, 6 pole, pin, 180°	10.00 in	196-5391, 3E-7639
19.60.029	2	Oxygen sensor, shielded	MIL, 6 pole, pin, 180°	51.00 in	141-2494

Oxygen Sensor for **WAUKESHA®** VHP G/GSI/LT Series Gas Engines

P/N	Figure	Description	Connector	Length	Equivalent to
A740106E-MOT	3	Oxygen sensor	2 pole, pin, 180°	17.00 in	A740106E, A740106D, A740106C

Oxygen Sensor Harness for **WAUKESHA®** Gas Engines

P/N	Figure	Description	Connector	Length	Equivalent to
06.30.110		Oxygen sensor harness	9 pole, pin, 180°	90.00 in	A740735

UEGO Oxygen Sensor

P/N	Figure	Description	Connector	Length	Equivalent to
19.60.007	4	UEGO oxygen sensor	8 pole, pin, 180°	15.75 in	DL08311001
19.71.013		UEGO oxygen sensor lead	8 pole, socket, 180°	79.00 in	DL08311003



Oxygen Sensor – Heated


P/N	Figure	Description	Connector	Length	Equivalent to
19.60.015	5	Oxygen sensor, heated	4 pole, pin, 180°	1.15 ft (0.35 m)	
19.71.015-2		Oxygen sensor lead	4 pole, socket, 180°	6.50 ft (2.00 m)	
19.71.015-3		Oxygen sensor lead	4 pole, socket, 180°	9.80 ft (3.00 m)	
19.71.015-15		Oxygen sensor lead	4 pole, socket, 180°	49.00 ft (15.00 m)	
19.71.015-30		Oxygen sensor lead	4 pole, socket, 180°	98.00 ft (30.00 m)	

Oxygen Sensor – Non Heated

P/N	Figure	Description	Connector	Length	Equivalent to
19.60.004	5	Oxygen sensor, non heated	2 pole, pin, 180°	1.15 ft (0.35 m)	
19.71.004-32		Oxygen sensor lead	2 pole, socket, 180°	32.00 ft (9.75 m)	
19.71.004-50		Oxygen sensor lead	2 pole, socket, 180°	50.00 ft (15.00 m)	
19.71.004-100		Oxygen sensor lead	2 pole, socket, 180°	100.00 ft (30.00 m)	

To increase life time of these critical sensors, there is also a stainless steel weld hub available that is welded into the exhaust pipe.

A heat shield can be screwed on top of the weld hub. This way the sensor does reach directly into the exhaust gas stream with all its deposits and the heat shield protects the sensor against transient temperature from the hot exhaust manifold.



Accessories for Oxygen Sensors

P/N	Figure	Description	Equivalent to
19.60.022	6	Heat shield	
19.60.023	7	Welding adaptor	



Sensor Systems

MAT – Manifold Air Temperature Sensors

P/N	Figure	Supersedes	Description	Thread	Fitting Length	Equivalent to
56.01.004	7	56.01.021	MAT sensor	G1/2	2.00 in (50 mm)	
56.01.011	7		MAT sensor	G1/2	3.00 in (75 mm)	
56.01.017	7		MAT sensor	G1/2	4.00 in (100 mm)	

Temperature Sensor for MAN® E08 & E28 Series Gas Engines

P/N	Figure	Description	Thread	Fitting Length	Equivalent to
56.01.025	8	Temperature sensor with switch	M14x1.5	1.60 in (40 mm)	51.27420-0008

MAP – Manifold Absolute Pressure Sensor (Automotive Design)

P/N	Figure	Description	Connector	Length	Equivalent to
19.60.002	9	MAP sensor	3 pole, socket		6910-314
19.71.002		MAP sensor lead	3 pole, pin, 180°	26.00 ft (8.00 m)	DL08220604

MAP – Manifold Absolute Pressure Sensors (Industrial Design)

P/N	Figure	Supersedes	Description	Thread	Pressure Range	Equivalent to
56.01.001	10		MAP sensor	G1/4	0 to 10.0 bar	
56.01.002	10		MAP sensor	G1/4	0 to 6.0 bar	
56.01.010	10		MAP sensor	G1/4	0 to 16.0 bar	
56.02.017	10	56.02.016	MAP sensor	G1/4	0 to 3.0 bar	



7



8



9



10


Sensor Harnesses for MAN® Gas Engines

MOTORTECH sensor harnesses are individually designed for use on MAN® gas engines. The harnesses are completely prewired and equipped with all sensors required to measure the relevant operating data of the engine. To transfer the measured values to the master control, a matching connecting harness is plugged to the main connector of the sensor harness.

Features

- Prewired harness with engine specific layout
- Sensors for measuring of following values: ¹⁾
 - ▶ Oil pressure and temperature
 - ▶ Coolant pressure and temperature
 - ▶ Manifold pressure and temperature
 - ▶ Engine speed
- Including all brackets and adaptors for mounting harness and sensors
- Connecting harness to master control

¹⁾ Number and type of sensors may vary due to different engine models.



Sensor Harnesses for MAN® E0834 Series Gas Engines

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.024		Harness with all sensors	E0834 E302/312	
06.30.022		Connecting harness to master control	E0834 E302/312	
06.30.101		Harness with all sensors	E0834 LE302	
06.30.102		Connecting harness to master control	E0834 LE302	

Sensor Harnesses for MAN® E0836 Series Gas Engines

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.023		Harness with all sensors	E0836 E302/312	
06.30.022		Connecting harness to master control	E0836 E302/312	
06.30.026		Harness with all sensors	E0836 LE202	
06.30.027		Connecting harness to master control	E0836 LE202	

Sensor Harnesses for MAN® E2676 Series Gas Engines **NEW**

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.164		Harness with all sensors	E2676 LE202/212	
06.30.165-15000		Connecting harness to master control	E2676 LE202/212	

Sensor Harnesses for MAN® E2876 Series Gas Engines

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.042		Harness with all sensors	E2876 E312	
06.30.043		Connecting harness to master control	E2876 E312	
06.30.093		Harness with all sensors	E2876 TE302	
06.30.060		Connecting harness to master control	E2876 TE302	
06.30.025		Harness with all sensors	E2876 LE202/302	
06.30.028		Connecting harness to master control	E2876 LE202/302	

Sensor Systems

Sensor Harnesses for MAN® E2848 Series Gas Engines

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.053		Harness with all sensors	E2848 LE322	
06.30.054		Connecting harness to master control	E2848 LE322	

Sensor Harnesses for MAN® E2842 Series Gas Engines

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.055		Harness with all sensors	E2842 E312	
06.30.056		Connecting harness to master control	E2842 E312	
06.30.040		Harness with all sensors	E2842 LE312	
06.30.039		Adaptor harness	E2842 LE312	
06.30.041		Adaptor harness	E2842 LE312	
06.30.044		Connecting harness to master control	E2842 LE312	
06.30.053		Harness with all sensors	E2842 LE322	
06.30.054		Connecting harness to master control	E2842 LE322	

Sensor Harnesses for MAN® E3268 Series Gas Engines **NEW**

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.162		Harness with all sensors	E3268 LE212/222	
06.30.163-15000		Connecting harness to master control	E3268 LE212/222	

Sensor Harnesses for MAN® E3262 Series Gas Engines **NEW**

P/N	Supersedes	Description	Engine Model	Equivalent to
06.30.166		Harness with all sensors	E3262 E302	
06.30.162		Harness with all sensors	E3262 LE202/212	
06.30.163-15000		Connecting harness to master control	E3262 E302/LE202/212	

CAN Connecting Harnesses for Data Logger to Master Control on MAN® E26 and E32 Series Gas Engines

P/N	Supersedes	Description	Connector	Length	Equivalent to
06.05.089-65		CAN connecting harness	4 pole, socket	65.00 ft (20.00 m)	
06.05.092-65		CAN connecting harness	6 pole, socket	65.00 ft (20.00 m)	

Harnesses for **WOODWARD®** L-Series Control

P/N	Supersedes	Description	Connector	Length	Equivalent to
13.20.002		Programming harness for L-Series ITB, LC50	12 pole, socket	180.00 in (4.60 m)	02-0004-174
13.20.003-295		Harness for L-Series	12 pole, socket	295.00 in (7.50 m)	
13.20.003-590		Harness for L-Series	12 pole, socket	590.00 in (15.00 m)	
13.20.004		Programming harness for L-Series	12 pole, socket	6.90 in (0.18 m)	8923-1061

Harnesses for **WOODWARD®** ProAct Series

P/N	Supersedes	Description	Connector	Length	Equivalent to
06.02.026-5		Harness for ProAct IV governor	MIL, 24 pole, socket, 90°	5.00 ft (1.50 m)	
06.02.026-15		Harness for ProAct IV governor	MIL, 24 pole, socket, 90°	15.00 ft (4.50 m)	
06.02.026-25		Harness for ProAct IV governor	MIL, 24 pole, socket, 90°	25.00 ft (7.50 m)	
06.02.026-50		Harness for ProAct IV governor	MIL, 24 pole, socket, 90°	50.00 ft (15.00 m)	
06.30.100		Harness for ProAct ISC integrated speed control	MIL, 24 pole, socket, 180°	50.00 ft (15.00 m)	

Air/Fuel Ratio Control Systems

VariFuel2 MOTORTECH AIR/GAS MIXER

MOTORTECH's VariFuel2 is a high-tech variable Venturi type air/gas mixer that can constantly adjust to any fuel changes and allows the engine to operate at its most efficient point. Series 100, 140, 200, 250, 300 and 350 are available for engines with an air requirement up to 12,000 m³/h. Coupled to an air/fuel ratio controller, lean-burn or stoichiometric, it precisely regulates the mixture. The VariFuel2 is very popular for applications with constant changes in calorific value of fuel.

VariFuel2 air/gas mixers are equipped with a high precision stepper motor which is extremely precisely actuated by the VariStep3 stepper motor driver. Different flow bodies and variable gas inlet and mixture outlet configurations allow flexible adaptation of the gas mixer to the respective application.



NEW

VariFuel2+ MOTORTECH AIR/GAS MIXER

VariFuel+ air/gas mixers are specially designed for use with natural gas-powered gas engines and are based on the general operating principle of the VariFuel2 series. The geometry of the built-in fuel ring, adapted to the application, ensures improved engine starting behavior and control of the air/gas mixture in natural gas operation.



VariFuel2 and VariFuel2+ air/gas mixers are suitable for a wide range of gas types:

- | | |
|----------------|----------------|
| ■ Natural gas | ■ Wood gas |
| ■ Biogas | ■ Wellhead gas |
| ■ Landfill gas | ■ Mine gas |
| ■ Sewage gas | |



Series 100-60



Series 140-80



Series 200-120



Series 250-150



Series 350-225

Operating Principle

Basic Design

The main task of a gas mixer is to mix the fuel (gas) and air in such a way that optimum combustion takes place in the gas engine. High efficiency and low emissions, in accordance with current regulations, are the decisive parameters for optimization.


In the VariFuel2, air and gas are mixed according to the Venturi principle. The air is sucked through the air intake into the Venturi nozzle by the suction vacuum of the engine. Due to the Venturi principle, a vacuum is created at the narrowest point, which sucks the gas through the gas inlet. In this way, gas and air are mixed and released at the mixture outlet.

Various mixer sizes and flow bodies **1** in the Venturi nozzle allow different volumetric flows to be achieved.

Regulation of the Air/Fuel Mixture

The fuel (gas) is guided into the nozzle via the adjustable openings **2** in a fuel ring **3**. The openings of the fuel ring are adjusted by a drive belt **4** via a stepper motor. The stepper motor **5** can be controlled by the VariStep3 stepper motor driver, which can process the signals of a master control.

In addition, the VariFuel2 air/gas mixers are equipped with a port for an air pressure gauge and a connection for the pulse line of a zero pressure regulator



Air/Fuel Ratio Control Systems



Scan the QR code® to download the specification table to specify a suitable air/gas mixer for your application.

Features

VariFuel2/VariFuel2+ Series	100-60	140-80	200-120	250-150	300-190	350-225
Air requirement	100 to 650 m³/h	200 to 1,300 m³/h	500 to 3,200 m³/h	1,800 to 5,200 m³/h	3,400 to 8,500 m³/h	6,000 to 12,000 m³/h
Available flow body sizes	23.0 to 55.0 mm in steps of 2.5 mm	23.0 to 72.5 mm in steps of 2.5 mm	23.0 to 107.5 mm in steps of 2.5 mm	23.0 to 110.0 mm in steps of 2,5 mm	35.0 to 140.0 mm in steps of 5.0 mm	35.0 to 150.0 mm in steps of 5.0 mm
Flexible inlet and outlet configuration	x	x	x	x	x	x
Driven by timing belt	x	x	x	x	x	x
Number of gas pressure gauge connections	1	1	1	1	1	1
Number of air pressure gauge connections	1	1	1	1	1	1
Hose connection for air inlet	x	x	x	x	x	x
Various flange connections for outlet	x	x	x	x	x	x
Various flange connections for gas inlet	x	x	x	x	x	x
The central flow body is fixed with 3 profiles. Their numerous small gas inlets provide an optimum mixture of gas and circulating air, granting a constant level of homogenization of the air-gas mix.	x	x	x	x	x	x

Accessories



2 Flow Bodies

Depending on the application, suitable flow bodies in different sizes are used to influence the flow velocity.

- Flow bodies are made of aluminum and, from a diameter of 60 mm, of high-strength thermoplastic material.



3 Outlet Flange Kits

Outlet flanges for easy connection of the VariFuel2/VariFuel2+ air/gas mixers to typical gas engines.

- Standard and engine-specific types are available.



4 Gas Inlet Flanges


Gas inlet flanges for connecting the gas train to the VariFuel2/VariFuel2+ air/gas mixer.

- Versions with different thread sizes are available for each gas mixer series.



Example for mounting on MAN® E3262 LE gas engine.

System Overview



Required Accessories

- 1 VariFuel2/VariFuel2+ air/gas mixer
- 2 Flow body
- 3 Outlet flange
- 4 Gas inlet flange
- 5 Stepper motor harness
- 6 VariStep3 stepper motor driver

Description

- A Gastrain (ZERO Pressure Regulator required)
- B Master control / Emission control system
- C ITB throttle body with integrated stepper motor
- D Stepper motor harness
- E Speed control kit incl.
 - VariStep3 stepper motor driver
 - SC100 speed control
- F Magnetic pickup
- G Flywheel
- H Engine
- I Air filter

Air/Fuel Ratio Control Systems

1 VariFuel2 Air/Gas Mixer – with Digital Stepper Motor¹⁾

P/N	Supersedes	Description
30.45.100-60D	30.45.100-50D	VariFuel2 air/gas mixer, series 100-60
30.45.140-80D	30.45.140-65D	VariFuel2 air/gas mixer, series 140-80
30.45.200-120D	30.45.200-100D	VariFuel2 air/gas mixer, series 200-120
30.45.250-150D		VariFuel2 air/gas mixer, series 250-150
30.45.300-190D		VariFuel2 air/gas mixer, series 300-190
30.45.350-225D		VariFuel2 air/gas mixer, series 350-225

¹⁾ Consult factory for availability of manually adjustable VariFuel2 air/gas mixers.

1 VariFuel2+ Air/Gas Mixer – with Digital Stepper Motor **NEW**

P/N	Supersedes	Description
30.45.101-60D		VariFuel2+ air/gas mixer, series 100-60
30.45.141-80D		VariFuel2+ air/gas mixer, series 140-80
30.45.201-120D		VariFuel2+ air/gas mixer, series 200-120
30.45.251-150D		VariFuel2+ air/gas mixer, series 250-150
30.45.301-190D		VariFuel2+ air/gas mixer, series 300-190
30.45.351-225D		VariFuel2+ air/gas mixer, series 350-225

2 Flow Bodies

P/N	Supersedes	Description	Diameter	VariFuel2/VariFuel2+ Series (D= digital / M= manual)					
				100-60D/M	140-80D/M	200-120D/M	250-150D/M	300-190D/M	350-225D/M
31.01.720-23.0-3		Flow body	23.0 mm	x	x	x	x		
31.01.720-27.5-3		Flow body	27.5 mm	x	x	x	x		
31.01.720-30.0-3		Flow body	30.0 mm	x	x	x	x		
31.01.720-32.5-3		Flow body	32.5 mm	x	x	x	x		
31.01.720-35.0-3		Flow body	35.0 mm	x	x	x	x	x	x
31.01.720-37.5-3		Flow body	37.5 mm	x	x	x	x		
31.01.720-40.0-3		Flow body	40.0 mm	x	x	x	x	x	x
31.01.720-42.5-3		Flow body	42.5 mm	x	x	x	x		
31.01.720-45.0-3		Flow body	45.0 mm	x	x	x	x	x	x
31.01.720-47.5-3		Flow body	47.5 mm	x	x	x	x		
31.01.720-50.0-3		Flow body	50.0 mm	x	x	x	x	x	x
31.01.720-52.5-3		Flow body	52.5 mm	x	x	x	x		
31.01.720-55.0-3		Flow body	55.0 mm	x	x	x	x	x	x
31.01.720-57.5-3		Flow body	57.5 mm		x	x	x		
31.01.720-60.0-3		Flow body	60.0 mm		x	x	x	x	x
31.01.720-62.5-3		Flow body	62.5 mm		x	x	x		
31.01.720-65.0-3		Flow body	65.0 mm		x	x	x	x	x
31.01.720-67.5-3		Flow body	67.5 mm		x	x	x		
31.01.720-70.0-3		Flow body	70.0 mm		x	x	x	x	x
31.01.720-72.5-3		Flow body	72.5 mm		x	x	x		
31.01.720-75.0-3		Flow body	75.0 mm			x	x	x	x
31.01.720-77.5-3		Flow body	77.5 mm			x	x		
31.01.720-80.0-3		Flow body	80.0 mm			x	x	x	x
31.01.720-82.5-3		Flow body	82.5 mm			x	x		
31.01.720-85.0-3		Flow body	85.0 mm			x	x	x	x
31.01.720-87.5-3		Flow body	87.5 mm			x	x		

2 Flow Bodies

P/N	Supersedes	Description	Diameter	VariFuel2/VariFuel2+ (D= digital / M= manual)					
				100-60D/M	140-80D/M	200-120D/M	250-150D/M	300-190D/M	350-225D/M
31.01.720-90.0-3		Flow body	90.0 mm			x	x	x	x
31.01.720-92.5-3		Flow body	92.5 mm			x	x		
31.01.720-95.0-3		Flow body	95.0 mm			x	x	x	x
31.01.720-97.5-3		Flow body	97.5 mm			x	x		
31.01.720-100.0-3		Flow body	100.0 mm			x	x	x	x
31.01.720-102.5-3		Flow body	102.5 mm			x	x		
31.01.720-107.5-3		Flow body	107.5 mm			x	x		
31.01.720-110.0-3		Flow body	110.0 mm				x	x	x
31.01.720-115.0-3		Flow body	115.0 mm					x	x
31.01.720-120.0-3		Flow body	120.0 mm					x	x
31.01.720-125.0-3		Flow body	125.0 mm					x	x
31.01.720-130.0-3		Flow body	130.0 mm					x	x
31.01.720-135.0-3		Flow body	135.0 mm					x	x
31.01.720-140.0-3		Flow body	140.0 mm					x	x
31.01.720-145.0-3		Flow body	145.0 mm						x
31.01.720-150.0-3		Flow body	150.0 mm						x

3 Outlet Flange Kits

P/N	Description	VariFuel2/VariFuel2+ (D= digital / M= manual)					
		100-60D/M	140-80D/M	200-120D/M	250-150D/M	300-190D/M	350-225D/M
31.01.764	Outlet flange kit, gas relaxation section for throttle, series 50	x					
31.01.765	Outlet flange kit, gas relaxation section for throttle, series 100	x					
31.01.766	Outlet flange kit, gas relaxation section for throttle, series 50	x					
31.01.768	Outlet flange kit, for MAN® E0834 LE302, E0836 LE202	x					
31.01.750	Outlet flange kit, for MAN® E2876 LE202/212/302		x				
31.01.752	Outlet flange kit, welding neck flange, DN100		x				
31.01.753	Outlet flange kit, for MAN® E0836 LE202		x				
31.01.755	Outlet flange kit, DN65-PN6		x				
31.01.756	Outlet flange kit, for MAN® E2842 E312		x				
31.01.757	Outlet flange kit, for throttle, series 100		x				
31.01.762	Outlet flange kit, gas relaxation section for throttle, series 100		x				
31.01.763	Outlet flange kit, gas relaxation section for throttle, series 140		x				
31.01.773	Outlet flange kit, for LIEBHERR® G934, G944		x				
31.01.781	Outlet flange kit, for LIEBHERR® G946		x				
31.02.113	Outlet flange kit, for MAN® E2676 E302		x				
31.02.115	Outlet flange kit, for MAN® E3262 E302		x				
31.02.118	Outlet flange kit, for MAN® E0836 LE302		x				
31.01.751	Outlet flange kit, welding neck flange, DN150			x			
31.01.754	Outlet flange kit, for MAN® E2842 LE312			x			
31.01.758	Outlet flange kit, hose connection, DN200			x			
31.01.759	Outlet flange kit, for MAN® E2676 LE202/212, E2876 LE202/212/302			x			
31.01.761	Outlet flange kit, welding neck flange, DN150 – aluminum			x			

Air/Fuel Ratio Control Systems

3 Outlet Flange Kits

P/N	Description	VariFuel2/VariFuel2+ Series (D= digital / M= manual)					
		100-60D/M	140-80D/M	200-120D/M	250-150D/M	300-190D/M	350-225D/M
31.01.767	Outlet flange kit, for DEUTZ® TCG2015V6/V8			x			
31.01.772	Outlet flange kit, for SHENGDONG® 600GF1-PS			x			
31.01.775	Outlet flange kit, for LIEBHERR® G9508			x			
31.01.776	Outlet flange kit, for LIEBHERR® G9512			x			
31.01.777	Outlet flange kit, for LIEBHERR® G946, DOOSAN® GV158.3013.D			x			
31.01.779	Outlet flange kit, linkage for 2 VariFuel2 – series 200-1xx			x			
31.01.780	Outlet flange kit, for MAN® E2848/42 LE322, E3268 LE2xx, E3262 LE2xx			x			

4 Gas Inlet Flanges

P/N	Description	Thread	VariFuel2/VariFuel2+ (D= digital / M= manual)					
			100-60D/M	140-80D/M	200-120D/M	250-150D/M	300-190D/M	350-225D/M
30.30.102	Gas inlet flange	G 1	x	x				
30.30.102-NPT	Gas inlet flange	1 NPT	x	x				
30.30.103	Gas inlet flange	G 1 1/4	x	x				
30.30.103-NPT	Gas inlet flange	1 1/4 NPT	x	x				
30.30.104	Gas inlet flange	G 1 1/2	x	x				
30.30.104-NPT	Gas inlet flange	1 1/2 NPT	x	x				
30.30.106	Gas inlet flange	G 1 1/2			x			
30.30.106-NPT	Gas inlet flange	1 1/2 NPT			x			
30.30.107	Gas inlet flange	G 2			x			
30.30.107-NPT	Gas inlet flange	2 NPT			x			
30.30.108	Gas inlet flange	G 2 1/2			x			
30.30.108-NPT	Gas inlet flange	2 1/2 NPT			x			
30.30.114	Gas inlet flange	G 4				x		
30.30.116	Gas inlet flange	G 5					x	
30.30.118	Gas inlet flange	G 6						x

5 Stepper Motor Harness – Standard

P/N	Description	VariFuel2/VariFuel2+ (D= digital)						Equivalent to
		100-60D	140-80D	200-120D	250-150D	300-190D	350-225D	
31.01.942 5A	Stepper motor harness, MIL, 10 pole, socket , 90°, length 10 m (400 in)	x	x	x	x	x	x	
31.01.947-10	Stepper motor harness, MIL, 10 pole, socket , 90°, length 10 m (400 in), with corrugated tube	x	x	x	x	x	x	
31.02.087-10 5B	Stepper motor harness, MIL, 10 pole, socket , 90°, length 10 m (400 in)	x	x	x	x	x	x	31.01.942

5 Stepper Motor Harness – Special

P/N	Description	VariFuel2/VariFuel2+ (D= digital)						Equivalent to
		100-60D	140-80D	200-120D	250-150D	300-190D	350-225D	
95.30.942-32 ¹⁾	Stepper motor harness, MIL, 10 pole, socket , 90°, length 10 m (400 in), with fitting for 1/2 in flex conduit	x	x	x	x	x	x	

¹⁾ Flex conduit has to be ordered separately or supplied by customer.

Accessories for Stepper Motor Harness – Special

P/N	Figure	Description
15.07.112	5C	Flex conduit, 1/2 in, black ¹⁾
15.07.221	5D	Fitting, 1/2 in, junction box to flex conduit
06.05.075		Junction box

¹⁾ Flex conduit needs to be ordered in m/ft in required length.

6 VariStep3 Stepper Motor Driver ¹⁾

P/N	Supersedes	Description	VariFuel2/VariFuel2+ (D= digital)					
			100-60D	140-80D	200-120D	250-150D	300-190D	350-225D
31.01.960	31.01.955	VariStep3 stepper motor driver	x	x	x	x	x	x

¹⁾ For multiple mixer applications each VariFuel2 air/gas mixer needs a single VariStep3 stepper motor driver.




Air/Fuel Ratio Control Systems

Isolation Amplifier ¹⁾

P/N	Figure	Description	VariFuel2/VariFuel2+ Series (D= digital)					
			100-60D	140-80D	200-120D	250-150D	300-190D	350-225
63.02.017	1	Isolation amplifier, configurable	x	x	x	x	x	x

¹⁾ Used to pass on the position signal of an EmCon5 emissions controller to a second VariStep3 stepper motor driver. This way two VariFuel2 air/gas mixers can be controlled with one EmCon5 emission controller on a V-engine.

System Overview



Test Kit for Commissioning

P/N	Figure	Description	VariFuel2/VariFuel2+ (D= digital / M= manual)					
			100-60D/M	140-80D/M	200-120D/M	250-150D/M	300-190D/M	350-225D/M
01.56.001	1	Test Kit for commissioning, flow bodies for air/gas mixers	x	x	x	x	x	x

Test and Calibration Box for VariStep Stepper Motor Cards and Stepper Motors

P/N	Figure	Description	VariFuel2/VariFuel2+ Series (D= digital)					
			100-60D	140-80D	200-120D	250-150D	300-190D	350-225D
31.01.965	2	Test and calibration box for VariStep stepper motor cards and stepper motors	x	x	x	x	x	x

Tools for Repair and Maintenance

P/N	Figure	Description	VariFuel2/VariFuel2+ (D= digital / M= manual)								
			100-50	100-60	140-65	140-80	200-100	200-120	200-150	300-190	350-225
31.01.948-100	3	VariFuel2 adjustment tool for belt tension	x(D/M)	x(D/M)							
31.01.948-140	3	VariFuel2 adjustment tool for belt tension			x(D/M)	x(D/M)					
31.01.948-200	3	VariFuel2 adjustment tool for belt tension					x(D/M)	x(D/M)			
31.01.948-250	3	VariFuel2 adjustment tool for belt tension							x(D/M)		
31.01.948-300	3	VariFuel2 adjustment tool for belt tension								x(D/M)	
31.01.948-350	3	VariFuel2 adjustment tool for belt tension									x(D/M)
31.01.943	4	VariFuel2 locking tool for toothed pulley	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)
31.01.949	5	VariFuel2 tool for inspection window	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)
31.01.959	6	VariFuel2 tool for maintenance cap, for series 100-50 up to S/N 05014433	x(D/M)								



Air/Fuel Ratio Control Systems

Repair Kits for VariFuel2/VariFuel2+ Air/Gas Mixers

P/N	Description	VariFuel2/VariFuel2+ Series (D= digital / M= manual)								
		100-50	100-60	140-65	140-80	200-100	200-120	250-150	300-190	350-225
31.01.997-1-100-50A	Basic kit, series 100-50 (up to S/N 05015052)	x(D/M)								
31.01.997-1-100-50B	Basic kit, series 100-50 (from S/N 05015053)	x(D/M)								
31.01.997-1-100-60	Basic kit, series 100-60		x(D/M)							
31.01.997-1-140-65	Basic kit, series 140-65			x(D/M)						
31.01.997-1-140-80	Basic kit, series 140-80				x(D/M)					
31.01.997-1-200-100A	Basic kit, series 200-100 (up to S/N 05010012)					x(D/M)				
31.01.997-1-200-100B	Basic kit, series 200-100 (from S/N 05010267)					x(D/M)				
31.01.997-1-200-120A	Basic kit, series 200-120 (up to S/N 05015009)						x(D/M)			
31.01.997-1-200-120B	Basic kit, series 200-120 (from S/N 05015201)						x(D/M)			
31.01.997-1-250-150	Basic kit, series 250-150							x(D/M)		
31.01.997-1-300-190	Basic kit, series 300-190								x(D/M)	
31.01.997-1-350-225	Basic kit, series 350-225									x(D/M)
31.01.997-2-100-50A	Stepper motor kit, Rev. A, series 100-50 ¹⁾	x(D)								
31.01.997-2-100-50B	Stepper motor kit, Rev. B, series 100-50	x(D)								
31.01.997-2-A	Stepper motor kit, Rev. A, series 140 to 200 ¹⁾			x(D)		x(D)	x(D)			
31.01.997-2-B	Stepper motor kit, Rev. B, series 140 to 350		x(D)	x(D)	x(D)	x(D)	x(D)	x(D)	x(D)	x(D)
31.01.997-3-100-50A	Outlet nozzle kit, series 100-50 (up to S/N 05015052)	x(D/M)								
31.01.997-3-100-50B	Outlet nozzle kit, series 100-50 (from S/N 05015053)	x(D/M)								
31.01.997-3-100-60	Outlet nozzle kit, series 100-60		x(D/M)							
31.01.997-3-140-65	Inlet nozzle kit, series 140-65			x(D/M)						
31.01.997-3-140-80	Outlet nozzle kit, series 140-80				x(D/M)					
31.01.997-3-200-100	Inlet nozzle kit, series 200-100					x(D/M)				
31.01.997-3-200-120A	Inlet nozzle kit, series 200-120 (up to S/N 05015009)						x(D/M)			
31.01.997-3-200-120B	Inlet nozzle kit, series 200-120 (from S/N 05015201)						x(D/M)			
31.01.997-3-250-150	Inlet nozzle kit, series 250-150							x(D/M)		
31.01.997-3-300-190	Outlet nozzle kit, series 300-190								x(D/M)	
31.01.997-3-350-225	Outlet nozzle kit, series 350-225									x(D/M)
31.01.997-4	Gauge ports kit, series 100 to 350	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)	x(D/M)

¹⁾ Consult factory for availability.

Gaskets for Outlet Flange Kits ¹⁾

Gasket		Included in	P/N Outlet Flange Kit
P/N VariFuel-Sided	P/N Engine-Sided		
31.01.365	03.90.050	Outlet flange kit, gas relaxation section for throttle, series 50	31.01.764
31.01.365	03.90.100	Outlet flange kit, gas relaxation section for throttle, series 100	31.01.765
31.01.858	03.90.050	Outlet flange kit, gas relaxation section for throttle, series 50	31.01.766
31.01.858	31.01.365	Outlet flange kit, for MAN® E0834 LE302, E0836 LE202	31.01.768
31.01.809	31.01.876	Outlet flange kit, for MAN® E2876 LE202/212/302	31.01.750
31.01.809		Outlet flange kit, welding neck flange, DN100	31.01.752
31.01.809	31.01.858	Outlet flange kit, for MAN® E0836 LE202	31.01.753
31.01.809	31.01.867	Outlet flange kit, DN65-PN6	31.01.755
31.01.809	31.01.871	Outlet flange kit, for MAN® E2842 E312	31.01.756
31.01.809	03.90.100	Outlet flange kit, for throttle, series 100	31.01.757
31.01.809	03.90.100	Outlet flange kit, gas relaxation section for throttle, series 100	31.01.762
31.01.809	03.90.140	Outlet flange kit, gas relaxation section for throttle, series 140	31.01.763
31.01.809		Outlet flange kit, for LIEBHERR® G934, G944	31.01.773
31.01.809		Outlet flange kit, for LIEBHERR® G946	31.01.781
31.01.876		Outlet flange kit, for MAN® E2676 E302	31.02.113
31.01.879		Outlet flange kit, for MAN® E3262 E302	31.02.115
31.01.879		Outlet flange kit, for MAN® E0836 LE302	31.02.118
31.01.828		Outlet flange kit, welding neck flange, DN150	31.01.751
31.01.828	31.01.863	Outlet flange kit, for MAN® E2842 LE312	31.01.754
31.01.828		Outlet flange kit, hose connection, DN200	31.01.758
31.01.879	31.01.879	Outlet flange kit, for MAN® E2676 LE202/212, E2876 LE202/212/302	31.01.759
31.01.828		Outlet flange kit, welding neck flange, DN150 – aluminum	31.01.761
31.01.828	31.01.886	Outlet flange kit, for DEUTZ® TCG2015V6/V8	31.01.767
31.01.371, 31.01.828	31.01.371, 31.01.372	Outlet flange kit, for SHENG Dong® 600GF1-PS	31.01.772
31.01.828		Outlet flange kit, for LIEBHERR® G936	31.01.774
31.01.828		Outlet flange kit, for LIEBHERR® G9508	31.01.775
31.01.828		Outlet flange kit, for LIEBHERR® G9512	31.01.776
31.01.828		Outlet flange kit, for LIEBHERR® G946, DOOSAN® GV158.3013.D	31.01.777
31.01.828		Outlet flange kit, for LIEBHERR® G9508	31.01.778
31.01.828	31.01.377	Outlet flange kit, linkage for 2 VariFuel2 – series 200-1xx	31.01.779
31.01.828	31.01.828	Outlet flange kit, for MAN® E2848/42 LE322, E3268 LE2xx, E3262 LE2xx	31.01.780

¹⁾ Gaskets included in each outlet flange kit.

Air/Fuel Ratio Control Systems

NEW

VariFuel2-TEM Air/Gas Mixer

For **MWM®** TCG 2016 V08 C, V12 C and V16 C Gas Engines

The VariFuel2-TEM air/gas mixer is based on the proven design of the VariFuel2 series and is specially designed for use with MWM® gas engines. Designed as a replacement and plug-and-play solution for the gas mixers used on the TCG 2016 series, the VariFuel2-TEM easily fits into the existing engine structure without any mechanical modifications.


In addition to full compatibility, both mechanically and in connection with existing TEM controllers, the VariFuel2-TEM contributes to an improvement of the starting behavior and mixture control via its variable fuel ring and enables low-maintenance operation over a long period of time.

Features

- Plug-and-play solution for easy replacement of the original gas mixer without mechanical modifications or cabling adjustments
- 1 Suitable flanges for direct connection to existing intake manifold, suction hose and gas train
- 2 Stepper motor with connecting cable and mating connector to multifunction rail
- 3 Position sensor suitable for cabling of the multifunction rail
- Direct control by existing TEM management system
- The variable fuel ring of the VariFuel2-TEM improves the mixture control behaviour and thus enables an optimized starting behaviour and performance, especially in operation with special gases
- Low-maintenance part reduces operating costs by saving expensive repair kits



System Overview



VariFuel2-TEM Air/Gas Mixer for **MWM**® TCG 2016 V08 C, V12 C and V16 C Gas Engines

P/N	Supersedes	Description	Equivalent to
30.45.200-120DG-XA		VariFuel2-TEM air/gas mixer for MWM® TCG 2016 V08 C, V12 C and V16 C gas engines	

Flow Bodies for VariFuel2-TEM Air/Gas Mixer ¹⁾

P/N	Supersedes	Description	Diameter	Application	Fuel	Equivalent to
31.01.720-85.0-3		Flow body	85.0 mm	MWM® TCG 2016 V08 C	Biogas	
31.01.720-70.0-3		Flow body	70.0 mm	MWM® TCG 2016 V08 C	Natural gas	
31.01.720-60.0-3		Flow body	60.0 mm	MWM® TCG 2016 V12 C	Biogas	
31.01.720-30.0-3		Flow body	30.0 mm	MWM® TCG 2016 V12 C	Natural gas	

¹⁾ Flow body needs to be ordered separately according to application.



Please note that mentioned flow bodies are specified on basis of available engine data and are for reference only. Please consult the factory or your nearest MOTORTECH sales partner to get the correct flow body specified for your engine application.



Scan the QR code® to download the questionnaire to identify a suitable flow body for your application.

Air/Fuel Ratio Control Systems

VariStep3 MOTORTECH STEPPER MOTOR DRIVER

The stepper motor driver developed by MOTORTECH guarantees the ideal control of the various types of MOTORTECH VariFuel2 and VariFuel2+ air/gas mixers and ITB throttle bodies with integrated stepper motor.

Features

- Precise mixer and throttle adjustment due to microstep operation
- Very fast response times
- Increased power output provides high torque and quick movement even when driving big stepper motors
- Accelerated reference run
- LEDs displaying unit status and activity
- Combination of several units without signal amplifier/splitter
- Integrated CANopen and Modbus RTU interface
- Configuration via MICT software
- Error data logging for improved diagnostic options
- Compact design
- Plug-in terminals
- Easy access to connectors and switches
- Switch board installation on DIN rail



VariStep3 Stepper Motor Driver for VariFuel2/VariFuel2+ Air/Gas Mixers and ITB Integrated Throttle Bodies

P/N	Supersedes	Description
31.01.960	31.01.955	VariStep3 stepper motor driver

Technical Data

- 18 to 32 V DC power supply
- -20 °C up to +60 °C (-4 °F up to 140 °F) permitted ambient temperature
- 0 to 20 mA/ 0 to 10V analog input and output, flexible configuration
- 5 digital inputs, 5 to 32 V compatible, DC-isolated
- 6 digital outputs, up to 32 V, 100 mA, DC-isolated

Interfaces

- CAN Bus 2.0b interface (CANopen protocol)
- RS485 interface (Modbus RTU)
- USB 1.1 interface

Configuration

- Using the graphic user interface MICT (MOTORTECH Integrated Configuration Tool)
- Manual control via push-button

Housing

- Protection class IP 20
- Dimensions 160 x 126 x 62 mm (6.3 x 5.0 x 2.4 in)

EmCon5

MOTORTECH LEAN-BURN EMISSION CONTROLLER

The EmCon5 is a lean-burn emission controller for gas engine co-generation units. It is designed to control the exhaust gas emission levels based on indirect measurements. Simply three input signals are required for the control purpose: manifold inlet pressure and temperature and engine load. A CH₄ input signal is optional. Use of an oxygen sensor is not required.

Following initial measurements of the engine emission levels and successful analysis, the EmCon5 guarantees optimal operation of the gas engine at the predefined emission limits.

All controller parameters are freely programmable. The adjustments and modifications are made via the computer-program “WinScope”. The EmCon5 fits perfectly with the VariFuel2 and VariFuel2+ air/gas mixer series.



MAP




MAT

Features

- Standardized system available
- Operates without oxygen sensor
- Two gas qualities programmable
- Easy to use
- Available with complete sensor harness (optional)
- Data logging
- Flexible control for reliable operation with biogas

Air/Fuel Ratio Control Systems

System Overview



Air/Fuel Ratio Control Systems



Control Unit

P/N	Figure	Supersedes	Description	Equivalent to
63.02.011	1		EmCon5 lean burn emission controller	

Sensor Harness

P/N	Figure	Supersedes	Description	Equivalent to
06.30.045	2		EmCon5 sensor harness, including MAT sensor P/N 56.01.004 and MAP sensor P/N 56.02.017	

MAT – Manifold Air Temperature Sensors

P/N	Figure	Supersedes	Description	Thread	Fitting Length	Equivalent to
56.01.004	3	56.01.021	MAT sensor	G1/2	2.00 in (50 mm)	
56.01.011	3		MAT sensor	G1/2	3.00 in (75 mm)	
56.01.017	3		MAT sensor	G1/2	4.00 in (100 mm)	

MAP – Manifold Absolute Pressure Sensor (Industrial Design)

P/N	Figure	Supersedes	Description	Thread	Pressure Range	Equivalent to
56.02.017	4	56.02.016	MAP sensor	G1/4	0 to 3.0 bar	

Load Transducer

P/N	Figure	Supersedes	Description	Equivalent to
63.02.013	5		Load transducer, 0 to 5 A → 0 to 20 mA/4 to 20 mA/0 to 10 V/2 to 10 V	



[1](#)



[2](#)



[3](#)



[4](#)



[5](#)

Exhaust Gas Aftertreatment

NEW

VariSCR
MOTORTECH NO_x EMISSION CONTROLLER

VariSCR NO_x Emission Controller for SCR Catalysts

MOTORTECH developed the new NO_x emission controller VariSCR to satisfy the increasing immission protection requirements in the future from the amendment to the emission values in TA-Luft (Technical Instructions on Air Quality Control). In addition to the exhaust gas aftertreatment the VariSCR can also control the air/fuel ratio.

After a transition time up to 2018, NO_x reduction from a current 500 mg/m³ to 100 mg/m³ for natural gas CHP applications (based on a reference oxygen content of 5% by volume) will become obligatory for new and existing CHP plants. To bring about constant reduction of NO_x-emissions in the SCR (Selective Catalytic Reduction) system, AdBlue®, a solution of 32.5% urea in water, will be injected into the exhaust gas flow in front of the SCR catalysts. The urea is converted into ammonia through thermolysis and hydrolysis. In the SCR catalysts, the ammonia then reduces the nitrogen oxides to water and nitrogen.

Besides the algorithms for NO_x reduction, the software also contains controllers for controlling the pump module to maintain constant delivery pressure, the heating controller for the dosing unit as well as optionally the fill-level monitoring in the AdBlue®-storage tank.



Available System Components

- VariSCR NO_x emission controller
- Sensor harness
- Wiring harness for dosing unit
- Wiring harness for pump module


Features

- Read out of the NO_x sensors in front of and behind the catalysts
- Control of the urea injection to the NO_x set-point value through monitoring of the raw and target emission after the SCR catalysts
- Control of the urea pump for controlling and monitoring the AdBlue® injection quantity, temperature, and the delivery pressure
- Regulation of the AdBlue® heating and circulation
- Fault detection and diagnostics
- Connection to master control via CAN-Bus
- Air/fuel ratio control possible through control of the VariFuel2 air/gas mixer

Exhaust Gas Aftertreatment



System Overview



VariSCR NO_x Emission Controller

Technical data

- 18 to 32 V DC power supply
- -20 °C to +60 °C (-4 °F up to 140 °F) permitted ambient temperature
- 0 to 20 mA/ 0 to 10 V analog input and output, freely configurable
- 5 digital inputs, 5 to 32 V, compatible, galvanic separation
- 6 digital outputs, up to 32 V, 100 mA, galvanic separation

Interfaces

- 2 CAN Bus 2.0b interfaces (CANopen protocol)
- RS485 interface (Modbus RTU)
- USB 1.1 interface

Configuration

- Using the graphical user interface MICT (MOTORTECH Integrated Configuration Tool)

Housing

- Protection class IP 20
- Dimensions 160 x 126 x 62 mm (6.3 x 5.0 x 2.4 in)

■ Exhaust Gas Aftertreatment

Catalysts

For Efficient and Reliable Emission Reduction

Increasingly stringent emission regulations require the use of exhaust gas aftertreatment technologies for the operation of stationary gas engines. Exhaust gas catalysts play an important role in reducing harmful emissions and complying with legal limits, thus contributing to the protection of the environment.


MOTORTECH catalysts are always designed and manufactured according to customer and application requirements and guarantee a successful reduction of harmful emissions and compliance with legal limits. With different housing concepts, tailor-made catalysts or elements are created which fit perfectly into a customer plant construction or as a replacement in existing engine sites.

General Features

- Catalysts are designed and manufactured according to specific customer requirements
- Coatings are calculated and produced for each application's specifications
- Stainless steel modular construction includes nickel alloys or ceramic substrates resistant to high temperatures
- Catalysts can be supplied as complete units, elements with flanges or as replacement elements
- High quality substitute catalyst solutions are available to replace all popular catalyst brands

Technical Features

- Precise control over critical manufacturing parameters assures optimum performance and longevity
- Formulated to be durable and tolerant of common contaminants
- Coating formulations engineered for long life and strong response to chemical washings
- Each catalyst is individually serial numbered and inspected for 100% traceability



Exhaust Gas Aftertreatment



Oxidation Catalyst for CO and VOC Reduction On Lean-Burn Gas Engines

Oxidation catalysts convert carbon monoxide (CO) and volatile organic compounds (VOC's including formaldehyde) from lean-burn reciprocating engines. MOTORTECH oxidation catalysts use only platinum precious metal for high performance, long life, poison resistance, and their ability to be chemically regenerated time after time. Field proven catalyst products are available for 2-stroke and 4-stroke engines, high-propane fuels, low-BTU fuels, refinery gases, biogases and high-sulfur fuels.

3-Way (NSCR) Catalyst for NOx, CO and VOC Reduction On Rich-Burn Gas Engines

NSCR (non-selective catalytic reduction) catalysts convert nitrogen oxides (NOx), carbon monoxide (CO) and volatile organic compounds (VOC's including formaldehyde) from the exhaust of rich-burn gas engines. These engines, fueled by natural gas, wellhead gas, refinery gas and others are used in gas compression and power generation.



Scan the QR code® to download the questionnaire to identify a suitable catalyst for your application.

Catalyst Inquiry Form

Contact Data

Company	Contact person
Address	
Phone	Fax
Email	

Catalyst Sizing

Manufacturer and model	Engine operating principle
Engine power (kW)	Max. exhaust gas mass flow (kg/hr)
Max. exhaust gas flow (Nm³/s)	Exhaust temperature at catalyst (°C)
Exhaust content in exhaust gas (ppm by vol. SO ₂)	Exhaust content in exhaust gas (ppm by vol. H ₂)
Exhaust content in exhaust gas (ppm by vol. H ₂)	Exhaust content in exhaust gas (ppm by vol. CO)
Exhaust content in exhaust gas (ppm by vol. CO)	Exhaust content in exhaust gas (ppm by vol. NO _x)
Exhaust content in exhaust gas (ppm by vol. NO _x)	Exhaust content in exhaust gas (ppm by vol. VOC)

Raw Emissions

Hazardous substances	Value	Unit

Emission Limits


Hazardous substances	Value	Unit

Reference oxygen concentration (%)	Max. allowable pressure drop (kPa)
------------------------------------	------------------------------------

Sizing of Catalyst Housing


Housing type	Max. housing length (mm)	Max. housing weight (kg)
Exhaust gas inlet (mm)	Flange specification	Housing with measurement points

Individual Housing Solutions and Acoustical Silencers on Request!




Exhaust Gas Aftertreatment

Catalysts for common Applications



Catalysts for GE JENBACHER® Gas Engines

P/N	Figure	Description	Application	Cell Density	Shell		Matrix Depth	Equivalent to
					Diameter	Depth		
21.02.504-30089-001E	1	Oxidation catalyst element	J312	300 cpsi	504 mm	100 mm	89 mm	EP-AL 600 (000207)
21.02.520-20213-001E	2	Oxidation catalyst element	J312	300 cpsi	520 mm	213 mm	89 mm	EP-AL 534-AWT (000165), 608158
21.02.520-20089-001E	3	Oxidation catalyst element	J312	200 cpsi	520 mm	133 mm	89 mm	EP-AL 837 (000213), 607401
21.02.518-30059-001E	4	Oxidation catalyst element	J412	300 cpsi	518 mm	100 mm	89 mm	586171
CAT03S44	5	Oxidation catalyst element	J420	200 cpsi	610 mm	133 mm	89 mm	607405



Catalysts for MWM® Gas Engines

P/N	Figure	Description	Application	Cell Density	Shell		Matrix Depth	Equivalent to
					Diameter	Depth		
CAT03S61	1	Oxidation catalyst element	TCG 2016 V08 C	300 cpsi	300 mm	89 mm	89 mm	EP-AL 300-AWT (000196)
21.01.390-20108-001-E	2	Oxidation catalyst element	TCG 2016 V12 C	200 cpsi	390 mm	133 mm	108 mm	EP-AL 400-AWT (000203)
21.01.441-20108-001E	3	Oxidation catalyst element	TCG 2016 V16 B	200 cpsi	441 mm	133 mm	114 mm	EP-AL 450-AWT (000204)

Exhaust Gas Aftertreatment



Catalysts for **MAN**® Gas Engines

P/N	Figure	Description	Application	Cell Density	Shell		Matrix Depth	Equivalent to
					Diameter	Depth		
21.02.254-30089-001E	1	Oxidation catalyst element	E2876, E2848, E2842	300 cpsi	254 mm	100 mm	89 mm	EP-AL 250-AWT (000191)
21.02.310-20089-001E	2	Oxidation catalyst element	E2842	200 cpsi	310 mm	133 mm	89 mm	EP-AL 300-AWT (000196)
HOUA1005	3	Oxidation catalyst with universal flange (DN100 PN6)	universal	300 cpsi	264 mm	300 mm	89 mm	EP-AL 200-DN100 PN6 (000190)
21.02.260-20089-001E	4	Oxidation catalyst element	Agenitor 250 kW	200 cpsi	260 mm	133 mm	89 mm	
21.02.339-20089-001E	5	Oxidation catalyst element	Agenitor 400 kW	200 cpsi	339 mm	160 mm	89 mm	

Catalysts for **MTU**® Gas Engines

P/N	Figure	Description	Application	Cell Density	Shell		Matrix Depth	Equivalent to
					Diameter	Depth		
EC-1950-14-S-CS	6	Catalyst housing with flanges (DN350 PN10) and access door for installation of element P/N 21.01.495-30089-001E	12V4000 GS L32FB		518 mm	1140 mm		
21.01.495-30089-001E	6	Oxidation catalyst element, fits into housing P/N EC-1950-14-S-CS	12V4000 GS L32FB	300 cpsi	495 mm	89 mm	89 mm	
EC-2850-20-S-CS	6	Catalyst housing with flanges (DN500 PN10) and access door for installation of element P/N 21.01.724-30089-001E	20V4000 GS L32FB		724 mm	1140 mm		
21.01.724-30089-001E	6	Oxidation catalyst element, fits into housing P/N EC-2850-20-S-CS	20V4000 GS L32FB	300 cpsi	724 mm	89 mm	89 mm	

■ Gas Engine Accessories

NEW


Valve Cover Conversion Kit with Flange Safety Device for Spark Plug Leads For **MAN®** E32 Series Gas Engines

A defective or damaged spark plug due to incorrect installation cannot only affect the engine operation. The enormous pressures, especially of the latest engine designs, can be the reason a defective spark plug or parts of it are catapulted out of the cylinder like a bullet. This means danger to life and limb of service or operating staff working in the close engine environment.

The conversion kit designed by MOTORTECH reduces the danger on site. The spark plug lead is fixed with a safety flange directly on the valve cover with its appropriate support. The spark plug well is closed so tightly, that the release of components gets prevented and operational safety is increased.

Features

- Kit includes all items for easy conversion
- Valve cover with included flange support and valve cover gasket for all MAN® E32 series gas engines
- Safety flange for fixing the spark plug lead
- The innovative flange design allows easy locking and unlocking of the spark plug lead when service is required
- Specially designed PolyMot™ spark plug leads with embedded groove in the Teflon® insulator to take up the safety flange
- The spring-loaded secondary terminal guarantees a reliable connection of the spark plug and the spark plug lead
- A variety of PolyMot™ spark plugs leads is available to fit different spark plugs and ignition coil types (optional)



Valve cover with flange support and valve cover gasket



Safety flange for spark plug lead



PolyMot™ spark plug lead with embedded groove for safety flange



The flange with the locked spark plug lead is fixed on the valve cover with two screws to prevent the release of components from the spark plug well.



To unlock the spark plug lead the two screws just have to be loosened. The safety flange can now be turned aside on the flange support.



The spark plug lead can then be removed for replacing spark plugs or other service activities.

Conversion Kit

P/N	Description	Equivalent to	Qty per Cylinder
64.01.055	Valve cover conversion kit for MAN® E32 series gas engines Contains:		1 pc
	1 Safety flange for spark plug lead 1 pc	51.25441-0913	
	2 Hexagon head screws for fixing the flange on the valve cover 2 pcs	51.03401-5109 51.03905-0186	
	3 Valve cover with flange support 1 pc		
	4 Valve cover gasket 1 pc		

PolyMot™ Spark Plug Leads (need to be ordered separately) ¹⁾

P/N	Description	For Use with		Qty per Cylinder
		Ignition Coil	Spark Plug	
06.85.1073-18	PolyMot™ spark plug lead	06.50.100, 06.50.104, 06.50.112, 06.50.300	BERU® 14GZ-LL	1 pc
06.85.1074-18	PolyMot™ spark plug lead	06.50.100, 06.50.104, 06.50.112, 06.50.300	DENSO® GL3-3/GL3-5, BOSCH® 7308	1 pc
06.85.1078-18	PolyMot™ spark plug lead	06.50.100, 06.50.104, 06.50.112, 06.50.300	DENSO® GE3-1/GE3-5, BERU® 14R-4DIU2, BOSCH® 7315	1 pc
06.85.1079-18	PolyMot™ spark plug lead	06.50.100, 06.50.104, 06.50.112, 06.50.300	MOTORTECH B4321	1 pc
06.85.1080-18	PolyMot™ spark plug lead	06.50.100, 06.50.104, 06.50.112, 06.50.300	MOTORTECH B8324	1 pc

¹⁾ Other spark plug lead versions available on request.

Accessories

P/N	Description	Equivalent to	Qty per Cylinder
75.10.621	Safety flange for spark plug lead, incl. hexagon head screws for fixing the flange on the valve cover ¹⁾	51.25441-0913	1 pc

¹⁾ Already included in conversion kit P/N 64.01.055.

■ Gas Engine Accessories



Combustion engines, compressors, turbines, slide bearings and gears – they all depend on a reliable supply of lubricating oil. For trouble-free operation, each of those systems, dependent on the design, requires a precisely defined oil level that may only be exceeded or undercut by a narrow margin. Moreover, the lubricating capacity of the oil is depleted after a certain operating time – it has to be changed.

Oil level monitoring, oil refill, and even an automated oil change – in other words, the complete management of the oil cycle – can be realized in a completely reliable manner with MOTORTECH's OLC oil level controller.

Advantages for the User

- Elimination of regular monitoring of the oil level
- Operation is not interrupted for monitoring the oil level
- Operating errors are avoided, no overfilling/lack of oil
- Automated oil change possible
- Less work for staff, increase in operational safety
- Visual surveillance of the oil level during operation is possible
- Remote monitoring from a central location

Features

- Housing made of a high-grade, saltwater-resistant aluminum alloy
- Individually and infinitely adjustable float switches with reed contacts
- Potential-free closing or opening switches, no voltage transfer
- One-shot switches with step response and unambiguous switching states
- Contacts do not come into contact with oil, protection class IP 65
- Vibration-proof, no interference caused by worn rods/valve seats
- 2, 3 or 4 contacts
- Optional analog level indicator 4 to 20 mA
- Floats resistant to all oils
- Contact protection thanks to integrated resistor
- Switch point adjustment requires the use of tools

- Fail-safe wires
- Suitable for mineral and synthetic oils
- 2 oil and 2 equalization connectors
- Pipe connections with standard inch threads
- Sight glass made of impact-resistant polycarbonate
- Glass sealed with Perbunan (NBR)
- Interior painted white for optimal recognition of oil level
- Slotted holes allow for height adjustment during installation
- Indication of engine wear based on refill frequency
- Indication of water in lubricating oil is possible



Product Variants

Oil Level Controller with Float Switches



The devices of this OLC version are ideal for use with gas engines and they stand out for their reliable monitoring of the oil level.

The housing, made of a saltwater-resistant aluminum alloy, accommodates 2, 3 or 4 float switches. The float switches are screwed into the housing with a clamp screw connection. Any immersion depth can be adjusted with a swivel nut, which makes it possible to set the desired switch point. Subsequent readjustment is also possible without any problems.

A large sight glass made of impact-resistant polycarbonate enables the visual assessment of the current oil level. The white inner coating facilitates viewing even with poor light conditions.

The slotted holes and the optional use of the vertical or horizontal pipe connection threads constitute significant advantages during the installation.

Float Switch (displayed as MIN Contact)



Oil Level Controller with analog Level Sensor

Unlike an oil level controller with float switches, this OLC version uses reed contacts that are distributed evenly in the guide tube across the entire measuring range of 125 mm. Every reed contact is connected to a resistor. When the float rises or falls with the oil level, the magnetic forces of an annular magnet activate a reed contact through which an electrical current flows. The aforementioned resistors bring about a type of sliding resistance.

The variable electrical signal, created by different resistance values, is converted into a standard signal within a range of 4 to 20 mA by a measuring transducer that is connected by cable. This signal can be used in many different ways in a control system (e. g. ALL-IN-ONE). A visual display on a screen or an LED bar graph is also possible.


Two versions of the OLC can be equipped with one or two float switches in addition to the analog sensor in order to provide a redundant monitoring signal for the minimum or maximum oil level.

■ Gas Engine Accessories

Automatic Oil Refill

Monitoring the optimal oil level and signaling a lack of oil or overfilling with the OLC oil level controller is imperative for stationary gas engines that are in continuous operation. Therefore, upgrading to an automatic oil refill is logical and enables operation without supervision.

If the oil level falls short of the switch point for the refill contact (or the set electrical current with an analog sensor), then the engine control system sends a signal to the refill valve or to a refill pump. Fresh oil will be supplied to the engine until the refill contact interrupts the flow of oil.



Required Accessories

- 1 OLC oil level controller

Accessories

- A Solenoid/double solenoid valve ¹⁾
alternative
- B Oil pump ²⁾

Description

- C Engine
- D Piston
- E Crankshaft
- F Oil pan
- G Compensation line

¹⁾ An oil storage tank positioned above the engine, from which the oil flows by gravity, requires a solenoid valve for blocking, or better yet a double solenoid valve for reasons of redundancy.

²⁾ An oil storage tank located below the engine must be equipped with an electric pump.

1 Oil Level Controllers with Analog Level Sensor 4 to 20 mA – Transducer in Metal Housing

P/N	Description	Add. Float Switch	Cable Length	Cable Insulation
80.01.214	OLC oil level controller with analog level sensor		4.0 m	PVC
80.01.214-1104	OLC oil level controller with analog level sensor	MIN	4.0 m	PVC
80.01.214-1204	OLC oil level controller with analog level sensor	MAX	4.0 m	PVC
80.01.214-2104	OLC oil level controller with analog level sensor	MIN/MAX	4.0 m	PVC

1 Oil Level Controllers with two Float Switches

P/N	Description	Cable Length	Cable Insulation
80.01.210-2001	OLC oil level controller	1.0 m	PVC
80.01.210-2004	OLC oil level controller	4.0 m	PVC

1 Oil Level Controllers with three Float Switches

P/N	Description	Cable Length	Cable Insulation
80.01.210-3001	OLC oil level controller	1.0 m	PVC
80.01.210-3004	OLC oil level controller	4.0 m	PVC

1 Oil Level Controllers with four Float Switches

P/N	Description	Cable Length	Cable Insulation
80.01.210-4001	OLC oil level controller	1.0 m	PVC
80.01.210-4004	OLC oil level controller	4.0 m	PVC

A Double Solenoid Valves

P/N	Description	Coil Voltage	Maximum Pressure	Cable Length	Cable Insulation
81.00.310-01	Double solenoid valve, 2/2 way	230 V/50 Hz	24 bar	1.0 m	PVC
81.00.310-04	Double solenoid valve, 2/2 way	230 V/50 Hz	24 bar	4.0 m	PVC
81.00.311-01	Double solenoid valve, 2/2 way	24 V	16 bar	1.0 m	PVC
81.00.311-04	Double solenoid valve, 2/2 way	24 V	16 bar	4.0 m	PVC
81.00.312-01	Double solenoid valve, 2/2 way	12 V	16 bar	1.0 m	PVC
81.00.312-04	Double solenoid valve, 2/2 way	12 V	16 bar	4.0 m	PVC
81.00.313-01	Double solenoid valve, 2/2 way	24 V/50 Hz	24 bar	1.0 m	PVC
81.00.313-04	Double solenoid valve, 2/2 way	24 V/50 Hz	24 bar	4.0 m	PVC

A Solenoid Valves

P/N	Description	Coil Voltage	Maximum Pressure	Cable Length	Cable Insulation
81.00.300-01	Solenoid valve, 2/2 way	230 V/50 Hz	24 bar	1.0 m	PVC
81.00.300-04	Solenoid valve, 2/2 way	230 V/50 Hz	24 bar	4.0 m	PVC
81.00.301-01	Solenoid valve, 2/2 way	24 V	16 bar	1.0 m	PVC
81.00.301-04	Solenoid valve, 2/2 way	24 V	16 bar	4.0 m	PVC
81.00.302-01	Solenoid valve, 2/2 way	12 V	16 bar	1.0 m	PVC
81.00.302-04	Solenoid valve, 2/2 way	12 V	16 bar	4.0 m	PVC
81.00.303-01	Solenoid valve, 2/2 way	24 V/50 Hz	24 bar	1.0 m	PVC
81.00.303-04	Solenoid valve, 2/2 way	24 V/50 Hz	24 bar	4.0 m	PVC

B Oil Pumps

P/N	Description	Voltage	Connected Load	Protection class	Max. Pump Capacity	Max Pressure
81.00.510	Oscillating piston pump	230 V/50 Hz	30 W	IP 66	0.4 l/min.	0.7 bar
81.00.511	Oscillating piston pump	230 V/50 Hz	60 W	IP 65	1.5 l/min.	2.5 bar


■ Gas Engine Accessories

Coolant Filtration

Stainless Steel Coolant Filters for Stationary Applications

These bypass filters with stainless steel filter elements clean coolant liquids from all deposits. Elements can be washed and do not need to be disposed. Increases water pump life, cylinder head efficiency and equipment availability. Reduces service and maintenance cost.

Coolant should be clean and clear!



Features

- Easy to install
- Cleans and maintains coolant system from rust and contaminants
- Increases water pump life
- Reduces coolant deposits and increases cylinder head efficiency and life
- Stainless steel filter elements can be cleaned – NO WASTE
- Visual flow indicator (stationary applications)
- Easy to service – decreases maintenance cost
- Filter micron rating: standard – 50 micron optional – 25 micron
- Flow rate up to 30 GPM

Technical Advantage

- Inhibits electro-chemical degradation of engine components. An industrial gas engine has the characteristics of a large battery when coolant is circulated through the engine block. Contaminants and suspended solids in the coolant act as a conductor, which more readily allows current to flow throughout the engine block, which degrades EPDM, buna, rubber, viton, and soft metal or alloy components / water pump bearings, impellers, etc.
- Cleaned coolant inhibits corrosion on engine components such as cylinder heads, cylinder liners and seals, water pump impellers and bearings, etc.
- Prevents “flash-off” in the cylinder heads when engine has an emergency stop; as the coolant can properly dissipate thermal loads
- Inhibits scale deposits on all coolant passages and interior thermal surfaces of the engine block.

Standard – For Temperatures up to 200 °F/95 °C

P/N	Figure	Description	Element Outside Diameter	Element Length	Micron Rating ¹⁾	Stand	Flow Indicator	Equivalent to
25.00.009-50-30	1	Coolant filter	5.00 in	9.00 in	50 µm	30.00 in	X	489501
25.00.009-50	1	Coolant filter	5.00 in	9.00 in	50 µm		X	
25.00.018-50-49	1	Coolant filter	5.00 in	18.00 in	50 µm	49.00 in	X	489625
25.00.018-50	1	Coolant filter	5.00 in	18.00 in	50 µm		X	

¹⁾ For 25 micron filter elements please change part number from -50 to -25.

High Temperature – For Temperatures from 200 °F/95 °C up to 400 °F/205 °C

P/N	Figure	Description	Element Outside Diameter	Element Length	Micron Rating ¹⁾	Stand	Flow Indicator	Equivalent to
25.00.009-50-30-HT	1	Coolant filter	5.00 in	9.00 in	50 µm	30.00 in	X	
25.00.009-50-HT	1	Coolant filter	5.00 in	9.00 in	50 µm		X	
25.00.018-50-49-HT	1	Coolant filter	5.00 in	18.00 in	50 µm	49.00 in	X	
25.00.018-50-HT	1	Coolant filter	5.00 in	18.00 in	50 µm		X	

¹⁾ For 25 micron filter elements please change part number from -50 to -25.

Single Filter Elements

P/N	Figure	Description	Element Outside Diameter	Element Length	Micron Rating	Equivalent to
25.00.109-25	2	Coolant filter element	5.00 in	9.00 in	25 µm	
25.00.109-50	2	Coolant filter element	5.00 in	9.00 in	50 µm	489508
25.00.118-25	2	Coolant filter element	5.00 in	18.00 in	25 µm	
25.00.118-50	2	Coolant filter element	5.00 in	18.00 in	50 µm	489626

Shipping Cases for Filter Elements

P/N	Figure	Description	For Element Length	Equivalent to
25.00.209	3	Shipping case	9.00 in	
25.00.218	3	Shipping case	18.00 in	



■ Gas Engine Accessories



Lube Oil Filtration

Stainless Steel Lube Oil Filters

The re-cleanable stainless steel filters for oil filtration are the environmentally friendly alternative to commonly used disposable filters.

Due to re-using of elements, payback starts immediately after installation. Filters are available as replacements for OEM filter elements or custom made to fit your application.

Efficiency & Design Benefits

- 100% stainless steel construction
- Increased surface area and flow rates
- Longer fluid life
- High heat tolerances
- High resistance to chemicals and corrosion
- Extended maintenance intervals
- Improves filtration performance
- Absolute rated contaminant removal
- Direct OEM replacements which require no modification

Environmental Benefits

- Eliminates disposal costs
- Eliminates disposal liability
- Reduce landfill waste and environmental harm
- Recyclable

Economical Benefits

- Reduce inventory needs and costs
- A one-time cost that pays back quickly
- Environmentally friendly



100% Stainless Steel Construction

Stainless steel micronic wire cloth available in micron ratings of 3-400 absolute. Welded serial #, ID tag

304 or 316, 20-gauge stainless steel perforated inner/outer tube 3/16 in on 1/4 in centers

High heat resistant adhesive attaches end caps to filter

Seals available in Buna-N, HSN, Teflon® and Viton to suit your application

Stainless Steel Replacement Elements available for:

Engine and Compressor Filters

WAUKESHA®
WHITE SUPERIOR®
CATERPILLAR®
INGERSOLL RAND®
COOPER BESSEMER®
AJAX®

HERCULES®
GARDNER®
DENVER®
ATLAS®
CORPCO®

Process and Hydraulic Filters

PECO®
PALL®
PEACOCK®
CUNO®
FILTERITE®
NOWATA®
SCHROEDER®
POROUS MEDIA®
FAIREY ARLON®
UCC®
STAUFF®

BALDWIN®
FACET®
FRAM®
HILCO®
REFILCO®
NUGENT®
VICKERS®
GRESN®
HYCON®
PARKER®
HYTREX®

Filter Element Kits ¹⁾

P/N	Description	Element Outside Diameter	Element Length	Micron Rating	Number of included Elements	Application	Equivalent to
25.00.300-1-CA	Lube filter element kit	7.00 in	30.00 in	38 µm	1	CATERPILLAR® G3508/12/16	
25.00.301-6-CA	Lube filter element kit	7.00 in	13.00 in	38 µm	6	CATERPILLAR® G3606/08/12/16	
25.00.303-1-CA	Lube filter element kit	5.00 in	9.00 in	38 µm	1	CATERPILLAR® G3406/08	
25.00.310-4-WA	Lube filter element kit	3.00 in	15.00 in	25 µm	4	WAUKESHA®	167602B
25.00.310-7-WA	Lube filter element kit	3.00 in	15.00 in	25 µm	7	WAUKESHA®	167602B
25.00.310-14-WA	Lube filter element kit	3.00 in	15.00 in	25 µm	14	WAUKESHA®	167602B
25.00.311-4-WA	Lube filter element kit	3.00 in	30.00 in	25 µm	4	WAUKESHA®	168660B, 489493
25.00.311-7-WA	Lube filter element kit	3.00 in	30.00 in	25 µm	7	WAUKESHA®	168660B, 489493
25.00.312-1-WA	Lube filter element kit	5.00 in	7.00 in	75 µm	1	WAUKESHA®	208472B, 489488
25.00.313-1-WA	Lube filter element kit	5.00 in	10.00 in	75 µm	1	WAUKESHA®	208472C, 489489
25.00.314-10-WA	Lube filter element kit	3.00 in	30.00 in	25 µm	10	WAUKESHA®	168660H
25.00.320-3-WS	Lube filter element kit	4.00 in	18.00 in	25 µm	3	WHITE SUPERIOR® 6G/GT/GTL/GTLA-B	
25.00.320-4-WS	Lube filter element kit	4.00 in	18.00 in	25 µm	4	WHITE SUPERIOR® 8G/GT/GTL/GTLA-B/SGTB	
25.00.320-5-WS	Lube filter element kit	4.00 in	18.00 in	25 µm	5	WHITE SUPERIOR® 12G/GT/GTL/GTLA-B/SGT/SGTA-B	
25.00.320-7-WS	Lube filter element kit	4.00 in	18.00 in	25 µm	7	WHITE SUPERIOR® 16G/GT/GTL/GTLA-B/SGT/SGTA-B	
25.00.330-1-AR	Lube filter element kit	4.00 in	9.00 in	38 µm	1	ARIEL®	A-661, A-0661

¹⁾ All steel lube filter element kits are supplied with a shipping case.

Single Filter Elements

P/N	Description	Element Outside Diameter	Element Length	Micron Rating	Included in Element Kit	Engine Manufacturer	Equivalent to
25.00.300-CA	Lube filter element	7.00 in	30.00 in	38 µm	25.00.300-1-CA	CATERPILLAR® (Triple Length Element)	
25.00.301-CA	Lube filter element	7.00 in	13.00 in	38 µm	25.00.301-6-CA	CATERPILLAR®	1W-4136
25.00.302-CA	Lube filter element	7.00 in	10.00 in	38 µm		CATERPILLAR®	1R-0726
25.00.303-CA	Lube filter element	5.00 in	9.00 in	38 µm	25.00.303-1-CA	CATERPILLAR®	1R-0716, B99
25.00.310-WA	Lube filter element	3.00 in	15.00 in	25 µm	25.00.310-4/-7/-14-WA	WAUKESHA®	167602B
25.00.311-WA	Lube filter element	3.00 in	30.00 in	25 µm	25.00.311-4/-7-WA	WAUKESHA®	168660B, 489493
25.00.312-WA	Lube filter element	5.00 in	7.00 in	75 µm	25.00.312-1-WA	WAUKESHA®	208472B, 489488
25.00.313-WA	Lube filter element	5.00 in	10.00 in	75 µm	25.00.313-1-WA	WAUKESHA®	208472C, 489489
25.00.314-WA	Lube filter element	3.00 in	30.00 in	25 µm	25.00.314-10-WA	WAUKESHA®	168660H
25.00.315-WA	Lube filter element	5.00 in	17.00 in	25 µm		WAUKESHA®	489491, 305351E
25.00.316-WA	Lube filter element	4.00 in	8.00 in	25 µm		WAUKESHA®	489495, 304126
25.00.317-WA	Lube filter element	5.00 in	12.00 in	25 µm		WAUKESHA®	489490, 305315C
25.00.318-WA	Lube filter element	4.00 in	16.00 in	25 µm		WAUKESHA®	172607, 489522
25.00.320-WS	Lube filter element	4.00 in	18.00 in	25 µm	25.00.320-3/-4/-5/-7-WS	WHITE SUPERIOR®	758-133
25.00.330-AR	Lube filter element	4.00 in	9.00 in	38 µm	25.00.330-1-AR	ARIEL®	A-661, A-0661
25.00.335-EMD	Lube filter element	6.00 in	30.00 in	38 µm		EMD® Locomotive Engines	8345482

Accessories

P/N	Description	For use with Element/Element Kit	Equivalent to
25.00.222	Pressure gauge, liquid filled		
25.00.226	Grommet seal	25.00.311-WA	
25.00.228	Grommet seal, Viton	25.00.300-CA, 25.00.302-CA	
25.00.229	Seal kit	25.00.330-1-AR	
25.00.231	Grommet seal, Viton	25.00.310-WA, 25.00.311-WA, 25.00.314-WA	

■ Gas Engine Accessories

Ultrasonic Cleaning Equipment

Ultrasonic Cleaning Station

- 2,000 Watts of ultrasonic cleaning power
- All new, versatile size to meet a variety of parts cleaning needs
- Environmentally safe aqueous cleaning
- Easy-to-operate controls for time, temperature and cleaning cycle automation
- Stainless steel tank construction
- Dual filter system
- Oil removing surface sparger
- Optional on-board task light
- Heavy-duty locking casters
- High velocity ultrasonics, metallurgically attached transducers
- Ultrasonic frequency sweep to enhance cleaning performance



P/N	Description	
25.00.001-110 ¹⁾	Complete ultrasonic cleaning station, 110 V Contains: ■ Ultrasonic cleaner ■ Soak tank ■ Backwash cabinet ■ Drying cabinet	Included Accessories: ■ 13 Watt high intensity inspection light ■ Poly tubing roll ■ Bag sealer ■ Soak solution, two barrels ■ Detergent for ultrasonic, two 20 liter pails ■ Syphon pump for transfer of soak solution ■ Instruction video on cleaning procedures ■ Layout drawing for setting up station ■ Cleaning detergent for two years
25.00.001-220 ¹⁾	Complete ultrasonic cleaning station, 220 V Contains: ■ Ultrasonic cleaner ■ Soak tank ■ Backwash cabinet ■ Drying cabinet	Included Accessories: ■ 13 Watt high intensity inspection light ■ Poly tubing roll ■ Bag sealer ■ Soak solution, two barrels ■ Detergent for ultrasonic, two 20 liter pails ■ Syphon pump for transfer of soak solution ■ Cleaning video on cleaning procedures ■ Layout drawing for setting up station ■ Cleaning detergent for two years

¹⁾ Does not include high pressure washer. Customer preference; 2,000 PSI required.

Gas Engine Accessories



Subcomponents



Soak Tank

- Durable powder coated finish
- Inside tank dimensions 48 x 20 x 16 in
- 1,500 Watt screw in heat element with built in thermostat
- 110 Volt power requirements
- Castor wheels for easy movement of unit
- Hinged lid
- Recirculation pump with 30 minute timer
- Optional heated tank



Backwash Cabinet

- Powder coated finish
- Slotted subfloor parts rack
- Water backsplash curtain
- Adjustable parts rack
- Solids sediment waste water tank – 3 stage
- High pressure washer not included



Drying Cabinet

- 4,800 Watt – 16,000 BTU heating unit 210 V
- Durable powder coated finish
- Inside cabinet dimensions 48 x 30 x 24 in
- 30 minute timer
- Hinged door with latch closures

Further Ultrasonic Cleaning Models and Accessories are available on request.



Ultrasonic Cleaning Station Console Style Unit

- Inside tank dimensions 40 x 12 x 40 in
- Electric heater, thermostatically controlled, 4,000 watts
- Ultrasonics – 40 KHz, 3,000 watts with pulse and sweep
- Transducers mounted on one side wall of tank
- Mechanical timer (1-30 minutes)
- Stainless steel lift cover
- Power requirements 240 V, 10, 50/60 Hz, 8 KVA



Ultrasonic Cleaning Station Cabinet Model

- Inside tank dimensions 48 x 16 x 16 in
- 25 KHz
- Variable power controls
- Built-in heater
- “Neptune” generator with pulse and sweep
- All stainless 316L cabinet construction
- Stainless lift off cover
- Heavy duty castors
- Recessed controls
- Recessed tank drain
- Available in 110 or 220 volt
- 2 year warranty on all components



Cleaning Vessel

- Filtration of the cleaning fluid to enable maximum cleaning efficiency and extend cleaning solution life
- Pump is 110 V
- Filter unit consists of a stainless steel P2 vessel with a 1/2 HP high-temperature pump, discharge and suction hose

■ Technical Support & Service



Certified Quality

Quality means that the customer returns and not the product. This goal is achieved with a series of automated test procedures and tough endurance tests, which culminate in our zero-defect strategy. Various certifications (e.g. ISO 9001:2015) of the company as well as individual areas according to particularly strict customer and QM requirements for research and development, production, assembly and maintenance confirm the high level of our quality management.



Subsidiaries and Sales Partners

All MOTORTECH subsidiaries and sales partners are regularly trained by experienced staff so that we can keep our comprehensive quality promise to our most distant customers. MOTORTECH does not simply satisfy industry standards and requirements – we exceed them!



Consulting

MOTORTECH's customer-focused know-how provides support and consultation for your new developments, project planning, and problem analyses. Moreover, we are ready to assist you with advice and service at any time. Just give us a call! You can be sure that our team will find an optimal solution for your particular problem area.



Warehousing

In order to guarantee you the best possible delivery to any place in the world, MOTORTECH maintains an extensive stock of parts and finished products. Optimized order processing and selected global logistics partners deliver even the smallest parts directly to where they are needed.

Demo Cases

As a sales aid MOTORTECH offers several demo cases that allow the travelling staff to demonstrate and show latest MOTORTECH products to their customers. These demonstration devices and cases will support the sales staff in doing a professional product demonstration.

Features

- MIC4 demo case for functional simulation of MIC ignition controllers and visualization via PowerView3 HMI module. Includes one channel ignition output to drive a standalone spark gap.
- DetCon20 demo case for functional simulation of DetCon detonation control system. Can be connected to MIC4 demo case to demonstrate the interaction between ignition and detonation control and the visualization of DetCon data via PowerView3 HMI Module.
- Demo cases with ignition parts for CATERPILLAR® and WAUKESHA® gas engines including a selection of common ignition coils, spark plugs, different kind of leads and cutaway models of spark plug leads, harnesses, AlphaRail wiring rails, etc.

P/N	Description
01.16.002	MIC4 demo case incl. ignition controller, PowerView3 HMI module and IPS pickup simulator
01.16.003	Spark gap for connection to MIC4 demo case
01.36.001	DetCon20 demo case incl. detonation controller and detonation simulator unit
06.05.911	Demo case with common ignition parts for WAUKESHA® gas engines
06.05.912	Demo case with common ignition parts for CATERPILLAR® gas engines



MOTInside – MOTORTECH Information Center

MOTInside – All MOTORTECH sales and product information at your hand and always up to date on your USB flash drive.

MOTInside MOTORTECH Information Center provides you with all current MOTORTECH sales, service and product information on a USB flash drive. This information can be accessed via the software „MOTInside“, pre-installed on the flash drive, without having an internet connection.

Contains:


- Operating manuals
- Configuration software
- Datasheets and specification sheets
- Catalogues and brochures
- Sales & Service Bulletins

The document database on the USB flash drive can be updated regularly each time the flash drive has access to the internet via the computer it is plugged in.

MOTInside – Your perfect companion for selling MOTORTECH products.

P/N	Description
01.01.001	MOTInside – MOTORTECH Information Center

More information about MOTInside is available at:
www.motortech.de/motinsideen.html



■ Technical Support & Service



Technical Training at MOTORTECH – The Key to your Success!

Qualified personnel are the prerequisite for seamless and efficient operation of your equipment and engine. To a large extent they define the level of availability, reliability and lifespan of your systems. The newly built training center at our headquarters in Celle is designed to teach specialists the professional handling of MOTORTECH products. All trainings are based on a hands-on approach and have practical relevance.

- **Module 1:** Introduction into gas engine technologies, Introduction to the MOTORTECH product world
- **Module 2:** MIC ignition controllers with MOST technology, DetCon detonation control
- **Module 3:** VariFuel2 air/gas mixer, EmCon5 emission control, speed control with ITB throttle body series

MOTORTECH's current seminars offer know-how and realistic solutions for today's challenges for professionals in the gas engine industry. *Pragmatic – prompt – competent!*

The training system is structured modular. The particular modules complement each other and deal with the topic on a whole altogether. Trainings can also be offered on an individual basis in order to cover specific learning needs.

- **Module 4:** ALL-IN-ONE Generator & CHP Control System – Beginners course
- **Module 5:** ALL-IN-ONE Generator & CHP Control System – Basics course
- **Module 6:** ALL-IN-ONE Generator & CHP Control System – Advanced users

More details about our training, participation conditions and all necessary registration forms are available for download at: www.motortech.de. The MOTORTECH training team is happy to be at your disposal for every special question you might have.

Service Team

Take advantage of MOTORTECH's many years of technical expertise in maintenance, repair and service. Our team participates in an ongoing training program and is familiar with the technical and maintenance procedures of all commonly used systems. Our technicians will perform know-how repairs using the latest test instruments and tools, either at your company site or at our own workshops, even on products that we did not produce. Furthermore, to assure you with the best possible delivery anywhere in the world, MOTORTECH maintains an extensive inventory of parts and finished goods.

Always At Your Site

Regardless of which part of the globe we need to travel to, we know that the stakes are high, and therefore we also outperform the others. That is because we want everything to run smoothly at your site, everywhere and at anytime. This is entirely in keeping with our motto: Let us drop everything and work on your problem!

“There is hardly any place we would not be able to support your needs and back up our products with service”



MOTORTECH Flat Rate Repair and Overhaul Service for Ignition Controllers and VariFuel2 Air/Gas Mixers

Quality without Compromise

Take advantage of our comprehensive flat rate overhaul services. These options offer you knowing in advance what the cost will be. Our intensive repair, overhaul and test procedures allow a full year of warranty on all ignition controllers and VariFuel2 air/gas mixers remanufactured by MOTORTECH.

Our economically remanufacturing processes cover intensive inspections, parts replacements, extensive reconditioning and full operational test procedures. Within an average of four weeks (depends on customer location) we return a fully functional product that looks as good as new.

Repair and Overhaul Service for Ignition Controllers **NEW**

Ignition controllers are subjected to extreme loads and must fulfill a wide range of technical requirements under very tough conditions. Parts that are constantly under stress will wear out and tend to fail. Based on years of technical experience MOTORTECH offers a repair and overhaul service for almost all popular ignition controllers in the field.



Complete Repair and Overhaul of:

- ALTRONIC® D.I.S. series
- ALTRONIC® DISN series
- ALTRONIC® CPU95 series
- ALTRONIC® CPU2000 series
- CATERPILLAR® ignition controllers for G3300 & G3400 series gas engines
- All FAIRBANKS MORSE® ignition controllers ¹⁾
- All MOTORTECH ignition controllers
- WAUKESHA® CEC series
- WAUKESHA® IPM-Diagnostic
- All WOODWARD® ignition controllers

¹⁾ Please note that due to difficulties in obtaining spare parts for FAIRBANKS MORSE® ignition controllers, we reserve the right to refuse repairs if sent in units are in a condition that is too poor for repair or overhaul. No warranty can generally be assumed for repairs of FAIRBANKS MORSE® ignition controllers carried out by MOTORTECH.

Repair and Overhaul Service for VariFuel2 Air/Gas Mixers **NEW**

MOTORTECH also offers a flat rate program for the repair and overhaul of the VariFuel2 air/gas mixers. Sent gas mixers are completely dismantled during the revision process and all components are thoroughly cleaned and tested. During subsequent assembly, defective or worn components are replaced. A final function test and a leakage test guarantee further faultless operation for a long time. As part of plant maintenance, this service is also available for functioning gas mixers to ensure continued operation.



Complete Repair and Overhaul of VariFuel2/VariFuel2+ Air/Gas Mixers:

- Series 100-50
- Series 100-60
- Series 140-65
- Series 140-80
- Series 200-100
- Series 200-120
- Series 250-150
- Series 300-190
- Series 350-225

A-Z

Topic	Page
A	
Accessories for Unshielded Ignition Coils	40
Accessories for Unshielded Spark Plug Leads.....	84
Actuator Replacement Kit	182
Air/Gas Mixers (VariFuel2)	194
Air/Gas Mixers for MWM® Gas Engines (VariFuel2-TEM) ...	206
C	
Catalysts.....	214
Consulting	230
D	
Detonation Control System – DetCon.....	148
Detonation Control Visualization (PowerView3)	153
E	
Emission Control System for SCR Catalysts (VariSCR)	212
Emission Control System – EmCon5	209
Extension Overhaul Kits for Ignition Coils	39, 95
Extensions for Ignition Coils	38, 94
Extensions for Integral Ignition Coils	97
Extensions for Shielded Spark Plugs	97
F	
Filtration – Coolant	222
Filtration – Lube Oil.....	226
G	
Generator & CHP Control System – ALL-IN-ONE	178
H	
Hardware Kit for WAUKESHA® VHP-GL Engines	46
Harnesses for Competition Ignition Control Systems.....	30
High Voltage Clamp (SparkScan1).....	115
High Voltage Indicator (SparkView)	114
I	
Ignition Coil Conversion Kits	37
Ignition Coil for WÄRTSILÄ® Gas Engines.....	36
Ignition Coil Tester.....	116
Ignition Coils for CATERPILLAR® Gas Engines	34

Topic	Page
Ignition Coils – ALTRONIC® Style	33
Ignition Coils – Externally Mounted	48
Ignition Coils – Externally Mounted with Diagnostic Interface	49
Ignition Coils – Flange Design.....	42
Ignition Coils – Flange Design with Diagnostic Interface	44
Ignition Coils – Flange Design with Diagnostic Interface and integrated Primary Lead.....	45
Ignition Coils – Flange Design with integrated Primary Lead	43
Ignition Coils – Integral Design	50
Ignition Coils – MOTORTECH Style	33
Ignition Coils – New MOTORTECH Style.....	32
Ignition Control Visualization (PowerView3)	26
Ignition Controllers – MIC3+ Series	12
Ignition Controllers – MIC3+CATDI.....	14
Ignition Controllers – MIC3+CEC.....	14
Ignition Controllers – MIC4 Series	15
Ignition Controllers – MIC4-ZS	18
Ignition Controllers – MIC5 Series	19
Ignition Controllers – MIC6 Series.....	21
Ignition Kits for Unshielded Applications	109
Ignition System for Single Cylinder Gas Engines (MOT601).....	28
Ignition Wiring Rail Upgrade Kits.....	104
M	
MOTORTECH Information Center (MOTInside).....	231
MOTORTECH Integrated Configuration Tool (MICT)	9
MOTORTECH Output Stage Technology (MOST)	8
O	
Oil Level Control System (OLC)	220
P	
Pickup Leads.....	57
Pickup Simulator (IPS)	117
Pickups.....	54

Topic	Page
Pickups for Special Applications	56
Primary Leads	66
Primary Leads for MOTORTECH AlphaRail Wiring Rails	70
Primary Leads for Special Applications.....	69
Protractor, Digital	120
R	
Reluctor Pins.....	60
Repair Kits for Shielded Spark Plug Lead Terminals.....	91
S	
Scope Meter, Digital	115
Sensor Harnesses	191
Sensors	188
Sensors – Manifold Absolute Pressure (MAP)	190
Sensors – Manifold Air Temperature (MAT)	190
Service Team.....	232
Spark Plug Accessories.....	146
Spark Plug Cleaning Kit	140
Spark Plug Extensions – PolyMot™.....	92
Spark Plug Leads (Non PolyMot™ Style)	80
Spark Plug Leads for CATERPILLAR® Gas Engines	78
Spark Plug Leads – PolyMot™	72
Spark Plug Leads – Shielded – Conventional.....	90
Spark Plug Leads – Shielded – MOT-Blues	88
Spark Plug Tools.....	140
Spark Plugs with extended Barrels (XT-Plugs)	134
Spark Plugs with extended Barrels (XTL-Plugs)	136
Spark Plugs – Bridge Design (MBP1800).....	130
Spark Plugs – DENSO®	124
Spark Plugs for Integral Ignition Coils (ICP-Plugs)	133
Spark Plugs – MHP-Plugs.....	129
Spark Plugs – Pre-Chamber Design (MPC1900)	131
Stepper Motor Driver (VariStep3)	208
T	
Technical Training	232

Topic	Page
Temperature Module Visualization (PowerView3)	159
Temperature Module with 20 Channels (TempScan20)...	158
Test Adaptor for Ignition Controllers	118
Thermocouple Rails.....	184
Thermocouples	186
Throttle Bodies	167
Throttle Bodies for MAN® Gas Engines	174
Throttle Bodies for WAUKESHA® Gas Engines.....	176
Throttle Bodies with Integrated Stepper Motor (ITB).....	170
Timing Light (Conventional)	120
Timing Light (ScopeLite)	119
Tools & Accessories for Triggering	64
Trigger Discs	58
Trigger Drives	60
Trigger Magnets	60
U	
Ultrasonic Cleaning Equipment.....	228
Unshielded Safety Leads for Shielded Spark Plugs (USL)	81
V	
Valve Cover Conversion Kit.....	111, 218
W	
Wiring Rail Kits for CATERPILLAR® Gas Engines.....	106
Wiring Rail System for Detonation Control (AlphaRail)....	154
Wiring Rail System for Ignition Control (AlphaRail)	98
Wiring Rail System for Temperature Control (AlphaRail)..	160
Workshop Equipment.....	120

■ Index

P/N	Page	P/N	Page	P/N	Page
01.01.001	231	02.85.995-2	91	06.02.026-25	193
01.16.002	231	02.85.996	91	06.02.026-50	193
01.16.003	231	02.85.996-2	91	06.02.027	12, 16
01.36.001	231	02.85.997	91	06.02.028	12, 16
01.56.001	203	02.85.997-2	91	06.02.034-160	12, 16, 19
1R-0716.....	227	02.85.1006	91	06.02.035-160	12, 16, 19
1R-0726.....	227	02.85.1007	91	06.02.036-160	12, 16, 19
1W-4136.....	227	02.85.1008	91	06.02.040-160	12, 16, 19
02-0004-174	193	02.85.1012	41	06.02.041-160	12, 16, 19
02.85.015-100	146	02.85.1012-100	86	06.02.046-160	14
02.85.016-100	146	02.99.004-100	85	06.02.048-160	24
02.85.017-100	146	2W-3742.....	30	06.02.049-160	24
02.85.757	84	2W-3744.....	30	06.02.617-L.....	16
02.85.758	84	2W-3747.....	33	06.02.618-L.....	12
02.85.814-82	84	2W-3748.....	30	06.05.075	13, 17, 20, 24,103, 157, 173, 201
02.85.865-82	84	03.90.050	205	06.05.076	165
02.85.870	95, 96	03.90.100	205	06.05.085	27, 153, 159, 165
02.85.881	95, 96	03.90.140	205	06.05.086-F.....	27, 153, 159
02.85.914-82	84	3E-7639.....	188	06.05.086-U	27, 153, 159
02.85.920-100	85	4W-2256.....	133	06.05.088-F.....	165
02.85.924-100	85	4W-4959.....	50	06.05.088-U	165
02.85.925-100	85	4W-5439.....	33	06.05.089-65	192
02.85.965-82	84	4W-5466.....	31	06.05.092-65	192
02.85.979	91	4W-5468.....	31	06.05.185	27, 153, 159, 165
02.85.991	91	06.00.511	117	06.05.186	27
02.85.991-2	91	06.01.040-L.....	70	06.05.187	27, 153, 159, 165
02.85.992	91	06.01.041-L.....	70	06.05.903-1	120
02.85.992-1	91	06.01.042-L.....	70	06.05.904-1	120
02.85.992-2	91	06.01.043-L.....	70	06.05.911	231
02.85.992-3	91	06.01.044-L.....	70	06.05.912	231
02.85.993	91	06.01.045-L.....	70	06.20.025	59
02.85.993-2	91	06.01.046-L.....	70	06.20.025-1	59
02.85.994	91	06.01.047-L.....	70	06.20.026	59
02.85.994-2	91	06.02.026-5	193	06.20.026-1	59
02.85.995	91	06.02.026-15	193		

P/N	Page	P/N	Page	P/N	Page
06.20.045-1	59	06.20.403	59	06.30.164	191
06.20.045-6	59	06.20.404	59	06.30.165-15000	191
06.20.045-8	59	06.22.400-1	61	06.30.166	192
06.20.069-1	59	06.22.400-6	61	06.31.030-1	30
06.20.069-6	59	06.22.400-8	61	06.31.030-2	30
06.20.069-12	59	06.23.001	61	06.31.032-1	30
06.20.070	59	06.23.004	61	06.31.032-2	30
06.20.251	59	06.30.022	191	06.50.003	33, 101
06.20.252	59	06.30.023	191	06.50.007	33
06.20.254	59	06.30.024	191	06.50.034	42, 43, 44
06.20.300	58	06.30.025	191	06.50.034-L-C	43
06.20.301	58	06.30.026	191	06.50.034-L-D	43
06.20.302	58	06.30.027	191	06.50.035	42, 43, 44, 45, 46
06.20.303	58	06.30.028	191	06.50.035-30-A	43, 45
06.20.304	58	06.30.039	192	06.50.035-36-E	43, 45
06.20.305	58	06.30.040	192	06.50.035-L-C	43
06.20.306	58	06.30.041	192	06.50.035-L-D	43
06.20.307	58	06.30.042	191	06.50.036	42, 44
06.20.308	58	06.30.043	191	06.50.036-L-C	43
06.20.309	58	06.30.044	192	06.50.036-L-D	43
06.20.310	58	06.30.045	211	06.50.053	33, 101
06.20.311	58	06.30.053	192	06.50.054	33, 101
06.20.312	58	06.30.054	192	06.50.055	29, 33, 101
06.20.313	58	06.30.055	192	06.50.059	36
06.20.314	58	06.30.056	192	06.50.060	33, 101
06.20.316	58	06.30.060	191	06.50.065	33, 101
06.20.317	58	06.30.093	191	06.50.100	32, 101
06.20.318	58	06.30.100	193	06.50.102	32, 101
06.20.319	58	06.30.101	191	06.50.103	33, 101
06.20.321	58	06.30.102	191	06.50.104	32, 101, 109,
06.20.322	58	06.30.110	188	110, 111, 112, 113	
06.20.323	58	06.30.111-60	69	06.50.105	32, 101
06.20.400	59	06.30.112	186	06.50.111	35
06.20.401	59	06.30.162	192	06.50.112	32, 101, 111, 112
06.20.402	59	06.30.163-15000	192	06.50.113	32, 101

Index

P/N	Page	P/N	Page	P/N	Page
06.50.141	34, 39, 95	06.60.022	54	06.80.116-100	86
06.50.142	34, 39, 95	06.60.023	54	06.80.116-180	41
06.50.143	34, 39, 95	06.60.027	54	06.80.116-180-100	86
06.50.144	34, 39, 95	06.60.040	54	06.80.126	41, 122
06.50.145	34, 39, 95	06.60.042	54	06.80.126-100	86
06.50.146	34, 39, 95	06.60.101	54	06.80.145-1	38, 94
06.50.147	34, 39, 95	06.60.102	54	06.80.145-2	38, 94
06.50.148	34, 39, 95	06.60.103	54	06.80.202	93
06.50.151	34, 39, 95	06.60.105	54	06.80.202-T	93
06.50.152	34, 39, 95	06.60.107	54	06.80.206	93
06.50.153	34, 39, 95	06.60.900	60	06.80.206-T	93
06.50.154	34, 39, 95	06.60.908	64	06.80.213	93
06.50.155	34, 39, 95	06.60.922	60	06.80.213-T	93
06.50.156	34, 39, 95	06.60.925	60	06.80.261	41, 82
06.50.157	34, 39, 95	06.60.926	64	06.80.261-100	85
06.50.158	34, 39, 95	06.70.191-180	30	06.80.279H	96
06.50.159	34, 39, 95	06.70.192-5	116	06.80.280H	96
06.50.160	34, 39, 95	06.70.192-6	116	06.80.309	93
06.50.161	35, 38, 94	06.71.001-L	57	06.80.309-T	93
06.50.162	35, 38, 94	06.71.002-L	57	06.80.310	93
06.50.164	35, 38, 94	06.71.007	57	06.80.310-T	93
06.50.165	35, 38, 94	06.75.103	64	06.80.315H	39, 96
06.50.170	35, 38, 94	06.77.006-72	30	06.80.319	93
06.50.174	35, 38, 94	06.77.006-96	30	06.80.319H	93
06.50.175	35, 38, 94	06.80.005	40	06.80.319-T	93
06.50.300	32, 101, 109, 110, 111, 112	06.80.006	40	06.80.320	93
06.50.301	32, 101	06.80.012-100	86	06.80.320H	93
06.51.133	95, 96	06.80.036	40	06.80.320-T	93
06.51.134	95, 96	06.80.037	40	06.80.321	46, 93
06.51.136	95, 96	06.80.091	41	06.80.321H	93
06.51.223	41	06.80.091-100	85	06.80.321-T	46, 93
06.51.248	77	06.80.104	60, 120	06.80.330	93
06.60.020	54	06.80.108	41	06.80.330-T	93
06.60.021	54	06.80.108-100	86	06.80.335H-1	96
		06.80.116	41, 122	06.80.340	93

P/N	Page	P/N	Page	P/N	Page
06.80.340-T.....	93	06.80.753-2	95	06.84.044-100	77, 87
06.80.349-L.....	96	06.80.754	39, 95, 96	06.84.047-100	87
06.80.356H	94	06.80.754-2	95, 96	06.84.048-100	87
06.80.360H	94	06.80.755-T.....	93	06.84.049-100	87
06.80.376-10	96	06.80.756-T.....	93	06.84.053-100	87
06.80.376-L.....	96	06.80.764	39, 95	06.84.059	74, 75, 76,77, 78, 80, 95, 96
06.80.381H	93	06.80.1013-T.....	38, 94	06.84.059-100	77, 87
06.80.415H	39, 96	06.80.1132	93	06.84.069	52
06.80.417H	39, 96	06.80.1134	93	06.84.077	76, 77
06.80.418H	39, 96	06.81.017	80	06.84.077-100	77, 87
06.80.419H	39, 96	06.81.051	95, 96	06.84.082	40
06.80.420H	39, 96	06.81.071	80	06.84.083	40
06.80.459H	38, 94	06.81.084	95, 96	06.84.090	87
06.80.460	38, 94	06.84.006	40	06.84.116	52
06.80.461	38, 94	06.84.008-100	85	06.84.117	52
06.80.469-T.....	93	06.84.009-100	85	06.84.121	77, 80
06.80.471-T.....	93	06.84.010-100	84	06.84.121-100	77, 87
06.80.480	39, 96	06.84.011	87	06.85.083-22	74
06.80.481	96	06.84.021	40	06.85.178-20	75
06.80.515H	39, 96	06.84.024	41	06.85.179-20	18, 75
06.80.600	38, 94	06.84.024-100	84	06.85.271	76
06.80.602	38, 94	06.84.025	41	06.85.272	76
06.80.741	39, 95	06.84.025-100	84	06.85.281	76
06.80.741-2	95	06.84.026	52	06.85.306-18	76
06.80.742	39, 95, 96	06.84.033	74, 77, 80	06.85.310H-11	18, 75
06.80.742-2	95, 96	06.84.033-100	77, 87	06.85.312	76
06.80.743	39, 95	06.84.034	80	06.85.320H-18	75
06.80.743-2	95	06.84.034-100	77, 87	06.85.326-16	76
06.80.744	39, 95, 96	06.84.038	80	06.85.357-26	76
06.80.744-2	95, 96	06.84.038-100	77, 87	06.85.379	80
06.80.751	39, 95	06.84.040	74, 75, 76, 77,80, 87, 93, 95, 96	06.85.380	80
06.80.751-2	95	06.84.040-100	77, 87	06.85.415H-16	74
06.80.752	39, 95, 96	06.84.043-100	84	06.85.422-16	76
06.80.752-2	95, 96	06.84.044	74, 75, 76, 77, 78, 80	06.85.423-16	76
06.80.753	39, 95				

Index

P/N	Page	P/N	Page	P/N	Page
06.85.429-14	76	06.85.836H-16	75, 109, 110	06.85.1019-16	74, 78
06.85.479	75	06.85.839H-16	74, 109	06.85.1020-24	74
06.85.487-18	74	06.85.848-16	76	06.85.1023-18	75, 111, 112
06.85.505-18	74	06.85.860-16	80	06.85.1030-16	74
06.85.514-16	80	06.85.864-26	74	06.85.1031-16	74, 109, 110
06.85.528-14	74	06.85.873-18	74	06.85.1037-16	74, 109
06.85.577H-16	74	06.85.894-18	76	06.85.1038-20	75, 109
06.85.580H-18	74	06.85.903-22	80	06.85.1042-18	75, 111, 112
06.85.586-14	74	06.85.908-22	74, 75, 76	06.85.1044-27	80
06.85.594-22	74	06.85.908-22-0	74	06.85.1046-16	80
06.85.649-16	76	06.85.909-24	74	06.85.1047-24	74
06.85.667-26	76	06.85.910-18	74	06.85.1049-16	74
06.85.670-16	74	06.85.912-24	76	06.85.1050-18	75
06.85.672H-22	76	06.85.913-30	76	06.85.1054-18	74, 78
06.85.675-16	74	06.85.926-20	74	06.85.1058-18	75
06.85.678-24	76	06.85.929-20	75, 109	06.85.1062-16	80
06.85.683-18	74	06.85.939-18	78	06.85.1063-14	76
06.85.688-16	76	06.85.945-16	76	06.85.1066-12	74
06.85.689-24	80	06.85.949-10	80	06.85.1068-18	74
06.85.690-24	80	06.85.952	80	06.85.1069-20	74
06.85.695-24	80	06.85.954-16	74	06.85.1070-18	75
06.85.697-20	80	06.85.957-22	74	06.85.1071-18	74
06.85.698-30	80	06.85.958-16	74	06.85.1072-28	75
06.85.699-16	76	06.85.959-18	75, 111, 112	06.85.1073-18	75, 111, 112, 219
06.85.705-16	76	06.85.964-20	80	06.85.1074-18	75, 111, 112, 219
06.85.709H-18	74	06.85.966-35	74	06.85.1078-18	75, 111, 112, 219
06.85.714-24	76	06.85.988-18	74	06.85.1079-18	75, 111, 112, 219
06.85.717H-24	74	06.85.989-18	74	06.85.1080-18	75, 111, 112, 219
06.85.719-16	80	06.85.993-24	76	06.85.1081-14	75
06.85.720-18	76	06.85.998-20	75	06.86.001-100	86
06.85.723-24	76	06.85.999-14	76	06.86.002-100	86
06.85.739-16	76	06.85.1000-14	76	06.86.003-100	86
06.85.751-18	74, 78	06.85.1005-24	75	06.86.005-100	86
06.85.773-15	80	06.85.1006	80	06.88.009-16	78
06.85.835-18	74	06.85.1014-12	74	06.88.010-16	78

P/N	Page	P/N	Page	P/N	Page
06.88.015-48	80	06.98.109	122	07.98.063	144
06.90.099-100	114	06.98.130	118	07.98.064-14	145
06.90.099-105	114	06.99.200-1	101	07.98.064-18	145
06.90.100	114, 115	06.99.200-2	101	07.98.064-78	145
06.90.104-100	119	06.99.200-3	101	07.98.065	144
06.90.104-200	119	6I-0407	186	07.98.066-BEX6.....	145
06.90.104-300	119	7/8GZ9.....	129, 143	07.98.066-BEX12.....	145
06.90.104-400	119	7/8GZ11.....	129, 143	07.98.067-BEX6.....	145
06.90.104-600	119	07.70.001	117	07.98.067-BEX12.....	145
06.90.105	114, 115	07.70.002-1	117	07.98.070-14	145
06.90.264	41	07.70.002-2	117	07.98.070-18	145
06.95.058	64	07.70.002-3	117	07.98.113	142
06.98.005-110	115	07.70.003	117	07.98.114-12	144
06.98.005-220	115	07.70.004	117	07.98.114-12-BEX6	144
06.98.011	122	07.70.005	117	07.98.114-12-BEX12	144
06.98.013	122	07.70.006	117	07.98.114-34	144
06.98.017	122	07.70.009	117	07.98.114-34-BEX6	144
06.98.019	122	07.70.010	117	07.98.114-34-BEX12	144
06.98.043-10	120	07.70.011	117	07.98.118-12	144
06.98.043-30	120	07.70.012	117	07.98.118-12-BEX6	144
06.98.046	122	07.70.013	117	07.98.118-12-BEX12	144
06.98.047	122	07.70.014	117	07.98.118-34	144
06.98.048	122	07.70.015	117	07.98.118-34-BEX6	144
06.98.050	122	07.98.022	144	07.98.118-34-BEX12	144
06.98.051	122	07.98.023	144	07.98.120-14	142
06.98.054	116	07.98.024	144	07.98.120-18	142
06.98.054-1	116	07.98.025	144	07.98.120-78	142
06.98.054-2	116	07.98.026	144	07.98.121-14	142
06.98.054-3	116	07.98.026-1	144	07.98.121-18	142
06.98.054-4	116	07.98.034	142	07.98.121-78	142
06.98.054-5	116	07.98.035	142	07.98.122-A	142
06.98.054-6	116	07.98.036	142	07.98.122-B	142
06.98.054-7	116	07.98.037	142	07.98.122-C	142
06.98.096	120	07.98.047	117	07.98.122-D	142
06.98.100-200	119	07.98.059	142	07.98.122-E.....	142

■ Index

P/N	Page	P/N	Page	P/N	Page
07.98.122-F.....	142	09.02.1300-L.....	81	09.02.3311-L.....	82
07.98.131	142	09.02.1301-L.....	81	09.02.4000-L.....	82
07.98.178-58	144	09.02.1310-L.....	81	09.02.4001-L.....	82
07.98.178-58-BEX6	144	09.02.1311-L.....	81	09.02.4100-L.....	82
07.98.178-58-BEX12	144	09.02.2000-L.....	81	09.02.4101-L.....	82
07.98.178-78	144	09.02.2001-L.....	81	09.02.4110-L.....	82
07.98.178-78-BEX6	144	09.02.2010-L.....	81	09.02.4200-L.....	82
07.98.178-78-BEX12	144	09.02.2011-L.....	81	09.02.4201-L.....	82
07.98.214-34	145	09.02.2100-L.....	81	09.02.4300-L.....	82
07.98.718	146	09.02.2101-L.....	81	09.02.4301-L.....	82
07.99.016	77	09.02.2110-L.....	81	09.02.5000-L.....	82
07.99.022-1-L.....	143	09.02.2111-L.....	81	09.02.5001-L.....	82
07.99.022-2-L.....	143	09.02.2200-L.....	81	09.02.5100-L.....	82
07.99.022-3-36	144	09.02.2201-L.....	81	09.02.5101-L.....	82
07.99.022-3-L.....	143	09.02.2210-L.....	81	09.02.5200-L.....	82
07.99.022-4-L.....	143	09.02.2211-L.....	81	09.02.5201-L.....	82
07.99.022-5-L.....	143	09.02.2300-L.....	81	09.02.5300-L.....	82
07.99.022-6-2	144	09.02.2301-L.....	81	09.02.5301-L.....	82
07.99.022-6-6	144	09.02.2310-L.....	81	09.02.7000-L.....	82
07.99.022-6-10	144	09.02.2311-L.....	81	09.02.7001-L.....	82
7W-2479.....	78	09.02.3000-L.....	81	09.02.7100-L.....	82
7W-4377.....	42	09.02.3001-L.....	82	09.02.7101-L.....	82
7W-8542.....	78	09.02.3010-L.....	82	09.02.7200-L.....	82
09.02.1000-L.....	81	09.02.3011-L.....	82	09.02.7201-L.....	82
09.02.1001-L.....	81	09.02.3100-L.....	82	09.02.7300-L.....	82
09.02.1010-L.....	81	09.02.3101-L.....	82	09.02.7301-L.....	82
09.02.1011-L.....	81	09.02.3110-L.....	82	09.03.1000-L.....	83
09.02.1100-L.....	81	09.02.3111-L.....	82	09.03.4000-L.....	83
09.02.1101-L.....	81	09.02.3200-L.....	82	09.04.1000-L.....	83
09.02.1110-L.....	81	09.02.3201-L.....	82	09.04.4000-L.....	83
09.02.1111-L.....	81	09.02.3210-L.....	82	09.05.1000-L.....	83
09.02.1200-L.....	81	09.02.3211-L.....	82	09.05.4000-L.....	83
09.02.1201-L.....	81	09.02.3300-L.....	82	09.06.1000-L.....	83
09.02.1210-L.....	81	09.02.3301-L.....	82	09.06.4000-L.....	83
09.02.1211-L.....	81	09.02.3310-L.....	82	09.07.1000-L.....	83

P/N	Page	P/N	Page	P/N	Page
09.07.4000-L.....	83	13.20.003-590	193	18GZ34	143
09.08.1000-L.....	83	13.20.004	193	18GZ44	142
09.08.4000-L.....	83	14-3CPU	125	19.60.002	190
09.09.1000-L.....	83	14FR-4DIU.....	125, 143	19.60.004	189
09.09.2000-L.....	83	14FR-4DIU3.....	129	19.60.007	188
09.09.4000-L.....	83	14FR-4DPUO	125	19.60.015	189
09.10.1000-L.....	83	14GZ6-77-2	129	19.60.022	189
09.10.2000-L.....	83	14GZ-GL.....	125	19.60.023	189
09.10.3000-L.....	83	14GZ-LL	75, 111, 112, 125, 129	19.60.027	188
09.10.4000-L.....	83	14GZ-LL2	129	19.60.029	188
09.11.1000-L.....	83	14GZ-LL-FR.....	125, 129	19.71.002	190
09.11.2000-L.....	83	14R-3CPU	125	19.71.004-32	189
09.11.3000-L.....	83	14R-4ADP	125	19.71.004-50	189
09.11.4000-L.....	83	14R-4CDP	125	19.71.004-100	189
09.12.1000-L.....	83	14R-4CIU	125	19.71.013	188
09.12.2000-L.....	83	14R-4CIU2	125	19.71.015-2	189
09.12.3000-L.....	83	14R-4DIU	143	19.71.015-3	189
09.12.4000-L.....	83	14R-4DIU2	75, 111, 112, 125	19.71.015-15	189
09.13.1000-L.....	83	14R-4DIU3	125	19.71.015-30	189
09.13.2000-L.....	83	14R-5BIU	125	21.01.390-20108-001-E	216
09.13.3000-L.....	83	14R-5BPU	125	21.01.441-20108-001E.....	216
09.13.4000-L.....	83	14R-5DPU	125	21.01.495-30089-001E.....	217
9Y-3362.....	78	15.02.226	64	21.01.724-30089-001E.....	217
9Y-3985.....	133	15.02.326	64	21.02.254-30089-001E.....	217
9Y-3987.....	52	15.02.426	64	21.02.260-20089-001E.....	217
9Y-7361.....	52	15.07.112	103, 173, 201	21.02.310-20089-001E.....	217
10.362-1	56	15.07.134	13, 17, 20, 24, 103, 157	21.02.339-20089-001E.....	217
10-320790-1	81, 83	15.07.221	103, 173, 201	21.02.504-30089-001E.....	216
10-382040-1	48, 81, 83	15.07.231	13, 17, 20, 24, 103, 157	21.02.518-30059-001E.....	216
11.020.....	36	18GZ4-77	125	21.02.520-20089-001E.....	216
11.371.....	36	18GZ5-77-2	125, 129, 143	21.02.520-20213-001E.....	216
0012E002200.....	38, 94	18GZ6-77-2	125, 129, 143	22.80.009	41
0012E006500.....	38, 94	18GZ7	125	22.80.009-100	85
13.20.002	193	18GZ20	125	22.85.802	122
13.20.003-295	193	18GZ22	125, 126, 129	22.85.802-100	85

■ Index

P/N	Page	P/N	Page	P/N	Page
22.85.803	122	25.00.310-WA.....	227	30.40.050-42	168
22.85.803-100	85	25.00.311-4/-7-WA.....	227	30.40.051-42	168
24.95.002	60	25.00.311-4-WA.....	227	30.40.100-60	168
25.00.001-110	228	25.00.311-7-WA.....	227	30.40.100-68	168
25.00.001-220	228	25.00.311-WA.....	227	30.40.101-60	168
25.00.009-50	225	25.00.312-1-WA.....	227	30.40.101-68	168
25.00.009-50-30	225	25.00.312-WA.....	227	30.40.140-75	168
25.00.009-50-30-HT	225	25.00.313-1-WA.....	227	30.40.140-80	168
25.00.009-50-HT	225	25.00.313-WA.....	227	30.40.140-85	168
25.00.018-50	225	25.00.314-10-WA.....	227	30.40.141-75	168
25.00.018-50-49	225	25.00.314-WA.....	227	30.40.141-80	168
25.00.018-50-49-HT	225	25.00.315-WA.....	227	30.40.141-85	168
25.00.018-50-HT	225	25.00.316-WA.....	227	30.40.150-90	168
25.00.109-25	225	25.00.317-WA.....	227	30.40.150-100	168
25.00.109-50	225	25.00.318-WA.....	227	30.40.151-90	168
25.00.118-25	225	25.00.320-3/-4/-5/-7-WS	227	30.40.151-100	168
25.00.118-50	225	25.00.320-3-WS.....	227	30.40.200-100	169
25.00.209	225	25.00.320-4-WS.....	227	30.40.200-105	169
25.00.218	225	25.00.320-5-WS.....	227	30.40.200-110	169
25.00.222	227	25.00.320-7-WS.....	227	30.40.200-115	169
25.00.226	227	25.00.320-WS.....	227	30.40.200-125	169
25.00.228	227	25.00.330-1-AR	227	30.40.201-100	169
25.00.229	227	25.00.330-AR	227	30.40.201-105	169
25.00.231	227	25.00.335-EMD.....	227	30.40.201-110	169
25.00.300-1-CA	227	28.10.014	165	30.40.201-115	169
25.00.300-CA	227	028-989-001	48, 49	30.40.201-125	169
25.00.301-6-CA	227	30.30.102	200	30.41.050-42-HT	168
25.00.301-CA	227	30.30.103	200	30.41.100-60-HT	168
25.00.302-CA	227	30.30.104	200	30.41.100-68-HT	168
25.00.303-1-CA	227	30.30.106	200	30.41.140-75-HT	168
25.00.303-CA	227	30.30.107	200	30.41.140-80-HT	168
25.00.310-4/-7/-14-WA	227	30.30.108	200	30.41.140-85-HT	168
25.00.310-4-WA.....	227	30.30.114	200	30.41.150-90-HT	168
25.00.310-7-WA.....	227	30.30.116	200	30.41.150-100-HT	168
25.00.310-14-WA.....	227	30.30.118	200	30.41.151-106-VHP-6	177

P/N	Page	P/N	Page	P/N	Page
30.41.151-106-VHP-12	177	31.01.720-30.0-3	198, 207	31.01.720-130.0-3	199
30.41.152-100-HT	175	31.01.720-32.5-3	198	31.01.720-135.0-3	199
30.41.200-100-HT	169	31.01.720-35.0-3	198	31.01.720-140.0-3	199
30.41.200-105-HT	169	31.01.720-37.5-3	198	31.01.720-145.0-3	199
30.41.200-110-HT	169	31.01.720-40.0-3	198	31.01.720-150.0-3	199
30.41.200-115-HT	169	31.01.720-42.5-3	198	31.01.750	199, 205
30.41.200-125-HT	169	31.01.720-45.0-3	198	31.01.751	199, 205
30.43.050-ID	172	31.01.720-47.5-3	198	31.01.752	199, 205
30.43.100-ID	172	31.01.720-50.0-3	198	31.01.753	199, 205
30.43.140-ID	172	31.01.720-52.5-3	198	31.01.754	199, 205
30.43.150-ID	172	31.01.720-55.0-3	198	31.01.755	199, 205
30.43.152-100	175	31.01.720-57.5-3	198	31.01.756	199, 205
30.43.200-ID	172	31.01.720-60.0-3	198, 207	31.01.757	199, 205
30.45.100-50D	198	31.01.720-62.5-3	198	31.01.758	199, 205
30.45.100-60D	198	31.01.720-65.0-3	198	31.01.759	199, 205
30.45.101-60D	198	31.01.720-67.5-3	198	31.01.761	199, 205
30.45.140-65D	198	31.01.720-70.0-3	198, 207	31.01.762	199, 205
30.45.140-80D	198	31.01.720-72.5-3	198	31.01.763	199, 205
30.45.141-80D	198	31.01.720-75.0-3	198	31.01.764	199, 205
30.45.200-100D	198	31.01.720-77.5-3	198	31.01.765	199, 205
30.45.200-120D	198	31.01.720-80.0-3	198	31.01.766	199, 205
30.45.200-120DG-XA	207	31.01.720-82.5-3	198	31.01.767	200, 205
30.45.201-120D	198	31.01.720-85.0-3	198, 207	31.01.768	199, 205
30.45.250-150D	198	31.01.720-87.5-3	198	31.01.772	200, 205
30.45.251-150D	198	31.01.720-90.0-3	199	31.01.773	199, 205
30.45.300-190D	198	31.01.720-92.5-3	199	31.01.774	205
30.45.301-190D	198	31.01.720-95.0-3	199	31.01.775	200, 205
30.45.350-225D	198	31.01.720-97.5-3	199	31.01.776	200, 205
30.45.351-225D	198	31.01.720-100.0-3	199	31.01.777	200, 205
31.01.365	205	31.01.720-102.5-3	199	31.01.778	205
31.01.371	205	31.01.720-107.5-3	199	31.01.779	200, 205
31.01.372	205	31.01.720-110.0-3	199	31.01.780	200, 205
31.01.377	205	31.01.720-115.0-3	199	31.01.781	199, 205
31.01.720-23.0-3	198	31.01.720-120.0-3	199	31.01.809	205
31.01.720-27.5-3	198	31.01.720-125.0-3	199	31.01.828	205

■ Index

P/N	Page	P/N	Page	P/N	Page
31.01.858	205	43.00.020-20	150	56.01.005-53	187
31.01.863	205	43.00.102	150	56.01.005-70	187
31.01.867	205	43.00.120	150	56.01.005-81	187
31.01.871	205	43.00.202	150	56.01.010	190
31.01.876	205	43.00.220	150	56.01.011	190, 211
31.01.879	205	43.00.421-12	108	56.01.017	190, 211
31.01.886	205	43.20.001	150, 151, 157	56.01.021	190, 211
31.01.942	173, 175, 177, 201	43.20.002	150, 152	56.01.025	190
31.01.943	203	43.20.018	152	56.01.090-10	164, 187
31.01.947-10	173, 201	43.30.004-60	150, 151	56.01.090-20	164, 187
31.01.948-100	203	43.30.016-25	157	56.01.090-25	164, 187
31.01.948-140	203	44.01.000	140	56.01.090-30	164, 187
31.01.948-200	203	44.01.005	140	56.01.090-40	164, 187
31.01.948-250	203	44.01.006	140	56.01.090-60	164, 187
31.01.948-300	203	44.01.009	140	56.01.090-K.....	164, 187
31.01.948-350	203	44.01.023	140	56.01.091-25	186
31.01.949	203	44.01.024	140	56.01.092-28	186
31.01.955	201, 208	44.01.025	140	56.01.094-23	185
31.01.959	203	44.04.005	60	56.01.094-59	185
31.01.960	177, 201, 208	44.99.011	64, 120	56.01.098-34	186
31.01.965	203	44.99.912	92, 93	56.01.180-10	164, 187
31.02.087-10	173, 175, 201	44.99.918	120	56.01.180-20	164, 187
31.02.113	199	51.13105-6013	175	56.01.180-25	164, 187
31.02.115	199	51.13105-6021	175	56.01.180-30	164, 187
31.02.118	199	51.25411-6028	186	56.01.180-40	164, 187
033-099-004	31	51.27420-0008	190	56.01.180-60	164, 187
34SG series	94	51.27421-0158	186	56.01.180-K.....	164, 187
37-4047	34	51.27421-0158-MOT.....	186	56.02.016	190
43.00.002	150	51.90020-0381-DS	151	56.02.017	190, 211
43.00.020	150	51.90020-0421-DS	151	63.02.011	211
43.00.020-04	150	51.90490-0022-DS	151	63.02.013	211
43.00.020-06	150	56.01.001	190	63.02.017	202
43.00.020-08	150	56.01.002	190	63.03.002-20	158, 165
43.00.020-12	150	56.01.004	190, 211	63.03.012-20	158, 165
43.00.020-16	150	56.01.005-42	187	63.04.002	173, 175

P/N	Page	P/N	Page	P/N	Page
63.04.175	182	63.50.120	180	66.60.001-125	54
63.04.176	182	63.50.129	180	66.60.001-175	54
63.50.002	181	63.60.001-50	173, 175	66.60.001-250	54, 110, 112
63.50.005	181	63.60.002-50	173, 175	66.60.001-400	54
63.50.006	181	64.01.055	219	66.60.001-600	54
63.50.007	181	64.40.038	185	66.60.002-125	54
63.50.007-HSS	181	66.00.310-6/-12	118	66.60.002-175	54
63.50.010-100	181	66.00.350-6	12	66.60.002-250	54
63.50.010-230	181	66.00.350-6/-12	118	66.60.002-450	54
63.50.010-xxx	181	66.00.350-12	12	66.60.002-600	54
63.50.011	181	66.00.356-8	14	66.60.003-60	54, 61, 109
63.50.022	181	66.00.357-12	14	66.60.003-100	54, 110, 111, 112
63.50.054	181	66.00.358-8	14	66.60.011-180	56
63.50.061	180	66.00.359-12	14	66.60.011-340	56
63.50.062	180	66.00.361-8	13	66.60.012-175	54
63.50.064	181	66.00.362-12	13	66.60.012-250	54
63.50.064-BTB	181	66.00.400-8	15	66.60.012-450	54
63.50.064-MCB	181	66.00.400-16	15	66.60.012-600	54
63.50.075	181	66.00.410-8	15, 16	66.60.021-300	56
63.50.082	180	66.00.410-16	15	66.60.023-450	56
63.50.085	180	66.00.413-16	17	72-00-0024	29
63.50.088	181	66.00.424-8	15, 16, 118	72-00-0025	29
63.50.092	181	66.00.424-8/-16	118	72-00-0026	29
63.50.093	181	66.00.424-16	15	72-00-0027	29
63.50.096	180	66.00.427-16	17	72-00-0028	29
63.50.097	180	66.00.440-8	16	72-70-0125	29
63.50.101	180	66.00.440-16	16	72-70-0235	29
63.50.104	180, 181	66.00.540-20	19, 20	75.00.433	113
63.50.104-HSS	180	66.00.541-20	19, 20, 118	75.00.434	113
63.50.105	180	66.00.542-20	19, 20	75.00.435	113
63.50.108	181	66.00.544-20	19, 20	75.00.436	113
63.50.112	181	66.00.645-24	24, 118	75.00.501	109
63.50.114	177	66.00.646-24	24	75.00.502	109
63.50.115	180	66.00.647-24	24	75.00.503	109
63.50.118	181	66.00.855-24/-24-D	19	75.00.504	109

■ Index

P/N	Page	P/N	Page	P/N	Page
75.00.505	109	75.00.609	110	75.10.303	101, 157, 164
75.00.506	109	75.00.610	112	75.10.404	17
75.00.507	110	75.00.611	111	75.10.621	219
75.00.508	110	75.00.627	112	75.30.046	186
75.00.509	110	75.00.631	112	75.30.131	60
75.00.510	112	75.00.647	112	75.30.131-1	60
75.00.511	111	75.00.651	109	75.30.132	60
75.00.536	105	75.00.652	109	75.30.133	60
75.00.537	105	75.00.653	109	75.30.133-1	60
75.00.538	105	75.00.654	109	75.30.137	61
75.00.539	105	75.00.655	109	75.30.143	37
75.00.540	105	75.00.656	109	75.30.144	37
75.00.581	109	75.00.657	110	75.30.146	17
75.00.582	109	75.00.658	110	75.30.148-6	177
75.00.583	109	75.00.659	110	75.30.148-12	177
75.00.584	109	75.00.660	112	75.30.149-6	177
75.00.585	109	75.00.661	111	75.30.149-12	177
75.00.586	109	75.00.668-141	111	75.30.150-08	18
75.00.587	110	75.00.668-142	111	75.30.150-12	18
75.00.588	110	75.00.668-143	111	75.30.150-16	18
75.00.589	110	75.00.668-181	111	75.30.154	37
75.00.590	112	75.00.668-182	111	75.30.155	37
75.00.591	111	75.00.669-141	112	75.30.156	36
75.00.595	111	75.00.669-142	112	75.30.157	36
75.00.596	111	75.00.669-143	112	75.41.001	110, 113
75.00.597	112	75.00.669-181	112	75.41.002	110, 113
75.00.598	112	75.00.669-182	112	75.41.003	109, 113
75.00.601	109	75.00.670-141	112	75.41.005	109, 113
75.00.602	109	75.00.670-142	112	75.41.006	109, 113
75.00.603	109	75.00.670-143	112	75.41.008	113
75.00.604	109	75.00.670-181	112	75.41.010	113
75.00.605	109	75.00.670-182	112	75.41.011	109, 113
75.00.606	109	75.10.097	101, 157, 164	75.41.013	110, 113
75.00.607	110	75.10.120	101, 157, 164	75.41.021	113
75.00.608	110	75.10.280	101, 157, 164	75.41.022	113

P/N	Page	P/N	Page	P/N	Page
75.41.023	111, 112, 113	77.81.607-DA	156	77.82.608-HA	162
75.41.026	110, 113	77.81.608-DA	156	77.82.609-HA	162
75.41.027	110, 113	77.81.609-DA	156	77.82.611-HA	162
75.41.033	111, 112, 113	77.81.611-DA	156	77.82.613-HA	162
75.90.295-100	146	77.81.613-DA	156	77.82.614-HA	162
76.64.005	33	77.81.614-DA	156	77.82.616-HA	162
76.64.291	129	77.81.616-DA	156	77.82.618-HA	162
76.64.292	129	77.81.618-DA	156	77.82.627-HD	162
76.64.302	33	77.81.627-DD	156	77.82.627-HF	162
76.64.375	129	77.81.627-DF	156	77.82.631-HG	162
76.70.007	165	77.81.631-DG	156	77.82.633-HF	162
77.41.117-L	157	77.81.633-DF	156	77.82.637-HA	162
77.41.317-L	157	77.81.637-DA	156	77.82.808-HA	162
77.42.317-L	165	77.81.808-DA	156	77.82.809-HA	162
77.42.327-L	165	77.81.809-DA	156	77.82.811-HA	162
77.49.006	20	77.81.811-DA	156	77.82.813-HA	162
77.49.007-L	20	77.81.813-DA	156	77.82.814-HA	162
77.49.008	20	77.81.814-DA	156	77.82.814-HF	162
77.49.029-1	12	77.81.814-DF	156	77.82.815-HA	162
77.49.029-L	12, 16	77.81.815-DA	156	77.82.816-HA	162
77.75.066	185	77.81.816-DA	156	77.82.818-HA	162
77.75.068-50	185	77.81.818-DA	156	77.82.822-HG	162
77.75.120-12	108	77.81.822-DG	156	80.01.210-2001	223
77.75.121-12	108	77.82.340-HA	162	80.01.210-2004	223
77.81.340-DA	156	77.82.344-HA	162	80.01.210-3001	223
77.81.344-DA	156	77.82.406-HA	162	80.01.210-3004	223
77.81.406-DA	156	77.82.407-HA	162	80.01.210-4001	223
77.81.407-DA	156	77.82.411-HA	162	80.01.210-4004	223
77.81.411-DA	156	77.82.427-HD	162	80.01.214	223
77.81.427-DD	156	77.82.437-HA	162	80.01.214-1104	223
77.81.437-DA	156	77.82.531-HA	162	80.01.214-1204	223
77.81.531-DA	156	77.82.541-HG	162	80.01.214-2104	223
77.81.541-DG	156	77.82.544-HG	162	81.00.300-01	223
77.81.544-DG	156	77.82.606-HA	162	81.00.300-04	223
77.81.606-DA	156	77.82.607-HA	162	81.00.301-01	223

■ Index

P/N	Page	P/N	Page	P/N	Page
81.00.301-04	223	95.01.020-60-RC	67	95.01.131-L.....	68
81.00.302-01	223	95.01.020-96-RC	67	95.01.132-L.....	68
81.00.302-04	223	95.01.020-180-RC	67	95.01.133-L.....	68
81.00.303-01	223	95.01.020-L.....	67	95.01.140-L.....	70
81.00.303-04	223	95.01.020-L-3.....	67	95.01.141-L.....	70
81.00.310-01	223	95.01.021-L.....	67	95.01.142-L.....	70
81.00.310-04	223	95.01.022-L.....	67	95.01.143-L.....	70
81.00.311-01	223	95.01.023-L.....	67	95.01.144-L.....	70
81.00.311-04	223	95.01.024-L.....	69	95.01.145-L.....	70
81.00.312-01	223	95.01.025-L.....	69	95.01.146-L.....	70
81.00.312-04	223	95.01.026-L.....	69	95.01.147-L.....	70
81.00.313-01	223	95.01.030-L.....	68	95.06.010-L.....	68
81.00.313-04	223	95.01.031-L.....	68	95.06.020-L.....	68
81.00.510	223	95.01.032-L.....	68	95.06.030-L.....	68
81.00.511	223	95.01.033-L.....	68	95.06.110-L.....	68
92.00.646-24	25	95.01.040-L.....	70	95.06.120-L.....	68
92.02.001-160	25	95.01.041-L.....	70	95.07.010-L.....	97
92.02.002-160	25	95.01.042-L.....	70	95.07.011-L.....	97
93.00.400-8	15	95.01.043-L.....	70	95.07.012-L.....	97
93.00.400-16	15	95.01.044-L.....	70	95.07.013-L.....	97
93.00.410-8	15	95.01.045-L.....	70	95.07.020-L.....	97
93.00.410-16	15	95.01.046-L.....	70	95.07.021-L.....	97
93.00.542-20	20	95.01.047-L.....	70	95.07.022-L.....	97
93.05.075	17, 20	95.01.107-24	69	95.07.023-L.....	97
95.01.010-42-RC	67	95.01.110-L.....	67	95.07.024-L.....	97
95.01.010-60-RC	67	95.01.110-L-3.....	67	95.08.001	48
95.01.010-96-RC	67	95.01.111-L.....	69	95.08.002	48
95.01.010-180-RC	67	95.01.120-30	46	95.08.003	48, 49, 101
95.01.010-L.....	67	95.01.120-L.....	67	95.08.005	48
95.01.010-L-3.....	67	95.01.120-L-3.....	67	95.08.020-6	51
95.01.011-L.....	69	95.01.121-L.....	67	95.08.040-6	51
95.01.012-14	69	95.01.122-L.....	67	95.08.050-11	51
95.01.013-30	69	95.01.123-L.....	67	95.08.070	49, 101
95.01.020-30	46	95.01.124-L.....	69	95.08.142-11	51
95.01.020-42-RC	67	95.01.130-L.....	68	95.08.143-6	51

P/N	Page	P/N	Page	P/N	Page
95.09.001	48	95.09.143-6	51	95.30.008-7	31
95.09.002	48	95.09.150	44	95.30.008-8	31
95.09.003	48	95.09.150-L-C	45	95.30.008-9	31
95.09.005	48, 49, 101	95.09.150-L-D	45	95.30.008-10	31
95.09.010	50	95.09.153	44	95.30.008-11	31
95.09.011	50	95.09.154	44	95.30.300-L	12, 16, 19
95.09.012-6	50	95.09.154-L-C	45	95.30.301-L	12, 16, 19
95.09.012-12	50	95.09.154-L-D	45	95.30.302-L	12, 16, 19
95.09.013-6	51	95.09.155	44, 46	95.30.942-32	173, 201
95.09.022-6	50	95.09.155-30-A	45	95.40.114-L	101
95.09.022-12	50	95.09.155-36-E	45	95.40.214-L	20
95.09.023-6	50	95.09.155-L-C	45	95.40.217-L	12, 16, 20
95.09.030	50	95.09.155-L-D	45	95.40.235-L	19, 24
95.09.031	50	95.09.156-20-B	45	95.40.314-L	101
95.09.033-6	50	95.09.157-28-G	45	95.60.010-L	57
95.09.040-6	50	95.09.222-6	50	95.60.020-L	57
95.09.040-12	50	95.09.222-12	50	95.60.030-L	57
95.09.050-6	51	95.09.223-6	50	95.60.040-L	57
95.09.051-6	51	95.09.233-6	50	95.60.050-400	57
95.09.053	48, 49, 101	95.30.007-1	31	95.70.001-125	55
95.09.054	48, 49, 101	95.30.007-2	31	95.70.001-175	55
95.09.055	48, 49, 101	95.30.007-4	31	95.70.001-250	55
95.09.060-11	51	95.30.007-5	31	95.70.001-400	55
95.09.061-11	51	95.30.007-8	31	95.70.001-600	55
95.09.070	49, 101	95.30.007-9	31	95.70.002-125	55
95.09.073	49, 101	95.30.007-10	31	95.70.002-175	55
95.09.074	49, 101	95.30.007-12	31	95.70.002-250	55
95.09.075	49, 101	95.30.007-13	31	95.70.002-450	55
95.09.100	44	95.30.007-14	31	95.70.002-600	55
95.09.122-11	51	95.30.008-1	31	95.70.003-60	55
95.09.123-6	51	95.30.008-2	31	95.70.003-100	55
95.09.133	44	95.30.008-3	31	95.70.012-175	55
95.09.134	42, 44	95.30.008-4	31	95.70.012-250	55
95.09.135	42, 44	95.30.008-5	31	95.70.012-450	55
95.09.142-11	51	95.30.008-6	31	95.70.012-600	55

■ Index

P/N	Page	P/N	Page	P/N	Page
95.75.024-1	104	95.86.614-NAN.....	100	123-4710	93
95.75.024-1-B	104	95.86.616-NAN.....	100	123-8641	93
95.75.025-1	104	95.86.618-NAN.....	100	124-0749	34, 39, 96
95.75.025-1-B	104	95.86.627-NDN.....	100	129-8802	34, 39, 96
95.75.048	107	95.86.627-NFN	100	131-3277	34, 39, 96
95.75.048-B	107	95.86.808-NAN.....	100	133-5078	94
95.75.067-1	104	95.86.809-NAN.....	100	141-2494	188
95.75.067-1-B	104	95.86.811-NAN.....	100	150-2050	38, 94
95.75.103	106	95.86.813-NAN.....	100	152-0807	186
95.75.103-B	106	95.86.814-NAN.....	100	165-1589	34, 39, 96
95.75.106	106	95.86.814-NFN	100	165-1590	34, 39, 96
95.75.106-B	106	95.86.815-NAN.....	100	165-1591	34, 39, 96
95.75.107	106	95.86.816-NAN.....	100	165-1592	34, 39, 96
95.75.107-B	106	95.86.818-NAN.....	100	169-4295	94
95.75.108	106	95.87.340-NAN.....	100	175-5341	186
95.75.108-B	106	95.87.344-NAN-04.....	100	191-5007	106
95.75.120-12	108	95.87.531-NAN-08.....	100	191-5008	106
95.75.121-12	108	95.87.541-NGN-10.....	100	191-9346	35
95.75.339-B	107	95.87.544-NGN-06.....	100	193-468157	35, 38, 94
95.75.340-B	107	95.87.631-NGN-08.....	100	194-8518	129
95.80.020-L.....	90	95.87.631-NGN-10.....	100	196-5391	188
95.80.030-L.....	90	95.87.633-NFN-22	100	198-2938	106
95.85.020-L.....	90	95.87.637-NAN.....	100	198-2941	106
95.85.030-L.....	90	95.87.822-NGN-06.....	100	199-9011	34
95.86.406-NAN.....	100	95.90.020-L.....	89	207-4508	93
95.86.407-NAN.....	100	95.90.030-L.....	89	207-4509	93
95.86.411-NAN.....	100	95.91.020-L.....	89	213-6308	106
95.86.427-NDN.....	100	95.91.030-L.....	89	213-7443	34, 39, 96
95.86.437-NAN.....	100	95.99.200-1	101	213-7444	34, 39, 96
95.86.606-NAN.....	100	95.99.200-2	101	215-2434	50
95.86.607-NAN.....	100	95.99.200-2-X.....	101	217-5922	78
95.86.608-NAN.....	100	106-9185	52	219-9946	106
95.86.609-NAN.....	100	107-2400	50	220G/SG series	94
95.86.611-NAN.....	100	108-0615	34, 39, 96	232-6346	34, 39, 96
95.86.613-NAN.....	100	122-8070	34, 39, 96	232-6347	34, 39, 96

P/N	Page	P/N	Page	P/N	Page
232-6348	34, 39, 96	418-4862	34	3400.7-21.07.02-03	38, 94
232-6349	34, 39, 96	437-4047	34	5419-735	93
232-6350	34, 39, 96	437-4049	34	5419-801	93
232-6351	35	437-4106	34	5419-802	93
232-6352	34, 39, 96	438-5682	35	5419-803	93
232-6353	34, 39, 96	451-00-042-00	168	5419-804	93
236-0484-DS	151	452-00-068-00	168	5419-805	93
241-9591	186	453-00-085-01	168	5419-806	93
243-4291	129	454-00-115-00	169	5419-807	93
250-2149	78	600-00-111-00	56	5419-808	93
251-2052	104	656-701-003	93	6910-314	190
251-2053	104	758-133	227	7302.....	125
258-4893	35, 38, 94	807.....	125	7303.....	125, 129
259-2078	34, 39, 96	827.....	125	7305.....	125, 129
260D-8810	29	837/9.....	35	7306.....	125, 129
262-4855	78	837/12.....	33	7307.....	125, 129
264-5323	38, 94	837/13.....	33	7308.....	75, 111, 112, 125, 129, 219
270A-8817	29	847.....	125	7311.....	125
283-5269	35	1187.....	29	7313.....	125
283-5270	38, 94	1215 3964.....	33	7315.....	111, 112, 125
283-5271	38, 94	1215 3965.....	33	7321.....	125
290-7079	104	1227 8370.....	18	7322.....	125
291-5862	104	1229 3602.....	186	8923-1061	193
306-6663	129	1229 6754.....	186	10000-06176	35
308-1380	38, 94	1229 8101 KM (TEM-ZS1).....	18	25080-01	93
310-3180	35	1229 9387.....	186	25080-02	93
330-2-AI-46	29	1229 9487.....	186	25080-03	93
356-3701	34	1229 9989.....	56	25080-04	93
383-2989	186	1230 0136.....	18	25080-05	93
400A-8811	29	1232 2279.....	186	25080-06	93
400A-8813	29	1242 0290.....	18	25080-07	93
400A-8814	29	1242 0480.....	18	25080-08	93
407L.....	125	1469-008	36	25080-09	93
407XL.....	125	2313-011	37	25080-10	93
418-4861	34	3076.....	74	25080-11	93

■ Index

P/N	Page	P/N	Page	P/N	Page
25080-12	93	101181-MOT.....	56	296064B	93
26400-01	93	118257	33	296064C.....	93
26400-02	93	120095 (18V34SG)	37	296064D	93
26400-03	93	120096 (20V34SG)	37	296064F.....	93
26400-04	93	167602B	227	296064H	93
26400-05	93	168660B	227	304126	227
26400-07	93	168660H	227	305315C.....	227
26400-08	93	169994B-DS	151	305351E.....	227
26400-10	93	172607	227	305805	59
26510-01	93	178622	30	305805A	59
26510-02	93	178788	31	305805F.....	59
26510-03	93	178788A	31	305805G	59
26510-04	93	178803	31	305805N	59
26510-05	93	178804	31	305805P.....	59
26510-06	93	194929	185	305805R.....	59
26510-07	93	208472B	227	305948A-DS	151
26510-08	93	208472C.....	227	393013-1	31
26510-10	93	208502C.....	31	393013-2	31
60615F.....	50	208502E.....	31	393013-3	31
60999G	133	208503K.....	46	393013-4	31
60999T.....	46	209728	30	393013-5	31
69692B	30	211288S.....	185	393013-6	31
69694.....	33	211357P.....	46, 93	393013-7	31
69694B	33	211357U	46, 93	393013-8	31
69694D	50	211797A	93	393013-9	31
69694F.....	42	214036D	185	393013-10	31
69694G	42, 46	214046	182	393013-12	31
69703.....	30	260604	60	393013-13	31
69919.....	46, 47, 129	260605	60	393013-14	31
69919A	129	269717B	30	393014-1	31
69919C.....	129	291001	33, 40, 81, 82, 83	393014-2	31
69919D	129	291001-S.....	48, 49, 81, 83	393014-3	31
69957.....	43	295962	187	393014-4	31
69957A	43	295962A	187	393014-5	31
101181	56	295962B	187	393014-6	31

P/N	Page	P/N	Page	P/N	Page
393014-7	31	591007	50	593130-L.....	97
393014-8	31	591008	50	593140-L.....	97
393014-9	31	591010	33, 40, 81, 82, 83	593600-1	13, 17, 20, 24, 103
393014-10	31	591010-S.....	48, 49, 81, 83	607401	216
393014-11	31	591011A	50	607405	216
393018-1	30	591011B	50	608158	216
393018-2	30	591011C.....	50	691118-1	54, 55
393023-1	30	591012	42	691118-2	54, 55
393023-2	30	591014-1	54, 55	691118-4	54, 55
489488	227	591014-2	54, 55	691118-6	54, 55
489489	227	591014-4	54, 55	701501	48, 49
489490	227	591014-6	54, 55	702930	69
489491	227	591018	42, 46	705165	69
489493	227	591040	33	720002	60
489495	227	593020-L.....	89, 90	740283	107
489501	225	593022-L.....	67	740744	31
489508	225	593024-L.....	69	740744-MOT.....	31
489522	227	593025-L.....	69	740746B	69
489625	225	593026-L.....	69	740746D	69
489626	225	593027-30	46	740753	31
501061	33, 40, 81, 82, 83	593027-L.....	67	740753-MOT.....	31
501061-S.....	48, 49, 81, 83	593029-L.....	67	790021	58
504137	91	593030-L.....	89, 90	790022	58
504205	91	593035-L.....	67	790104-1	58
510480	91	593036-L.....	67	790105-1	58
583017-42	67	593041-1	30	790106-1	58
583017-60	67	593041-2	30	790108-1	58
583017-60KT.....	69	593048-L.....	57	790114-1	58
583017-96	67	593052-L.....	57	790115-1	58
583017-180	67	593054-L.....	57	790116-1	58
583018-42	67	593057-L.....	57	790118-1	58
583018-60	67	593068-1	69	790122-1	58
583018-96	67	593068-2	69	790144	58
583018-180	67	593069-L.....	68	790150	58
586171	216	593120-L.....	97	790151	58

Index

P/N	Page	P/N	Page	P/N	Page
790165	58	A755-L-2	89, 90	A740106E.....	188
790169	58	A69694G	42, 46	A740106E-MOT.....	188
790302-1	59	A168368E.....	59	A740735	188
790303-1	59	A204072	177	A740746	69
790314-1	59	A204072A	177	A740749	31
790316-1	59	A211357L.....	93	A740749-MOT.....	31
790318-1	59	A211357N	93	A740750	31
791015-1	56	A211357R	93	A740750-MOT.....	31
791016-2	56	A211357T.....	93	ALTOS-1	91
791037-4	56	A211357V	93	ALTSS-2	91
791041-3	56	A211357X.....	93	AWH42-“L”.....	81
791050-1	54, 55	A211357Y.....	93	AWH62-“L”.....	82
791050-2	54, 55	A211357Z.....	93	AWH72-“L”.....	82
791050-4	54, 55	A211797G	93	AWH82-“L”.....	82
791050-6	54, 55	A211797H	46, 93	B99	227
793012-6	30	A211797J	93	B754-L.....	68
793012-8	30	A211797K.....	93	B2224	129
793012-12	30	A211797M.....	93	B2324	129
2881124	36, 37	A211797P.....	46, 93	B2424	129
2881178	48, 49	A211797R	46, 93	B4321	74, 75, 77, 78, 80, 87, 109, 110, 111, 112, 129, 143
3340063	38, 94	A211797S	93	B7224	74, 75, 129
3341380	38, 94	A211797T.....	93	B7324	129
3394578	33	A296064C	93	B7424	129
4011615	36, 37	A296064D	93	B8124	93, 129, 143
8345482	227	A296064E.....	93	B8324	18, 46, 47, 75, 77, 87, 93, 111, 112, 129, 143
263210167	38, 94	A296064F.....	93	B8324-LTN	129
A260D-8810	29	A296064G	93	B8324/-LTN	93
A400A-8811	29	A296064H	93	B8524	129
A400A-8813	29	A296064J	93	BENDOS-1.....	91
A400A-8814	29	A296064K.....	93	BM-11533-B	31
A400A-8817	29	A296064L.....	93	C754-L.....	68
A-661	227	A296805	93	CAT03S44.....	216
A718	146	A296805A	93	CAT03S61	216
A754-L.....	68	A740106C	188		
A755-L.....	89, 90	A740106D	188		

P/N	Page	P/N	Page	P/N	Page
D14	76, 77, 87		87, 109, 125, 129, 143	M-400A-8811	29
D14N	76, 77, 80, 87	GL3-1.....	125	M-400A-8813	29
D16	76	GL3-3.....	18, 75, 125, 143	M-400A-8814	29
D211359G	184	GL3-5..	18, 75, 111, 112, 125, 129, 143	M“L”-1C.....	97
D211359G-MOT	184, 185	GN3-1	125	M“L”-2C.....	97
DL08220604.....	190	GT3-1.....	76, 80, 93, 125, 129	M“L”-2E	97
DL08311001.....	188	HOUA1005.....	217	M“L”-2S	97
DL08311003.....	188	HT1300-L.....	89, 90	MPC1800.....	131
E204072.....	177	HT1400-L.....	89, 90	MPC1900.....	131
E204072A.....	177	HT2300-L.....	89, 90	PB78WPC.....	125
EC-1950-14-S-CS.....	217	HT2400-L.....	89, 90	PPT2477AA6	50
EC-2850-20-S-CS.....	217	ICG-625	52	PPT2477AA12	50
EP-AL 200-DN100 PN6.....	217	ICPB412.....	133	PPT2477AB6.....	51
EP-AL 250-AWT.....	217	ICPB432.....	133, 143	PPT2477AD.....	48, 49, 81, 82, 83
EP-AL 300-AWT.....	216, 217	ICPB812.....	133, 143	PPT2477ADL	48, 83
EP-AL 400-AWT.....	216	ICPB832.....	133, 143	PPT2477L.....	82
EP-AL 450-AWT.....	216	J1443DP	125	PPT2477P	82
EP-AL 534-AWT.....	216	J1463DP	125, 129	R407L	125
EP-AL 600	216	K97F.....	143	R407XL.....	125
EP-AL 837	216	KB77WPCC.....	125	R717.....	129
F204072A.....	177	L1843B.....	125, 126	R807LL	125
FB77WPCC	46, 47, 74, 75, 76, 77, 87, 93, 125, 129, 143	L1843IP.....	125, 129	R65431A	48, 49
FM601	29	L1863B.....	125	RB75N	125
FMOS-1.....	91	L1863DP.....	125	RB75PP.....	125
GE3-1	125, 143	L1863IP.....	125, 129	RB75WPCC.....	75, 125, 129, 143
GE3-5	74, 75, 76, 77, 78, 80, 87, 109, 110, 111, 112, 125, 129, 143	L2252IP.....	129	RB75WPCC-1.....	125
GE5-1	125	L2282IP.....	129	RB76N	125
GL3-1	74, 76, 77, 87, 125, 143	LT2001-L.....	68	RB76PP.....	125
GL3-3 ..	46, 47, 74, 75, 76, 93, 125, 143	LT2011-L.....	68	RB77CC.....	125
GL3-4	93	LT2100-L.....	68	RB77WPCC.....	125
GL3-5	125, 129, 143	LT73002-L.....	67	RB114-1	129
GK3-1	125, 143	LT73012-L.....	67	RB212-1	129
GK3-5	74, 75, 76, 77, 80,	M82N	76	RB485-1	129
		M-260D-8810	29	RC78PYP.....	74, 75, 77, 80, 87, 125, 129, 143
		M-270A-8817	29		

Index

P/N	Page	P/N	Page	P/N	Page
RC78PYP15	125	RSL2LBL-“L”AIPS	81	USL2BL-“L”A.....	81
RC78WYP15	125	RSL2LC-“L”A	82	USL2BL-“L”AIPS.....	81
RHL79G	143	RSL2LC-“L”AIPS	82	USL2C-“L”A	81
RL15B.....	125	RSL2LCL-“L”A.....	82	USL2C-“L”AIPS.....	82
RL85G.....	125	RSL2LCL-“L”AIPS.....	82	USL2CL-“L”A.....	82
RM77N	76, 80, 93, 125, 129, 143	RSL2LE-“L”A	82	USL2CL-“L”AIPS.....	82
RM77PP	125, 129	RSL2LE-“L”AIPS	82	USL2E-“L”A	82
RN79G	74, 75, 76, 77, 78,	RSL2LF-“L”A	82	USL2F-“L”A.....	82
.....	80, 87, 125, 129, 143	RSL2LF-“L”AIPS	82	USL2F-“L”AIPS.....	82
RSL2A-“L”A	81	RSL2LG-“L”A.....	82	USL2G-“L”A.....	82
RSL2A-“L”AIPS.....	81	RSL2-LG-“L”AIPS.....	82	USL2G-“L”AIPS	82
RSL2AL-“L”A.....	81	RTB77WPCC	133, 143	USL2LA-“L”A.....	81
RSL2AL-“L”AIPS	81	RTL85G	133, 143	USL2LA-“L”AIPS.....	81
RSL2B-“L”A	81	RTM77N.....	133, 143	USL2LAL-“L”A	81
RSL2B-“L”AIPS.....	81	RTM77PP	133	USL2LAL-“L”AIPS	81
RSL2BL-“L”A.....	81	RTN79G	133, 143	USL2LB-“L”A	81
RSL2BL-“L”AIPS	81	RW77N	129	USL2LB-“L”AIPS.....	81
RSL2C-“L”A.....	82	RW77PP.....	74, 129	USL2LBL-“L”A	81
RSL2C-“L”AIPS.....	82	RW78N	129	USL2LBL-“L”AIPS	81
RSL2CL-“L”A.....	82	RW80N	74, 76, 77, 80, 87, 129	USL2LC-“L”A.....	82
RSL2CL-“L”AIPS	82	RW80PP.....	74, 143	USL2LC-“L”AIPS.....	82
RSL2E-“L”A.....	82	RW82P.....	76	USL2LCL-“L”A	82
RSL2E-“L”AIPS.....	82	SC1K.....	91	USL2LCL-“L”AIPS	82
RSL2F-“L”A.....	82	SC2K.....	91	USL2LE-“L”A.....	82
RSL2F-“L”AIPS	82	SFI-KIT	29	USL2LE-“L”AIPS.....	82
RSL2G-“L”A	82	SL2E-“L”AIPS.....	82	USL2LF-“L”A.....	82
RSL2G-“L”AIPS	82	U827	125	USL2LF-“L”AIPS	82
RSL2LA-“L”A.....	81	U847	125	USL2LG-“L”A	82
RSL2LA-“L”AIPS.....	81	USL2A-“L”A	81	USL2LG-“L”AIPS.....	82
RSL2LAL-“L”A	81	USL2A-“L”AIPS	81	USLA14SPB-“L”A	83
RSL2LAL-“L”AIPS.....	81	USL2AL-“L”A.....	81	USLA18SPB-“L”A	83
RSL2LB-“L”A.....	81	USL2AL-“L”AIPS.....	81	USLA18T22-“L”A	83
RSL2LB-“L”AIPS.....	81	USL2B-“L”A	81	USLA18T33-“L”A	83
RSL2LBL-“L”A	81	USL2B-“L”AIPS	81	USLA35SPB-“L”A	83

P/N	Page
USLA36SPB-“L”A	83
USLA45SPB-“L”A	83
USLA51SPB-“L”A	83
USLA78SPB-“L”A	83
USLASB180-“L”A	83
USLASL90-“L”A	83
USLB18T22-“L”A	83
USLB18T33-“L”A	83
USLB78SPB-“L”A	83
USLBSB180-“L”A	83
USLBSL90-“L”A	83
USLC18T22-“L”A	83
USLC18T33-“L”A	83
USLCSB180-“L”A	83
USLCSL90-“L”A	83
USLE14SPB-“L”A	83
USLE18SPB-“L”A	83
USLE18T22-“L”A	83
USLE18T33-“L”A	83
USLE35SPB-“L”A	83
USLE36SPB-“L”A	83
USLE45SPB-“L”A	83
USLE51SPB-“L”A	83
USLE78SPB-“L”A	83
USLESB180-“L”A	83
USLESL90-“L”A	83
W18	129
W77N	129, 143
W80N	74, 143
Z00-17-001-00	33